



INTERNATIONAL STANDARD ISO/IEC 9594-3:2005 TECHNICAL CORRIGENDUM 4

Published 2012-09-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Systems Interconnection — The Directory: Abstract service definition

TECHNICAL CORRIGENDUM 4

Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — L'annuaire: Définition du service abstrait

RECTIFICATIF TECHNIQUE 4

Technical Corrigendum 4 to ISO/IEC 9594-3:2005 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in collaboration with ITU-T. The identical text is published as Rec. ITU-T X.511 (2005)/Cor.4 (04/2012).

IECNORM.COM : Click to view the full PDF of ISO/IEC 9594-3:2005/Cor 4:2012

INTERNATIONAL STANDARD

RECOMMENDATION ITU-T

**Information technology – Open Systems Interconnection – The Directory:
Abstract service definition**

Technical Corrigendum 4

(covering resolution to defect reports 363, 364 and 367)

1) Correction of the defects reported in defect report 363

Update the second paragraph of clause 7.6.1 of X.511 as shown:

A **contextSelection** is said to govern **an one or more** attribute types if any of the following conditions occur:

- the **ContextSelection** specifies **allContexts** (in which case all attribute values of all attribute types are selected);
- the **ContextSelection** **data type** has a **selectedContexts component** which includes a **set of TypeAndContextAssertion** **data types where the whose-type component specifies an attribute type including its subtypes that** is **governed by the contextAssertions component the same as or a supertype of the attribute type**; or
- the **ContextSelection** **data type** has a **selectedContexts** which **component** includes a **TypeAndContextAssertion** **data types where the whose-type is component specifies the object identifiers** **id-oa-allAttributeTypes**.

2) Correction of the defects reported in defect report 364

In clause 12.7 and Annex A update **securityError** as shown:

```
securityError ERROR ::= {
  PARAMETER          OPTIONAL-PROTECTED { SET {
    problem      [0]  SecurityProblem,
    spkmInfo     [1]  SPKM-ERROR  OPTIONAL,
    COMPONENTS OF  CommonResults } }
  CODE              id-errcode-securityError }
```

3) Correction of the defects reported in defect report 367

In clause 7.10 and in Annex A, delete the attributeCertificationPath component of the security parameters and mark the tag as not reusable.

Also in clause 7.10, delete the text associated with the attributeCertificationPath component.

Delete the last two sentences of the first paragraph of clause 8.1.1.

In clause 8.1.1 and in Annex A, delete the attributeCertificationPath component and mark the tag as not reusable.

In clause 8.1.2, replace the fourth paragraph with:

For the **strong** alternative, the specification for the parameters of **strongCredential** are:

- the **certificate-path** component, if present, shall hold a certification path as specified by the **CertificationPath** data type as defined in clause 7.6 of ITU-T Rec. X.509 | ISO/IEC 9594-8;
- the **bind-token** component shall be signed and shall have the subcomponents as specified below; and
- the **name** component shall hold the distinguished name of the requestor.