

INTERNATIONAL
STANDARD

ISO/IEC
8651-4

Second edition
1995-06-01

**Information technology — Computer
graphics — Graphical Kernel System (GKS)
language bindings —**

Part 4:
C

*Technologies de l'information — Infographie — Interfaces langage avec
GKS —*

Partie 4: C



Reference number
ISO/IEC 8651-4:1995(E)

Contents

Foreword.....	v
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	2
3 The C language binding.....	3
3.1 Classification and designation.....	3
3.2 Functions versus macros.....	3
3.3 Character strings.....	3
3.4 Function identifiers.....	3
3.5 Registration.....	3
3.6 Identifiers for graphical items.....	4
3.7 Return values.....	4
3.8 Headers.....	4
3.8.1 gks.h	4
3.8.2 gks_compat.h	4
3.9 Memory management.....	5
3.9.1 Functions which return simple lists.....	5
3.9.2 Functions which return complex data structures.....	5
3.10 Error handling.....	7
3.10.1 Application supplied error handlers.....	7
3.10.2 Error codes.....	7
3.10.3 C-specific GKS errors.....	7
3.11 Colour representations and specifications.....	7
3.12 Colour characteristics.....	7
3.13 Storage of multi-dimensional arrays.....	8
3.13.1 Storage of 2*3 matrices.....	8
3.13.2 Storage of conics in 3*3 matrices.....	8
3.13.3 Storage of colour arrays.....	8
3.14 Compatibility with the 1991 edition.....	8
4 Tables.....	9
4.1 Abbreviation policy in construction of identifiers.....	9
4.2 Table of abbreviations used.....	9
4.3 Function names.....	13
4.3.1 List ordered alphabetically by bound name.....	13
4.3.2 List ordered alphabetically by GKS name.....	20
5 Type definitions.....	28
5.1 Mapping of GKS data types.....	28
5.2 Environment-defined type definitions.....	28
5.3 Implementation dependent type definitions.....	29
5.4 Implementation independent type definitions.....	35
6 Macro definitions.....	91
6.1 Function identifiers.....	91
6.1.1 In order of appearance.....	91
6.1.2 In alphabetical order.....	95

© ISO/IEC 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

6.2	Error codes.....	99
6.3	Miscellaneous.....	104
6.3.1	Linetypes.....	104
6.3.2	Marker types.....	104
6.3.3	Hatch styles.....	104
6.3.4	Colour models.....	104
6.3.5	Prompt and echo types.....	105
6.3.6	Default parameter of gopen_gks	105
7	C GKS function interface.....	106
7.1	Notational conventions.....	106
7.2	Workstation independent functions.....	106
7.2.1	Control functions.....	106
7.2.2	Output functions.....	108
7.2.3	Design output functions.....	110
7.2.4	Primitive attribute functions.....	113
7.2.5	Normalization transformation functions.....	119
7.2.6	NDC picture functions.....	120
7.2.7	Metafile functions.....	121
7.2.8	Picture part store functions.....	122
7.2.9	Input functions.....	124
7.2.10	Font and glyph functions.....	131
7.2.11	Audit and playback functions.....	131
7.2.12	Inquiry functions.....	132
7.2.13	Utility functions.....	145
7.3	Workstation functions.....	148
7.3.1	Control functions.....	148
7.3.2	Inquiry functions.....	155
7.3.3	Retrieval functions.....	172
7.3.4	Viewing utility functions.....	173
7.3.5	Colour utility functions.....	173
7.4	Segment functions and workstation activation functions.....	173
7.4.1	Segment functions.....	173
7.4.2	Workstation activation functions.....	176
7.4.3	Utility functions.....	176
	Annexes.....	177
A	Compiled GKS/C specification.....	177
A.1	Data types in compilation order.....	177
A.2	Macros.....	223
A.3	Function calls.....	231
A.4	Compatibility layer.....	260
B	Sample programs.....	271
B.1	STAR.....	271
B.2	IRON.....	273
C	Short function identifiers.....	280
C.1	In order of appearance.....	280
C.2	In alphabetical order.....	287
D	Memory management.....	294
D.1	Introduction.....	294
D.2	Functions that return simple lists.....	294
D.2.1	Operation of ginq_list_line_inds	295
D.3	Functions that return structured data.....	297
D.3.1	Operation of gcreate_store	298

	D.3.2	Operation of ginq_stroke_st and ginq_pat_rep	300
	D.3.3	Operation of gdel_store	304
E		Compatibility with the 1991 edition of ISO/IEC 86514	307
	E.1	Comparison of this edition of ISO/IEC 86514 with the 1991 edition.....	307
	E.1.1	Changes in ISO/IEC 86514 data types.....	307
	E.1.2	Changes in ISO/IEC 86514 functions	308
	E.2	The compatibility layer	309
	E.3	The header gks_compat.h	309
	E.4	Data types in gks_compat.h	309
	E.4.1	Renamed data types	309
	E.4.2	Renamed fields of data types	309
	E.4.3	Obsolete data types.....	310
	E.5	Macros	314
	E.6	Functions in the compatibility layer.....	314
	E.6.1	Replaced functions.....	314
	E.6.2	Obsolete functions	317
F		Function lists.....	324
	F.1	Alphabetic by GKS name.....	324
	F.2	Alphabetic by binding name	331

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 8651-4 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 24, *Computer graphics and image processing*.

This second edition cancels and replaces the first edition (ISO/IEC 8651-4:1991), which has been technically revised.

ISO/IEC 8651-4 consists of the following parts, under the general title *Information technology — Computer graphics — Graphical Kernel System (GKS) language bindings*:

- *Part 1: FORTRAN*
- *Part 2: Pascal*
- *Part 3: Ada*
- *Part 4: C*

Annexes A to F of this part of ISO/IEC 8651 are for information only.

Introduction

The Graphical Kernel System (GKS) functional description is registered as ISO/IEC 7942-1:1994. As explained in the Scope and Field of Application of ISO/IEC 7942-1, that International Standard is specified in a language independent manner and needs to be embedded in language dependent layers (language bindings) for use with particular programming languages.

The purpose of this part of ISO/IEC 8651 is to define a standard binding for the C computer programming language.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 8651-4:1995

Information technology — Computer graphics — Graphical Kernel System (GKS) language bindings —

Part 4:

C

1 Scope

The Graphical Kernel System (GKS), ISO/IEC 7942-1:1994, specifies a language independent nucleus of a graphics system. For integration into a programming language, GKS is embedded in a language dependent layer obeying the particular conventions of that language. This part of ISO/IEC 8651 specifies such a language dependent layer for the C language.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 8651. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO/IEC 8651 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/IEC 7942-1:1994, *Information technology – Computer graphics and image processing – Graphical Kernel System (GKS) – Part 1 : Functional description*.

ISO/IEC 9899:1990, *Programming languages – C*.

ISO/IEC TR 9973:1994, *Information technology – Computer graphics and image processing – Procedures for registration of graphical Items*.

3 The C language binding

The C language binding of GKS shall be as described in clauses 3 to 7.

3.1 Classification and designation

This part of ISO/IEC 8651 incorporates the rules of conformance defined in the GKS Standard (ISO/IEC 7942-1) for GKS implementations, with those additional requirements specifically defined for C bindings in GKS.

The following criteria shall determine conformance of an implementation to this part of ISO/IEC 8651:

In order to conform, an implementation of the C binding of GKS shall implement GKS as specified in ISO/IEC 7942-1. It shall make visible all of the declarations in the C binding specified in this part of ISO/IEC 8651 for a specific level of C.

Thus, for example, the syntax of the function names shall be precisely as specified in the binding and parameters shall be of the data types stated in the binding.

3.2 Functions versus macros

An implementation may substitute macros for functions. However, the macros shall be designed so that side-effects work properly. In general, a macro cannot be used to replace the error handling function **gerr_hand**. See also 3.10.

3.3 Character strings

The C language represents character strings as an array of characters terminated by the null character (i.e. `'\0'`). This means that the null character is not usable as a printable character.

3.4 Function identifiers

The function names of GKS are all mapped to C functions which begin with the letter **g**. Words and phrases used in the GKS function names are often abbreviated in the representation and are always separated with the underscore character `"_"`. The set of such abbreviations is given in 4.2, and the resulting C function names are listed in 4.3. For example, the abbreviation for the GKS function DELETE SEGMENT FROM WORKSTATION is **gdel_seg_ws**. **del**, **seg**, and **ws** are abbreviations for DELETE, SEGMENT, and WORKSTATION. The conjunctive FROM is mapped to the null string.

The C language (ISO/IEC 9899) requires that compilers recognize internal identifiers which are distinct in at least 31 characters. That standard also requires that external identifiers (i.e. those seen by the linker) be recognized to a minimum of six characters, independent of case.

Implementations which run in environments where two distinct C internal identifiers would be equivalent, if they were both external identifiers, shall include a set of object-like macros in the header which equate the long names to a set of short names. A possible set of short names for a compiler that accepts only 8 characters for external definitions may be found in annex C.

3.5 Registration

ISO/IEC 7942 reserves certain value ranges for registration¹ as graphical items. The registered graphical items will be bound to the C programming language (and other programming languages). The registered item binding will be consistent with the binding presented in this part of ISO/IEC 8651.

¹ For the purpose of this part of ISO/IEC 8651 and according to the rules for the designation and operation of registration authorities in the ISO/IEC Directives, the ISO/IEC council has designated the National Institute of Standards and Technology (Institute of Computer Sciences and Technology), A-266 Technology Building, Gaithersburg, MD 20899, USA to act as registration authority.

3.6 Identifiers for graphical items

Generalized Drawing Primitives and Escape functions are referenced via identifiers. This part of ISO/IEC 8651 specifies the format of the identifiers but it does not specify the registration of the identifiers. The identifiers are used as arguments to the functions **ggdp** and **gescape**.

An implementation may also represent GDPs and Escapes as separate functions, but this is not required.

There are two formats for these identifiers. One format is for registered GDPs and Escapes and the other format is for unregistered GDPs and Escapes.

The format for registered GDP identifiers is:

```
#define      GGDP_Rn      (n)          /* where 'n' is the registered GDP
                                         identifier */
```

The format for unregistered GDP identifiers is:

```
#define      GGDP_Un      (-n)         /* where 'n' is implementation
                                         dependent */
```

The format for registered Escape function identifiers is:

```
#define      GESCAPE_Rn   (n)          /* where 'n' is the registered
                                         Escape identifier */
```

The format for unregistered Escape function identifiers is:

```
#define      GESCAPE_Un   (-n)         /* where 'n' is implementation
                                         dependent */
```

3.7 Return values

All GKS/C functions have return value **void**.

3.8 Headers

3.8.1 gks.h

C provides a mechanism to access information stored in a header via the **#include** preprocessing directive. Clause 5 of this part of ISO/IEC 8651 describes the data types that shall be defined in the header **gks.h** which shall be included in any application program that intends to use GKS via the C binding.

This part of ISO/IEC 8651 uses the data type **size_t** (inter alia as a field in the data type **Gdata**). The type **size_t** is environment-defined (i.e. **unsigned long** or **unsigned int**) and is defined in the headers **<stdio.h>**, **<stddef.h>**, **<stdlib.h>**, **<string.h>**, **<time.h>**.

Additional implementation-dependent items may be placed in this header if needed. These items should start with the sentinel "G" or "g", as far as applicable.

The header **gks.h** shall also contain external declarations for all GKS/C functions because they have a **void** return type. For example, the declaration for the function **gopen_gks** would look like this:

```
extern void gopen_gks(const char *err_file, size_t memory);
```

3.8.2 gks_compat.h

For application programs which used to run on top of the 1991 edition of this part of ISO/IEC, the header **gks_compat.h** is provided. **gks_compat.h** includes GKS/C data types that are no longer supported, as well as external declarations for all GKS/C functions that are no longer supported. Implementations of this part of ISO/IEC 8651 shall support these functions in a compatibility layer, according to the guidelines in Annex G of ISO/IEC 7942-1:1994.

3.9 Memory management

The application shall allocate the memory needed for the data returned by the implementation. In general, the application will allocate a C structure and pass a pointer to that structure to an inquiry routine, which will then place information into the structure. However, a number of inquiry functions return variable length data, the length of which is not known *a priori* by the application.

These functions fall into two classes. One class of functions returns a simple, homogeneous, list of items. For example, the function INQUIRE LIST OF MARKER INDICES returns a list of the available marker indices. The other class returns complex, heterogeneous data structures. For example, the function INQUIRE GKS STATE LIST ENTRY returns a piece of the GKS state which may include several data structures of different length. The binding of these two classes of functions is described in detail below. Subclause 3.10 describes the errors that can be invoked during execution of functions which use the memory management policy.

3.9.1 Functions which return simple lists

Inquiry functions which return a list of items are bound such that the application can inquire about a portion of the list. This list is a subset of the implementation's internal list and is called the application's list. This allows the application to process the implementation's list in a piecewise manner rather than all at once.

The application allocates the memory for a list and passes that list to the implementation. The implementation places the results of the inquiry into the list. In order to support this policy of memory management, three additional parameters have been added to functions which return lists:

- a) **num_elems_appl_list**: An integer input parameter which is the length of the application's list. The value of **num_elems_appl_list** indicates the number of items (i.e. list elements) which will fit into the application list. A value of 0 is valid and allows the application to determine the size of the implementation's list (which is returned via **num_elems_impl_list**) without having the implementation return any of the elements of its list. If **num_elems_appl_list** is negative, **GE_APPL_LIST_LENGTH_LT_ZERO** is returned as the value of the error indicator parameter.
- b) **start_ind**: An integer input parameter which is an index into the implementation's list. (Index 0 is the first element of both the implementation's and application's list.) **start_ind** indicates the first item in the implementation's list that is copied into index 0 of the application's list. Items are copied sequentially from the implementation's list into the application's list until the application's list is full or there are no more items in the implementation's list. If **start_ind** is out of range, error **GE_START_IND_INVAL** is returned as the value of the error indicator parameter.
- c) **num_elems_impl_list**: An output parameter which is a pointer to an integer. The implementation stores into this parameter the number of items that are in the implementation's list.

In annex D, a possible underlying mechanism is described.

3.9.2 Functions which return complex data structures

The data returned by inter alia the ESCAPE function, the AWAIT INPUT function and the functions which return state lists or description tables can be complex in structure. They cannot be represented by a simple list of items. It would be an onerous task for the application to have to allocate and prepare data structures for these routines. In order to facilitate this task of using these inquiry functions, the binding defines a new resource, called a *Store*, to manage the memory for these functions.

The *Store* resource is opaque to the application. The application does not know the structure of the *Store* or how it is implemented. The *Store* is defined as a **void ***. This part of ISO/IEC 8651 defines two new functions which create (in CREATE STORE, bound as **gcreate_store**) and delete (in DELETE STORE, bound as **del_store**) a *Store*.

A *Store* is used by the implementation to manage the memory needed by the functions which return complex data structures. Without specifying an implementation of a *Store*, it is safe to say that it will contain

and control memory needed to hold the data returned by these functions and also contain some bookkeeping information about the contents and size of the memory.

The semantics of the *Store* resource provide two levels of memory management. The implementation is responsible for managing the memory at a low level because it uses, reuses, allocates and deallocates memory from the system in order to return information to the application. But the application is ultimately responsible for managing the memory at a high level because it creates and deletes *Stores*.

A *Store* is passed as a parameter to a function returning complex data structures. Another parameter to this function is a pointer to a pointer to a structure which defines the format of the returned data. The *Store* contains memory for the structure and any additional memory referenced by fields within the structure. The application accesses the returned data through its pointer to the structure. It does not use the *Store* to access the data.

A *Store* continues to hold the information from the function until the *Store* is deleted by the DELETE STORE function or until the *Store* is used as an argument to a subsequent function, which returns complex data structures. At that time, the old information is replaced with the new. Thus multiple calls to functions overwrite the contents of a *Store*. A *Store* only contains the results of the last function.

This part of ISO/IEC 8651 defines two errors that can occur when using or creating a *Store*; these errors are described in 6.2. For most functions using a *Store*, these and other errors are returned via the "error indicator" parameter. However, the function ESCAPE does not have an error indicator parameter. For this function, the error reporting mechanism is used when an error is encountered. For this function, the implementation shall, in addition to reporting the error, set the pointer to the returned data to NULL when an error occurs. See the binding of these functions for more information.

The definitions for the functions CREATE STORE and DELETE STORE follow:

CREATE STORE

Parameters:

Out	error indicator	I
Out	store	STORE

Effect: Creates a *Store* and returns a handle to it in the output parameter *store*. If the *Store* cannot be created, the error indicator is set to one of the following error values:

GE_GKS_NOT_OPEN	GKS not in proper state;
	GKS shall be in the state (GKOP, *)
GE_ERR_ALLOC_STORE	Error while allocating Store

Errors: None.

DELETE STORE

Parameters:

Out	error indicator	I
Out	store	STORE

Effect: Deletes the *Store* and all internal resources associated with it. If there is not an error, the parameter *store* will be set to NULL to signify that it is no longer valid. If an error is detected, the error indicator is set to one of the following values:

GE_GKS_NOT_OPEN	GKS not in proper state;
	GKS shall be in the state (GKOP, *)

Errors: None.

In 7.2.13.2, the C specification of these functions is given. In annex D, a possible underlying mechanism is

illustrated.

3.10 Error handling

3.10.1 Application supplied error handlers

User-defined error handlers shall accept the same arguments as the standard error handler. The user-defined error handler is specified by the utility function (see also 7.2.13.2)

SET ERROR HANDLER

Parameters:

In	New error handling function	Function
Out	Old error handling function	Function

Effect: Sets the GKS error handling function to *New error handling function* and returns the current error handling function to *Old error handling function*.

Errors: None.

Application defined error handling functions accept the same arguments as the standard error handler. They may invoke the standard error logging function ERROR LOGGING.

ISO/IEC 7942 defines the initial error handling function to be ERROR HANDLING, that is, the value of the parameter *Old error handling function* points to ERROR HANDLING, when SET ERROR HANDLER is called for the first time.

When the application changes the error handling function, the implementation will invoke the new function when an error is detected. If the application calls the default error handling function ERROR HANDLING, ERROR HANDLING will always call the function ERROR LOGGING.

If *New error handler* is not a valid pointer, the error handling will automatically be done by the standard error handler ERROR HANDLING.

User-defined error handlers may invoke the standard error logging function ERROR LOGGING.

3.10.2 Error codes

Hard coding numbers into a program decreases its maintainability. Therefore, this part of ISO/IEC 8651 defines a set of constants for the GKS error numbers. Each error constant begins with the characters **GE_**. See also 6.2 for the error macros.

3.10.3 C-specific GKS errors

This part of ISO/IEC 8651 defines some additional error messages. In 6.2 the numbers and their macros are given.

3.11 Colour representations and specifications

GKS defines 4 colour models (RGB, CIE L*u*v* 1976, HLS and HSV) of which RGB and CIE L*u*v* are mandatory. For each of these models, a colour specification is defined (**Grgb**, **Gcieluv**, **Ghsv**, **Ghls**). The colour representation and specification are defined in 5.4 by the types **Gcolr_rep** and **Gcolr_specif**.

3.12 Colour characteristics

GKS defines the colour characteristics as a basic type. The colour characteristics is defined in this part of ISO/IEC 8651 by the data type **Gcolr_chars**, which is documented in 5.3.

3.13 Storage of multi-dimensional arrays

3.13.1 Storage of 2*3 matrices

The entries of **Gtran_matrix** data types shall be stored such that the segment transformation is defined by

$$\begin{aligned} \text{Tp.x} &= \text{mat}[0,0]*\text{p.x} + \text{mat}[0,1]*\text{p.y} + \text{mat}[0,2]; \\ \text{Tp.y} &= \text{mat}[1,0]*\text{p.x} + \text{mat}[1,1]*\text{p.y} + \text{mat}[1,2]; \end{aligned}$$

where **p** is a 2D point, **Tp** its transformation and **mat** is of type **Gtran_matrix**.

3.13.2 Storage of conics in 3*3 matrices

The entries of **Gconic_matrix** data types shall be stored such that the conic is defined by

$$\begin{aligned} a[0,0]x^2 + (a[0,1] + a[1,0])xy + a[1,1]y^2 \\ + (a[0,2] + a[2,0])x + (a[1,2] + a[2,1])y + a[2,2] = 0 \end{aligned}$$

where **a** is of type **Gconic_matrix**.

3.13.3 Storage of colour arrays

The entries of **Gpat_rep** data types shall be stored such that the colour specifier at the (i,j)-th entry is given by

$$\begin{aligned} \text{xxx}_{i,j} &= \text{colr_rect.dir_colr.xxx}[i + \text{DX}*j]; i = 0, \dots, \text{DX} - 1; j \\ \text{colr_ind}_{i,j} &= \text{colr_rect.colr_array}[i + \text{DX}*j]; \\ \text{DX} &= \text{colr_rect.dims.size_x}; \\ \text{DY} &= \text{colr_rect.dims.size_y}; \end{aligned}$$

where **xxx** = (rgb|cieluv|hls|hsv) is of type **Gxxx** and **colr_rect** is of type **Gpat_rep**.

3.14 Compatibility with the 1991 edition

In the second (1994) edition of ISO/IEC 7942 some functions and data types of the 1985 edition have been overtaken or deprecated. They are documented in the informative annex G. Examples are the GKSM functions, which have been overtaken by AUDIT functions.

In this edition of ISO/IEC 8651-4 all functions and all data types of the 1991 edition (the C binding of the 1985 edition of ISO/IEC 7942) have been preserved. The support of overtaken or deprecated functions or data types falls into two categories:

- 1) *Functions which have been renamed (e.g. INQUIRE TEXT EXTENT → GET TEXT EXTENT) or which have been incorporated into more compact functions (e.g. the OUTPUT functions).*
These functions and their related data types are documented in clauses 5 and 7. For example, the function CREATE OUTPUT PRIMITIVE has been bound to the C function **gcreate_out_prim**. Besides that, however, the output functions **gpolyline**, **gpolyline_set**, **gnurb_set**, **gconic_sec_set**, **gpolymarker**, **gfill_area**, **gfill_area_set**, **gell_sec_set**, **gell_seg_set**, **gell_disc_set**, **gclosed_nurb_set**, **gtext**, **gcell_array**, **gdesign**, **ggdp** have been defined.
- 2) *Functions which have been deprecated (INQUIRE GKS LEVEL) or which have been overtaken by other functions (GKSM functions, for example).*
These functions are documented in annex E. They will be deleted at the next edition of this part of ISO/IEC 8651.

4 Tables

4.1 Abbreviation policy in construction of identifiers

In the construction of the several data types, function names, etc., the following policy is applied:

- 1) All identifiers in the C binding are abbreviated using the same abbreviations for every component and using underscores to denote blanks.
- 2) The plural of an expression is constructed by adding an "s" after its abbreviation; so, for example, "vector" is abbreviated to "vec" and "vectors" is abbreviated to "vecs"; if an expression is mapped to NULL, so will be its plural.
- 3) Digits are also preceded by underscores.
- 4) The word REALIZED is not abbreviated in the second field of the enumeration data type **Ginq_type**; in all other cases it is abbreviated using the list in 4.2.
- 5) Construction of GKS/C identifiers:
 - a) Function names:
"g" (lower case) followed by abbreviated function name in lower case;
 - b) Data types:
"G" (upper case) followed by abbreviated data type in lower case;
 - c) Fields of data types; the following refinements are used: "redundant" (words in the field name that are identical to those in the structure name) parts are omitted, if the context allows this; thus the linewidth in the field of **Gline_bundle** is abbreviated to **width**, because the context makes clear which width is used;
 - d) Function macros:
"Gfn_" followed by abbreviation of function name;
 - e) Error macros:
"GE_" followed by some abbreviated expression;
 - f) Fields of enumeration types:
"G" (upper case) followed by a prefix followed by an abbreviation of the field name; this prefix is constant for each enumeration field; all the fields are in upper case.

4.2 Table of abbreviations used

In this table, only words which are abbreviated are listed. They are used for

function names;
data types;
fields of data types;
error macros.

The word "NULL" denotes those words which are deleted completely when forming function names or data types.

Word or Phrase	Abbreviation
CIE L*u*v* (colour model)	cieluv
accumulate	accum
actual	act
addition	add
alignment	align
allocate	alloc
and	NULL

application	appl
arithmetic	arith
associate(d)	assoc
at	NULL
attribute	attr
attribute source flag	asf
availability	avail
available	avail
begin	beg
between	NULL
boundaries	bndries
boundary	bndry
buffer	buf
cannot	cant
centre	ctr
character	char
characteristics	chars
circular	circ
classification	class
clipping	clip
colour	colr
component	comp
composite	comp
composition	comp
concatenation	concat
connection	conn
contour	cont
control	ctrl
conversion	conv
coordinate	coord
correspondence	corr
criterion	crit
current	cur
dashed	dash
default	def
defined	def
delete	del
deletion	dcl
dependent	dep
description table	dt
designation	design
detectability	det
detectable	det
device	dev
device coordinate(s)	dc
digital	digit
dimension	dim
direction	dir
display	disp
dotted	dot
duplicate	dup
elliptic	ell

equal
error
evaluate
expansion
facility
factor
fill area
from
function
generalized drawing primitive
generic
gks closed
gks open
graphical
handling
height
highlighted
highlighting
homogeneous
horizontal
hue lightness saturation (colour model)
hue saturation value (colour model)
hyperbola
identifier
implemantation
implicit
in
in use
index
indicator
individual
initial
initialize
input
input/output
inquire
instance
integer
interior
invalid
invisible
length
less than
less than or equal
library
locator
logical
luminance
mapped
mapping
maximum
measure

eq
err
eval
expan
fac
NULL
fill
NULL
func
gdp
gen
gkcl
gkop
graph
hand
ht
highl
highl
homo
hor
hls
hsv
hyp
id
impl
impl
NULL
NULL
ind
ind
indiv
init
init
in
io
inq
inst
int
int
inval
invis
NULL
lt
le
lib
loc
NULL
lum
map
map
max
meas

memory	mem
metafile	mf
minimum	min
monochrome	monochr
nominal	nom
normal	norm
normalization	norm
normalized device coordinate(s)	ndc
number	num
of	NULL
on	NULL
operating	op
operation	op
orientation	ori
output	out
overflow	overf
parallelogram	paral
parameter	param
pattern	pat
picture	pic
picture part closed	ppcl
picture part open	ppop
pointer	ptr
polynomial	pol
position	pos
precision	prec
predefined	pred
primary	prim
primitive	prim
priority	pri
process	proc
prompt	pr
prompt and echo type	pet
queue	NULL
rational	rat
realized	real
record	rec
rectangle	rect
red green blue (colour model)	rgb
reference	ref
registered	reg
reject	rej
relative	rel
replication	repl
representation	rep
request(ed)	req
retrieve	ret
rubber	rub
saturation	satur
scale factor	NULL
section	sec
sector	sec

segment	seg
segment closed	sgcl
segment open	sgop
select	sel
selection	sel
selector	sel
sequence	seq
source	src
spacing	space
specification	specif
specified	specif
specifier	specif
state	st
state list	sl
stencil closed	stcl
stencil open	stop
storage	store
supported	NULL
suppress	suppr
tiling closed	tlcl
tiling open	tlop
to	NULL
tracking	track
transform(ation)	tran
unavailable	unavail
undefined	undef
undetectable	undet
unregistered	u
used	NULL
valuator	val
vector	vec
vertical	vert
viewport	vp
visibility	vis
visible	vis
visual	vis
which	NULL
window	win
with	NULL
workstation	ws
world coordinate	wc

4.3 Function names

4.3.1 List ordered alphabetically by bound name

gaccum_tran_matrix	ACCUMULATE TRANSFORMATION MATRIX
gactivate_ws	ACTIVATE WORKSTATION
gadd_set_names_nameset	ADD SET OF NAMES TO NAMESET
gadd_set_names_ndc_pic	ADD SET OF NAMES TO NDC PICTURE
gadd_set_scissors_ndc_pic	ADD SET OF SCISSORS TO NDC PICTURE
gadd_set_scissors_scissor_set	ADD SET OF SCISSORS TO SCISSOR SET

gappend_pic_part	APPEND PICTURE PART
gar_pic_part	ARCHIVE PICTURE PART
gassoc_seg_ws	ASSOCIATE SEGMENT WITH WORKSTATION
gaudit	AUDIT
gawait_event	AWAIT EVENT
gawait_in	AWAIT INPUT
gcell_array	CELL ARRAY
gclear_ws	CLEAR WORKSTATION
gclose_gks	CLOSE GKS
gclose_pic_part	CLOSE PICTURE PART
gclose_seg	CLOSE SEGMENT
gclose_stencil	CLOSE STENCIL
gclose_tiling	CLOSE TILING
gclose_ws	CLOSE WORKSTATION
gclosed_nurb_set	CLOSED NURB SET
gconic_sec_set	CONIC SECTION SET
gconv_colr	CONVERT COLOUR
gcopy_blank_real_pic_real_mf	COPY BLANK REALIZED PICTURE TO REALIZED METAFILE
gcopy_ndc_mf_pic_ndc_pic	COPY NDC METAFILE PICTURE TO NDC PICTURE
gcopy_ndc_pic_ndc_mf	COPY NDC PICTURE TO NDC METAFILE
gcopy_ndc_pic_pic_part_store	COPY NDC PICTURE TO PICTURE PART STORE
gcopy_pic_part_pic_part_store	COPY PICTURE PART FROM PICTURE PART STORE
gcopy_real_mf_pic_backdrop	COPY REALIZED METAFILE PICTURE TO BACKDROP
gcopy_real_pic_real_mf	COPY REALIZED PICTURE TO REALIZED METAFILE
gcopy_seg_ws	COPY SEGMENT FROM WORKSTATION
gcreate_out_prim	CREATE OUTPUT PRIMITIVE
gcreate_seg	CREATE SEGMENT
gcreate_stencil_bndry	CREATE STENCIL FROM BOUNDARY
gcreate_stencil_conts	CREATE STENCIL FROM CONTOURS
gcreate_store	CREATE STORAGE
gcreate_tiling_comp	CREATE TILING COMPONENT
gdeactivate_ws	DEACTIVATE WORKSTATION
gdef_in_dev	DEFINE LOGICAL INPUT DEVICE
gdel_pic_part	DELETE PICTURE PART
gdel_prims_ndc_pic	DELETE PRIMITIVES FROM NDC PICTURE
gdel_seg	DELETE SEGMENT
gdel_seg_ws	DELETE SEGMENT FROM WORKSTATION
gdel_stencil	DELETE STENCIL
gdel_store	DELETE STORAGE
gdel_tiling	DELETE TILING
gdesign	DESIGN
gell_disc_set	ELLIPTIC DISC SET
gell_sec_set	ELLIPTIC SECTOR SET
gell_seg_set	ELLIPTIC SEGMENT SET
gemergency_close_gks	EMERGENCY CLOSE GKS
gerr_hand	ERROR HANDLING
gerr_log	ERROR LOGGING
gescape	ESCAPE
geval_circ_arc_3_point	EVALUATE CIRCULAR ARC 3 POINT
geval_circ_arc_ctr	EVALUATE CIRCULAR ARC CENTRE
geval_circle	EVALUATE CIRCLE
geval_ell	EVALUATE ELLIPSE

geval_ell_arc	EVALUATE ELLIPTIC ARC
geval_hyp_arc	EVALUATE HYPERBOLIC ARC
geval_par_arc	EVALUATE PARABOLIC ARC
geval_tran_matrix	EVALUATE TRANSFORMATION MATRIX
geval_view_map_matrix	EVALUATE VIEW MAPPING MATRIX
geval_view_ori_matrix	EVALUATE VIEW ORIENTATION MATRIX
geval_wc_ord	EVALUATE WC ORDINATE
gfill_area	FILL AREA
gfill_area_set	FILL AREA SET
gflush_dev_events	FLUSH DEVICE EVENTS
ggdp	GENERALIZED DRAWING PRIMITIVE
gget_choice	GET CHOICE
gget_glyph_name	GET GLYPH NAME
gget_loc	GET LOCATOR
gget_map_seg_name	GET MAPPED SEGMENT NAME
gget_map_ws_id	GET MAPPED WORKSTATION IDENTIFIER
gget_pick	GET PICK
gget_stencil_attr	GET STENCIL ATTRIBUTE
gget_string	GET STRING
gget_stroke	GET STROKE
gget_text_extent	GET TEXT EXTENT
gget_val	GET VALUATOR
gget_ws_status	GET WORKSTATION STATUS
ginit_choice	INITIALIZE CHOICE
ginit_in_dev	INITIALIZE LOGICAL INPUT DEVICE
ginit_loc	INITIALIZE LOCATOR
ginit_pick	INITIALIZE PICK
ginit_string	INITIALIZE STRING
ginit_stroke	INITIALIZE STROKE
ginit_val	INITIALIZE VALUATOR
ginq_area_fac	INQUIRE AREA FACILITIES
ginq_area_ind	INQUIRE AREA INDEX
ginq_area_rep	INQUIRE AREA REPRESENTATION
ginq_asfs	INQUIRE ATTRIBUTE SOURCE FLAGS
ginq_char_exp	INQUIRE CHARACTER EXPANSION FACTOR
ginq_char_ht	INQUIRE CHARACTER HEIGHT
ginq_char_spc	INQUIRE CHARACTER SPACING
ginq_char_up_vec	INQUIRE CHARACTER UP VECTOR
ginq_choice_st	INQUIRE CHOICE DEVICE STATE
ginq_colr_fac	INQUIRE COLOUR FACILITIES
ginq_colr_rep	INQUIRE COLOUR REPRESENTATION
ginq_cur_cont_attr	INQUIRE CURRENT CONTOUR ATTRIBUTES
ginq_cur_norm_tran_num	INQUIRE CURRENT NORMALIZATION TRANSFORMATION NUMBER
ginq_cur_pick_id	INQUIRE CURRENT PICK IDENTIFIER VALUE
ginq_def_choice_data	INQUIRE DEFAULT CHOICE DEVICE DATA
ginq_def_font_ind_map	INQUIRE DEFAULT FONT INDEX MAPPING
ginq_def_loc_data	INQUIRE DEFAULT LOCATOR DEVICE DATA
ginq_def_pick_data	INQUIRE DEFAULT PICK DEVICE DATA
ginq_def_string_data	INQUIRE DEFAULT STRING DEVICE DATA
ginq_def_stroke_data	INQUIRE DEFAULT STROKE DEVICE DATA
ginq_def_val_data	INQUIRE DEFAULT VALUATOR DEVICE DATA
ginq_disp_spc_size	INQUIRE DISPLAY SPACE SIZE

ginq_edge_colr_ind	INQUIRE EDGE COLOUR INDEX
ginq_edge_colr_specif	INQUIRE EDGE COLOUR SPECIFIER
ginq_edge_flag	INQUIRE EDGE FLAG
ginq_edgetype	INQUIRE EDGETYPE
ginq_edgewidth	INQUIRE EDGEWIDTH SCALE FACTOR
ginq_font_ind_map	INQUIRE FONT INDEX MAPPING
ginq_gen_ws_dt_entry	INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY
ginq_gks_dt_entry	INQUIRE GKS DESCRIPTION TABLE ENTRY
ginq_gks_sl_entry	INQUIRE GKS STATE LIST ENTRY
ginq_global_tran_matrix	INQUIRE GLOBAL TRANSFORMATION MATRIX
ginq_in_dev_comps	INQUIRE INPUT DEVICE COMPOSITIONS
ginq_in_dev_init_values	INQUIRE INPUT DEVICE INITIAL VALUES
ginq_in_overf	INQUIRE INPUT QUEUE OVERFLOW
ginq_in_queue	INQUIRE INPUT QUEUE
ginq_in_table	INQUIRE INPUT DEVICE OPERATING MODES AND INITIAL VALUES
ginq_int_colr_ind	INQUIRE INTERIOR COLOUR INDEX
ginq_int_colr_specif	INQUIRE INTERIOR COLOUR SPECIFIER
ginq_int_style	INQUIRE INTERIOR STYLE
ginq_int_style_ind	INQUIRE INTERIOR STYLE INDEX
ginq_line_colr_ind	INQUIRE LINE COLOUR INDEX
ginq_line_colr_specif	INQUIRE LINE COLOUR SPECIFIER
ginq_line_fac	INQUIRE LINE FACILITIES
ginq_line_ind	INQUIRE LINE INDEX
ginq_line_rep	INQUIRE LINE REPRESENTATION
ginq_linetype	INQUIRE LINETYPE
ginq_linewidth	INQUIRE LINewidth SCALE FACTOR
ginq_list_area_inds	INQUIRE LIST OF AREA INDICES
ginq_list_avail_fonts	INQUIRE LIST OF AVAILABLE FONTS
ginq_list_avail_gdps	INQUIRE LIST OF AVAILABLE GENERALIZED DRAWING PRIMITIVES
ginq_list_avail_ws_types	INQUIRE LIST OF AVAILABLE WORKSTATION TYPES
ginq_list_colr_inds	INQUIRE LIST OF COLOUR INDICES
ginq_list_line_inds	INQUIRE LIST OF LINE INDICES
ginq_list_marker_inds	INQUIRE LIST OF MARKER INDICES
ginq_list_norm_trans	INQUIRE LIST OF NORMALIZATION TRANSFORMATIONS
ginq_list_pat_inds	INQUIRE LIST OF PATTERN INDICES
ginq_list_text_inds	INQUIRE LIST OF TEXT INDICES
ginq_list_vp_in_pris	INQUIRE LIST OF VIEWPORT INPUT PRIORITIES
ginq_loc_st	INQUIRE LOCATOR DEVICE STATE
ginq_local_tran_matrix	INQUIRE LOCAL TRANSFORMATION MATRIX
ginq_marker_colr_ind	INQUIRE MARKER COLOUR INDEX
ginq_marker_colr_specif	INQUIRE MARKER COLOUR SPECIFIER
ginq_marker_fac	INQUIRE MARKER FACILITIES
ginq_marker_ind	INQUIRE MARKER INDEX
ginq_marker_rep	INQUIRE MARKER REPRESENTATION
ginq_marker_size	INQUIRE MARKER SIZE SCALE FACTOR
ginq_marker_type	INQUIRE MARKER TYPE
ginq_name_open_pic_part	INQUIRE NAME OF OPEN PICTURE PART
ginq_name_open_seg	INQUIRE NAME OF OPEN SEGMENT
ginq_name_open_stencil	INQUIRE NAME OF OPEN STENCIL
ginq_name_open_tiling	INQUIRE NAME OF OPEN TILING
ginq_nameset	INQUIRE NAMESET
ginq_norm_tran	INQUIRE NORMALIZATION TRANSFORMATION

ginq_num_avail_in	INQUIRE NUMBER OF AVAILABLE INPUT DEVICES
ginq_op_st_entry	INQUIRE OPERATING STATE ENTRY
ginq_pat_fac	INQUIRE PATTERN FACILITIES
ginq_pat_ref_point	INQUIRE PATTERN REFERENCE POINT
ginq_pat_rep	INQUIRE PATTERN REPRESENTATION
ginq_pat_size	INQUIRE PATTERN SIZE
ginq_pick_st	INQUIRE PICK DEVICE STATE
ginq_pred_area_rep	INQUIRE PREDEFINED AREA REPRESENTATION
ginq_pred_colr_rep	INQUIRE PREDEFINED COLOUR REPRESENTATION
ginq_pred_line_rep	INQUIRE PREDEFINED LINE REPRESENTATION
ginq_pred_marker_rep	INQUIRE PREDEFINED MARKER REPRESENTATION
ginq_pred_pat_rep	INQUIRE PREDEFINED PATTERN REPRESENTATION
ginq_pred_text_rep	INQUIRE PREDEFINED TEXT REPRESENTATION
ginq_route_dir	INQUIRE ROUTE DIRECTION
ginq_scissor_mode	INQUIRE SCISSOR MODE
ginq_scissor_set	INQUIRE SCISSOR SET
ginq_seg_attr	INQUIRE SEGMENT ATTRIBUTES
ginq_sel_table	INQUIRE TABLE OF SELECTION CRITERIA
ginq_set_active_wss	INQUIRE SET OF ACTIVE WORKSTATIONS
ginq_set_assoc_wss	INQUIRE SET OF ASSOCIATED WORKSTATIONS
ginq_set_avail_in_devs	INQUIRE SET OF AVAILABLE INPUT DEVICES
ginq_set_avail_meass	INQUIRE SET OF AVAILABLE MEASURES
ginq_set_avail_triggers	INQUIRE SET OF AVAILABLE TRIGGERS
ginq_set_open_audits	INQUIRE SET OF OPEN AUDITS
ginq_set_open_playbacks	INQUIRE SET OF OPEN PLAYBACKS
ginq_set_open_wss	INQUIRE SET OF OPEN WORKSTATIONS
ginq_set_pic_part_names	INQUIRE SET OF PICTURE PART NAMES IN USE
ginq_set_seg_names	INQUIRE SET OF SEGMENT NAMES IN USE
ginq_set_seg_names_ws	INQUIRE SET OF SEGMENT NAMES ON WORKSTATION
ginq_set_stencil_names	INQUIRE SET OF STENCIL NAMES IN USE
ginq_set_tiling_names	INQUIRE SET OF TILING NAMES IN USE
ginq_specif_ws_dt_entry	INQUIRE SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY
ginq_specif_ws_dt_entry_st	INQUIRE SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY STATE
ginq_stencil_attr	INQUIRE STENCIL ATTRIBUTES
ginq_string_st	INQUIRE STRING DEVICE STATE
ginq_stroke_st	INQUIRE STROKE DEVICE STATE
ginq_text_align	INQUIRE TEXT ALIGNMENT
ginq_text_colr_ind	INQUIRE TEXT COLOUR INDEX
ginq_text_colr_specif	INQUIRE TEXT COLOUR SPECIFIER
ginq_text_extent	INQUIRE TEXT EXTENT
ginq_text_fac	INQUIRE TEXT FACILITIES
ginq_text_font_prec	INQUIRE TEXT FONT AND PRECISION
ginq_text_ind	INQUIRE TEXT INDEX
ginq_text_path	INQUIRE TEXT PATH
ginq_text_rep	INQUIRE TEXT REPRESENTATION
ginq_text_skew_angle	INQUIRE TEXT SKEW ANGLE
ginq_val_st	INQUIRE VALUATOR DEVICE STATE
ginq_view_pris	INQUIRE VIEW PRIORITIES
ginq_view_rep	INQUIRE VIEW REPRESENTATION
ginq_vis_effects_st	INQUIRE VISUAL EFFECTS STATE
ginq_ws_class	INQUIRE WORKSTATION CLASSIFICATION
ginq_ws_conn_type	INQUIRE WORKSTATION CONNECTION AND TYPE

ginq_ws_sl_entry	INQUIRE WORKSTATION STATE LIST ENTRY
ginq_ws_st	INQUIRE WORKSTATION STATE
ginq_ws_win_vp	INQUIRE WORKSTATION WINDOW AND VIEWPORT
ginsert_seg	INSERT SEGMENT
ginst_stencil	INSTANCE STENCIL
ginst_stencil_path	INSTANCE STENCIL ALONG PATH
ginst_stencil_seq_path	INSTANCE STENCIL SEQUENCE ALONG PATH
gmessage	MESSAGE
gnurb_set	NURB SET
gopen_gks	OPEN GKS
gopen_pic_part	OPEN PICTURE PART
gopen_stencil	OPEN STENCIL
gopen_tiling	OPEN TILING
gopen_ws	OPEN WORKSTATION
gplayback	PLAYBACK
gpolyline	POLYLINE
gpolyline_set	POLYLINE SET
gpolymarker	POLYMARKER
gproc_audit_item	PROCESS AUDIT ITEM
gread_item_audit	READ ITEM FROM AUDIT
gread_item_func_name_audit	READ ITEM FUNCTION NAME FROM AUDIT
gremove_backdrop	REMOVE BACKDROP
gremove_set_names_nameset	REMOVE SET OF NAMES FROM NAMESET
gremove_set_names_ndc_pic	REMOVE SET OF NAMES FROM NDC PICTURE
gremove_set_scissors_ndc_pic	REMOVE SET OF SCISSORS FROM NDC PICTURE
gremove_set_scissors_scissor_set	REMOVE SET OF SCISSORS FROM SCISSOR SET
grename_pic_part	RENAME PICTURE PART
grename_seg	RENAME SEGMENT
grename_stencil	RENAME STENCIL
grename_tiling	RENAME TILING
greopen_pic_part	REOPEN PICTURE PART
greorder_ndc_pic	REORDER NDC PICTURE
greg_choice	REQUEST CHOICE
greg_in	REQUEST INPUT
greg_loc	REQUEST LOCATOR
greg_pick	REQUEST PICK
greg_string	REQUEST STRING
greg_stroke	REQUEST STROKE
greg_val	REQUEST VALUATOR
greset_specif_ws_dt_entry_st	RESET SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY STATE
grestore_gks_sl	RESTORE GKS STATE LIST
grestore_ws_sl	RESTORE WORKSTATION STATE LIST
gret_pic_part_ar	RETRIEVE PICTURE PART FROM ARCHIVE
groute	ROUTE
gsample_choice	SAMPLE CHOICE
gsample_in	SAMPLE INPUT
gsample_loc	SAMPLE LOCATOR
gsample_pick	SAMPLE PICK
gsample_string	SAMPLE STRING
gsample_stroke	SAMPLE STROKE
gsample_val	SAMPLE VALUATOR
gsave_gks_sl	SAVE GKS STATE LIST

gsave_ws_sl	SAVE WORKSTATION STATE LIST
gset_norm_tran	SELECT NORMALIZATION TRANSFORMATION
gset_area_ind	SET AREA INDEX
gset_area_rep	SET AREA REPRESENTATION
gset_asfs	SET ATTRIBUTE SOURCE FLAGS
gset_char_code	SET CHARACTER CODE
gset_char_expan	SET CHARACTER EXPANSION FACTOR
gset_char_ht	SET CHARACTER HEIGHT
gset_char_space	SET CHARACTER SPACING
gset_char_up_vec	SET CHARACTER UP VECTOR
gset_choice_mode	SET CHOICE MODE
gset_colr_rep	SET COLOUR REPRESENTATION
gset_cont_attr	SET CONTOUR ATTRIBUTE
gset_det	SET DETECTABILITY
gset_edge_colr_ind	SET EDGE COLOUR INDEX
gset_edge_colr_specif	SET EDGE COLOUR SPECIFIER
gset_edge_flag	SET EDGE FLAG
gset_edgetype	SET EDGETYPE
gset_edgewidth	SET EDGEWIDTH SCALE FACTOR
gset_err_hand	SET ERROR HANDLING
gset_font_ind_map	SET FONT INDEX MAPPING
gset_global_tran_matrix	SET GLOBAL TRANSFORMATION MATRIX
gset_highl	SET HIGHLIGHTING
gset_in_dev_mode	SET LOGICAL INPUT DEVICE MODE
gset_int_colr_ind	SET INTERIOR COLOUR INDEX
gset_int_colr_specif	SET INTERIOR COLOUR SPECIFIER
gset_int_style	SET INTERIOR STYLE
gset_int_style_ind	SET INTERIOR STYLE INDEX
gset_line_colr_ind	SET LINE COLOUR INDEX
gset_line_colr_specif	SET LINE COLOUR SPECIFIER
gset_line_ind	SET LINE INDEX
gset_line_rep	SET LINE REPRESENTATION
gset_linetype	SET LINETYPE
gset_linewidth	SET LINEWIDTH SCALE FACTOR
gset_loc_mode	SET LOCATOR MODE
gset_local_tran_matrix	SET LOCAL TRANSFORMATION MATRIX
gset_marker_colr_ind	SET LINE COLOUR INDEX
gset_marker_colr_specif	SET MARKER COLOUR SPECIFIER
gset_marker_ind	SET MARKER INDEX
gset_marker_rep	SET MARKER REPRESENTATION
gset_marker_size	SET MARKER SIZE SCALE FACTOR
gset_marker_type	SET MARKER TYPE
gset_nameset	SET NAMESSET
gset_ndc_pic_prim_attr	SET NDC PICTURE PRIMITIVE ATTRIBUTE
gset_norm_tran_num	SET NORMALIZATION TRANSFORMATION NUMBER
gset_pat_ref_point	SET PATTERN REFERENCE POINT
gset_pat_rep	SET PATTERN REPRESENTATION
gset_pat_size	SET PATTERN SIZE
gset_pick_id	SET PICK IDENTIFIER
gset_pick_mode	SET PICK MODE
gset_prim_attr	SET PRIMITIVE ATTRIBUTE
gset_rep	SET REPRESENTATION

gset_scissor_mode	SET SCISSOR MODE
gset_scissor_set	SET SCISSOR SET
gset_seg_attr	SET SEGMENT ATTRIBUTE
gset_seg_pri	SET SEGMENT PRIORITY
gset_seg_tran	SET SEGMENT TRANSFORMATION
gset_stencil_attr	SET STENCIL ATTRIBUTE
gset_string_mode	SET STRING MODE
gset_stroke_mode	SET STROKE MODE
gset_text_align	SET TEXT ALIGNMENT
gset_text_colr_ind	SET TEXT COLOUR INDEX
gset_text_colr_specif	SET TEXT COLOUR SPECIFIER
gset_text_font_prec	SET TEXT FONT AND PRECISION
gset_text_ind	SET TEXT INDEX
gset_text_path	SET TEXT PATH
gset_text_rep	SET TEXT REPRESENTATION
gset_text_skew_angle	SET TEXT SKEW ANGLE
gset_val_mode	SET VALUATOR MODE
gset_view	SET VIEW
gset_view_pri	SET VIEW PRIORITY
gset_view_sel_crit	SET VIEW SELECTION CRITERION
gset_vis	SET VISIBILITY
gset_vp	SET VIEWPORT
gset_vp_in_pri	SET VIEWPORT INPUT PRIORITY
gset_win	SET WINDOW
gset_win_vp	SET WINDOW AND VIEWPORT
gset_ws_sel_crit	SET WORKSTATION SELECTION CRITERION
gset_ws_vis_effects	SET WORKSTATION VISUAL EFFECTS
gset_ws_vp	SET WORKSTATION VIEWPORT
gset_ws_win	SET WORKSTATION WINDOW
gset_ws_win_vp	SET WORKSTATION WINDOW AND VIEWPORT
gtext	TEXT
gwrite_user_rec_audit	WRITE USER RECORD TO AUDIT

4.3.2 List ordered alphabetically by GKS name

ACCUMULATE TRANSFORMATION MATRIX	gaccum_tran_matrix
ACTIVATE WORKSTATION	gactivate_ws
ADD SET OF NAMES TO NAMESET	gadd_set_names_nameset
ADD SET OF NAMES TO NDC PICTURE	gadd_set_names_ndc_pic
ADD SET OF SCISSORS TO NDC PICTURE	gadd_set_scissors_ndc_pic
ADD SET OF SCISSORS TO SCISSOR SET	gadd_set_scissors_scissor_set
APPEND PICTURE PART	gappend_pic_part
ARCHIVE PICTURE PART	gar_pic_part
ASSOCIATE SEGMENT WITH WORKSTATION	gassoc_seg_ws
AUDIT	gaudit
AWAIT EVENT	gawait_event
AWAIT INPUT	gawait_in
CELL ARRAY	gcell_array
CLEAR WORKSTATION	gclear_ws
CLOSE GKS	gclose_gks
CLOSE PICTURE PART	gclose_pic_part
CLOSE SEGMENT	gclose_seg

CLOSE STENCIL	gclose_stencil
CLOSE TILING	gclose_tiling
CLOSE WORKSTATION	gclose_ws
CLOSED NURB SET	gclosed_nurb_set
CONIC SECTION SET	gconic_sec_set
CONVERT COLOUR	gconv_colr
COPY BLANK REALIZED PICTURE TO REALIZED METAFILE	gcopy_blank_real_pic_real_mf
COPY NDC METAFILE PICTURE TO NDC PICTURE	gcopy_ndc_mf_pic_ndc_pic
COPY NDC PICTURE TO NDC METAFILE	gcopy_ndc_pic_ndc_mf
COPY NDC PICTURE TO PICTURE PART STORE	gcopy_ndc_pic_pic_part_store
COPY PICTURE PART FROM PICTURE PART STORE	gcopy_pic_part_pic_part_store
COPY REALIZED METAFILE PICTURE TO BACKDROP	gcopy_real_mf_pic_backdrop
COPY REALIZED PICTURE TO REALIZED METAFILE	gcopy_real_pic_real_mf
COPY SEGMENT FROM WORKSTATION	gcopy_seg_ws
CREATE OUTPUT PRIMITIVE	gcreate_out_prim
CREATE SEGMENT	gcreate_seg
CREATE STENCIL FROM BOUNDARY	gcreate_stencil_bndry
CREATE STENCIL FROM CONTOURS	gcreate_stencil_conts
CREATE STORAGE	gcreate_store
CREATE TILING COMPONENT	gcreate_tiling_comp
DEACTIVATE WORKSTATION	gdeactivate_ws
DEFINE LOGICAL INPUT DEVICE	gdef_in_dev
DELETE PICTURE PART	gdel_pic_part
DELETE PRIMITIVES FROM NDC PICTURE	gdel_prims_ndc_pic
DELETE SEGMENT	gdel_seg
DELETE SEGMENT FROM WORKSTATION	gdel_seg_ws
DELETE STENCIL	gdel_stencil
DELETE STORAGE	gdel_store
DELETE TILING	gdel_tiling
DESIGN	gdesign
ELLIPTIC DISC SET	gell_disc_set
ELLIPTIC SECTOR SET	gell_sec_set
ELLIPTIC SEGMENT SET	gell_seg_set
EMERGENCY CLOSE GKS	gemergency_close_gks
ERROR HANDLING	gerr_hand
ERROR LOGGING	gerr_log
ESCAPE	gescape
EVALUATE CIRCLE	geval_circle
EVALUATE CIRCULAR ARC 3 POINT	geval_circ_arc_3_point
EVALUATE CIRCULAR ARC CENTRE	geval_circ_arc_ctr
EVALUATE ELLIPSE	geval_ell
EVALUATE ELLIPTIC ARC	geval_ell_arc
EVALUATE HYPERBOLIC ARC	geval_hyp_arc
EVALUATE PARABOLIC ARC	geval_par_arc
EVALUATE TRANSFORMATION MATRIX	geval_tran_matrix
EVALUATE VIEW MAPPING MATRIX	geval_view_map_matrix
EVALUATE VIEW ORIENTATION MATRIX	geval_view_ori_matrix
EVALUATE WC ORDINATE	geval_wc_ord
FILL AREA	gfill_area
FILL AREA SET	gfill_area_set
FLUSH DEVICE EVENTS	gflush_dev_events
GENERALIZED DRAWING PRIMITIVE	ggdp

GET CHOICE	gget_choice
GET GLYPH NAME	gget_glyph_name
GET LOCATOR	gget_loc
GET MAPPED SEGMENT NAME	gget_map_seg_name
GET MAPPED WORKSTATION IDENTIFIER	gget_map_ws_id
GET PICK	gget_pick
GET STENCIL ATTRIBUTE	gget_stencil_attr
GET STRING	gget_string
GET STROKE	gget_stroke
GET TEXT EXTENT	gget_text_extent
GET VALUATOR	gget_val
GET WORKSTATION STATUS	gget_ws_status
INITIALIZE CHOICE	ginit_choice
INITIALIZE LOCATOR	ginit_loc
INITIALIZE LOGICAL INPUT DEVICE	ginit_in_dev
INITIALIZE PICK	ginit_pick
INITIALIZE STRING	ginit_string
INITIALIZE STROKE	ginit_stroke
INITIALIZE VALUATOR	ginit_val
INQUIRE AREA FACILITIES	ginq_area_fac
INQUIRE AREA INDEX	ginq_area_ind
INQUIRE AREA REPRESENTATION	ginq_area_rep
INQUIRE ATTRIBUTE SOURCE FLAGS	ginq_asfs
INQUIRE CHARACTER EXPANSION FACTOR	ginq_char_expan
INQUIRE CHARACTER HEIGHT	ginq_char_ht
INQUIRE CHARACTER SPACING	ginq_char_space
INQUIRE CHARACTER UP VECTOR	ginq_char_up_vec
INQUIRE CHOICE DEVICE STATE	ginq_choice_st
INQUIRE COLOUR FACILITIES	ginq_colr_fac
INQUIRE COLOUR REPRESENTATION	ginq_colr_rep
INQUIRE CURRENT CONTOUR ATTRIBUTES	ginq_cur_cont_attrs
INQUIRE CURRENT NORMALIZATION TRANSFORMATION NUMBER	ginq_cur_norm_tran_num
INQUIRE CURRENT PICK IDENTIFIER VALUE	ginq_cur_pick_id
INQUIRE DEFAULT CHOICE DEVICE DATA	ginq_def_choice_data
INQUIRE DEFAULT FONT INDEX MAPPING	ginq_def_font_ind_map
INQUIRE DEFAULT LOCATOR DEVICE DATA	ginq_def_loc_data
INQUIRE DEFAULT PICK DEVICE DATA	ginq_def_pick_data
INQUIRE DEFAULT STRING DEVICE DATA	ginq_def_string_data
INQUIRE DEFAULT STROKE DEVICE DATA	ginq_def_stroke_data
INQUIRE DEFAULT VALUATOR DEVICE DATA	ginq_def_val_data
INQUIRE DISPLAY SPACE SIZE	ginq_disp_space_size
INQUIRE EDGE COLOUR INDEX	ginq_edge_colr_ind
INQUIRE EDGE COLOUR SPECIFIER	ginq_edge_colr_specif
INQUIRE EDGE FLAG	ginq_edge_flag
INQUIRE EDGETYPE	ginq_edgetype
INQUIRE EDGEWIDTH SCALE FACTOR	ginq_edgewidth
INQUIRE FONT INDEX MAPPING	ginq_font_ind_map
INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY	ginq_gen_ws_dt_entry
INQUIRE GKS DESCRIPTION TABLE ENTRY	ginq_gks_dt_entry
INQUIRE GKS STATE LIST ENTRY	ginq_gks_sl_entry
INQUIRE GLOBAL TRANSFORMATION MATRIX	ginq_global_tran_matrix
INQUIRE INPUT DEVICE COMPOSITIONS	ginq_in_dev_comps

INQUIRE INPUT DEVICE INITIAL VALUES	ginq_in_dev_init_values
INQUIRE INPUT DEVICE OPERATING MODES AND INITIAL VALUES	ginq_in_table
INQUIRE INPUT QUEUE	ginq_in_queue
INQUIRE INPUT QUEUE OVERFLOW	ginq_in_overf
INQUIRE INTERIOR COLOUR INDEX	ginq_int_colr_ind
INQUIRE INTERIOR COLOUR SPECIFIER	ginq_int_colr_specif
INQUIRE INTERIOR STYLE	ginq_int_style
INQUIRE INTERIOR STYLE INDEX	ginq_int_style_ind
INQUIRE LINE COLOUR INDEX	ginq_line_colr_ind
INQUIRE LINE COLOUR SPECIFIER	ginq_line_colr_specif
INQUIRE LINE FACILITIES	ginq_line_facs
INQUIRE LINE INDEX	ginq_line_ind
INQUIRE LINE REPRESENTATION	ginq_line_rep
INQUIRE LINETYPE	ginq_linetype
INQUIRE LINEWIDTH SCALE FACTOR	ginq_linewidth
INQUIRE LIST OF AREA INDICES	ginq_list_area_inds
INQUIRE LIST OF AVAILABLE FONTS	ginq_list_avail_fonts
INQUIRE LIST OF AVAILABLE GENERALIZED DRAWING PRIMITIVES	ginq_list_avail_gdps
INQUIRE LIST OF AVAILABLE WORKSTATION TYPES	ginq_list_avail_ws_types
INQUIRE LIST OF COLOUR INDICES	ginq_list_colr_inds
INQUIRE LIST OF LINE INDICES	ginq_list_line_inds
INQUIRE LIST OF MARKER INDICES	ginq_list_marker_inds
INQUIRE LIST OF NORMALIZATION TRANSFORMATIONS	ginq_list_norm_trans
INQUIRE LIST OF PATTERN INDICES	ginq_list_pat_inds
INQUIRE LIST OF TEXT INDICES	ginq_list_text_inds
INQUIRE LIST OF VIEWPORT INPUT PRIORITIES	ginq_list_vp_in_pris
INQUIRE LOCAL TRANSFORMATION MATRIX	ginq_local_tran_matrix
INQUIRE LOCATOR DEVICE STATE	ginq_loc_st
INQUIRE MARKER COLOUR INDEX	ginq_marker_colr_ind
INQUIRE MARKER COLOUR SPECIFIER	ginq_marker_colr_specif
INQUIRE MARKER FACILITIES	ginq_marker_facs
INQUIRE MARKER INDEX	ginq_marker_ind
INQUIRE MARKER REPRESENTATION	ginq_marker_rep
INQUIRE MARKER SIZE SCALE FACTOR	ginq_marker_size
INQUIRE MARKER TYPE	ginq_marker_type
INQUIRE NAME OF OPEN PICTURE PART	ginq_name_open_pic_part
INQUIRE NAME OF OPEN SEGMENT	ginq_name_open_seg
INQUIRE NAME OF OPEN STENCIL	ginq_name_open_stencil
INQUIRE NAME OF OPEN TILING	ginq_name_open_tiling
INQUIRE NAMESSET	ginq_nameset
INQUIRE NORMALIZATION TRANSFORMATION	ginq_norm_tran
INQUIRE NUMBER OF AVAILABLE INPUT DEVICES	ginq_num_avail_in
INQUIRE OPERATING STATE ENTRY	ginq_op_st_entry
INQUIRE PATTERN FACILITIES	ginq_pat_facs
INQUIRE PATTERN REFERENCE POINT	ginq_pat_ref_point
INQUIRE PATTERN REPRESENTATION	ginq_pat_rep
INQUIRE PATTERN SIZE	ginq_pat_size
INQUIRE PICK DEVICE STATE	ginq_pick_st
INQUIRE PREDEFINED AREA REPRESENTATION	ginq_pred_area_rep
INQUIRE PREDEFINED COLOUR REPRESENTATION	ginq_pred_colr_rep
INQUIRE PREDEFINED LINE REPRESENTATION	ginq_pred_line_rep
INQUIRE PREDEFINED MARKER REPRESENTATION	ginq_pred_marker_rep

INQUIRE PREDEFINED PATTERN REPRESENTATION	<code>ginq_pred_pat_rep</code>
INQUIRE PREDEFINED TEXT REPRESENTATION	<code>ginq_pred_text_rep</code>
INQUIRE ROUTE DIRECTION	<code>ginq_route_dir</code>
INQUIRE SCISSOR MODE	<code>ginq_scissor_mode</code>
INQUIRE SCISSOR SET	<code>ginq_scissor_set</code>
INQUIRE SEGMENT ATTRIBUTES	<code>ginq_seg_attrs</code>
INQUIRE SET OF ACTIVE WORKSTATIONS	<code>ginq_set_active_wss</code>
INQUIRE SET OF ASSOCIATED WORKSTATIONS	<code>ginq_set_assoc_wss</code>
INQUIRE SET OF AVAILABLE INPUT DEVICES	<code>ginq_set_avail_in_devs</code>
INQUIRE SET OF AVAILABLE MEASURES	<code>ginq_set_avail_meass</code>
INQUIRE SET OF AVAILABLE TRIGGERS	<code>ginq_set_avail_triggers</code>
INQUIRE SET OF OPEN AUDITS	<code>ginq_set_open_audits</code>
INQUIRE SET OF OPEN PLAYBACKS	<code>ginq_set_open_playbacks</code>
INQUIRE SET OF OPEN WORKSTATIONS	<code>ginq_set_open_wss</code>
INQUIRE SET OF PICTURE PART NAMES IN USE	<code>ginq_set_pic_part_names</code>
INQUIRE SET OF SEGMENT NAMES IN USE	<code>ginq_set_seg_names</code>
INQUIRE SET OF SEGMENT NAMES ON WORKSTATION	<code>ginq_set_seg_names_ws</code>
INQUIRE SET OF STENCIL NAMES IN USE	<code>ginq_set_stencil_names</code>
INQUIRE SET OF TILING NAMES IN USE	<code>ginq_set_tiling_names</code>
INQUIRE SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY	<code>ginq_specif_ws_dt_entry</code>
INQUIRE SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY STATE	<code>ginq_specif_ws_dt_entry_st</code>
INQUIRE STENCIL ATTRIBUTES	<code>ginq_stencil_attrs</code>
INQUIRE STRING DEVICE STATE	<code>ginq_string_st</code>
INQUIRE STROKE DEVICE STATE	<code>ginq_stroke_st</code>
INQUIRE TABLE OF SELECTION CRITERIA	<code>ginq_sel_table</code>
INQUIRE TEXT ALIGNMENT	<code>ginq_text_align</code>
INQUIRE TEXT COLOUR INDEX	<code>ginq_text_colr_ind</code>
INQUIRE TEXT COLOUR SPECIFIER	<code>ginq_text_colr_specif</code>
INQUIRE TEXT EXTENT	<code>ginq_text_extent</code>
INQUIRE TEXT FACILITIES	<code>ginq_text_fac</code>
INQUIRE TEXT FONT AND PRECISION	<code>ginq_text_font_prec</code>
INQUIRE TEXT INDEX	<code>ginq_text_ind</code>
INQUIRE TEXT PATH	<code>ginq_text_path</code>
INQUIRE TEXT REPRESENTATION	<code>ginq_text_rep</code>
INQUIRE TEXT SKEW ANGLE	<code>ginq_text_skew_angle</code>
INQUIRE VALUATOR DEVICE STATE	<code>ginq_val_st</code>
INQUIRE VIEW PRIORITIES	<code>ginq_view_pris</code>
INQUIRE VIEW REPRESENTATION	<code>ginq_view_rep</code>
INQUIRE VISUAL EFFECTS STATE	<code>ginq_vis_effects_st</code>
INQUIRE WORKSTATION CLASSIFICATION	<code>ginq_ws_class</code>
INQUIRE WORKSTATION CONNECTION AND TYPE	<code>ginq_ws_conn_type</code>
INQUIRE WORKSTATION STATE	<code>ginq_ws_st</code>
INQUIRE WORKSTATION STATE LIST ENTRY	<code>ginq_ws_sl_entry</code>
INQUIRE WORKSTATION WINDOW AND VIEWPORT	<code>ginq_ws_win_vp</code>
INSERT SEGMENT	<code>ginsert_seg</code>
INSTANCE STENCIL	<code>ginst_stencil</code>
INSTANCE STENCIL ALONG PATH	<code>ginst_stencil_path</code>
INSTANCE STENCIL SEQUENCE ALONG PATH	<code>ginst_stencil_seq_path</code>
MESSAGE	<code>gmessage</code>
NURB SET	<code>gnurb_set</code>
OPEN GKS	<code>gopen_gks</code>
OPEN PICTURE PART	<code>gopen_pic_part</code>

OPEN STENCIL	gopen_stencil
OPEN TILING	gopen_tiling
OPEN WORKSTATION	gopen_ws
PLAYBACK	gplayback
POLYLINE	gpolyline
POLYLINE SET	gpolyline_set
POLYMARKER	gpolymarker
PROCESS AUDIT ITEM	gproc_audit_item
READ ITEM FROM AUDIT	gread_item_audit
READ ITEM FUNCTION NAME FROM AUDIT	gread_item_func_name_audit
REMOVE BACKDROP	gremove_backdrop
REMOVE SET OF NAMES FROM NAMESET	gremove_set_names_nameset
REMOVE SET OF NAMES FROM NDC PICTURE	gremove_set_names_ndc_pic
REMOVE SET OF SCISSORS FROM NDC PICTURE	gremove_set_scissors_ndc_pic
REMOVE SET OF SCISSORS FROM SCISSOR SET	gremove_set_scissors_scissor_set
RENAME PICTURE PART	grename_pic_part
RENAME SEGMENT	grename_seg
RENAME STENCIL	grename_stencil
RENAME TILING	grename_tiling
REOPEN PICTURE PART	greopen_pic_part
REORDER NDC PICTURE	greorder_ndc_pic
REQUEST CHOICE	greq_choice
REQUEST INPUT	greq_in
REQUEST LOCATOR	greq_loc
REQUEST PICK	greq_pick
REQUEST STRING	greq_string
REQUEST STROKE	greq_stroke
REQUEST VALUATOR	greq_val
RESET SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY STATE	greset_specif_ws_dt_entry_st
RESTORE GKS STATE LIST	grestore_gks_sl
RESTORE WORKSTATION STATE LIST	grestore_ws_sl
RETRIEVE PICTURE PART FROM ARCHIVE	gret_pic_part_ar
ROUTE	groute
SAMPLE CHOICE	gsample_choice
SAMPLE INPUT	gsample_in
SAMPLE LOCATOR	gsample_loc
SAMPLE PICK	gsample_pick
SAMPLE STRING	gsample_string
SAMPLE STROKE	gsample_stroke
SAMPLE VALUATOR	gsample_val
SAVE GKS STATE LIST	gsave_gks_sl
SAVE WORKSTATION STATE LIST	gsave_ws_sl
SELECT NORMALIZATION TRANSFORMATION	gsel_norm_tran
SET AREA INDEX	gset_area_ind
SET AREA REPRESENTATION	gset_area_rep
SET ATTRIBUTE SOURCE FLAGS	gset_asfs
SET CHARACTER CODE	gset_char_code
SET CHARACTER EXPANSION FACTOR	gset_char_expan
SET CHARACTER HEIGHT	gset_char_ht
SET CHARACTER SPACING	gset_char_space
SET CHARACTER UP VECTOR	gset_char_up_vec
SET CHOICE MODE	gset_choice_mode

SET COLOUR REPRESENTATION	<code>gset_colr_rep</code>
SET CONTOUR ATTRIBUTE	<code>gset_cont_attr</code>
SET DETECTABILITY	<code>gset_det</code>
SET EDGE COLOUR INDEX	<code>gset_edge_colr_ind</code>
SET EDGE COLOUR SPECIFIER	<code>gset_edge_colr_specif</code>
SET EDGE FLAG	<code>gset_edge_flag</code>
SET EDGETYPE	<code>gset_edgetype</code>
SET EDGEWIDTH SCALE FACTOR	<code>gset_edgewidth</code>
SET ERROR HANDLING	<code>gset_err_hand</code>
SET FONT INDEX MAPPING	<code>gset_font_ind_map</code>
SET GLOBAL TRANSFORMATION MATRIX	<code>gset_global_tran_matrix</code>
SET HIGHLIGHTING	<code>gset_highl</code>
SET INTERIOR COLOUR INDEX	<code>gset_int_colr_ind</code>
SET INTERIOR COLOUR SPECIFIER	<code>gset_int_colr_specif</code>
SET INTERIOR STYLE	<code>gset_int_style</code>
SET INTERIOR STYLE INDEX	<code>gset_int_style_ind</code>
SET LINE COLOUR INDEX	<code>gset_line_colr_ind</code>
SET LINE COLOUR INDEX	<code>gset_line_colr_ind</code>
SET LINE COLOUR SPECIFIER	<code>gset_line_colr_specif</code>
SET LINE INDEX	<code>gset_line_ind</code>
SET LINE REPRESENTATION	<code>gset_line_rep</code>
SET LINETYPE	<code>gset_linetype</code>
SET LINEWIDTH SCALE FACTOR	<code>gset_linewidth</code>
SET LOCAL TRANSFORMATION MATRIX	<code>gset_local_tran_matrix</code>
SET LOCATOR MODE	<code>gset_loc_mode</code>
SET LOGICAL INPUT DEVICE MODE	<code>gset_in_dev_mode</code>
SET MARKER COLOUR SPECIFIER	<code>gset_marker_colr_specif</code>
SET MARKER INDEX	<code>gset_marker_ind</code>
SET MARKER REPRESENTATION	<code>gset_marker_rep</code>
SET MARKER SIZE SCALE FACTOR	<code>gset_marker_size</code>
SET MARKER TYPE	<code>gset_marker_type</code>
SET NAMESET	<code>gset_nameset</code>
SET NDC PICTURE PRIMITIVE ATTRIBUTE	<code>gset_ndc_pic_prim_attr</code>
SET NORMALIZATION TRANSFORMATION NUMBER	<code>gset_norm_tran_num</code>
SET PATTERN REFERENCE POINT	<code>gset_pat_ref_point</code>
SET PATTERN REPRESENTATION	<code>gset_pat_rep</code>
SET PATTERN SIZE	<code>gset_pat_size</code>
SET PICK IDENTIFIER	<code>gset_pick_id</code>
SET PICK MODE	<code>gset_pick_mode</code>
SET PRIMITIVE ATTRIBUTE	<code>gset_prim_attr</code>
SET REPRESENTATION	<code>gset_rep</code>
SET SCISSOR MODE	<code>gset_scissor_mode</code>
SET SCISSOR SET	<code>gset_scissor_set</code>
SET SEGMENT ATTRIBUTE	<code>gset_seg_attr</code>
SET SEGMENT PRIORITY	<code>gset_seg_pri</code>
SET SEGMENT TRANSFORMATION	<code>gset_seg_tran</code>
SET STENCIL ATTRIBUTE	<code>gset_stencil_attr</code>
SET STRING MODE	<code>gset_string_mode</code>
SET STROKE MODE	<code>gset_stroke_mode</code>
SET TEXT ALIGNMENT	<code>gset_text_align</code>
SET TEXT COLOUR INDEX	<code>gset_text_colr_ind</code>
SET TEXT COLOUR SPECIFIER	<code>gset_text_colr_specif</code>

SET TEXT FONT AND PRECISION
SET TEXT INDEX
SET TEXT PATH
SET TEXT REPRESENTATION
SET TEXT SKEW ANGLE
SET VALUATOR MODE
SET VIEW
SET VIEW PRIORITY
SET VIEW SELECTION CRITERION
SET VIEWPORT
SET VIEWPORT INPUT PRIORITY
SET VISIBILITY
SET WINDOW
SET WINDOW AND VIEWPORT
SET WORKSTATION SELECTION CRITERION
SET WORKSTATION VIEWPORT
SET WORKSTATION VISUAL EFFECTS
SET WORKSTATION WINDOW
SET WORKSTATION WINDOW AND VIEWPORT
TEXT
WRITE USER RECORD TO AUDIT

gset_text_font_prec
gset_text_ind
gset_text_path
gset_text_rep
gset_text_skew_angle
gset_val_mode
gset_view
gset_view_pri
gset_view_sel_crit
gset_vp
gset_vp_in_pri
gset_vis
gset_win
gset_win_vp
gset_ws_sel_crit
gset_ws_vp
gset_ws_vis_effects
gset_ws_win
gset_ws_win_vp
gtext
gwrite_user_rec_audit

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 8651-4:1995

5 Type definitions

5.1 Mapping of GKS data types

The GKS document specifies a set of abstract data types. This clause gives the mapping from those data types to the data types defined in this part of ISO/IEC 8651.

GKS data type	C binding data type
Archive name	Gint
Archive specifier	void *
Audit identifier	Gint
Audit specifier	void *
Audit user data	Gaudit_user_data
Character code	char
Colour characteristics	Gcolor_chars
Error file	char *
Escape function identifier	Gint
Escape input data record	Gescape_in_data
Escape output data record	Gescape_out_data
GDP data record	Ggdp_data
GDP function identifier	Gint
Glyph name	Gint
ISO/IEC 9541 font name	Gint
Input data record	Gin_data
Integer	Gint
Measure process identifier	Gint
NDC metafile specifier	void *
Name	Gint
Nonnegative integer	Gint
Pick identifier	Gint
Picture identifier	Gint
Picture part name	Gint
Real number	Gfloat
Realized metafile specifier	void *
Scissor identifier	Gint
Segment name	Gint
Stencil name	Gint
Filing name	Gint
Trigger process identifier	Gint
Workstation generic type	Gint
Workstation identifier	Gint
Workstation specifier	void *

5.2 Environment-defined type definitions

The data types defined in this clause allow for the ease of porting GKS/C implementations between different environments. These types are used as the basis for all the other data types.

An implementation shall document the C types used for GKS/C types **Gfloat** and **Gint**.

Gfloat floating point number

This data type shall be defined by the implementation as a floating point type suitable for use within

GKS/C. Suggest:

```
typedef float Gfloat;
```

Gint integer

This data type shall be defined by the implementation as a signed integral type suitable for use within GKS/C. Suggest:

```
typedef int Gint;
```

size_t

An additional environment-defined data type is the type **size_t**. Depending on the environment, **size_t** can be defined as **unsigned int** or **unsigned long**. **size_t** is defined in the headers **<stdio.h>**, **<stdlib.h>**, **<stddef.h>**, **<string.h>**, **<time.h>**.

5.3 Implementation dependent type definitions

This subclause presents the skeleton structure of the implementation dependent data types.

REMARKS:

- In order to produce syntactically correct data types, several implementation and registration dependent parts are of type **Gdata**. They can be replaced by any other structure.
- The data of registered prompt and echo types are represented by structures with the names **pet_rn** (n the prompt and echo type), whereas the data of unregistered prompt and echo types are represented by structures with the names **pet_un** (-n the prompt and echo type).
- The data of registered and unregistered GDPs, escape input and escape output are denoted in a similar way.
- For the input data, the mandatory part, as specified in GKS (ISO/IEC 7942-1), is defined outside the union part of **Gxxx_data**. This mandatory part is implementation independent. Some of the **pet_rn** fields are given as structures of other type than **Gdata** for illustrative reasons. Thus, e.g. the **pet_r2** field of **Gchoice_data** contains a list of prompts, because GKS defines prompt and echo type 2 this way for the CHOICE device;

Gaudit_user_data audit user data record

```
typedef struct {
    Gint id; /* identifier */
    union {
        Gdata impl_dep; /* impl. dependent */
    } data;
} Gaudit_user_data;
```

Gchoice_data choice data

```

typedef struct {
    union Gchoice_pets {
        struct Gchoice_pet_r1 {
            Gdata    impl_dep;           /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gchoice_pet_r2 {
            Gint      num_prs;           /* number of prompts */
            Gpr_flag  *prs;              /* prompt array */
            Gdata      impl_dep;         /* impl. dep. */
        } pet_r2; /* pet 2 data */
        struct Gchoice_pet_r3 {
            Gint      num_strings;       /* number of choice strings */
            char      **strings;         /* array of choice strings */
            Gdata      impl_dep;         /* impl. dep. */
        } pet_r3; /* pet 3 data */
        struct Gchoice_pet_r4 {
            Gint      num_strings;       /* number of choice strings */
            char      **strings;         /* array of choice strings */
            Gdata      impl_dep;         /* impl. dep. */
        } pet_r4; /* pet 4 data */
        struct Gchoice_pet_r5 {
            Gint      seg_name;          /* segment name */
            Gint      num_pick_ids;      /* number of pick identifiers */
            Gint      *pick_ids;         /* array of pick identifiers */
            Gdata      impl_dep;         /* impl. dep. */
        } pet_r5; /* pet 5 data */
        struct Gchoice_pet_ul {
            Gdata      impl_dep;         /* impl. dep. */
        } pet_ul; /* pet -1 data */
        /* . . . impl. defined PET's */
    } pets;
} Gchoice_data;

```

Gcolr_chars colour characteristics

```

typedef struct {
    enum Gcolr_chars_type {GTYPE_CIELUV, GTYPE_OTHER } type;
    union {
        Gcieluv  prim_colr[3]; /* CIELUV primary colours */
        Gdata     impl_dep;     /* impl. dep. */
    } chars;
} Gcolr_chars;

```

Gescape_in_data escape input data record

```
typedef union {
    struct Gescape_in_r1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_r1; /* escape 1 data */
    struct Gescape_in_u1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_u1; /* escape -1 data */
    /* etc. */
} Gescape_in_data;
```

Gescape_out_data escape output data record

```
typedef union {
    struct Gescape_out_r1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_r1; /* escape 1 data */
    struct Gescape_out_u1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_u1; /* escape -1 data */
    /* etc. */
} Gescape_out_data;
```

Ggdp_data gdp data record

```
typedef union {
    struct Ggdp_r1 {
        Gdata impl_dep; /* impl. dep. */
    } gdp_r1; /* gdp 1 data */
    struct Ggdp_u1 {
        Gdata impl_dep; /* impl. dep. */
    } gdp_u1; /* gdp -1 data */
    /* etc. */
} Ggdp_data;
```

Gloc_data locator data record

```

typedef struct {
    union Gloc_pets {
        struct Gloc_pet_r1 {
            Gdata                                impl_dep;    /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gloc_pet_r2 {
            Gdata                                impl_dep;    /* impl. dep. */
        } pet_r2; /* pet 2 data */
        struct Gloc_pet_r3 {
            Gdata                                impl_dep;    /* impl. dep. */
        } pet_r3; /* pet 3 data */
        struct Gloc_pet_r4 {
            Gattr_ctrl_flag                      attr_ctrl_flag;
            /* attribute                          control flag */
            Gline_attrs                          line_attrs;
            /* line                             attributes */
            Gdata                                impl_dep;    /* impl. dep. */
        } pet_r4; /* pet 4 data */
        struct Gloc_pet_r5 {
            Gattr_ctrl_flag                      attr_ctrl_flag;
            /* attribute                          control flag */
            Gline_fill_ctrl_flag                 line_fill_ctrl_flag;
            /* line/area                          control flag */
            union Gloc_attrs {
                Gline_attrs                      line_attrs;
                /* line                          attrs. */
                Gareas_attrs                     area_attrs;
                /* interior                      attrs. */
            } attrs;
            Gdata                                impl_dep;    /* impl. dep. */
        } pet_r5; /* pet 5 data */
        struct Gloc_pet_r6 {
            Gdata                                impl_dep;    /* impl. dep. */
        } pet_r6; /* pet 6 data */
        struct Gloc_pet_u1 {
            Gdata                                impl_dep;    /* impl. dep. */
        } pet_u1; /* pet -1 data */
        /* . . . impl. defined PET's */
    } pets;
} Gloc_data;

```

Gpick_data pick data

```

typedef struct {
    union Gpick_pets {
        struct Gpick_pet_r1 {
            Gdata    impl_dep;    /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gpick_pet_r2 {
            Gint      pick_id;     /* pick identifier*/
            Gint      seg_name;    /* segment name*/
            Gnameset  set_names;   /* set of names*/
            Gdata     impl_dep;    /* impl. dep. */
        } pet_r2; /* pet 2 data */
        struct Gpick_pet_r3 {
            Gnameset  set_names;   /* set of names*/
            Gdata     impl_dep;    /* impl. dep. */
        } pet_r3; /* pet 3 data */
        struct Gpick_pet_ul {
            Gdata     data;        /* data */
        } pet_ul; /* pet -1 data */
        /* etc. */
    } pets;
} Gpick_data;

```

Gstring_data string data record

```

typedef struct {
    Gint  in_buf_size; /* input buffer size (nr. of bytes) */
    Gint  init_pos;    /* initial [cursor] position */
    union Gstring_pets {
        struct Gstring_pet_r1 {
            Gdata    impl_dep;    /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gstring_pet_ul {
            Gdata    impl_dep;    /* impl. dep. */
        } pet_ul; /* pet -1 data */
        /* etc. */
    } pets;
} Gstring_data;

```

Gstroke_data stroke data

```

typedef struct {
    Gint    init_pos;          /* initial buffer editing position */
    Gint    in_buf_size;      /* input buffer size (nr. of points) */
    Gfloat  x_interval;       /* X interval */
    Gfloat  y_interval;       /* Y interval */
    Gfloat  time_interval;    /* time interval */
    union Gstroke_pets {
        struct Gstroke_pet_r1 {
            Gdata          impl_dep; /* impl. dep. */
        } pet_r1;          /* pet 1 data */
        struct Gstroke_pet_r2 {
            Gdata          impl_dep; /* impl. dep. */
        } pet_r2;          /* pet 2 data */
        struct Gstroke_pet_r3 {
            Gattr_ctrl_flag attr_ctrl_flag;
            /* attribute control flag */
            Gmarker_attrs  marker_attrs;
            /* marker attrs. */
            Gdata          impl_dep; /* impl. dep. */
        } pet_r3;          /* pet 3 data */
        struct Gstroke_pet_r4 {
            Gattr_ctrl_flag attr_ctrl_flag;
            /* attribute control flag */
            Gline_attrs     line_attrs;
            /* line attrs. */
            Gdata          impl_dep; /* impl. dep. */
        } pet_r4;          /* pet 4 data */
        struct Gstroke_pet_ul {
            Gdata          impl_dep; /* impl. dep. */
        } pet_ul;          /* pet -1 data */
        /* etc. */
    } pets;
} Gstroke_data;

```

Gval_data valuator data record

```

typedef struct {
    Gfloat    low_value;    /* low value */
    Gfloat    high_value;   /* high value */
    union Gval_pets {
        struct Gval_pet_r1 {
            Gdata    impl_dep;    /* impl. dep. */
        } pet_r1;    /* pet 1 data */
        struct Gval_pet_r2 {
            Gdata    impl_dep;    /* impl. dep. */
        } pet_r2;    /* pet 2 data */
        struct Gval_pet_r3 {
            Gdata    impl_dep;    /* impl. dep. */
        } pet_r3;    /* pet 3 data */
        struct Gval_pet_ul {
            Gdata    impl_dep;    /* impl. dep. */
        } pet_ul;    /* pet -1 data */
        /* etc. */
    } pets;
} Gval_data;

```

5.4 Implementation independent type definitions

Gabut_specif ABUT specifier

```

typedef enum {
    GABUT_RIGHT,
    GABUT_LEFT,
    GABUT_TOP,
    GABUT_BOTTOM,
    GABUT_CTR_VERT,
    GABUT_CTR_HOR,
    GABUT_CAP_LINE,
    GABUT_BASE_LINE
} Gabut_specif;

```

Garea_attrs area attributes

```

typedef struct {
    Gasf    int_style_asf;    /* interior style ASF */
    Gasf    style_ind_asf;    /* style index ASF */
    Gasf    colr_ind_asf;    /* colour specifier ASF */
    Gasf    edge_flag_asf;    /* edge flag ASF */
    Gasf    edgetype_asf;    /* edgetype ASF */
    Gasf    edgewidth_asf;    /* edgewidth scale factor ASF */
    Gasf    edge_colr_ind_asf; /* edge colour specifier ASF */
    Gint    ind;    /* area index */
    Garea_bundle    bundle;    /* area bundle */
} Garea_attrs;

```

Garea_bundle area bundle

```

typedef struct {
    Gint_style    int_style;      /* interior style          */
    Gint          style_ind;      /* interior style index    */
    Gcolr_kind    colr_kind;      /* interior colour kind    */
    Gint          colr_ind;       /* interior colour index   */
    Gcolr_rep     int_dir_colr;   /* direct interior colour  */
    Gedge_flag    edge_flag;     /* edge flag               */
    Gint          edgetype;       /* edgetype                */
    Gfloat         edgewidth;     /* edgewidth scale factor  */
    Gcolr_kind    edge_colr_kind; /* edge colour kind        */
    Gint          edge_colr_ind;  /* edge colour index       */
    Gcolr_rep     edge_dir_colr;  /* direct edge colour      */
} Garea_bundle;

```

Garea_bundle_table area bundle table

```

typedef struct {
    Gint          num_inds;       /* number of area indices  */
    Gint          *inds;         /* list of area indices    */
    Garea_bundle *bundles;       /* list of area bundles    */
} Garea_bundle_table;

```

Garea_facs area facilities

```

typedef struct {
    Gint          num_int_styles; /* number of interior styles */
    Gint_style    int_styles[5]; /* list of available interior styles */
    Gint_list     hatch_styles;  /* list of available hatch styles */
    Gint          num_pred_inds; /* number of predef. area indices */
    Gint_list     edgetypes;     /* list of edgetypes          */
    Gint          num_edgewidths; /* number of available edgewidths */
    Gfloat         nom_edgewidth; /* nominal edgewidth          */
    Gfloat         min_edgewidth; /* min. edgewidth             */
    Gfloat         max_edgewidth; /* max. edgewidth             */
} Garea_facs;

```

Gasf attribute source flag

```

typedef enum {
    GASF_BUNDLED,
    GASF_INDIV
} Gasf;

```

Gasfs attribute source flags

```

typedef struct {
    Gasf  linetype;          /* linetype ASF */
    Gasf  linewidth;        /* linewidth scale factor ASF */
    Gasf  line_colr_ind;     /* line colour ASF */
    Gasf  marker_type;      /* marker type ASF */
    Gasf  marker_size;      /* marker size scale factor ASF */
    Gasf  marker_colr_ind;  /* marker colour ASF */
    Gasf  text_font_prec;   /* text font and precision ASF */
    Gasf  char_expan;       /* character expansion factor ASF */
    Gasf  char_space;       /* character spacing ASF */
    Gasf  text_colr_ind;    /* text colour ASF */
    Gasf  int_style;        /* interior style ASF */
    Gasf  int_style_ind;    /* interior style index ASF */
    Gasf  int_colr_ind;     /* interior colour ASF */
    Gasf  edge_flag;        /* edge flag ASF */
    Gasf  edgetype;         /* edgetype ASF */
    Gasf  edgewidth;        /* edgewidth scale factor ASF */
    Gasf  edge_colr_ind;    /* edge colour ASF */
} Gasfs;

```

Gattr_ctrl_flag attribute control flag

```

typedef enum {
    GFLAG_CUR,
    GFLAG_SPECIF
} Gattr_ctrl_flag;

```

Gaudit_flag audit flag

```

typedef enum {
    GAUDIT_OFF,
    GAUDIT_ON
} Gaudit_flag;

```

Gaudit_op audit operation

```

typedef struct {
    enum Gaudit_op_type {
        GAUDIT_OPEN, GAUDIT_CLOSE, GAUDIT_BEGIN, GAUDIT_END
    } type;
    void *specif; /* audit specifier */
} Gaudit_op;

```

Gbasic_in_data basic input data

```

typedef struct{
    Gin_class class; /* basic input [measure] class */
    union {
        Gloc_data    loc_data;      /* locator data */
        Gstroke_data stroke_data;    /* stroke data */
        Gval_data     val_data;      /* valuator data */
        Gchoice_data  choice_data;   /* choice data */
        Gpick_data    pick_data;     /* pick data */
        Gstring_data  string_data;   /* string data */
    } in_data; /* input data */
} Gbasic_in_data;

```

Gbasic_in_value basic input value

```

typedef struct{
    Gin_class class; /* basic input [measure] class */
    union {
        Gloc      loc;      /* locator value */
        Gstroke    stroke;   /* stroke value */
        Gfloat     val;      /* valuator value */
        Gchoice    choice;   /* choice value */
        Gpick      pick;     /* pick value */
        char       *string;  /* string value */
    } in_value; /* input value */
} Gbasic_in_value;

```

Gbdry boundary

```

typedef struct {
    enum Gbdry_type {
        GBNDRY_CLOSED_PATH,
        GBNDRY_ELL_DISC
    } type;
    union {
        Gpath_list    closed_path_seq; /* closed path sequence */
        Gconic_matrix ell_disc;        /* elliptic disc */
    } value;
} Gbdry;

```

Gbdry_list boundary list

```

typedef struct {
    Gint    num_bndries; /* number of boundaries in list */
    Gbdry  *bndries;     /* list of boundaries */
} Gbdry_list;

```

Gcap cap

```
typedef enum {
    GCAP_BUT,
    GCAP_ROUND,
    GCAP_SQUARE
} Gcap;
```

Gchange_flag change flag

```
typedef enum {
    GFLAG_CHANGED,
    GFLAG_NOT_CHANGED
} Gchange_flag;
```

Gchoice choice [value]

```
typedef struct {
    Gchoice_status    status;    /* status */
    Gint              num;       /* choice number */
} Gchoice;
```

Gchoice_status choice status

```
typedef enum {
    GCHOICE_OK,
    GCHOICE_NO_CHOICE
} Gchoice_status;
```

Gcieluv CIE L*u*v* [colour specification]

```
typedef struct {
    Gfloat    u_prime; /* u' coefficient */
    Gfloat    v_prime; /* v' coefficient */
    Gfloat    y;       /* y luminance */
} Gcieluv;
```

Gclip_ind clipping indicator

```
typedef enum {
    GIND_NO_CLIP,
    GIND_CLIP
} Gclip_ind;
```

Gclosed_path_op_st closed path operating state

```
typedef enum {
    GCP_ST_CPCL,
    GCP_ST_CPOP
} Gclosed_path_op_st;
```

Gcolr_avail colour available

```
typedef enum {
    GAVAIL_MONOCHR,
    GAVAIL_COLR
} Gcolr_avail;
```

Gcolr_facs colour facilities

```
typedef struct {
    Gint      num_colr_models; /* number of colour models */
    Gint      colr_models[4]; /* list of available colour models */
    Gint      num_colrs;      /* number of colours */
    Gcolr_chars chars;        /* colour characteristics */
    Gcolr_avail colr_avail;    /* colour availability */
    Gint      num_pred_inds;   /* number of predef. colour indices */
} Gcolr_fac;
```

Gcolr_kind colour kind

```
typedef enum {
    GCOLR_INDIR,
    GCOLR_RGB,
    GCOLR_CIELUV,
    GCOLR_HLS,
    GCOLR_HSV
} Gcolr_kind;
```

Gcolr_rep colour representation

```
typedef union {
    Grgb      rgb; /* Red Green Blue colour specification */
    Gcieluv    cieluv; /* CIE L*u*v* 1976 colour specification */
    Ghls      hls; /* Hue Luminance Saturation colour specification */
    Ghsv      hsv; /* Hue Saturation Value colour specification */
              /* etc. */
} Gcolr_rep;
```

Gcolr_specif colour specifier

```
typedef struct {
    Gcolr_kind kind; /* colour kind */
    union {
        Gint      ind; /* colour index */
        Grgb      rgb; /* Red Green Blue colour specification */
        Gcieluv    cieluv; /* CIE L*u*v* 1976 colour specification */
        Ghls      hls; /* Hue Luminance Saturation colour specification */
        Ghsv      hsv; /* Hue Saturation Value colour specification */
    } value;
} Gcolr_specif;
```

Gcolr_table colour table

```
typedef struct {
    Gint      num_inds;      /* number of colour indices */
    Gint      *inds;        /* list of colour indices */
    Gcolr_specif *colr_specifs; /* list of colour specifications */
} Gcolr_table;
```

Gcomp_data composite data

```
typedef struct {
    Gint      num_devs;      /* number of [basic] devices */
    Gbasic_in_data *basic_in_data; /* list of basic input data */
} Gcomp_data;
```

Gcomp_value composite value

```
typedef struct {
    Gint      num_devs;      /* number of [basic] devices */
    Gbasic_in_value *basic_in_value; /* list of basic input values */
} Gcomp_value;
```

Gconic_matrix conic matrix

```
typedef Gfloat Gconic_matrix[3][3];
```

Gconic_sec conic section

```
typedef struct {
    Gconic_matrix matrix;      /* conic matrix */
    Gpoint point_1;           /* point # 1 */
    Gpoint point_2;           /* point # 2 */
    Gsense_flag sense_flag;    /* sense flag */
} Gconic_sec;
```

Gconic_sec_list conic primitive list

```
typedef struct {
    Gint      num_conic_prims; /* number of conic primitives in list */
    Gconic_sec *conic_prims;  /* list of conic primitives */
} Gconic_sec_list;
```

Gcont_attr_name contour attribute name

```
typedef enum {
    GNAME_STYLE,
    GNAME_WIDTH,
    GNAME_CAP,
    GNAME_JOIN
} Gcont_attr_name;
```

Gcont_attr_value contour attribute value

```

typedef struct {
    Gcont_attr_name  name;    /* attribute name    */
    union {
        Gint      style;    /* style    */
        Gfloat    width;    /* width    */
        Gcap      cap;      /* cap    */
        Gjoin     join;     /* join    */
    } value;
} Gcont_attr_value;

```

Gcont_attrs contour attributes

```

typedef struct {
    Gint      style;    /* style    */
    Gfloat    width;    /* width    */
    Gcap      cap;      /* cap    */
    Gjoin     join;     /* join    */
} Gcont_attrs;

```

Gconv_flag conversion flag

```

typedef enum {
    GCONV_DONE,
    GCONV_APPROX,
    GCONV_NOT_CONV
} Gconv_flag;

```

Gcoord_switch coordinate switch

```

typedef enum {
    GCOORD_WC,
    GCOORD_NDC
} Gcoord_switch;

```

Gctrl_flag control flag

```

typedef enum {
    GFLAG_COND,
    GFLAG_ALWAYS
} Gctrl_flag;

```

Gctrl_point_list control point list

```

typedef struct {
    enum Grat { /* rationality (RATIONAL|POLYNOMIAL) */
        GNURB_RAT,
        GNURB_POL
    } rat;
    Gint num_points; /* number of points in the list */
    union {
        Ghomo_point *homo_points; /* list of homg. points */
        Gpoint *points; /* list of points */
    } ctrl_points;
} Gctrl_point_list;

```

Gdata data

```

typedef struct {
    size_t size; /* size of data */
    void *data; /* pointer to data */
} Gdata;

```

Gdc_units device coordinate units

```

typedef enum {
    GDC_METRES,
    GDC_OTHER
} Gdc_units;

```

Gdesign design

```

typedef struct {
    Gint stencil_name; /* stencil name */
    Gpoint stencil_origin; /* stencil origin */
    Gtran_matrix stencil_tran; /* stencil transformation */
    Gint tiling_name; /* tiling name */
    Gpoint tiling_origin; /* tiling origin */
    Gtran_matrix tiling_tran; /* tiling transformation */
} Gdesign;

```

Gdet detectability

```

typedef enum {
    GSEG_UNDET,
    GSEG_DET
} Gdet;

```

Gdev_comp device composition

```
typedef struct {
    Gdev_id    id;           /* device id      */
    Gint_list  meas_set;     /* measure set    */
    Gint_list  trigger_set;  /* trigger set    */
} Gdev_comp;
```

Gdev_comp_list device composition list

```
typedef struct {
    Gint      num_devs;      /* number of [basic] devices in list */
    Gdev_comp *dev_comps;    /* list of device compositions        */
} Gdev_comp_list;
```

Gdev_id device identifier

```
typedef struct {
    Gint      ws_id;        /* workstation identifier */
    Gint      num;          /* device number          */
    Gin_class in_class;     /* input [measure] class  */
} Gdev_id;
```

Gdev_id_in_value_list device identifier and input value list

```
typedef struct {
    Gint      num_devs;      /* number of [basic] devices in list */
    Gdev_id   *dev_ids;      /* list of device id values           */
    Gin_value *in_values;    /* list of device input values        */
} Gdev_id_in_value_list;
```

Gdev_id_list device identifier list

```
typedef struct {
    Gint      num_dev_ids;    /* number of device identifiers in list */
    Gdev_id   *dev_ids;      /* list of device identifiers           */
} Gdev_id_list;
```

Gdisp_space_size display space size

```
typedef struct {
    Gdc_units  dc_units;      /* device coordinate units             */
    Gfloat_size size_dc;      /* display space size [in] dc [units]  */
    Gint_size  size_raster;   /* display space size [in] raster [units] */
} Gdisp_space_size;
```

Gecho_switch echo switch

```
typedef enum {
    GSWITCH_NO_ECHO,
    GSWITCH_ECHO
} Gecho_switch;
```

Gedge_flag edge flag

```
typedef enum {
    GEDGE_OFF,
    GEDGE_ON
} Gedge_flag;
```

Gell_disc_list elliptic disc list

```
typedef struct {
    Gint      num_ell_discs; /* number of elliptic discs in list */
    Gconic_matrix *ell_discs; /* list of elliptic discs */
} Gell_disc_list;
```

Gfloat_list float list

```
typedef struct {
    Gint  num_floats; /* number of floats in list */
    Gint  *floats; /* list of floats */
} Gfloat_list;
```

Gfloat_size float size

```
typedef struct {
    Gfloat  size_x; /* x size */
    Gfloat  size_y; /* y size */
} Gfloat_size;
```

Gfont_ind_map font index mapping

```
typedef struct {
    Gint  ind; /* font index */
    Gint  iso9541_name; /* ISO 9541 font name */
} Gfont_ind_map;
```

Gfunc_params function parameters

```

typedef struct {
    Gint    func_id;
    union {

        struct Gopen_gks {
            char          *err_file;
        } open_gks;
        struct Gsave_gks_sl {
            Ggks_sl_name_list    entry_names;
            Ggks_sl_entry_list    entries;
        } save_gks_sl;
        struct Grestore_gks_sl {
            Ggks_sl_entry_list    entries;
        } restore_gks_sl;
        struct Gescape {
            Gint                func_id;
            Gescape_in_data    in_data;
            Gescape_out_data    out_data;
        } escape;
        struct Groute {
            Groute_dir        dir;
        } route;
        struct Gcreate_out_prim {
            Gprim_params    prim_params;
        } create_out_prim;
        struct Gopen_stencil {
            Gint                stencil_name;
            Ginside_rule        inside_rule;
        } open_stencil;
        struct Grename_stencil {
            Gint                old_name;
            Gint                new_name;
        } rename_stencil;
        struct Gdel_stencil {
            Gint                name;
        } del_stencil;
        struct Gcreate_stencil_bndry {
            Gint                stencil_name;
            Ginside_rule        inside_rule;
            Gbndry_list        bndry;
        } create_stencil_bndry;
        struct Gcreate_stencil_conts {
            Gint                stencil_name;
            Ginside_rule        inside_rule;
            Gpath_list        path_seq;
        } create_stencil_conts;
        struct Gset_cont_attr {
            Gcont_attr_value    cont_attr;
        } set_cont_attr;
    }
}

```

```

struct Gset_stencil_attr {
    Gint          stencil_name;
    Gstencil_attr_value  stencil_attr;
} set_stencil_attr;
struct Gget_stencil_attr {
    Gint          stencil_name;
    Gstencil_attr_name  attr_name;
    Gstencil_attr_value  attr;
} get_stencil_attr;
struct Ginst_stencil {
    Gint          stencil_name;
    Gint          inst_name;
    Gtran_matrix  stencil_tran;
    Ginst_specif  inst_specif;
} inst_stencil;
struct Ginst_stencil_path {
    Gint          stencil_name;
    Gint          inst_name;
    Gpoint        start_map;
    Gpoint        end_map;
    Gint          inst_num;
    Gpath         path;
} inst_stencil_path;
struct Ginst_stencil_seq_path {
    Gseq_specif_list  inst_seq_specif;
    Gpath_specif      path_specif;
    Gtran_matrix      stencil_tran;
} inst_stencil_seq_path;
struct Gopen_tiling {
    Gint          tiling_name;
} open_tiling;
struct Grename_tiling {
    Gint          old_name;
    Gint          new_name;
} rename_tiling;
struct Gdel_tiling {
    Gint          name;
} del_tiling;
struct Gcreate_tiling_comp {
    Gtiling_params  tiling_params;
    Gpoint          origin;
    Grepl_tech      repl_tech;
} create_tiling_comp;
struct Gset_prim_attr {
    Gprim_attr_value  attr_value;
} set_prim_attr;
struct Gadd_set_names_nameset {
    Gnameset         set_names;
} add_set_names_nameset;
struct Gremove_set_names_nameset {
    Gnameset         set_names;
} remove_set_names_nameset;

```

```

struct Gadd_set_scissors_scissor_set {
    Gscissor_list    scissor_set;
} add_set_scissors_scissor_set;
struct Gremove_set_scissors_scissor_set {
    Gint_list        scissor_ids;
} remove_set_scissors_scissor_set;
struct Gset_win_vp {
    Gint              tran_num;
    Gtran             norm_tran;
} set_win_vp;
struct Gset_vp_in_pri {
    Gint              tran_num;
    Gint              ref_tran_num;
    Grel_pri          rel_pri;
} set_vp_in_pri;
struct Gset_scissor_mode {
    Gscissor_mode     scissor_mode;
} set_scissor_mode;
struct Gset_norm_tran_num {
    Gint              tran_num;
} set_norm_tran_num;
struct Gdel_prims_ndc_pic {
    Gsel_crit         sel_crit;
} del_prims_ndc_pic;
struct Gadd_set_names_ndc_pic {
    Gnameset          set_names;
    Gsel_crit         sel_crit;
} add_set_names_ndc_pic;
struct Gremove_set_names_ndc_pic {
    Gnameset          set_names;
    Gsel_crit         sel_crit;
} remove_set_names_ndc_pic;
struct Gset_ndc_pic_prim_attr {
    Gsel_crit         sel_crit;
    Gprim_attr_value  attr_value;
} set_ndc_pic_prim_attr;
struct Gadd_set_scissors_ndc_pic {
    Gscissor_list     scissor_set;
    Gsel_crit         sel_crit;
} add_set_scissors_ndc_pic;
struct Gremove_set_scissors_ndc_pic {
    Gint_list         scissor_ids;
    Gsel_crit         sel_crit;
} remove_set_scissors_ndc_pic;
struct Greorder_ndc_pic {
    Gsel_crit         source_sel_crit;
    Gsel_crit         ref_sel_crit;
    Grel_pos          rel_pos;
} reorder_ndc_pic;
struct Gcopy_ndc_pic_ndc_mf {
    void              *mf_specif;
    Gint              pic_id;
}

```

```

        Gsel_crit      sel_crit;
        Gnameset       set_names;
    } copy_ndc_pic_ndc_mf;
    struct Gcopy_ndc_mf_pic_ndc_pic {
        void            *mf_specif;
        Gint            pic_id;
        Gnameset       set_names;
    } copy_ndc_mf_pic_ndc_pic;
    struct Gopen_pic_part {
        Gint            pic_part_name;
    } beg_pic_part;
    struct Gar_pic_part {
        Gint            pic_part_name;
        void            *ar_specif;
        Gint            ar_name_pic_part;
    } ar_pic_part;
    struct Gret_pic_part_ar {
        void            *ar_specif;
        Gint            ar_name_pic_part;
        Gint            pic_part_name;
    } ret_pic_part_ar;
    struct Greopen_pic_part {
        Gint            pic_part_name;
    } reopen_pic_part;
    struct Gappend_pic_part {
        Gint            source_pic_part_name;
        Gint            sink_pic_part_name;
        Gtran_matrix    global_tran_matrix;
        Gtran_mode      global_tran_mode;
        Gtran_matrix    local_tran_matrix;
        Gtran_mode      local_tran_mode;
        Gnameset       set_names;
    } append_pic_part;
    struct Grename_pic_part {
        Gint            old_pic_part_name;
        Gint            new_pic_part_name;
    } rename_pic_part;
    struct Gdel_pic_part {
        Gint            pic_part_name;
    } del_pic_part;
    struct Gcopy_pic_part_pic_part_store {
        Gint            pic_part_name;
        Gsel_crit      sel_crit;
        Gtran_matrix    global_tran_matrix;
        Gtran_mode      global_tran_mode;
        Gtran_matrix    local_tran_matrix;
        Gtran_mode      local_tran_mode;
        Gnameset       set_names;
        Gscissor_sel    scissor_sel;
    } copy_pic_part_pic_part_store;
    struct Gcopy_ndc_pic_pic_part_store {
        Gsel_crit      sel_crit;

```

```

        Gint          pic_part_name;
        Gnameset      set_names;
    } copy_ndc_pic_pic_part_store;
    struct Gset_in_dev_mode {
        Gdev_id        dev_id;
        Gop_mode        op_mode;
    } set_in_dev_mode;
    struct Greq_in {
        Gdev_id        dev_id;
        Gin_status      in_status;
        Gin_value        log_in_value;
    } req_in;
    struct Gsample_in {
        Gdev_id        dev_id;
        Gin_value        log_in_value;
    } sample_in;
    struct Gawait_in {
        Gfloat          timeout;
        Gdev_id_in_value_list dev_id_values;
    } await_in;
    struct Gflush_dev_events {
        Gdev_id        dev_id;
    } flush_dev_events;
    struct Gset_font_ind_map {
        Gfont_ind_map  font_ind_map;
    } set_font_ind_map;
    struct Gget_glyph_name {
        Gint          font_ind;
        char          character;
        Gint          glyph_name;
    } get_glyph_name;
    struct Gset_char_code {
        Gint          font_ind;
        char          character;
        Gint          glyph_name;
    } set_char_code;
    struct Geval_tran_matrix {
        Gpoint        point;
        Gvec          shift;
        Gfloat        angle;
        Gvec          scale;
        Gcoord_switch coord_switch;
        Gtran_matrix  tran_matrix;
    } eval_tran_matrix;
    struct Gaccum_tran_matrix {
        Gtran_matrix  matrix;
        Gpoint        point;
        Gvec          shift;
        Gfloat        angle;
        Gvec          scale;
        Gcoord_switch coord_switch;
        Gtran_matrix  tran_matrix;
    }

```

```

} accum_tran_matrix;
struct Geval_circle {
    Gpoint      ctr;
    Gfloat      radius;
    Gconic_matrix circle;
} eval_circle;
struct Geval_ell {
    Gpoint      ctr;
    Gpoint      conj_radius_end_point[2];
    Gconic_matrix ell;
} eval_ell;
struct Geval_circ_arc_3_point {
    Gpoint      circ_point[3];
    Gconic_sec   circ_arc;
} eval_circ_arc_3_point;
struct Geval_circ_arc_ctr {
    Gpoint      ctr;
    Gvec        vec[2];
    Gsense_flag sense_flag;
    Gfloat      radius;
    Gconic_sec   circ_arc;
} eval_circ_arc_ctr;
struct Geval_ell_arc {
    Gpoint      ctr;
    Gpoint      conj_radius_end_point[2];
    Gvec        vec[2];
    Gconic_sec   conic_arc;
} eval_ell_arc;
struct Geval_hyp_arc {
    Gpoint      ctr;
    Gpoint      tran_radius_end_point;
    Gpoint      conj_radius_end_point;
    Gvec        vec[2];
    Gconic_sec   conic_arc;
} eval_hyp_arc;
struct Geval_par_arc {
    Gpoint      intersec_point;
    Gpoint      start_point;
    Gpoint      end_point;
    Gconic_sec   conic_arc;
} eval_par_arc;
struct Geval_wc_ord {
    Gfloat      wc_ord;
    Gord_sel    ord_sel;
    Gfloat      ndc_value;
} eval_wc_ord;
struct Gopen_ws {
    Gint        ws_id;
    void        *ws_specif_info;
    Gint        ws_gen_type;
} open_ws;
struct Gclose_ws {

```

```

    Gint          ws_id;
} close_ws;
struct Gsave_ws_sl {
    Gint          ws_id;
    Gws_sl_name_list entry_names;
    Gws_sl_entry_list entry_list;
} save_ws_sl;
struct Grestore_ws_sl {
    Gint          ws_id;
    Gws_sl_entry_list entries;
} restore_ws_sl;
struct Gget_ws_status {
    Gint          ws_id;
    Gws_status    ws_status;
} get_ws_status;
struct Gremove_backdrop {
    Gint          ws_id;
} remove_backdrop;
struct Gset_rep {
    Gint          ws_id;
    Grep          rep_value;
} set_rep;
struct Gset_view_pri {
    Gint          ws_id;
    Gint          view_ind;
    Gint          ref_view_ind;
    Grel_pri      rel_pri;
} set_view_pri;
struct Gset_view_sel_crit {
    Gint          ws_id;
    Gint          view_ind;
    Gsel_crit     sel_crit;
} set_view_sel_crit;
struct Gset_view {
    Gint          ws_id;
    Gint          ind;
    Gtran_matrix  ori_matrix;
    Gtran_matrix  map_matrix;
    Gscissor      scissor;
} set_view;
struct Gset_ws_vis_effects {
    Gint          ws_id;
    Gvis_effects_st vis_effects_st;
} set_ws_vis_effects;
struct Gset_ws_win_vp {
    Gint          ws_id;
    Gtran         ws_tran;
} set_ws_win_vp;
struct Gdef_in_dev {
    Gdev_id       dev_id;
    Gint_list     meas_set;
    Gint_list     trigger_set;

```



```

    Ginit_value    init_value;
} def_in_dev;
struct Ginit_in_dev {
    Gdev_id        dev_id;
    Ginit_value    init_value;
} init_in_dev;
struct Gset_ws_sel_crit {
    Gint           ws_id;
    Gsel           sel;
} set_ws_sel_crit;
struct Gcopy_real_pic_real_mf {
    Gint           ws_id;
    void           *mf_specif;
    Gint           pic_id;
} copy_real_pic_real_mf;
struct Gcopy_blank_real_pic_real_mf {
    Gint           ws_id;
    void           *mf_specif;
    Gint           pic_id;
} copy_blank_real_pic_real_mf;
struct Gcopy_real_mf_pic_backdrop {
    Gint           ws_id;
    void           *mf_specif;
    Gint           pic_id;
} copy_real_mf_pic_backdrop;
struct Gmessage {
    Gint           ws_id;
    char           *message;
} message;
struct Greset_specif_ws_dt_entry_st {
    Gint           ws_id;
    Gws_dt_name    ws_dt_name;
} reset_specif_ws_dt_entry_st;
struct Gget_text_extent {
    Gint           ws_id;
    Gpoint         pos;
    char           *str;
    Gtext_extent   extent;
} get_text_extent;
struct Geval_view_ori_matrix {
    Gpoint         ref_point;
    Gvec           view_up;
    Gtran_matrix   view_ori_matrix;
} eval_view_ori_matrix;
struct Geval_view_map_matrix {
    Gtran          win_vp;
    Gtran_matrix   view_map_matrix;
} eval_view_map_matrix;
struct Gconv_colr {
    Gint           ws_id;
    Gcolr_specif   colr_specif;
    Gint           colr_model;

```

```

        Gcolr_specif   colr_coords;
        Gconv_flag     conv_flag;
    } conv_colr;
    struct Gcreate_seg {
        Gint            seg_name;
    } create_seg;
    struct Grename_seg {
        Gint            old_seg_name;
        Gint            new_seg_name;
    } rename_seg;
    struct Gdel_seg {
        Gint            seg_name;
    } del_seg;
    struct Gdel_seg_ws {
        Gint            ws_id;
        Gint            seg_name;
    } del_seg_ws;
    struct Gassoc_seg_ws {
        Gint            ws_id;
        Gint            seg_name;
    } assoc_seg_ws;
    struct Gcopy_seg_ws {
        Gint            ws_id;
        Gint            seg_name;
    } copy_seg_ws;
    struct Ginsert_seg {
        Gint            seg_name;
        Gtran_matrix    tran_matrix;
    } insert_seg;
    struct Gset_seg_attr {
        Gint            seg_name;
        Gseg_attr_value seg_attr_value;
    } set_seg_attr;
    struct Gactivate_ws {
        Gint            ws_id;
    } activate_ws;
    struct Gdeactivate_ws {
        Gint            ws_id;
    } deactivate_ws;
    struct Gclear_ws {
        Gint            ws_id;
        Gctrl_flag      ctrl_flag;
    } clear_ws;
    struct Gget_map_seg_name {
        Gint            seg_name;
        Gint            map_seg_name;
    } get_map_seg_name;
    struct Gget_map_ws_id {
        Gint            ws_id;
        Gint            map_ws_id;
    } get_map_ws_id;
} func_data;

```

```
} Gfunc_params;
```

REMARK. For each field **xxx** the value of **func_id** is given by the macro **Gfn_xxx**. See sub-clause 6.1 for numerical values of **Gfn_xxx**.

Ggks_dt_entry GKS description table entry

```
typedef struct {
    Ggks_dt_name      name;          /* entry name */
    union {
        Gint_list     avail_ws_gen_types; /* list of available ws. types */
        Gint_list     avail_fonts;        /* list of available fonts */
        Gfont_ind_map def_font_ind_map;    /* default font index mapping*/
    } value;
} Ggks_dt_entry;
```

Ggks_dt_name GKS description table name

```
typedef enum {
    GGKS_DT_AVAIL_WS_GEN_TYPES, /* list of available ws. types */
    GGKS_DT_AVAIL_FONTS,        /* list of available fonts */
    GGKS_DT_DEF_FONT_IND_MAP    /* default font index mapping*/
} Ggks_dt_name;
```

Ggks_op_st GKS operating state

```
typedef enum {
    GOP_ST_GKCL,
    GOP_ST_GKOP
} Ggks_op_st;
```

Ggks_sl_entry GKS state list entry

```
typedef struct {
    Ggks_sl_name      name;          /* entry name */
    union {
        Groute_dir     route_dir;      /* route direction */
        Gscissor_mode   scissor_mode;   /* scissor mode */
        Gint_list       open_wss;        /* list of open workstations. */
        Gint_list       active_wss;      /* list of active workstations */
        Gopen_audit_list open_audits;    /* set of open audits */
        Gint_list       open_playbacks;  /* set of open playbacks */
        Gin_queue       in_queue;        /* input queue */
        Gfont_ind_map   font_ind_map;    /* font index mapping */
        Gint            pick_id;         /* pick identifier */
        Gnameset        nameset;        /* nameset */
        Gtran_matrix    global_tran_matrix; /* global
                                           transformation matrix */
        Gtran_matrix    local_tran_matrix; /* local
                                           transformation matrix */
        Gfloat_size     pat_size;        /* pattern size */
        Gpoint          pat_ref_point;   /* pattern reference point */
        Gfloat          char_ht;         /* character height */
    }
}
```

Gvec	char_up_vec;	/* character up vector	*/
Gfloat	text_skew_angle;	/* text skew angle	*/
Gtext_path	text_path;	/* text path	*/
Gtext_align	text_align;	/* text alignment	*/
Gscissor_list	scissor_set;	/* scissor set	*/
Gint	line_ind;	/* line index	*/
Gint	linetype;	/* linetype	*/
Gfloat	linewidth;	/* linewidth scale factor	*/
Gcolr_specif	line_colr_specif;	/* line colour specifier	*/
Gint	marker_ind;	/* marker index	*/
Gint	marker_type;	/* marker type	*/
Gfloat	marker_size;	/* marker size scale factor	*/
Gcolr_specif	marker_colr_specif;	/* marker colour specifier	*/
Gint	area_ind;	/* area ind	*/
Gint_style	int_style;	/* interior style	*/
Gint	int_style_ind;	/* interior style index	*/
Gcolr_specif	int_colr_specif;	/* interior colour specifier	*/
Gedge_flag	edge_flag;	/* edge flag	*/
Gint	edgetype;	/* edgetype	*/
Gfloat	edgewidth;	/* edgewidth scale factor	*/
Gcolr_specif	edge_colr_specif;	/* edge colour specifier	*/
Gint	text_ind;	/* text index	*/
Gtext_font_prec	text_font_prec;	/* text font	*/
		and precision	*/
Gfloat	char_expan;	/* character expansion factor	*/
Gfloat	char_space;	/* character spacing	*/
Gcolr_specif	text_colr_specif;	/* text colour specifier	*/
Gasfs	asfs;	/* asfs	*/
Gint	norm_tran_num;	/* current norm. tran.	*/
	number	*/	
Gtran	norm_tran[64];	/* list of norm. tran.	*/
Gint	vp_in_pri[64];	/* list of vp input pris	*/
Gint	name_open_pic_part;	/* name of open pic. part	*/
Gint_list	pic_part_names;	/* list of picture parts	*/
	in use	*/	
Gint	name_open_seg;	/* name of open segment	*/
Gint_list	seg_names;	/* list of segments	*/
	in use	*/	
Gseg_sl_list	seg_sls;	/* list of segment	*/
		state lists	*/
Gint	name_open_stencil;	/* name of open stencil	*/
Gint_list	stencil_names;	/* list of stencils	*/
	in use	*/	
Gstencil_sl_list	stencil_sls;	/* list of stencil	*/
		state lists in use	*/
Gcont_attrs	cont_attrs;	/* contour attributes	*/
Gint	name_open_tiling;	/* name of open tiling	*/
Gint_list	tiling_names;	/* list of tilings in use	*/

```

    } value;
} Ggks_sl_entry;

```

Ggks_sl_entry_list GKS state list entry list

```
typedef struct {  
    Gint      num_gks_sl_entries; /* number of entries in list */  
    Ggks_sl_entry *gks_sl_entries; /* list of entries */  
} Ggks_sl_entry_list;
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 8651-4:1995

Ggks_sl_name GKS state list name

```

typedef enum {
    GGKS_SL_ROUTE_DIR,          /* route direction          */
    GGKS_SL_SCISSOR_MODE,       /* scissor mode             */
    GGKS_SL_OPEN_WSS,           /* list of open workstations */
    GGKS_SL_ACTIVE_WSS,         /* list of active workstations */
    GGKS_SL_OPEN_AUDITS,        /* set of open audits       */
    GGKS_SL_OPEN_PLAYBACKS,     /* set of open playbacks    */
    GGKS_SL_IN_QUEUE,           /* input queue               */
    GGKS_SL_FONT_IND_MAP,       /* font index mapping        */
    GGKS_SL_PICK_ID,            /* pick identifier           */
    GGKS_SL_NAMESET,            /* nameset                   */
    GGKS_SL_GLOBAL_TRAN_MATRIX, /* global transformation matrix */
    GGKS_SL_LOCAL_TRAN_MATRIX,  /* local transformation matrix */
    GGKS_SL_PAT_SIZE,           /* pattern size              */
    GGKS_SL_PAT_REF_POINT,      /* Pattern reference point   */
    GGKS_SL_CHAR_HT,            /* Character height          */
    GGKS_SL_CHAR_UP_VEC,        /* character up vector       */
    GGKS_SL_TEXT_SKEW_ANGLE,     /* text skew angle           */
    GGKS_SL_TEXT_PATH,          /* text path                 */
    GGKS_SL_TEXT_ALIGN,         /* text alignment            */
    GGKS_SL_SCISSOR_SET,        /* scissor set               */
    GGKS_SL_LINE_IND,           /* line index                */
    GGKS_SL_LINETYPE,           /* linetype                  */
    GGKS_SL_LINEWIDTH,          /* linewidth scale factor    */
    GGKS_SL_LINE_COLR_SPECIF,   /* line colour specifier     */
    GGKS_SL_MARKER_IND,         /* marker index              */
    GGKS_SL_MARKER_TYPE,        /* marker type               */
    GGKS_SL_MARKER_SIZE,        /* marker size scale factor  */
    GGKS_SL_MARKER_COLR_SPECIF, /* marker colour specifier   */
    GGKS_SL_AREA_IND,           /* area ind                  */
    GGKS_SL_INT_STYLE,          /* interior style            */
    GGKS_SL_INT_STYLE_IND,      /* interior style index       */
    GGKS_SL_INT_COLR_SPECIF,    /* interior colour specifier  */
    GGKS_SL_EDGE_FLAG,          /* edge flag                 */
    GGKS_SL_EDGETYPE,           /* edgetype                  */
    GGKS_SL_EDGEWIDTH,          /* edgewidth scale factor    */
    GGKS_SL_EDGE_COLR_SPECIF,   /* edge colour specifier     */
    GGKS_SL_TEXT_IND,           /* text index                */
    GGKS_SL_TEXT_FONT_PREC,     /* text font and precision   */
    GGKS_SL_CHAR_EXPAN,         /* character expansion factor */
    GGKS_SL_CHAR_SPACE,         /* character spacing          */
    GGKS_SL_TEXT_COLR_SPECIF,   /* text colour specifier     */
    GGKS_SL_ASFS,               /* asfs                      */
    GGKS_SL_NORM_TRAN_NUM,      /* current norm. tran. number */
    GGKS_SL_NORM_TRANS,         /* list of norm. tran.       */
    GGKS_SL_VP_IN_PRI,          /* list of vp input pris     */
    GGKS_SL_NAME_OPEN_PIC_PART, /* name of open pic. part    */

```

```

GGKS_SL_PIC_PART_NAMES,      /* list of picture part names in use */
GGKS_SL_CONT_ATTRS,         /* contour attributes */
GGKS_SL_NAME_OPEN_SEG,      /* nme of open segment */
GGKS_SL_SEG_NAMES,          /* list of segments in use */
GGKS_SL_SEG_SLS,            /* list of segment
                             state lists */
GGKS_SL_NAME_OPEN_STENCIL,   /* name of open stencil */
GGKS_SL_STENCIL_NAMES,       /* list of stencils in use */
GGKS_SL_STENCIL_SLS,         /* list of stencil
                             state lists in use */
GGKS_SL_NAME_OPEN_TILING,    /* name of open tiling */
GGKS_SL_TILING_NAMES         /* list of tilings in use */
} Ggks_sl_name;

```

Ggks_sl_name_list GKS state list name list

```

typedef struct {
    Gint      num_gks_sl_names; /* number of names in list */
    Ggks_sl_name *gks_sl_names; /* list of names */
} Ggks_sl_name_list;

```

Ghighl highlighting

```

typedef enum {
    GSEG_NORM,
    GSEG_HIGHL
} Ghighl;

```

Ghls Hue Luminance Saturation [colour specification]

```

typedef struct {
    Gfloat hue; /* hue */
    Gfloat lightness; /* lightness */
    Gfloat satur; /* saturation */
} Ghls;

```

Ghomo_point homogeneous point

```

typedef struct {
    Gfloat xw; /* x coordinate */
    Gfloat yw; /* y coordinate */
    Gfloat w; /* w coordinate */
} Ghomo_point;

```

Ghsv Hue Saturation Value [colour specification]

```

typedef struct {
    Gfloat hue; /* hue */
    Gfloat satur; /* saturation */
    Gfloat value; /* value */
} Ghsv;

```

Gin_class input [measure] class

```

typedef enum {
    GIN_NONE,
    GIN_LOC,
    GIN_STROKE,
    GIN_VAL,
    GIN_CHOICE,
    GIN_PICK,
    GIN_STRING,
    GIN_COMP
} Gin_class;

```

Gin_data input data

```

typedef union {
    Gloc_data      loc_data;      /* locator data */
    Gstroke_data   stroke_data;   /* strokedata */
    Gval_data      val_data;      /* valuator data */
    Gchoice_data   choice_data;   /* choice data */
    Gpick_data     pick_data;     /* pick data */
    Gstring_data   string_data;   /* string data */
    Gcomp_data     comp_data;     /* composite data */
} Gin_data;

```

Gin_dev_init_value input device initial value

```

typedef struct {
    Gdev_id      dev_id;      /* device identifier */
    Ginit_value   init_value; /* initial value */
} Gin_dev_init_value;

```

Gin_dev_init_value_list input initial value list

```

typedef struct {
    Gint          num_devs;      /* number of input devices */
    Gin_dev_init_value *init_values; /* list of input initial values */
} Gin_dev_init_value_list;

```

Gin_queue input queue

```

typedef struct {
    Gint          num_items; /* number of input items */
    Gin_queue_item *in_items; /* input items */
} Gin_queue;

```

Gin_queue_item input item [in queue]

```
typedef struct {
    Gdev_id    dev_id;    /* device identifier */
    Gin_value  in_value;  /* input value */
} Gin_queue_item;
```

Gin_status [input] status

```
typedef enum {
    GIN_STATUS_NONE,
    GIN_STATUS_OK ,
    GIN_STATUS_NO_IN
} Gin_status;
```

Gin_value input value

```
typedef union {
    Gloc      loc;        /* locator value */
    Gstroke   stroke;     /* strokevalue */
    Gfloat    val;        /* valuator value */
    Gchoice   choice;     /* choice value */
    Gpick     pick;       /* pick value */
    char      *string;    /* string value */
    Gcomp_value comp;     /* composite value */
} Gin_value;
```

Ginit_in initial input

```
typedef struct {
    Gin_value  in_value;  /* input value */
    Gint       pet;       /* prompt and echo type */
    Gecho_switch echo_switch; /* echo switch */
    Glimit     echo_area; /* echo area */
    Gin_data   in_data;   /* input data */
} Ginit_in;
```

Ginit_sel initial selector

```
typedef enum {
    GSEL_INIT_VALUE, /* initial value */
    GSEL_PET,        /* prompt and echo type */
    GSEL_ECHO_SWITCH, /* echo switch */
    GSEL_ECHO_AREA,  /* echo area */
    GSEL_IN_DATA,    /* input data */
    GSEL_ALL         /* all initial input */
} Ginit_sel;
```

Ginit_value initial value

```
typedef struct {
    Ginit_sel sel; /* initial selector */
    union {
        Gin_value    init_value; /* input value */
        Gint          pet;        /* prompt and echo type */
        Gecho_switch  echo_switch; /* echo switch */
        Glimit        echo_area;  /* echo area */
        Gin_data      in_data;    /* input data */
        Ginit_in      all;        /* all initial input */
    } value;
} Ginit_value;
```

Ginq_type inquire type

```
typedef enum {
    GINQ_SET,
    GINQ_REALIZED
} Ginq_type;
```

Ginside_rule inside rule

```
typedef enum {
    GRULE_EVEN_ODD,
    GRULE_WINDING
} Ginside_rule;
```

Ginst_specif instance specifier

```

typedef struct {
    enum Ginst_type { /* instance type */
        GINST_PUT,
        GINST_ALIGN,
        GINST_MAP
    } type;
    union {
        struct Gput_inst {
            Gpoint  ref_point_inst;          /* ref. point on instance */
            Gpoint  ref_point_open_stencil; /* ref. point on
                                                open stencil */
        } put;
        struct Galign_inst {
            Gpoint  ref_point_inst;          /* ref. point on instance */
            Gpoint  dir_point_inst;         /* direction point on instance */
            Gpoint  ref_point_open_stencil; /* ref. point on
                                                open stencil */
            Gpoint  dir_point_open_stencil; /* direction point on
                                                open stencil */
        } align;
        struct Gmap_inst {
            Gpoint  ref_point_inst[3];      /* 3 ref. points on instance */
            Gpoint  corr_point_open_stencil[3]; /* 3 corr. points on
                                                open stencil */
        } map;
    } specif;
} Ginst_specif;

```

Gint_list integer list

```

typedef struct {
    Gint  num_ints; /* number of integers in list */
    Gint  *ints;    /* list of integers */
} Gint_list;

```

Gint_size integer size

```

typedef struct {
    Gint  size_x; /* x size */
    Gint  size_y; /* y size */
} Gint_size;

```

Gint_style interior style

```
typedef enum {
    GSTYLE_HOLLOW,
    GSTYLE_SOLID,
    GSTYLE_PAT,
    GSTYLE_HATCH,
    GSTYLE_EMPTY
} Gint_style;
```

Gjoin join

```
typedef struct {
    enum Gjoin_name { /* name (ROUND|BEVEL|MITRED) */
        GJOIN_ROUND,
        GJOIN_BEVEL,
        GJOIN_MITRED
    } name;
    Gfloat mitred; /* mitred value */
} Gjoin;
```

Glimit limit

```
typedef struct {
    Gfloat x_min; /* x min */
    Gfloat x_max; /* x max */
    Gfloat y_min; /* y min */
    Gfloat y_max; /* y max */
} Glimit;
```

Glimit_list limit list

```
typedef struct {
    Gint num_limits; /* number of limits in list */
    Glimit *limits; /* list of limits */
} Glimit_list;
```

Gline_attrs line attributes

```
typedef struct {
    Gasf type_asf; /* linetype ASF */
    Gasf width_asf; /* linewidth scale factor ASF */
    Gasf colr_ind_asf; /* line colour specifier ASF */
    Gint ind; /* line index */
    Gline_bundle bundle; /* line bundle */
} Gline_attrs;
```

Gline_bundle line bundle

```

typedef struct {
    Gint      type;          /* linetype          */
    Gfloat     width;        /* linewidth scale factor */
    Gcolr_kind colr_kind;    /* colour kind       */
    Gint       colr_ind;     /* colour index      */
    Gcolr_rep  dir_colr;     /* direct colour     */
} Gline_bundle;

```

Gline_bundle_table line bundle table

```

typedef struct {
    Gint      num_inds;      /* number of line indices */
    Gint      *inds;        /* list of line indices   */
    Gline_bundle *bundles;  /* list of line bundles   */
} Gline_bundle_table;

```

Gline_fac line facilities

```

typedef struct {
    Gint_list  types;        /* list of linetypes      */
    Gint       num_widths;   /* number of available linewidths */
    Gfloat     nom_width;    /* nominal linewidth      */
    Gfloat     min_width;    /* min. linewidth         */
    Gfloat     max_width;    /* max. linewidth         */
    Gint       num_pred_inds; /* number of predef. line indices */
} Gline_fac;

```

Gline_fill_ctrl_flag line/fill control flag

```

typedef enum {
    GFLAG_LINE,
    GFLAG_FILL
} Gline_fill_ctrl_flag;

```

Gloc locator value

```

typedef struct {
    Gpoint     point;        /* loc point             */
    Gint       norm_tran_num; /* norm. tran. number    */
} Gloc;

```

Gmarker_attrs marker attributes

```

typedef struct {
    Gasf      type_asf;      /* marker type ASF          */
    Gasf      size_asf;      /* marker size scale factor ASF */
    Gasf      colr_ind_asf;  /* marker colour specifier ASF */
    Gint      ind;           /* marker index              */
    Gmarker_bundle bundle;   /* marker bundle              */
} Gmarker_attrs;

```

Gmarker_bundle marker bundle

```

typedef struct {
    Gint      type;          /* marker type                */
    Gfloat     size;         /* marker size scale factor   */
    Gcolr_kind colr_kind;    /* colour kind                 */
    Gint      colr_ind;      /* colour index                */
    Gcolr_rep  dir_colr;     /* direct colour               */
} Gmarker_bundle;

```

Gmarker_bundle_table marker bundle table

```

typedef struct {
    Gint      num_inds;      /* number of marker indices   */
    Gint      *inds;        /* list of marker indices     */
    Gmarker_bundle *bundles; /* list of marker bundles     */
} Gmarker_bundle_table;

```

Gmarker_facs marker facilities

```

typedef struct {
    Gint_list types;        /* list of marker types       */
    Gint      num_sizes;    /* number of available marker sizes */
    Gfloat     nom_size;    /* nominal marker size        */
    Gfloat     min_size;    /* min. marker size           */
    Gfloat     max_size;    /* max. marker size           */
    Gint      num_pred_inds; /* number of predef. marker indices */
} Gmarker_facs;

```

Gnameset nameset

```

typedef struct {
    Gint_list ws_ids;       /* list of ws identifiers     */
    Gint_list seg_names;    /* list of segment names      */
    Gint_list names;        /* list of names               */
} Gnameset;

```

Gnum_in number [of] input [devices]

```

typedef struct {
    Gint    loc;      /* number of locator devices */
    Gint    stroke;   /* number of stroke devices */
    Gint    val;      /* number of valuator devices */
    Gint    choice;   /* number of choice devices */
    Gint    pick;     /* number of pick devices */
    Gint    string;   /* number of string devices */
    Gint    comp;     /* number of composed devices */
} Gnum_in;

```

Gnurb NURB

```

typedef struct {
    Gint    order;    /* order */
    Gctrl_point_list ctrl_point_list; /* list of control points */
    Gfloat_list weights; /* list of weight factors */
    Gfloat_list knots; /* list of knots */
    Gfloat   t_min;   /* t_min */
    Gfloat   t_max;   /* t_max */
} Gnurb;

```

Gnurb_list NURB list

```

typedef struct {
    Gint    num_nurbs; /* number of NURBs in list */
    Gnurb   *nurbs;    /* list of NURBs */
} Gnurb_list;

```

Gop_mode operating mode

```

typedef enum {
    GOP_REQ,
    GOP_SAMPLE,
    GOP_EVENT
} Gop_mode;

```

Gop_modes_init_values operating modes and initial values

```

typedef struct {
    Gint    num_in_devs; /* number of input devices */
    Gdev_id dev_ids;     /* device identifiers */
    Gop_mode op_modes;   /* operating modes */
    Ginit_in init_ins;   /* initial input values */
} Gop_modes_init_values;

```

Gop_st_entry operating state entry

```

typedef struct {
    Gop_st_name      name;          /* GKS operating state name */
    union {
        Ggks_op_st   gks;          /* GKS operating state */
        Gpic_part_op_st pic_part;  /* picture part operating state */
        Gstencil_op_st stencil;    /* stencil operating state */
        Gseg_op_st    seg;          /* segment operating state */
        Gclosed_path_op_st closed_path; /* closed path operating state */
        Gtiling_op_st tiling;      /* tiling operating state */
    } value;
} Gop_st_entry;

```

Gop_st_name operating state entry name

```

typedef enum {
    GOP_ST_GKS,          /* GKS operating state */
    GOP_ST_PIC_PART,    /* picture part operating state */
    GOP_ST_STENCIL,     /* stencil operating state */
    GOP_ST_SEG,         /* segment operating state */
    GOP_ST_CLOSED_PATH, /* closed path operating state */
    GOP_ST_TILING       /* tiling operating state */
} Gop_st_name;

```

Gopen_audit_list open audit list

```

typedef struct {
    Gint      num_audits; /* number of audits */
    Gint      *audit_ids; /* list of audit identifiers */
    Gaudit_flag *audit_flags; /* list of audit flags */
} Gopen_audit_list;

```

Gord_sel ordinate selector

```

typedef enum {
    GORD_X,
    GORD_Y
} Gord_sel;

```

Gpat_rep pattern representation

```

typedef struct {
    Gint_size    dims;           /* colour array's dimensions */
    Gcolr_kind   colr_kind;      /* colour kind                */
    Gint         *colr_array;    /* colour array               */
    union {
        Grgb     *rgb;          /* RGB colours                */
        Gcieluv  *cieluv;       /* CIELUV colours             */
        Ghls     *hls;          /* HLS colours                */
        Ghsv     *hsv;          /* HSV colours                */
    } dir_colr;
} Gpat_rep;

```

Gpat_table pattern table

```

typedef struct {
    Gint    num_inds;    /* number of pattern indices */
    Gint    *inds;      /* list of pattern indices   */
    Gpat_rep *pat_reps; /* list of pattern representations */
} Gpat_table;

```

Gpath path

```

typedef struct {
    enum Gpath_type { /* path type */
        GPATH_LINE,
        GPATH_NURB,
        GPATH_CONIC_SEC
    } type;
    union {
        Gpoint_list polyline; /* polyline */
        Gnurb        nurb;    /* NURB */
        Gconic_sec   conic_sec; /* conic section */
    } value;
} Gpath;

```

Gpath_list path list

```

typedef struct {
    Gint    num_paths; /* number of paths in list */
    Gpath   *paths;    /* list of paths           */
} Gpath_list;

```

Gpath_specif path specifier

```
typedef struct {
    Gabut_specif  abut_specif;  /* Abut specifier    */
    Gpath         path;         /* path              */
    Gpoint        ref_point;    /* reference point   */
} Gpath_specif;
```

Gpic_part_op_st picture part operating state

```
typedef enum {
    GOP_ST_PPCL,
    GOP_ST_PPOP
} Gpic_part_op_st;
```

Gpick pick [value]

```
typedef struct {
    Gpick_status  status;      /* status            */
    Gnameset      set_names;   /* set of names      */
    Gint          seg_name;    /* segment name      */
    Gint          pick_id;     /* pick identifier   */
} Gpick;
```

Gpick_status pick status

```
typedef enum {
    GPICK_OK,
    GPICK_NO_PICK
} Gpick_status;
```

Gplayback_op playback operation

```
typedef struct {
    enum Gplayback_op_type {
        GPLAYBACK_OPEN, GPLAYBACK_CLOSE
    } type;
    void *specif; /* audit specifier */
} Gplayback_op;
```

Gpoint point

```
typedef struct {
    Gfloat x; /* x coordinate */
    Gfloat y; /* y coordinate */
} Gpoint;
```

Gpoint_list point list

```
typedef struct {  
    Gint    num_points;    /* number of points in the list */  
    Gpoint  *points;       /* list of points */  
} Gpoint_list;
```

Gpoint_list_list list of point lists

```
typedef struct {  
    Gint    num_point_lists; /* number of point lists in the list */  
    Gpoint_list *point_lists; /* list of point lists */  
} Gpoint_list_list;
```

Gpr_flag prompt flag

```
typedef enum {  
    GPR_OFF,  
    GPR_ON  
} Gpr_flag;
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 8651-4:1995

Gprim_attr_name primitive attribute name

```

typedef enum {
    GNAME_PICK_ID,          /* pick identifier          */
    GNAME_NAMESET,          /* nameset                  */
    GNAME_SCISSOR_SET,      /* scissor set              */
    GNAME_GLOBAL_TRAN_MATRIX, /* global transformation matrix */
    GNAME_LOCAL_TRAN_MATRIX, /* local transformation matrix */
    GNAME_PAT_SIZE,         /* pattern size             */
    GNAME_PAT_REF_POINT,    /* pattern reference point   */
    GNAME_CHAR_HT,          /* character height         */
    GNAME_CHAR_UP_VEC,      /* character up vector       */
    GNAME_TEXT_SKEW_ANGLE,  /* text skew angle          */
    GNAME_TEXT_PATH,        /* text path                */
    GNAME_TEXT_ALIGN,       /* text alignment           */
    GNAME_LINE_IND,         /* line index               */
    GNAME_LINETYPE,         /* linetype                 */
    GNAME_LINEWIDTH,        /* linewidth scale factor   */
    GNAME_LINE_COLR_SPECIF, /* line colour specifier    */
    GNAME_MARKER_IND,       /* marker index             */
    GNAME_MARKER_TYPE,      /* marker type              */
    GNAME_MARKER_SIZE,      /* marker size scale factor */
    GNAME_MARKER_COLR_SPECIF, /* marker colour specifier  */
    GNAME_AREA_IND,         /* area index               */
    GNAME_INT_STYLE,        /* interior style           */
    GNAME_INT_STYLE_IND,    /* interior style index     */
    GNAME_INT_COLR_SPECIF,  /* interior colour specifier */
    GNAME_EDGE_FLAG,        /* edge flag                */
    GNAME_EDGETYPE,         /* edgetype                 */
    GNAME_EDGEWIDTH,        /* edgewidth scale factor   */
    GNAME_EDGE_COLR_SPECIF, /* edge colour specifier    */
    GNAME_TEXT_IND,         /* text index               */
    GNAME_TEXT_FONT_PREC,   /* text font and precision  */
    GNAME_CHAR_EXPAN,       /* character expansion factor */
    GNAME_CHAR_SPACE,       /* character spacing         */
    GNAME_TEXT_COLR_SPECIF, /* text colour specifier    */
    GNAME_ASFS              /* asfs                     */
} Gprim_attr_name;

```

Gprim_attr_value primitive attribute value

```

typedef struct {
    Gprim_attr_name name; /* primitive attribute name */
    union {
        Gint      pick_id;          /* pick identifier */
        Gnameset  nameset;          /* nameset */
        Gscissor_list scissor_set;  /* scissor set */
        Gtran_matrix global_tran_matrix; /* global transformation matrix */
        Gtran_matrix local_tran_matrix; /* local transformation matrix */
        Gfloat_size pat_size;        /* pattern size */
        Gpoint     pat_ref_point;    /* pattern reference point */
        Gfloat      char_ht;         /* character height */
        Gvec        char_up_vec;     /* character up vector */
        Gfloat      text_skew_angle; /* text skew angle */
        Gtext_path  text_path;       /* text path */
        Gtext_align text_align;      /* text alignment */
        Gint        line_ind;        /* line index */
        Gint        linetype;        /* linetype */
        Gfloat      linewidth;       /* linewidth scale factor */
        Gcolr_specif line_colr_specif; /* line colour specifier */
        Gint        marker_ind;      /* marker index */
        Gint        marker_type;     /* marker type */
        Gfloat      marker_size;     /* marker size scale factor */
        Gcolr_specif marker_colr_specif; /* marker colour specifier */
        Gint        area_ind;        /* area ind */
        Gint_style  int_style;        /* interior style */
        Gint        int_style_ind;    /* interior style index */
        Gcolr_specif int_colr_specif; /* interior colour specifier */
        Gedge_flag  edge_flag;       /* edge flag */
        Gint        edgetype;        /* edgetype */
        Gfloat      edgewidth;       /* edgewidth scale factor */
        Gcolr_specif edge_colr_specif; /* edge colour specifier */
        Gint        text_ind;        /* text index */
        Gtext_font_prec text_font_prec; /* text font and precision */
        Gfloat      char_expan;      /* character expansion factor */
        Gfloat      char_space;      /* character spacing */
        Gcolr_specif text_colr_specif; /* text colour specifier */
        Gasfs       asfs;           /* asfs */
    };

```

```

    }value;
} Gprim_attr_value;

```

Gprim_params primitive parameters

```

typedef struct {
    Gprim_type type; /* primitive type */
    union {
        Gpoint_list_list    polyline_set;    /* polyline set*/
        Gnurb_list          nurb_set;        /* NURB set*/
        Gconic_sec_list     conic_sec_set;    /* conic section set*/

        Gpoint_list         polymarker;      /* polymarker */

        Gpoint_list_list    fill_area_set;    /* fill area set*/
        Gnurb_list          closed_nurb_set;  /* closed NURB set*/
        Gconic_sec_list     ell_sec_set;      /* elliptic sector set*/
        Gconic_sec_list     ell_seg_set;      /* elliptic segment set*/
        Gell_disc_list      ell_disc_set;     /* elliptic disc set*/

        struct Gtext {
            char            *string;          /* character string */
            Gpoint          pos;              /* text position */
        } text;

        struct Gcell_array {
            Grect           rect;              /* cell rectangle */
            Gpat_rep        array;             /* cell array */
        } cell_array;

        Gdesign             design;            /* design */

        struct Ggdp {
            Gpoint_list     point_list;        /* point_list */
            Gint            id;                /* gdp identifier */
            Ggdp_data       gdp_data;         /* gdp_data */
        } gdp;
    } value;
} Gprim_params;

```

Gprim_type primitive type

```
typedef enum {  
    GPRIM_LINE_SET,  
    GPRIM_NURB_SET,  
    GPRIM_CONIC_SEC_SET,  
    GPRIM_MARKER,  
    GPRIM_FILL_SET,  
    GPRIM_CLOSED_NURB_SET,  
    GPRIM_ELL_SEC_SET,  
    GPRIM_ELL_SEG_SET,  
    GPRIM_ELL_DISC_SET,  
    GPRIM_TEXT,  
    GPRIM_CELL_ARRAY,  
    GPRIM_DESIGN,  
    GPRIM_GDP  
} Gprim_type;
```

Gproc_op process operation

```
typedef enum {  
    GPROC_SKIP,  
    GPROC_DO  
} Gproc_op;
```

Grect rectangle

```
typedef struct {  
    Gpoint p; /* point p */  
    Gpoint q; /* point q */  
} Grect;
```

Grel_pos relative position

```
typedef enum {  
    GPOS_FRONT,  
    GPOS_BACK  
} Grel_pos;
```

Grel_pri relative priority

```
typedef enum {  
    GPRI_HIGHER,  
    GPRI_LOWER  
} Grel_pri;
```

Grep representation

```

typedef struct {
    Gint ind; /* index */
    enum Grep_design { /* representation designation */
        GREP_LINE,      /* line bundle */
        GREP_MARKER,    /* marker bundle */
        GREP_AREA,      /* area bundle */
        GREP_PAT,       /* pattern representation */
        GREP_TEXT,      /* text bundle */
        GREP_COLR,      /* colr specification */
        GREP_UNDEF      /* undefined */
    } design;
    union {
        Gline_bundle    line_bundle; /* line bundle */
        Gmarker_bundle  marker_bundle; /* marker bundle */
        Gtext_bundle    text_bundle; /* text bundle */
        Gareal_bundle   area_bundle; /* area bundle */
        Gpat_rep        pat_rep; /* pattern representation */
        Gcolr_specif    colr_specif; /* colour specification */
    } value;
} Grep;

```

Grepl_tech replication technique

```

typedef struct {
    enum Grepl_dir {
        GREPL_DX,
        GREPL_DY,
        GREPL_DXY,
        GREPL_DYX
    } dir;
    union {
        Gfloat dx; /* dx */
        Gfloat dy; /* dy */
        Gvec dxy; /* dxy */
        Gvec dyx; /* dyx */
    } value;
} Grepl_tech;

```

Grgb Red Green Blue [colour specification]

```

typedef struct {
    Gfloat red; /* red intensity */
    Gfloat green; /* green intensity */
    Gfloat blue; /* blue intensity */
} Grgb;

```

Groute_dir direction

```
typedef enum {
    GDIR_NDC,
    GDIR_BACKDROP
} Groute_dir;
```

Gscissor scissor

```
typedef struct {
    Gclip_ind    clip_ind;           /* clipping indicator */
    Glimit_list  clip_rect_set;      /* clipping rectangle set */
    Gshield_ind  shield_ind;         /* shielding indicator */
    Glimit_list  shield_rect_set;     /* shielding rectangle set */
} Gscissor;
```

Gscissor_list scissor list

```
typedef struct {
    Gint         num_scissors;       /* number of scissors in list */
    Gint         *scissor_ids;       /* list of scissor identifications */
    Gscissor     *scissors;          /* list of scissors */
} Gscissor_list;
```

Gscissor_mode scissor mode

```
typedef enum {
    GSCISSOR_LOCUS,
    GSCISSOR_SHAPE
} Gscissor_mode;
```

Gscissor_sel scissor select

```
typedef enum {
    GSCISSOR_CHANGE,
    GSCISSOR_LEAVE
} Gscissor_sel;
```

Gseg_attr_name segment attribute name

```
typedef enum {
    GNAME_TRAN_MATRIX, /* transformation matrix */
    GNAME_VIS,          /* visibility */
    GNAME_HIGHL,        /* hightlighting */
    GNAME_PRI,          /* segment priority */
    GNAME_DET           /* detectability */
} Gseg_attr_name;
```

Gseg_attr_value segment attribute value

```

typedef struct {
    Gseg_attr_name name; /* segment attribute name */
    union {
        Gtran_matrix  tran_matrix; /* transformation matrix */
        Gvis           vis;         /* visibility */
        Ghighl         highl;       /* hightlighting */
        Gfloat         pri;         /* segment priority */
        Gdet           det;         /* detectability */
    } value;
} Gseg_attr_value;

```

Gseg_attrs segment attributes

```

typedef struct {
    Gtran_matrix  tran_matrix; /* transformation matrix */
    Gvis           vis;         /* visibility */
    Ghighl         highl;       /* hightlighting */
    Gfloat         pri;         /* segment priority */
    Gdet           det;         /* detectability */
} Gseg_attrs;

```

Gseg_op_st segment operating state

```

typedef enum {
    GOP_ST_SGCL,
    GOP_ST_SGOP
} Gseg_op_st;

```

Gseg_sl segment state list

```

typedef struct {
    Gint          name;         /* segment name */
    Gint_list     assoc_wss;    /* associated workstations */
    Gseg_attrs    attrs;       /* segment attributes */
} Gseg_sl;

```

Gseg_sl_list list of segment state lists

```

typedef struct {
    Gint          num_seg_sls; /* number of segment state lists in list */
    Gseg_sl       *seg_sls;    /* list of segment state lists */
} Gseg_sl_list;

```

Gsel selection

```

typedef struct {
    Gsel_crit_type  type; /* selection type */
    Gsel_crit       crit; /* selection criterion */
} Gsel;

```

Gsel_crit selection criterion

```

typedef struct GSEL_CRIT *Gsel_crit_ptr;
typedef struct GSEL_CRIT {
    Gsel_crit_op      op;                /* operation */
    union {
        Gnameset      compar;           /* comparison
                                         (EQUALS|CONTAINS|IS-IN) */;
        struct Gdyad_sel_crit {
            Gsel_crit_ptr left;          /* left selection operand */
            Gsel_crit_ptr right;         /* right selection operand */
        } dyad;                          /* dyadic criterion (AND|OR) */
        Gsel_crit_ptr monad;             /* monadic criterion (NOT) */
    } value;
} Gsel_crit;

```

Gsel_crit_op selection criterion operation

```

typedef enum {
    GOP_CONTAINS,
    GOP_IS_IN,
    GOP_EQUALS,
    GOP_SEL_ALL,
    GOP_REJ_ALL,
    GOP_AND,
    GOP_OR,
    GOP_NOT
} Gsel_crit_op;

```

Gsel_crit_type selection criterion type

```

typedef enum {
    GSEL_DISP,
    GSEL_HIGHL,
    GSEL_DET
} Gsel_crit_type;

```

Gsel_table selection table

```

typedef struct {
    Gint  num_sels; /* number of selections */
    Gsel  *sels;    /* table of selections */
} Gsel_table;

```

Gsense_flag sense flag

```

typedef enum {
    GFLAG_CLOCKWISE,
    GFLAG_ANTI_CLOCKWISE
} Gsense_flag;

```

Gseq_specif sequence specifier

```
typedef struct {
    Gint    inst_name;      /* instance name          */
    Gint    stencil_name;   /* existing stencil name   */
    Gpoint  ref_point;      /* reference point         */
} Gseq_specif;
```

Gseq_specif_list sequence specifier list

```
typedef struct {
    Gint    num_seq_specifs; /* number of sequence specifiers */
    Gseq_specif *seq_specif; /* list of sequence specifiers   */
} Gseq_specif_list;
```

Gshield_ind shielding indicator

```
typedef enum {
    GIND_NO_SHIELD,
    GIND_SHIELD
} Gshield_ind;
```

Gstencil_attr_name stencil attribute name

```
typedef enum {
    GNAME_TOP_Y,
    GNAME_CAP_Y,
    GNAME_HALF_Y,
    GNAME_BASE_Y,
    GNAME_BOTTOM_Y,
    GNAME_CTR_Y,
    GNAME_LEFT_X,
    GNAME_RIGHT_X,
    GNAME_CTR_X,
    GNAME_CTR,
    GNAME_ORIGIN,
    GNAME_CTR_TOP,
    GNAME_CTR_BOTTOM,
    GNAME_CTR_LEFT,
    GNAME_CTR_RIGHT,
    GNAME_TOP_LEFT,
    GNAME_TOP_RIGHT,
    GNAME_BOTTOM_LEFT,
    GNAME_BOTTOM_RIGHT
} Gstencil_attr_name;
```

Gstencil_attr_value stencil attribute value

```

typedef struct {
    Gstencil_attr_name  name;          /* attribute name */
    union {
        Gfloat          top_y;         /* top y          */
        Gfloat          half_y;        /* half y         */
        Gfloat          base_y;        /* base y         */
        Gfloat          bottom_y;      /* bottom y       */
        Gfloat          ctr_y;         /* centre y       */
        Gfloat          left_x;        /* left x         */
        Gfloat          ctr_x;         /* centre x       */
        Gfloat          right_x;       /* right x        */
        Gpoint          ctr;          /* centre         */
        Gpoint          origin;        /* origin         */
        Gpoint          ctr_top;       /* centre top     */
        Gpoint          ctr_bottom;    /* centre bottom  */
        Gpoint          ctr_left;      /* centre left    */
        Gpoint          ctr_right;     /* centre right   */
        Gpoint          top_left;      /* top left       */
        Gpoint          top_right;     /* top right      */
        Gpoint          bottom_left;   /* bottom left    */
        Gpoint          bottom_right;  /* bottom right   */
    } value;
} Gstencil_attr_value;

```

Gstencil_attrs stencil attributes

```

typedef struct {
    Gfloat  top_y;         /* top y          */
    Gfloat  cap_y;         /* cap y          */
    Gfloat  half_y;        /* half y         */
    Gfloat  base_y;        /* base y         */
    Gfloat  bottom_y;      /* bottom y       */
    Gfloat  ctr_y;         /* centre y       */
    Gfloat  left_x;        /* left x         */
    Gfloat  ctr_x;         /* centre x       */
    Gfloat  right_x;       /* right x        */
    Gpoint  ctr;          /* centre         */
    Gpoint  origin;       /* origin         */
    Gpoint  ctr_top;      /* centre top     */
    Gpoint  ctr_bottom;   /* centre bottom  */
    Gpoint  ctr_right;    /* centre right   */
    Gpoint  top_left;     /* top left       */
    Gpoint  top_right;    /* top right      */
    Gpoint  bottom_left;  /* bottom left    */
    Gpoint  bottom_right; /* bottom right   */
} Gstencil_attrs;

```

Gstencil_op_st stencil operating state

```
typedef enum {
    GOP_ST_STCL,
    GOP_ST_STOP
} Gstencil_op_st;
```

Gstencil_sl stencil state list

```
typedef struct {
    Gint          name;      /* stencil name          */
    Gstencil_attrs attrs;    /* stencil attributes    */
} Gstencil_sl;
```

Gstencil_sl_list list of stencil state lists

```
typedef struct {
    Gint          num_stencil_sls; /* number of stencil_sls in the list */
    Gstencil_sl   *stencil_sls;   /* list of stencil_sls              */
} Gstencil_sl_list;
```

Gstore store

```
typedef void *Gstore;
```

Gstroke stroke value

```
typedef struct {
    Gpoint_list point_list; /* stroke point list */
    Gint         norm_tran_num; /* norm. tran. number */
} Gstroke;
```

Gtext_align text alignment

```
typedef struct {
    enum Ghor_text_align { /* horizontal text alignment */
        GHOR_NORM,
        GHOR_LEFT,
        GHOR_CTR,
        GHOR_RIGHT
    } hor;
    enum Gvert_text_align { /* vertical text alignment */
        GVERT_NORM,
        GVERT_TOP,
        GVERT_CAP,
        GVERT_HALF,
        GVERT_BASE,
        GVERT_BOTTOM
    } vert;
} Gtext_align;
```

Gtext_bundle text bundle

```

typedef struct {
    Gtext_font_prec    text_font_prec;    /* text font and precision    */
    Gfloat             char_expan;        /* character expansion factor */
    Gfloat             char_space;        /* character spacing          */
    Gcolr_kind         colr_kind;         /* colour kind                */
    Gint               colr_ind;         /* colour index               */
    Gcolr_rep          dir_colr;         /* direct colour              */
} Gtext_bundle;

```

Gtext_bundle_table text bundle table

```

typedef struct {
    Gint             num_inds;    /* number of character indices */
    Gint             *inds;       /* list of character indices    */
    Gtext_bundle     *bundles;    /* list of text bundles         */
} Gtext_bundle_table;

```

Gtext_extent text extent

```

typedef struct {
    Gpoint    concat_point;    /* concatenation point    */
    Gpoint    paral[4];        /* text extent parallelogram */
} Gtext_extent;

```

Gtext_facs text facilities

```

typedef struct {
    Gint             num_font_precs;    /* number of fonts and precisions */
    Gtext_font_prec *font_precs;        /* list of fonts and precisions    */
    Gint             num_char_hts;      /* number of character heights     */
    Gfloat           min_char_ht;        /* min. character height           */
    Gfloat           max_char_ht;        /* max. character height           */
    Gint             num_char_expans;    /* number of char. expansion      */
                                           /* factors                         */
    Gfloat           min_char_expan;     /* min. expansion factor           */
    Gfloat           max_char_expan;     /* max. expansion factor           */
    Gint             num_pred_inds;     /* number of predef. text indices  */
} Gtext_fac;

```

Gtext_font_prec text font [and] precision

```

typedef struct {
    Gint             font;    /* character font */
    Gtext_prec       prec;    /* text precision */
} Gtext_font_prec;

```

Gtext_path text path

```
typedef enum {
    GPATH_RIGHT,
    GPATH_LEFT,
    GPATH_UP,
    GPATH_DOWN
} Gtext_path;
```

Gtext_prec text precision

```
typedef enum {
    GPREC_STRING,
    GPREC_CHAR,
    GPREC_STROKE
} Gtext_prec;
```

Gtiling_op_st tiling operating state

```
typedef enum {
    GOP_ST_TLCL,
    GOP_ST_TLOP
} Gtiling_op_st;
```

Gtiling_params tiling parameters

```
typedef struct {
    Gtiling_type      type;          /* tiling type */
    union {
        struct Gtiling_line_area { /* line or area primitives in tiling */
            Gcolr_specif  colr_specif; /* colour specifier */
            union { /* geometric data of line or area primitive */
                Gpoint_list_list  polyline_set; /* polyline set*/
                Gnurb_list        nurb_set; /* NURB set*/
                Gconic_sec_list    conic_sec_set; /* conic section set*/

                Gpoint_list_list  fill_area_set; /* fill area set*/
                Gnurb_list        closed_nurb_set; /* closed NURB set*/
                Gconic_sec_list    ell_sec_set; /* elliptic sector set*/
                Gconic_sec_list    ell_seg_set; /* elliptic segment set*/
                Gell_disc_list     ell_disc_set; /* elliptic disc set*/
            } geom_data;
        } tiling_line_area;
        Gdesign              design; /* design */
    } value;
} Gtiling_params;
```

Gtiling_type tiling type

```

typedef enum {
    GTILING_LINE_SET,
    GTILING_NURB_SET,
    GTILING_CONIC_SEC_SET,
    GTILING_FILL_SET,
    GTILING_CLOSED_NURB_SET,
    GTILING_ELL_SEC_SET,
    GTILING_ELL_SEG_SET,
    GTILING_ELL_DISC_SET,
    GTILING_DESIGN
} Gtiling_type;

```

Gtran transformation

```

typedef struct {
    Glimit  win;  /* window      */
    Glimit  vp;   /* viewport   */
} Gtran;

```

Gtran_matrix transformation matrix

```

typedef Gfloat Gtran_matrix[2][3];

```

Gtran_mode transformation mode

```

typedef enum {
    GTRAN_REPLACE,
    GTRAN_PRE,
    GTRAN_POST
} Gtran_mode;

```

Gvec vector

```

typedef struct {
    Gfloat  delta_x;  /* x coordinate */
    Gfloat  delta_y;  /* y coordinate */
} Gvec;

```

Gview_rep view representation

```

typedef struct {
    Gsel_crit  sel_crit;  /* view selection criterion */
    Gtran_matrix  ori_matrix;  /* view orientation matrix */
    Gtran_matrix  map_matrix;  /* view mapping matrix */
    Gscissor  scissor;  /* view scissor */
} Gview_rep;

```

Gvis visibility

```
typedef enum {  
    GSEG_INVIS,  
    GSEG_VIS  
} Gvis;
```

Gvis_effects_st visual effects state

```
typedef enum {  
    GST_SUPPR,  
    GST_ALLOW  
} Gvis_effects_st;
```

Gws_class workstation classification [display kind]

```
typedef enum {  
    GCLASS_VEC,  
    GCLASS_RASTER,  
    GCLASS_OTHER  
} Gws_class;
```

Gws_dt_entry workstation description table entry

```

typedef struct {
    Gws_dt_name          name;          /* entry name */
    union {
        Gws_type         type;          /* workstation type */
        Gws_status        ws_status;     /* ws. status */
        Gdc_units          dc_units;      /* DC units */
        Gdisp_space_size  disp_space_size; /* displace space size */
        Gws_class          ws_class;      /* ws. classification */
        Gline_facs         line_facs;     /* line facilities */
        Gline_bundle_table pred_line_bundles; /* predefined line bundle table */
        Gmarker_facs       marker_facs;   /* marker facilities */
        Gmarker_bundle_table pred_marker_bundles; /* predefined marker bundle table */
        Gareafacs          area_facs;     /* area facilities */
        Gareafacs_bundle_table pred_area_bundles; /* predefined area bundle table */
        Gpat_table         pred_pat_reps; /* predefined pattern bundle table */
        Gtext_facs         text_facs;     /* text facilities */
        Gtext_bundle_table pred_text_bundles; /* predefined text bundle table */
        Gcolr_facs         colr_facs;     /* colour facilities */
        Gcolr_table        pred_colr_reps; /* predefined colour bundle table */
        Gint_list          gdp_ids;       /* list of available GDPs */
        Gdev_id_list       dev_ids;       /* list of available input devices */
        Gin_dev_init_value_list in_init_values; /* input device initial values */
        Gint_list          meas_ids;      /* list of available measures */
        Gint_list          trigger_ids;    /* list of available triggers */
        Gdev_comp_list     dev_comps;     /* device compositions */
    } value;
} Gws_dt_entry;

```

Gws_dt_name workstation description table name

```
typedef enum {  
    GWS_DT_TYPE,  
    GWS_DT_STATUS,  
    GWS_DT_DC_UNITS,  
    GWS_DT_DISP_SPACE_SIZE,  
    GWS_DT_CLASS,  
    GWS_DT_LINE_FACS,  
    GWS_DT_LINE_BUNDLE_TABLE,  
    GWS_DT_MARKER_FACS,  
    GWS_DT_MARKER_BUNDLE_TABLE,  
    GWS_DT_AREA_FACS,  
    GWS_DT_AREA_BUNDLE_TABLE,  
    GWS_DT_PAT_TABLE,  
    GWS_DT_TEXT_FACS,  
    GWS_DT_TEXT_BUNDLE_TABLE,  
    GWS_DT_COLR_FACS,  
    GWS_DT_COLR_TABLE,  
    GWS_DT_GDP_IDS,  
    GWS_DT_DEV_IDS,  
    GWS_DT_IN_DEV_INIT_VALUES,  
    GWS_DT_MEAS_IDS,  
    GWS_DT_TRIGGER_IDS,  
    GWS_DT_DEV_COMPS  
} Gws_dt_name;
```

Gws_sl_entry workstation state list entry

```

typedef struct {
    Gws_sl_name      name;          /* entry name */
    union {
        Gws_st       ws_st;        /* ws. state
                                   (ACTIVE|INACTIVE) */
        struct {
            void       *specif;     /* specifier and type */
            Gint       type;
            Gline_bundle_table line_bundle_table; /* line bundle
                                                    table */
            Gmarker_bundle_table marker_bundle_table; /* marker
                                                    bundle table */
            Gtext_bundle_table text_bundle_table; /* text
                                                    bundle table */
            Garea_bundle_table area_bundle_table; /* area
                                                    bundle table */
            Gpat_table pat_table; /* pattern
                                   bundle table */
            Gcolr_table colr_table; /* colour
                                   bundle table */
            Gtran       ws_win_vp; /* window
                                   and viewport */
            Gvis_effects_st vis_effects_st; /* visual effects
                                   state */
            Gop_modes_init_values op_modes_init_values; /* input device
                                   operating modes
                                   and initial values */
            Gsel_table sel_table; /* selection table */
            Gint_list stored_segs; /* set of
                                   stored segments */
            Gview_rep view_rep[16]; /* view bundle table */
            Gint view_pri[16]; /* view priorities */
        } entry;
    } Gws_sl_entry;

```

Gws_sl_entry_list workstation state list entry value list

```

typedef struct {
    Gint      num_entries; /* number of WSL entry values
                           in list */
    Gws_sl_entry *entries; /* list of WSL entry values */
} Gws_sl_entry_list;

```

Gws_sl_name workstation state list name

```

typedef enum{
    GWS_SL_ST,
    GWS_SL_CONN_TYPE,
    GWS_SL_LINE_BUNDLE_TABLE,
    GWS_SL_MARKER_BUNDLE_TABLE,
    GWS_SL_TEXT_BUNDLE_TABLE,
    GWS_SL_AREA_BUNDLE_TABLE,
    GWS_SL_PAT_TABLE,
    GWS_SL_COLR_TABLE,
    GWS_SL_WIN_VP,
    GWS_SL_VIS_EFFECTS_ST,
    GWS_SL_OP_MODES_INIT_VALS,
    GWS_SL_SEL_TABLE,
    GWS_SL_STORED_SEGS,
    GWS_SL_VIEW_TABLE,
    GWS_SL_VIEW_PRIS
} Gws_sl_name;

```

Gws_sl_name_list workstation state list entry name list

```

typedef struct {
    Gint      num_names; /* number of WSL entry names in list */
    Gws_sl_name *names; /* list of WSL entry names */
} Gws_sl_name_list;

```

Gws_st workstation state

```

typedef enum {
    GWS_INACTIVE,
    GWS_ACTIVE
} Gws_st;

```

Gws_status workstation status

```

typedef enum {
    GWS_UP_TO_DATE,
    GWS_NOT_UP_TO_DATE
} Gws_status;

```

Gws_type workstation type

```

typedef struct {
    Gint  gen_type; /* generic type */
    void *specif_info; /* specific information */
} Gws_type;

```

6 Macro definitions

6.1 Function identifiers

The error functions require a unique mapping of the GKS functions to a set of numbers. The names for these function identifiers are the same as the GKS function names except that the sentinel character has been replaced by "Gfn_".

Below, the function identifier macros are listed, with their numerical values. These values are identical with the values of the function identifiers in the previous edition of ISO/IEC 8651-4, if the corresponding functions were also defined in the 1991 edition.

6.1.1 In order of appearance

```

#define Gfn_open_gks (0)
#define Gfn_close_gks (1)
#define Gfn_save_gks_sl (200)
#define Gfn_restore_gks_sl (201)
#define Gfn_escape (11)
#define Gfn_emergency_close_gks (153)
#define Gfn_err_hand (154)
#define Gfn_err_log (155)
#define Gfn_route (202)
#define Gfn_create_out_prim (203)
#define Gfn_polyline (12)
#define Gfn_polyline_set (204)
#define Gfn_nurb_set (205)
#define Gfn_conic_sec_set (206)
#define Gfn_polymarker (13)
#define Gfn_fill_area (15)
#define Gfn_fill_area_set (207)
#define Gfn_ell_sec_set (208)
#define Gfn_ell_seg_set (209)
#define Gfn_ell_disc_set (210)
#define Gfn_closed_nurb_set (211)
#define Gfn_text (14)
#define Gfn_cell_array (16)
#define Gfn_design (212)
#define Gfn_gdp (17)
#define Gfn_open_stencil (213)
#define Gfn_close_stencil (214)
#define Gfn_rename_stencil (215)
#define Gfn_del_stencil (216)
#define Gfn_create_stencil_bndry (217)
#define Gfn_create_stencil_conts (218)
#define Gfn_set_cont_attr (219)
#define Gfn_set_stencil_attr (220)
#define Gfn_get_stencil_attr (221)
#define Gfn_inst_stencil (222)
#define Gfn_inst_stencil_path (223)
#define Gfn_inst_stencil_seq_path (224)
#define Gfn_open_tiling (225)

```

```

#define Gfn_close_tiling (226)
#define Gfn_rename_tiling (227)
#define Gfn_del_tiling (228)
#define Gfn_create_tiling_comp (229)
#define Gfn_set_prim_attr (230)
#define Gfn_set_line_ind (18)
#define Gfn_set_linetype (19)
#define Gfn_set_linewidth (20)
#define Gfn_set_line_colr_specif (231)
#define Gfn_set_line_colr_ind (21)
#define Gfn_set_marker_ind (22)
#define Gfn_set_marker_type (23)
#define Gfn_set_marker_size (24)
#define Gfn_set_marker_colr_specif (232)
#define Gfn_set_marker_colr_ind (25)
#define Gfn_set_text_ind (26)
#define Gfn_set_text_font_prec (27)
#define Gfn_set_char_expan (28)
#define Gfn_set_char_space (29)
#define Gfn_set_text_colr_specif (233)
#define Gfn_set_text_colr_ind (30)
#define Gfn_set_char_ht (31)
#define Gfn_set_char_up_vec (32)
#define Gfn_set_text_path (33)
#define Gfn_set_text_align (34)
#define Gfn_set_text_skew_angle (234)
#define Gfn_set_area_ind (235)
#define Gfn_set_int_style (236)
#define Gfn_set_int_style_ind (237)
#define Gfn_set_int_colr_specif (238)
#define Gfn_set_int_colr_ind (239)
#define Gfn_set_pat_size (39)
#define Gfn_set_pat_ref_point (40)
#define Gfn_set_global_tran_matrix (240)
#define Gfn_set_local_tran_matrix (241)
#define Gfn_set_edge_flag (242)
#define Gfn_set_edgetype (243)
#define Gfn_set_edgewidth (244)
#define Gfn_set_edge_colr_specif (245)
#define Gfn_set_edge_colr_ind (246)
#define Gfn_set_asfs (41)
#define Gfn_set_pick_id (42)
#define Gfn_set_nameset (247)
#define Gfn_set_scissor_set (248)
#define Gfn_add_set_names_nameset (249)
#define Gfn_remove_set_names_nameset (250)
#define Gfn_add_set_scissors_scissor_set (251)
#define Gfn_remove_set_scissors_scissor_set (252)
#define Gfn_set_win_vp (49)
#define Gfn_set_win (49)
#define Gfn_set_vp (50)
#define Gfn_set_vp_in_pri (50)

```


#define	Gfn_set_scissor_mode	(253)
#define	Gfn_set_norm_tran_num	(254)
#define	Gfn_sel_norm_tran	(52)
#define	Gfn_del_prims_ndc_pic	(255)
#define	Gfn_remove_set_names_ndc_pic	(256)
#define	Gfn_add_set_names_ndc_pic	(257)
#define	Gfn_set_ndc_pic_prim_attr	(258)
#define	Gfn_add_set_scissors_ndc_pic	(259)
#define	Gfn_remove_set_scissors_ndc_pic	(260)
#define	Gfn_reorder_ndc_pic	(261)
#define	Gfn_copy_ndc_pic_ndc_mf	(262)
#define	Gfn_copy_ndc_mf_pic_ndc_pic	(263)
#define	Gfn_open_pic_part	(264)
#define	Gfn_close_pic_part	(265)
#define	Gfn_ar_pic_part	(266)
#define	Gfn_ret_pic_part_ar	(267)
#define	Gfn_reopen_pic_part	(268)
#define	Gfn_append_pic_part	(269)
#define	Gfn_rename_pic_part	(270)
#define	Gfn_del_pic_part	(271)
#define	Gfn_copy_pic_part_pic_part_store	(272)
#define	Gfn_copy_ndc_pic_pic_part_store	(273)
#define	Gfn_set_in_dev_mode	(274)
#define	Gfn_set_loc_mode	(75)
#define	Gfn_set_stroke_mode	(76)
#define	Gfn_set_val_mode	(77)
#define	Gfn_set_choice_mode	(78)
#define	Gfn_set_pick_mode	(79)
#define	Gfn_set_string_mode	(80)
#define	Gfn_req_in	(275)
#define	Gfn_req_loc	(81)
#define	Gfn_req_stroke	(82)
#define	Gfn_req_val	(83)
#define	Gfn_req_choice	(84)
#define	Gfn_req_pick	(85)
#define	Gfn_req_string	(86)
#define	Gfn_sample_in	(276)
#define	Gfn_sample_loc	(87)
#define	Gfn_sample_stroke	(88)
#define	Gfn_sample_val	(89)
#define	Gfn_sample_choice	(90)
#define	Gfn_sample_pick	(91)
#define	Gfn_sample_string	(92)
#define	Gfn_await_in	(277)
#define	Gfn_await_event	(93)
#define	Gfn_flush_dev_events	(278)
#define	Gfn_get_loc	(95)
#define	Gfn_get_stroke	(96)
#define	Gfn_get_val	(97)
#define	Gfn_get_choice	(98)
#define	Gfn_get_pick	(99)
#define	Gfn_get_string	(100)

```

#define Gfn_set_font_ind_map (279)
#define Gfn_get_glyph_name (280)
#define Gfn_set_char_code (281)
#define Gfn_audit (282)
#define Gfn_write_user_rec_audit (283)
#define Gfn_playback (284)
#define Gfn_read_item_func_name_audit (285)
#define Gfn_read_item_audit (286)
#define Gfn_proc_audit_item (287)
#define Gfn_eval_tran_matrix (105)
#define Gfn_accum_tran_matrix (106)
#define Gfn_eval_circle (288)
#define Gfn_eval_ell (289)
#define Gfn_eval_circ_arc_3_point (290)
#define Gfn_eval_circ_arc_ctr (291)
#define Gfn_eval_ell_arc (292)
#define Gfn_eval_hyp_arc (293)
#define Gfn_eval_par_arc (294)
#define Gfn_eval_wc_ord (295)
#define Gfn_set_err_hand (156)
#define Gfn_create_store (296)
#define Gfn_del_store (297)
#define Gfn_open_ws (2)
#define Gfn_close_ws (3)
#define Gfn_save_ws_sl (298)
#define Gfn_restore_ws_sl (299)
#define Gfn_get_ws_status (300)
#define Gfn_remove_backdrop (301)
#define Gfn_set_rep (302)
#define Gfn_set_line_rep (43)
#define Gfn_set_marker_rep (44)
#define Gfn_set_text_rep (45)
#define Gfn_set_area_rep (303)
#define Gfn_set_pat_rep (47)
#define Gfn_set_colr_rep (48)
#define Gfn_set_view_pri (304)
#define Gfn_set_view_sel_crit (305)
#define Gfn_set_view (306)
#define Gfn_set_ws_vis_effects (307)
#define Gfn_set_ws_win_vp (308)
#define Gfn_set_ws_win (54)
#define Gfn_set_ws_vp (55)
#define Gfn_def_in_dev (309)
#define Gfn_init_in_dev (310)
#define Gfn_init_loc (69)
#define Gfn_init_stroke (70)
#define Gfn_init_val (71)
#define Gfn_init_choice (72)
#define Gfn_init_pick (73)
#define Gfn_init_string (74)
#define Gfn_set_ws_sel_crit (311)
#define Gfn_copy_real_pic_real_mf (312)

```

```

#define Gfn_copy_blank_real_pic_real_mf (313)
#define Gfn_copy_real_mf_pic_backdrop (314)
#define Gfn_message (10)
#define Gfn_reset_specif_ws_dt_entry_st (315)
#define Gfn_get_text_extent (316)
#define Gfn_eval_view_ori_matrix (317)
#define Gfn_eval_view_map_matrix (318)
#define Gfn_conv_colr (319)
#define Gfn_create_seg (56)
#define Gfn_close_seg (57)
#define Gfn_rename_seg (58)
#define Gfn_del_seg (59)
#define Gfn_del_seg_ws (60)
#define Gfn_assoc_seg_ws (61)
#define Gfn_copy_seg_ws (62)
#define Gfn_insert_seg (63)
#define Gfn_set_seg_attr (320)
#define Gfn_set_seg_tran (64)
#define Gfn_set_vis (65)
#define Gfn_set_highl (66)
#define Gfn_set_det (68)
#define Gfn_set_seg_pri (67)
#define Gfn_activate_ws (4)
#define Gfn_deactivate_ws (5)
#define Gfn_clear_ws (6)
#define Gfn_get_map_seg_name (321)
#define Gfn_get_map_ws_id (322)

```

6.1.2 In alphabetical order

```

#define Gfn_accum_tran_matrix (106)
#define Gfn_activate_ws (4)
#define Gfn_add_set_names_nameset (249)
#define Gfn_add_set_names_ndc_pic (257)
#define Gfn_add_set_scissors_ndc_pic (259)
#define Gfn_add_set_scissors_scissor_set (251)
#define Gfn_append_pic_part (269)
#define Gfn_ar_pic_part (266)
#define Gfn_assoc_seg_ws (61)
#define Gfn_audit (282)
#define Gfn_await_event (93)
#define Gfn_await_in (277)
#define Gfn_cell_array (16)
#define Gfn_clear_ws (6)
#define Gfn_close_gks (1)
#define Gfn_close_pic_part (265)
#define Gfn_close_seg (57)
#define Gfn_close_stencil (214)
#define Gfn_close_tiling (226)
#define Gfn_close_ws (3)
#define Gfn_closed_nurb_set (211)
#define Gfn_conic_seg_set (206)

```

#define	Gfn_conv_colr	(319)
#define	Gfn_copy_blank_real_pic_real_mf	(313)
#define	Gfn_copy_ndc_mf_pic_ndc_pic	(263)
#define	Gfn_copy_ndc_pic_ndc_mf	(262)
#define	Gfn_copy_ndc_pic_pic_part_store	(273)
#define	Gfn_copy_pic_part_pic_part_store	(272)
#define	Gfn_copy_real_mf_pic_backdrop	(314)
#define	Gfn_copy_real_pic_real_mf	(312)
#define	Gfn_copy_seg_ws	(62)
#define	Gfn_create_out_prim	(203)
#define	Gfn_create_seg	(56)
#define	Gfn_create_stencil_bndry	(217)
#define	Gfn_create_stencil_conts	(218)
#define	Gfn_create_store	(296)
#define	Gfn_create_tiling_comp	(229)
#define	Gfn_deactivate_ws	(5)
#define	Gfn_def_in_dev	(309)
#define	Gfn_del_pic_part	(271)
#define	Gfn_del_prims_ndc_pic	(255)
#define	Gfn_del_seg	(59)
#define	Gfn_del_seg_ws	(60)
#define	Gfn_del_stencil	(216)
#define	Gfn_del_store	(297)
#define	Gfn_del_tiling	(228)
#define	Gfn_design	(212)
#define	Gfn_ell_disc_set	(210)
#define	Gfn_ell_sec_set	(208)
#define	Gfn_ell_seg_set	(209)
#define	Gfn_emergency_close_gks	(153)
#define	Gfn_err_hand	(154)
#define	Gfn_err_log	(155)
#define	Gfn_escape	(11)
#define	Gfn_eval_circ_arc_3_point	(290)
#define	Gfn_eval_circ_arc_ctr	(291)
#define	Gfn_eval_circle	(288)
#define	Gfn_eval_ell	(289)
#define	Gfn_eval_ell_arc	(292)
#define	Gfn_eval_hyp_arc	(293)
#define	Gfn_eval_par_arc	(294)
#define	Gfn_eval_tran_matrix	(105)
#define	Gfn_eval_view_map_matrix	(318)
#define	Gfn_eval_view_ori_matrix	(317)
#define	Gfn_eval_wc_ord	(295)
#define	Gfn_fill_area	(15)
#define	Gfn_fill_area_set	(207)
#define	Gfn_flush_dev_events	(278)
#define	Gfn_gdp	(17)
#define	Gfn_get_choice	(98)
#define	Gfn_get_glyph_name	(280)
#define	Gfn_get_loc	(95)
#define	Gfn_get_map_seg_name	(321)
#define	Gfn_get_map_ws_id	(322)

```

#define Gfn_get_pick (99)
#define Gfn_get_stencil_attr (221)
#define Gfn_get_string (100)
#define Gfn_get_stroke (96)
#define Gfn_get_text_extent (316)
#define Gfn_get_val (97)
#define Gfn_get_ws_status (300)
#define Gfn_init_choice (72)
#define Gfn_init_in_dev (310)
#define Gfn_init_loc (69)
#define Gfn_init_pick (73)
#define Gfn_init_string (74)
#define Gfn_init_stroke (70)
#define Gfn_init_val (71)
#define Gfn_insert_seg (63)
#define Gfn_inst_stencil (222)
#define Gfn_inst_stencil_path (223)
#define Gfn_inst_stencil_seq_path (224)
#define Gfn_message (10)
#define Gfn_nurb_set (205)
#define Gfn_open_gks (0)
#define Gfn_open_pic_part (264)
#define Gfn_open_stencil (213)
#define Gfn_open_tiling (225)
#define Gfn_open_ws (2)
#define Gfn_playback (284)
#define Gfn_polyline (12)
#define Gfn_polyline_set (204)
#define Gfn_polymarker (13)
#define Gfn_proc_audit_item (287)
#define Gfn_read_item_audit (286)
#define Gfn_read_item_func_name_audit (285)
#define Gfn_remove_backdrop (301)
#define Gfn_remove_set_names_nameset (250)
#define Gfn_remove_set_names_ndc_pic (256)
#define Gfn_remove_set_scissors_ndc_pic (260)
#define Gfn_remove_set_scissors_scissor_set (252)
#define Gfn_rename_pic_part (270)
#define Gfn_rename_seg (58)
#define Gfn_rename_stencil (215)
#define Gfn_rename_tiling (227)
#define Gfn_reopen_pic_part (268)
#define Gfn_reorder_ndc_pic (261)
#define Gfn_req_choice (84)
#define Gfn_req_in (275)
#define Gfn_req_loc (81)
#define Gfn_req_pick (85)
#define Gfn_req_string (86)
#define Gfn_req_stroke (82)
#define Gfn_req_val (83)
#define Gfn_reset_specif_ws_dt_entry_st (315)
#define Gfn_restore_gks_sl (201)

```

#define	Gfn_restore_ws_sl	(299)
#define	Gfn_ret_pic_part_ar	(267)
#define	Gfn_route	(202)
#define	Gfn_sample_choice	(90)
#define	Gfn_sample_in	(276)
#define	Gfn_sample_loc	(87)
#define	Gfn_sample_pick	(91)
#define	Gfn_sample_string	(92)
#define	Gfn_sample_stroke	(88)
#define	Gfn_sample_val	(89)
#define	Gfn_save_gks_sl	(200)
#define	Gfn_save_ws_sl	(298)
#define	Gfn_sel_norm_tran	(52)
#define	Gfn_set_area_ind	(235)
#define	Gfn_set_area_rep	(303)
#define	Gfn_set_asfs	(41)
#define	Gfn_set_char_code	(281)
#define	Gfn_set_char_expan	(28)
#define	Gfn_set_char_ht	(31)
#define	Gfn_set_char_space	(29)
#define	Gfn_set_char_up_vec	(32)
#define	Gfn_set_choice_mode	(78)
#define	Gfn_set_colr_rep	(48)
#define	Gfn_set_cont_attr	(219)
#define	Gfn_set_det	(68)
#define	Gfn_set_edge_colr_ind	(246)
#define	Gfn_set_edge_colr_specif	(245)
#define	Gfn_set_edge_flag	(242)
#define	Gfn_set_edgetype	(243)
#define	Gfn_set_edgewidth	(244)
#define	Gfn_set_err_hand	(156)
#define	Gfn_set_font_ind_map	(279)
#define	Gfn_set_global_tran_matrix	(240)
#define	Gfn_set_highl	(66)
#define	Gfn_set_in_dev_mode	(274)
#define	Gfn_set_int_colr_ind	(239)
#define	Gfn_set_int_colr_specif	(238)
#define	Gfn_set_int_style	(236)
#define	Gfn_set_int_style_ind	(237)
#define	Gfn_set_line_colr_ind	(21)
#define	Gfn_set_line_colr_specif	(231)
#define	Gfn_set_line_ind	(18)
#define	Gfn_set_line_rep	(43)
#define	Gfn_set_linetype	(19)
#define	Gfn_set_linewidth	(20)
#define	Gfn_set_loc_mode	(75)
#define	Gfn_set_local_tran_matrix	(241)
#define	Gfn_set_marker_colr_ind	(25)
#define	Gfn_set_marker_colr_specif	(232)
#define	Gfn_set_marker_ind	(22)
#define	Gfn_set_marker_rep	(44)
#define	Gfn_set_marker_size	(24)

```

#define Gfn_set_marker_type (23)
#define Gfn_set_nameset (247)
#define Gfn_set_ndc_pic_prim_attr (258)
#define Gfn_set_norm_tran_num (254)
#define Gfn_set_pat_ref_point (40)
#define Gfn_set_pat_rep (47)
#define Gfn_set_pat_size (39)
#define Gfn_set_pick_id (42)
#define Gfn_set_pick_mode (79)
#define Gfn_set_prim_attr (230)
#define Gfn_set_rep (302)
#define Gfn_set_scissor_mode (253)
#define Gfn_set_scissor_set (248)
#define Gfn_set_seg_attr (320)
#define Gfn_set_seg_pri (67)
#define Gfn_set_seg_tran (64)
#define Gfn_set_stencil_attr (220)
#define Gfn_set_string_mode (80)
#define Gfn_set_stroke_mode (76)
#define Gfn_set_text_align (34)
#define Gfn_set_text_colr_ind (30)
#define Gfn_set_text_colr_specif (233)
#define Gfn_set_text_font_prec (27)
#define Gfn_set_text_ind (26)
#define Gfn_set_text_path (33)
#define Gfn_set_text_rep (45)
#define Gfn_set_text_skew_angle (234)
#define Gfn_set_val_mode (77)
#define Gfn_set_view (306)
#define Gfn_set_view_pri (304)
#define Gfn_set_view_sel_crit (305)
#define Gfn_set_vis (65)
#define Gfn_set_vp (50)
#define Gfn_set_vp_in_pri (50)
#define Gfn_set_win (49)
#define Gfn_set_win_vp (49)
#define Gfn_set_ws_sel_crit (311)
#define Gfn_set_ws_vis_effects (307)
#define Gfn_set_ws_vp (55)
#define Gfn_set_ws_win (54)
#define Gfn_set_ws_win_vp (308)
#define Gfn_text (14)
#define Gfn_write_user_rec_audit (283)

```

6.2 Error codes

The error codes are represented by macros. The range of the numeric values of the macros is between 1000 and 2000.

Below, the error macros are listed.

```

#define GE_NO_ERR (0) /* No error */
#define GE_GKS_NOT_OPEN (1001) /* GKS not open */

```



```

#define GE_GKS_OPEN           (1002)/* GKS already open */
#define GE_PP_NOT_OPEN        (1003)/* Picture part not open */
#define GE_PP_OPEN            (1004)/* Picture part already open */
#define GE_SEG_NOT_OPEN       (1005)/* Segment not open */
#define GE_SEG_OPEN           (1006)/* Segment already open */
#define GE_ST_NOT_OPEN        (1007)/* Stencil not open */
#define GE_ST_OPEN            (1008)/* Stencil already open */
#define GE_TL_NOT_OPEN        (1009)/* Tiling not open */
#define GE_TL_OPEN            (1010)/* Tiling already open */
#define GE_WS_TYPE_NOT_SUPP    (1011)/* Specified workstation type not supported */
#define GE_WS_NOT_OPEN        (1012)/* Specified workstation not open */
#define GE_WS_OPEN            (1013)/* Specified workstation already open */
#define GE_WS_NOT_ACTIVE      (1014)/* Specified workstation not active */
#define GE_WS_ACTIVE          (1015)/* Specified workstation already active */
#define GE_AUDIT_NOT_OPEN     (1016)/* Specified audit trail not open */
#define GE_AUDIT_OPEN         (1017)/* Specified audit trail already open */
#define GE_PLAYBACK_NOT_OPEN  (1018)/* Specified playback not open */
#define GE_PLAYBACK_OPEN     (1019)/* Specified playback already open */
#define GE_PP_NOT_EXIST       (1020)/* Specified picture part does not exist */
#define GE_PP_NAME_USE        (1021)/* Specified picture part name already in use */
#define GE_OLD_PP_NOT_EXIST   (1022)/* Old picture part does not exist */
#define GE_NEW_PP_NAME_USE    (1023)/* New picture part name already in use */
#define GE_SRC_PP_NOT_EXIST   (1024)/* Source picture part does not exist */
#define GE_SINK_PP_NOT_EXIST  (1025)/* Sink picture part does not exist */
#define GE_SEG_NOT_EXIST      (1026)/* Segment does not exist */
#define GE_SEG_NAME_IN_USE    (1027)/* Segment name already in use */
#define GE_ST_NOT_EXIST       (1028)/* Specified stencil does not exist */
#define GE_ST_NAME_USE        (1029)/* Specified stencil name already in use */
#define GE_OLD_ST_NOT_EXIST   (1030)/* Old stencil does not exist */
#define GE_NEW_ST_NAME_USE    (1031)/* New stencil name already in use */
#define GE_INST_NAME_EQ_ST_NAME_USE (1032)/* Instance name same as stencil name already in use */
#define GE_TL_NOT_EXIST       (1033)/* Specified tiling does not exist */
#define GE_TL_NAME_USE        (1034)/* Specified tiling name already in use */
#define GE_OLD_TL_NOT_EXIST   (1035)/* Old tiling does not exist */
#define GE_NEW_TL_NAME_USE    (1036)/* New tiling name already in use */
#define GE_IN_Q_OVERFLOW      (1037)/* Input queue has overflowed */
#define GE_IN_Q_NOT_OVERFLOW  (1038)/* Input queue has not overflowed ever or since the last invocation of INQUIRE INPUT QUEUE OVERFLOW */
#define GE_IN_Q_OVERFLOW_WS_CLOSED (1039)/* Input queue has overflowed but

```



```

associated workstation has been closed
*/
#define GE_ESCAPE_FUNC_NOT_SUPP (1040)/* Specified escape function not sup-
ported */
#define GE_GLYPH_NOT_AVAIL (1041)/* Specified glyph not available */
#define GE_FONT_NAME_NOT_AVAIL (1042)/* Specified font name not available
*/
#define GE_LINETYPE_NOT_SUPP (1043)/* Linetype not supported */
#define GE_MARKER_TYPE_NOT_SUPP (1044)/* Marker type not supported */
#define GE_FONT_NOT_SUPP_PREC (1045)/* Text font not supported for speci-
fied precision */
#define GE_INT_STYLE_NOT_SUPP (1046)/* Specified interior style not sup-
ported */
#define GE_HATCH_STYLE_NOT_SUPP (1047)/* Specified hatch style not supported
*/
#define GE_EDGETYPE_NOT_SUPP (1048)/* Edgetype not supported */
#define GE_COLR_MODEL_NOT_SUPP (1049)/* Specified colour model not sup-
ported */
#define GE_GDP_NOT_SUPP (1050)/* GDP not supported */
#define GE_IN_DEV_NOT_EXIST (1051)/* Input device does not exist */
#define GE_COMB_MEAS_TRIG_NOT_AVAIL (1052)/* Specified combination of measures
and triggers cannot be provided */
#define GE_SEG_NOT_EXIST_WS (1053)/* Segment does not exist on specified
workstation */
#define GE_PIC_NOT_EXIST_IN_MF (1054)/* Specified picture does not exist in
specified metafile */
#define GE_NO_ITEM_PLAYBACK (1055)/* No item left on specified playback
*/
#define GE_PLAYBACK_ITEM_INVALID (1056)/* Playback item invalid */
#define GE_PP_NOT_EXIST_AR (1057)/* Picture part does not exist in
archive */
#define GE_EDGE_NOT_INTERSECT_PATH (1058)/* Edge does not intersect path */
#define GE_START_VEC_NOT_INTERSECT_HYP (1059)/* Start vector does not inter-
sect hyperbola */
#define GE_END_VEC_NOT_INTERSECT_HYP (1060)/* End vector does not intersect
hyperbola */
#define GE_OLD_PP_NAME_EQ_NEW_PP_NAME (1061)/* Old picture part name and new pic-
ture part name are the same */
#define GE_OLD_ST_NAME_EQ_NEW_ST_NAME (1062)/* Old stencil name and new stencil
name are the same */
#define GE_OLD_TL_NAME_EQ_NEW_TL_NAME (1063)/* Old tiling name and new tiling name
are the same */

/*
 * Binding specific errors
 */

#define GE_START_IND_INVALID (2201)/* Start index out of range */
#define GE_APPL_LIST_LENGTH_LT_ZERO (2202)/* Length of application list negative
*/
#define GE_ENUM_TYPE_INVALID (2203)/* Enumeration type out of range */
#define GE_ALLOC_STORE (2204)/* Error while allocating Store */

```

```

#define GE_ALLOC_MEM_STORE      (2205)/* Error while allocating memory for
                                   Store */

#define GE_ERR_FILE_INVAL      (2250)/* Error file invalid */
#define GE_INSUFF_STORE        (2251)/* Insufficient storage */
#define GE_ENTRIES_INVAL      (2252)/* Entry values invalid */
#define GE_ESC_FUNC_ID_INVAL   (2253)/* Escape function identifier invalid
                                   */
#define GE_ESC_IN_DATA_INVAL   (2254)/* Escape input data record invalid */
#define GE_ERR_NUM_INVAL      (2255)/* Error number invalid */
#define GE_FUNC_NAME_INVAL     (2256)/* Function name invalid */
#define GE_DIR_INVAL           (2257)/* Direction invalid */
#define GE_PRIM_TYPE_INVAL     (2258)/* Primitive type invalid */
#define GE_NUM_POINTS_INVAL    (2259)/* Number of points invalid */
#define GE_CODE_INVAL          (2260)/* Code in string invalid */
#define GE_DIMS_COLR_ARRAY_INVAL (2261)/* Dimensions of colour array invalid
                                   */
#define GE_GDP_ID_INVAL        (2262)/* GDP identifier invalid */
#define GE_GDP_DATA_INVAL      (2263)/* GDP data record invalid */
#define GE_NURB_DEF_INVAL      (2264)/* NURB definition invalid */
#define GE_CONIC_SEC_INVAL     (2265)/* Conic section invalid */
#define GE_INSIDE_RULE_INVAL   (2266)/* Inside rule invalid */
#define GE_SEQ_PATHS_INVAL     (2267)/* Sequence of paths invalid */
#define GE_CONT_ATTR_NAME_INVAL (2268)/* Contour attribute name invalid */
#define GE_CONT_ATTR_VALUE_INVAL (2269)/* Contour attribute value invalid */
#define GE_ST_NAME_INVAL       (2270)/* Stencil name invalid */
#define GE_OLD_NEW_ST_NAME_INVAL (2271)/* Old or new stencil name invalid */
#define GE_ST_ATTR_NAME_INVAL  (2272)/* Stencil attribute name invalid */
#define GE_BNDRY_SPECIF_INVAL  (2273)/* Boundary specification invalid */
#define GE_ST_ATTR_VALUE_INVAL (2274)/* Stencil attribute value invalid */
#define GE_INST_NAME_INVAL     (2275)/* Instance name invalid */
#define GE_INST_TYPE_INVAL     (2276)/* Instance type invalid */
#define GE_INST_SPECIF_INVAL   (2277)/* Instance specification invalid */
#define GE_PATH_INVAL          (2278)/* Path invalid */
#define GE_TL_NAME_INVAL       (2279)/* Tiling name invalid */
#define GE_REPL_TECH_INVAL     (2280)/* Replication technique invalid */
#define GE_ATTR_NAME_INVAL     (2281)/* Attribute name invalid */
#define GE_ATTR_VALUE_INVAL    (2282)/* Attribute value invalid */
#define GE_SET_NAMES_INVAL     (2283)/* Set of names invalid */
#define GE_SCISSOR_SPECIF_INVAL (2284)/* Scissor specification invalid */
#define GE_SCISSOR_IDS_INVAL   (2285)/* Scissor identifiers invalid */
#define GE_SCISSOR_MODE_INVAL  (2286)/* Scissor mode invalid */
#define GE_TRAN_NUM_INVAL      (2287)/* Transformation number invalid */
#define GE_WIN_DEF_INVAL       (2288)/* Window definition invalid */
#define GE_VP_DEF_INVAL        (2289)/* Viewport definition invalid */
#define GE_SEL_CRIT_INVAL      (2290)/* Selection criterion invalid */
#define GE_MF_SPECIF_INVAL     (2291)/* Metafile specifier invalid */
#define GE_PIC_ID_INVAL        (2292)/* Picture identifier invalid */
#define GE_PP_NAME_INVAL       (2293)/* Picture part name invalid */
#define GE_AR_SPECIF_INVAL     (2294)/* Archive specifier invalid */
#define GE_AR_NAME_PP_INVAL    (2295)/* Archive name of picture part
                                   invalid */

```

```

#define GE_SRC_PP_NAME_INVAL      (2296)/* Source picture part name invalid */
#define GE_SINK_PP_NAME_INVAL     (2297)/* Sink picture part name invalid */
#define GE_GLOBAL_TRAN_MODE_INVAL (2298)/* Global transformation mode invalid
*/
#define GE_LOCAL_TRAN_MODE_INVAL  (2299)/* Local transformation mode invalid
*/
#define GE_OLD_PP_NAME_INVAL      (2300)/* Old picture part name invalid */
#define GE_NEW_PP_NAME_INVAL     (2301)/* New picture part name invalid */
#define GE_SCISSOR_SEL_INVAL      (2302)/* Scissor select invalid */
#define GE_IN_DEV_INVAL           (2303)/* Input device identifier invalid */
#define GE_OP_MODE_INVAL          (2304)/* Operating mode invalid */
#define GE_TIMEOUT_INVAL          (2305)/* Timeout invalid */
#define GE_FONT_IND_ZERO          (2306)/* Font index zero */
#define GE_FONT_NAME_INVAL        (2307)/* Font name invalid */
#define GE_CHAR_CODE_INVAL        (2308)/* Character code invalid */
#define GE_AUDIT_ID_INVAL         (2309)/* Audit identifier invalid */
#define GE_AUDIT_OP_INVAL         (2310)/* Audit operation invalid */
#define GE_AUDIT_USER_DATA_INVAL  (2311)/* Audit user data record invalid */
#define GE_PLAYBACK_OP_INVAL      (2312)/* Playback operation invalid */
#define GE_PROC_OP_INVAL          (2313)/* Process operation invalid */
#define GE_ENTRY_NAME_INVAL       (2314)/* Entry name invalid */
#define GE_FIXED_POINT_INVAL      (2315)/* Fixed point invalid */
#define GE_SHIFT_VEC_INVAL        (2316)/* Shift vector invalid */
#define GE_RADIUS_INVAL           (2317)/* Radius or conjugate radius invalid
*/
#define GE_RADII_ID               (2318)/* Radii identical */
#define GE_POINTS_COLLIN          (2319)/* Points collinear */
#define GE_SENSE_FLAG_INVAL       (2320)/* Sense flag invalid */
#define GE_ORD_SEL_INVAL          (2321)/* Ordinate selector invalid */
#define GE_WS_ID_INVAL            (2322)/* Workskstation identifier invalid */
#define GE_WS_TYPE_INVAL          (2323)/* Workskstation type invalid */
#define GE_WS_SPECIF_INVAL        (2324)/* Workskstation specifier invalid */
#define GE_REP_INVAL              (2325)/* Representation invalid */
#define GE_IND_INVAL              (2326)/* Bundle ndex invalid */
#define GE_TYPE_ZERO              (2327)/* Linetype, marker type or edgetype
zero */
#define GE_SCALE_FAC_NEG          (2328)/* Linewidth, marker size or edgewidth
scale factor negative */
#define GE_CHAR_EXPAN_NOT_POS     (2329)/* Character expansion factor <= 0 */
#define GE_EDGE_FLAG_INVAL        (2330)/* Edge flag invalid */
#define GE_INT_STYLE_INVAL        (2331)/* Interior style invalid */
#define GE_COLR_IND_INVAL         (2332)/* Colour index invalid */
#define GE_PAT_IND_INVAL          (2333)/* Pattern index invalid */
#define GE_COLR_SPECIF_INVAL      (2334)/* Colour specification invalid */
#define GE_VIEW_IND_INVAL         (2335)/* View index invalid */
#define GE_REF_IND_INVAL          (2336)/* Reference index invalid */
#define GE_REL_PRI_INVAL          (2337)/* Relative priority invalid */
#define GE_VIEW_SCISSOR_INVAL     (2338)/* View scissor invalid */
#define GE_VIS_EFFECTS_ST_INVAL   (2339)/* Visual effects state invalid */
#define GE_WS_WIN_LIMITS_INVAL    (2340)/* Workstation window limits invalid
*/
#define GE_WS_VP_LIMITS_INVAL     (2341)/* Workstation viewport limits invalid

```

```

*/
#define GE_WS_VP_NOT_IN_DISP_SPACE (2342)/* Workstation viewport not in display
space */
#define GE_MEAS_SEQ_INVALID (2343)/* Measure sequence invalid */
#define GE_TRIGGER_SET_INVALID (2344)/* Trigger set invalid */
#define GE_ECHO_SWITCH_INVALID (2345)/* Echo switch invalid */
#define GE_ECHO_AREA_RECT_INVALID (2346)/* Echo area rectangle invalid */
#define GE_SEL_TYPE_INVALID (2347)/* Selection type invalid */
#define GE_TYPE_RETURNED_VALUES_INVALID (2348)/* Type returned values invalid */
#define GE_WS_GEN_TYPE_INVALID (2349)/* Workstation generic type invalid */
#define GE_COLR_MODEL_INVALID (2350)/* Colour model invalid */
#define GE_SEG_NAME_INVALID (2351)/* Segment name invalid */
#define GE_OLD_NEW_SEG_NAME_INVALID (2352)/* Old or new segment name invalid */
#define GE_SEG_ATTR_VALUE_INVALID (2353)/* Segment attribute value invalid */

```

6.3 Miscellaneous

6.3.1 Linetypes

```

#define GLINE_SOLID (1) /* Solid linetype */
#define GLINE_DASH (2) /* Dashed linetype */
#define GLINE_DOT (3) /* Dotted linetype */
#define GLINE_DASH_DOT (4) /* Dashed-dotted linetype */
#define GLINE_DASH_DOT_DOT (5) /* Dashed-dotted-dotted linetype */

```

6.3.2 Marker types

```

#define GMARKER_DOT (1) /* Dotted marker type */
#define GMARKER_PLUS (2) /* Plus (+) marker type */
#define GMARKER_ASTERISK (3) /* Asterisk (*) marker type */
#define GMARKER_CIRCLE (4) /* Circle (o) marker type */
#define GMARKER_CROSS (5) /* Cross (X) marker type */

```

6.3.3 Hatch styles

```

#define GHATCH_HOR (1) /* horizontal hatch lines */
#define GHATCH_VERT (2) /* vertical hatch lines */
#define GHATCH_DIAG_45 (3) /* diagonal hatch lines 45 degree */
#define GHATCH_DIAG_135 (4) /* diagonal hatch lines 135 degree */
#define GHATCH_HOR_VERT (5) /* hor. and vert. hatch lines */
#define GHATCH_DIAG_45_135 (6) /* diag. hatch lines 45 and 135
degree */

```

6.3.4 Colour models

```

#define GMODEL_RGB (1) /* Red-Green-Blue */
#define GMODEL_CIELUV (2) /* CIE Luv 1976 */
#define GMODEL_HSV (3) /* Hue-Saturation-Value */
#define GMODEL_HLS (4) /* Hue-Lightness-Saturation */

```

6.3.5 Prompt and echo types

```

#define GLOC_DEF (1) /* Locator default */
#define GLOC_CROSS_HAIR (2) /* Locator cross-hair */
#define GLOC_TRACK_CROSS (3) /* Locator tracking cross */
#define GLOC_RUB_BAND (4) /* Locator rubber band */
#define GLOC_RECT (5) /* Locator rectangle */
#define GLOC_DIGIT (6) /* Locator digital */

#define GSTROKE_DEF (1) /* Stroke default */
#define GSTROKE_DIGIT (2) /* Stroke digit */
#define GSTROKE_MARKER (3) /* Stroke polymarker */
#define GSTROKE_LINE (4) /* Stroke polyline */

#define GVAL_DEF (1) /* Valuator default */
#define GVAL_GRAPH (2) /* Valuator graphical */
#define GVAL_DIGIT (3) /* Valuator digital */

#define GCHOICE_DEF (1) /* Choice default */
#define GCHOICE_PR_ECHO (2) /* Choice prompt and echo */
#define GCHOICE_STRING_PR (3) /* Choice string and prompt */
#define GCHOICE_STRING_IN (4) /* Choice string input */
#define GCHOICE_SEG (5) /* Choice segment */

#define GPICK_DEF (1) /* Pick default */
#define GPICK_GROUP_HIGHL (2) /* Pick group highlighting */
#define GPICK_SEG_HIGHL (3) /* Pick segment highlighting */
#define GPICK_SET_NAMES_HIGHL (3) /* Pick set of names highlighting */

#define GSTRING_DEF (1) /* String default */

```

6.3.6 Default parameter of `gopen_gks`

```

#define GDEF_ERR_FILE (((char *)0)) /* Default error file name */

```

7 C GKS function interface

7.1 Notational conventions

The binding of each GKS function follows the following template:

GKS Function Name

```
void gfunction(
    Gtype0  arg0,    /* argument 0 explanation */
    Gtype1  arg1,    /* argument 1 explanation */
    Gtype2  arg2,    /* argument 2 explanation */
);
```

"GKS Function Name" is the name of the function as listed in the GKS standard.

The C function name bound to the GKS function is **gfunction**. **arg0**, **arg1**, and **arg2** are the arguments to the function and correspond to the parameters of the GKS function definition. **Gtype0**, **Gtype1**, and **Gtype2** are the C data types of the arguments. The definitions of these types are listed in clause 5 of this part of ISO/IEC 8651.

To the right of each argument declaration is a C comment field which contains a brief explanation of the argument. If the comment begins with "OUT" it means the argument is used as an output parameter; the implementation returns data to the application through this argument. Arguments without "OUT" are input parameters.

All GKS/C functions have a **void** return type.

REMARK.

- 1) The C functions of 7.2 are C bindings of the functions of clause 12 of ISO/IEC 7942-1 (1994);
- 2) The C functions of 7.3 are C bindings of the functions of clause 13 of ISO/IEC 7942-1 (1994);
- 3) The C functions of 7.4 are C bindings of the functions of clause 14 of ISO/IEC 7942-1 (1994).

7.2 Workstation independent functions

7.2.1 Control functions

OPEN GKS

```
void gopen_gks(
    const char *err_file, /* name of error file */
    size_t mem_units /* number of units of memory available
                      for buffer space */
);
```

REMARK.

- 1) If **err_file** has the value **GDEF_ERR_FILE**, the **stderr** stream is used.
- 2) The second parameter is unused.

CLOSE GKS

```
void gclose_gks(
    void
);
```

SAVE GKS STATE LIST

```
void gsave_gks_sl(
    const Ggks_sl_name_list  *entry_names,  /* GKS state list entry
                                           names */
    Gstore                  store,          /* handle to Store object */
    Ggks_sl_entry_list      **entries       /* OUT GKS state
                                           list entries */
);
```

REMARK. The memory referenced by ***entries** is managed by the parameter **store**.

RESTORE GKS STATE LIST

```
void grestore_gks_sl(
    const Ggks_sl_entry_list  *entries  /* GKS state list entries */
);
```

ESCAPE

```
void gescape(
    Gint          func_id,      /* escape function identifier */
    const Gescape_in_data *in_data, /* escape input data record */
    Gstore        store,       /* handle to Store object */
    Gescape_out_data **out_data /* OUT escape output data
                                record */
);
```

REMARK. The memory referenced by ***out_data** is managed by the parameter **store**.

EMERGENCY CLOSE GKS

```
void gemergency_close_gks(
    void
);
```

ERROR HANDLING

```
void gerr_hand(
    Gint      err_num,  /* error number */
    Gint      func_num, /* number of function that detected the error */
    const char *err_file /* name of error file */
);
```

ERROR LOGGING

```

void gerr_log(
    Gint      err_num,    /* error number          */
    Gint      func_num,   /* number of function that detected the error */
    const char *err_file /* name of error file    */
);

```

ROUTE

```

void groute(
    Groute_dir dir /* direction */
);

```

7.2.2 Output functions

CREATE OUTPUT PRIMITIVE

```

void gcreate_out_prim(
    const Gprim_params *prim_params /* primitive parameters */
);

```

[CREATE OUTPUT PRIMITIVE]
POLYLINE

```

void gpolyline(
    const Gpoint_list *point_list /* list of points */
);

```

[CREATE OUTPUT PRIMITIVE]
POLYLINE SET

```

void gpolyline_set(
    const Gpoint_list_list *point_list_list /* list of point lists */
);

```

[CREATE OUTPUT PRIMITIVE]
NURB SET

```

void gnurb_set(
    const Gnurb_list *nurb_set /* NURB parameter lists */
);

```

[CREATE OUTPUT PRIMITIVE]
CONIC SECTION SET

```

void gconic_sec_set(
    const Gconic_sec_list *conic_sec_set /* Conic section set */
);

```

**[CREATE OUTPUT PRIMITIVE]
POLYMARKER**

```
void gpolymarker(  
    const Gpoint_list  *point_list  /* list of points  */  
);
```

**[CREATE OUTPUT PRIMITIVE]
FILL AREA**

```
void gfill_area(  
    const Gpoint_list  *point_list  /* list of points  */  
);
```

**[CREATE OUTPUT PRIMITIVE]
FILL AREA SET**

```
void gfill_area_set(  
    const Gpoint_list_list  *point_list_list /* list of point lists  */  
);
```

**[CREATE OUTPUT PRIMITIVE]
CLOSED NURB SET**

```
void gclosed_nurb_set(  
    const Gnurb_list  *closed_nurb_set  /* NURB parameter lists  */  
);
```

**[CREATE OUTPUT PRIMITIVE]
ELLIPTIC SECTOR SET**

```
void gell_sec_set(  
    const Gconic_sec_list  *ell_sec_set  /* elliptic sector set  */  
);
```

**[CREATE OUTPUT PRIMITIVE]
ELLIPTIC SEGMENT SET**

```
void gell_seg_set(  
    const Gconic_sec_list  *ell_seg_set  /* elliptic segment set  */  
);
```

**[CREATE OUTPUT PRIMITIVE]
ELLIPTIC DISC SET**

```
void gell_disc_set(  
    const Gell_disc_list  *ell_disc_set  /* elliptic disc set  */  
);
```

**[CREATE OUTPUT PRIMITIVE]
TEXT**

```
void gtext(
    const Gpoint  *text_pos,      /* text position      */
    const char    *char_string   /* character string   */
);
```

**[CREATE OUTPUT PRIMITIVE]
CELL ARRAY**

```
void gcell_array(
    const Grect    *rect,          /* cell rectangle     */
    const Gpat_rep *colr_array     /* colour array       */
);
```

**[CREATE OUTPUT PRIMITIVE]
DESIGN**

```
void gdesign(
    const Gdesign  *design /* design */
);
```

**[CREATE OUTPUT PRIMITIVE]
GENERALIZED DRAWING PRIMITIVE**

```
void ggdp(
    const Gpoint_list *point_list, /* list of points */
    Gint              gdp_id,      /* gdp identifier */
    const Ggdp_data   *gdp_data   /* gdp data record */
);
```

7.2.3 Design output functions

OPEN STENCIL

```
void gopen_stencil(
    Gint      stencil_name, /* stencil name */
    Ginside_rule inside_rule /* inside rule */
);
```

CLOSE STENCIL

```
void gclose_stencil(
    void
);
```

RENAME STENCIL

```

void grename_stencil(
    Gint    old_name,    /* old stencil name */
    Gint    new_name     /* new stencil name */
);

```

DELETE STENCIL

```

void gdel_stencil(
    Gint    name /* stencil name */
);

```

CREATE STENCIL FROM BOUNDARY

```

void gcreate_stencil_bndry(
    Gint          stencil_name, /* stencil name */
    Ginside_rule  inside_rule, /* inside rule */
    const Gbndry_list *bndry   /* boundary */
);

```

CREATE STENCIL FROM CONTOURS

```

void gcreate_stencil_conts(
    Gint          stencil_name, /* stencil name */
    Ginside_rule  inside_rule, /* inside rule */
    const Gpath_list *path_seq /* path sequence */
);

```

SET CONTOUR ATTRIBUTE

```

void gset_cont_attr(
    const Gcont_attr_value *cont_attr /* contour attribute */
);

```

SET STENCIL ATTRIBUTE

```

void gset_stencil_attr(
    Gint          stencil_name, /* stencil name */
    const Gstencil_attr_value *stencil_attr /* stencil attribute */
);

```

GET STENCIL ATTRIBUTE

```

void gget_stencil_attr(
    Gint          stencil_name, /* stencil name */
    Gstencil_attr_name attr_name, /* stencil attribute name */
    Gint          *err_ind,      /* OUT error indicator */
    Gstencil_attr_value *attr    /* OUT stencil attribute */
);

```

INSTANCE STENCIL

```

void ginst_stencil(
    Gint          stencil_name, /* stencil name          */
    Gint          inst_name,    /* instance name        */
    Gtran_matrix  stencil_tran, /* stencil transformation */
    const Ginst_specif *inst_specif /* instance specifier    */
);

```

INSTANCE STENCIL ALONG PATH

```

void ginst_stencil_path(
    Gint          stencil_name, /* stencil name          */
    Gint          inst_name,    /* instance name        */
    const Gpoint  *start_map,   /* start map            */
    const Gpoint  *end_map,     /* end map              */
    Gint          inst_num,     /* instance number      */
    const Gpath   *path_def     /* path definition      */
);

```

INSTANCE STENCIL SEQUENCE ALONG PATH

```

void ginst_stencil_seq_path(
    const Gseq_specif_list *inst_seq_specif, /* instance sequence
                                                specifier          */
    const Gpath_specif     *path_specif,     /* path specifier    */
    Gtran_matrix           stencil_tran      /* stencil transformation */
);

```

OPEN TILING

```

void gopen_tiling(
    Gint tiling_name /* tiling name */
);

```

CLOSE TILING

```

void gclose_tiling(
    void
);

```

RENAME TILING

```

void grename_tiling(
    Gint old_name, /* old tiling name */
    Gint new_name  /* new tiling name */
);

```

DELETE TILING

```
void gdel_tiling(
    Gint name /* tiling name */
);
```

CREATE TILING COMPONENT

```
void gcreate_tiling_comp(
    const Gtiling_params *tiling_params, /* tiling parameters */
    const Gpoint *origin, /* origin */
    const Grepl_tech *repl_tech /* replication technique */
);
```

7.2.4 Primitive attribute functions

SET PRIMITIVE ATTRIBUTE

```
void gset_prim_attr(
    const Gprim_attr_value *attr_value /* attr_value */
);
```

[SET PRIMITIVE ATTRIBUTE]
SET PICK IDENTIFIER

```
void gset_pick_id(
    Gint pick_id /* pick identifier */
);
```

[SET PRIMITIVE ATTRIBUTE]
SET NAMESET

```
void gset_nameset(
    const Gnameset *nameset /* nameset */
);
```

[SET PRIMITIVE ATTRIBUTE]
SET SCISSOR SET

```
void gset_scissor_set(
    const Gscissor_list *scissor_set /* scissor_set */
);
```

[SET PRIMITIVE ATTRIBUTE]
SET GLOBAL TRANSFORMATION MATRIX

```
void gset_global_tran_matrix(
    Gtran_matrix global_tran_matrix /* global transformation
                                     matrix */
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET LOCAL TRANSFORMATION MATRIX**

```
void gset_local_tran_matrix(  
    Gtran_matrix  local_tran_matrix  /* local transformation  
                                     matrix */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET PATTERN SIZE**

```
void gset_pat_size(  
    const Gfloat_size  *pat_size  /* pattern size */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET PATTERN REFERENCE POINT**

```
void gset_pat_ref_point(  
    const Gpoint  *pat_ref_point  /* pattern reference point */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET CHARACTER HEIGHT**

```
void gset_char_ht(  
    Gfloat  char_ht  /* character height */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET CHARACTER UP VECTOR**

```
void gset_char_up_vec(  
    const Gvec  *char_up_vec  /* character up vector */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET TEXT SKEW ANGLE**

```
void gset_text_skew_angle(  
    Gfloat  text_skew_angle  /* text skew angle */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET TEXT PATH**

```
void gset_text_path(  
    Gtext_path  text_path  /* text path */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET TEXT ALIGNMENT

```
void gset_text_align(  
    const Gtext_align *text_align /* text alignment */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET LINE INDEX

```
void gset_line_ind(  
    Gint line_ind /* line index */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET LINETYPE

```
void gset_linetype(  
    Gint linetype /* linetype */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET LINEWIDTH SCALE FACTOR

```
void gset_linewidth(  
    Gfloat linewidth /* linewidth scale factor */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET LINE COLOUR SPECIFIER

```
void gset_line_colr_specif(  
    const Gcolr_specif *line_colr_specif /* line colour specifier */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET LINE COLOUR INDEX

```
void gset_line_colr_ind(  
    Gint line_colr_ind /* line colour index */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET MARKER INDEX

```
void gset_marker_ind(  
    Gint marker_ind /* marker index */  
);
```

[SET PRIMITIVE ATTRIBUTE]**SET MARKER TYPE**

```
void gset_marker_type(  
    Gint marker_type /* marker type */  
);
```

[SET PRIMITIVE ATTRIBUTE]**SET MARKER SIZE SCALE FACTOR**

```
void gset_marker_size(  
    Gfloat marker_size /* marker size scale factor */  
);
```

[SET PRIMITIVE ATTRIBUTE]**SET MARKER COLOUR SPECIFIER**

```
void gset_marker_colr_specif(  
    const Gcolr_specif *marker_colr_specif /* marker colour  
                                            specifier */  
);
```

[SET PRIMITIVE ATTRIBUTE]**SET MARKER COLOUR INDEX**

```
void gset_marker_colr_ind(  
    Gint marker_colr_ind /* marker colour index */  
);
```

[SET PRIMITIVE ATTRIBUTE]**SET AREA INDEX**

```
void gset_area_ind(  
    Gint area_ind /* area index */  
);
```

[SET PRIMITIVE ATTRIBUTE]**SET INTERIOR STYLE**

```
void gset_int_style(  
    Gint_style int_style /* interior style */  
);
```

[SET PRIMITIVE ATTRIBUTE]**SET INTERIOR STYLE INDEX**

```
void gset_int_style_ind(  
    Gint int_style_ind /* interior style index */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET INTERIOR COLOUR SPECIFIER

```
void gset_int_colr_specif(  
    const Gcolr_specif *int_colr_specif /* interior colour specifier */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET INTERIOR COLOUR INDEX

```
void gset_int_colr_ind(  
    Gint int_colr_ind /* interior colour index */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET EDGE FLAG

```
void gset_edge_flag(  
    Gedge_flag edge_flag /* edge flag */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET EDGETYPE

```
void gset_edgetype(  
    Gint edgetype /* edgetype */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET EDGEWIDTH SCALE FACTOR

```
void gset_edgewidth(  
    Gfloat edgewidth /* edgewidth scale factor */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET EDGE COLOUR SPECIFIER

```
void gset_edge_colr_specif(  
    const Gcolr_specif *edge_colr_specif /* edge colour specifier */  
);
```

[SET PRIMITIVE ATTRIBUTE]
SET EDGE COLOUR INDEX

```
void gset_edge_colr_ind(  
    Gint edge_colr_ind /* edge colour index */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET TEXT INDEX**

```
void gset_text_ind(  
    Gint    text_ind    /* text index    */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET TEXT FONT AND PRECISION**

```
void gset_text_font_prec(  
    const Gtext_font_prec    *text_font_prec    /* text font and precision    */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET CHARACTER EXPANSION FACTOR**

```
void gset_char_expan(  
    Gfloat    char_expan    /* character expansion factor    */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET CHARACTER SPACING**

```
void gset_char_space(  
    Gfloat    char_space    /* character spacing    */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET TEXT COLOUR SPECIFIER**

```
void gset_text_colr_specif(  
    const Gcolr_specif    *text_colr_specif    /* text colour specifier    */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET TEXT COLOUR INDEX**

```
void gset_text_colr_ind(  
    Gint    text_colr_ind    /* text colour index    */  
);
```

**[SET PRIMITIVE ATTRIBUTE]
SET ATTRIBUTE SOURCE FLAGS**

```
void gset_asfs(  
    const Gasfs    *asfs    /* list of attribute source flags    */  
);
```

ADD SET OF NAMES TO NAMESET

```
void gadd_set_names_nameset(
    const Gnameset *set_names /* set of names */
);
```

REMOVE SET OF NAMES FROM NAMESET

```
void gremove_set_names_nameset(
    const Gnameset *set_names /* set of names */
);
```

ADD SET OF SCISSORS TO SCISSOR SET

```
void gadd_set_scissors_scissor_set(
    const Gscissor_list *set_scissors /*set of scissors */
);
```

REMOVE SET OF SCISSORS FROM SCISSOR SET

```
void gremove_set_scissors_scissor_set(
    const Gint_list *scissor_ids /* scissor identifiers */
);
```

7.2.5 Normalization transformation functions

SET WINDOW AND VIEWPORT

```
void gset_win_vp(
    Gint tran_num, /* transformation number */
    const Gtran *win_vp /* window and viewport limits */
);
```

[SET WINDOW AND VIEWPORT]

SET WINDOW

```
void gset_win(
    Gint tran_num, /* transformation number */
    const Glimit *win /* window limits */
);
```

[SET WINDOW AND VIEWPORT]

SET VIEWPORT

```
void gset_vp(
    Gint tran_num, /* transformation number */
    const Glimit *vp /* viewport limits */
);
```

SET VIEWPORT INPUT PRIORITY

```

void gset_vp_in_pri(
    Gint      tran_num,      /* transformation number      */
    Gint      ref_tran_num,  /* reference transformation number */
    Grel_pri  rel_pri       /* relative priority          */
);

```

SET SCISSOR MODE

```

void gset_scissor_mode(
    Gscissor_mode  scissor_mode /* scissor mode */
);

```

SET NORMALIZATION TRANSFORMATION NUMBER

```

void gset_norm_tran_num(
    Gint  tran_num /* transformation number */
);

```

[SET NORMALIZATION TRANSFORMATION NUMBER]
SELECT NORMALIZATION TRANSFORMATION

```

void gsel_norm_tran(
    Gint  tran_num /* transformation number */
);

```

7.2.6 NDC picture functions

DELETE PRIMITIVES FROM NDC PICTURE

```

void gdel_prims_ndc_pic(
    const Gsel_crit  *sel_crit /* selection criterion */
);

```

ADD SET OF NAMES TO NDC PICTURE

```

void gadd_set_names_ndc_pic(
    const Gnameset  *set_names, /* set of names */
    const Gsel_crit  *sel_crit  /* selection criterion */
);

```

REMOVE SET OF NAMES FROM NDC PICTURE

```

void gremove_set_names_ndc_pic(
    const Gnameset  *set_names, /* set of names */
    const Gsel_crit  *sel_crit  /* selection criterion */
);

```

SET NDC PICTURE PRIMITIVE ATTRIBUTE

```

void gset_ndc_pic_prim_attr(
    const Gsel_crit      *sel_crit,    /* selection criterion */
    const Gprim_attr_value *attr_value /* attr_value          */
);

```

ADD SET OF SCISSORS TO NDC PICTURE

```

void gadd_set_scissors_ndc_pic(
    const Gscissor_list *set_scissors, /* scissor set */
    const Gsel_crit     *sel_crit      /* selection criterion */
);

```

REMOVE SET OF SCISSORS FROM NDC PICTURE

```

void gremove_set_scissors_ndc_pic(
    const Gint_list *scissor_ids, /* scissor identifiers */
    const Gsel_crit *sel_crit     /* selection criterion */
);

```

REORDER NDC PICTURE

```

void greorder_ndc_pic(
    const Gsel_crit *source_sel_crit, /* source selection criterion */
    const Gsel_crit *ref_sel_crit,    /* reference selection criterion */
    Grel_pos        rel_pos,          /* relative position           */
);

```

7.2.7 Metafile functions

COPY NDC PICTURE TO NDC METAFILE

```

void gcopy_ndc_pic_ndc_mf(
    const void *mf_specif, /* metafile specifier */
    Gint       pic_id,     /* picture identifier  */
    const Gsel_crit *sel_crit, /* selection criterion */
    const Gnameset *set_names /* set of names        */
);

```

COPY NDC METAFILE PICTURE TO NDC PICTURE

```

void gcopy_ndc_mf_pic_ndc_pic(
    const void *mf_specif, /* metafile specifier */
    Gint       pic_id,     /* picture identifier  */
    const Gnameset *set_names /* set of names        */
);

```

7.2.8 Picture part store functions

OPEN PICTURE PART

```
void gopen_pic_part(  
    Gint    pic_part_name    /* picture part name    */  
);
```

CLOSE PICTURE PART

```
void gclose_pic_part(  
    void  
);
```

ARCHIVE PICTURE PART

```
void gar_pic_part(  
    Gint    pic_part_name,    /* picture part name    */  
    const void *ar_specif,    /* archive specifier    */  
    Gint    ar_name_pic_part  /* archive name of picture part */  
);
```

RETRIEVE PICTURE PART FROM ARCHIVE

```
void gret_pic_part_ar(  
    const void *ar_specif,    /* archive specifier    */  
    Gint    ar_name_pic_part, /* archive name of picture part */  
    Gint    pic_part_name    /* picture part name    */  
);
```

REOPEN PICTURE PART

```
void greopen_pic_part(  
    Gint    pic_part_name    /* picture part name    */  
);
```

APPEND PICTURE PART

```

void gappend_pic_part(
    Gint          source_pic_part_name, /* source
                                         picture part name */
    Gint          sink_pic_part_name,   /* sink
                                         picture part name */
    const Gtran_matrix global_tran_matrix, /* global
                                         transformation matrix */
    Gtran_mode     global_tran_mode,      /* global
                                         transformation mode */
    const Gtran_matrix local_tran_matrix, /* local
                                         transformation matrix */
    Gtran_mode     local_tran_mode,       /* local
                                         transformation mode */
    const Gnameset  *set_names            /* set of names */
);

```

RENAME PICTURE PART

```

void grename_pic_part(
    Gint  old_pic_part_name, /* old picture part name */
    Gint  new_pic_part_name /* new picture part name */
);

```

DELETE PICTURE PART

```

void gdel_pic_part(
    Gint  pic_part_name /* picture part name */
);

```

COPY PICTURE PART FROM PICTURE PART STORE

```

void gcopy_pic_part_pic_part_store(
    Gint          pic_part_name, /* picture part name */
    const Gsel_crit *sel_crit,   /* selection criterion */
    const Gtran_matrix global_tran_matrix, /* global
                                         transformation matrix */
    Gtran_mode     global_tran_mode,      /* global
                                         transformation mode */
    const Gtran_matrix local_tran_matrix, /* local
                                         transformation matrix */
    Gtran_mode     local_tran_mode,       /* local
                                         transformation mode */
    const Gnameset  *set_names,          /* set of names */
    Gscissor_sel     scissor_sel         /* scissor select */
);

```

COPY NDC PICTURE TO PICTURE PART STORE

```

void gcopy_ndc_pic_pic_part_store(
    const Gsel_crit  *sel_crit,      /* sel. criterion      */
    Gint             pic_part_name,  /* picture part name   */
    const Gnameset   *set_names     /* set of names        */
);

```

7.2.9 Input functions

SET LOGICAL INPUT DEVICE MODE

```

void gset_in_dev_mode(
    const Gdev_id  *dev_id,  /* input device number */
    Gop_mode       op_mode   /* operating mode       */
);

```

**[SET LOGICAL INPUT DEVICE MODE]
SET LOCATOR MODE**

```

void gset_loc_mode(
    Gint          ws_id,      /* workstation identifier */
    Gint          loc_num,    /* locator device number  */
    Gop_mode       op_mode,   /* operating mode         */
    Gecho_switch  echo_switch /* echo switch            */
);

```

**[SET LOGICAL INPUT DEVICE MODE]
SET STROKE MODE**

```

void gset_stroke_mode(
    Gint          ws_id,      /* workstation identifier */
    Gint          stroke_num, /* stroke device number   */
    Gop_mode       op_mode,   /* operating mode         */
    Gecho_switch  echo_switch /* echo switch            */
);

```

**[SET LOGICAL INPUT DEVICE MODE]
SET VALUATOR MODE**

```

void gset_val_mode(
    Gint          ws_id,      /* workstation identifier */
    Gint          val_num,    /* valuator device number */
    Gop_mode       op_mode,   /* operating mode         */
    Gecho_switch  echo_switch /* echo switch            */
);

```

[SET LOGICAL INPUT DEVICE MODE]
SET CHOICE MODE

```
void gset_choice_mode(
    Gint      ws_id,      /* workstation identifier */
    Gint      choice_num, /* choice device number   */
    Gop_mode  op_mode,    /* operating mode         */
    Gecho_switch echo_switch /* echo switch           */
);
```

[SET LOGICAL INPUT DEVICE MODE]
SET PICK MODE

```
void gset_pick_mode(
    Gint      ws_id,      /* workstation identifier */
    Gint      pick_num,   /* pick device number    */
    Gop_mode  op_mode,    /* operating mode         */
    Gecho_switch echo_switch /* echo switch           */
);
```

[SET LOGICAL INPUT DEVICE MODE]
SET STRING MODE

```
void gset_string_mode(
    Gint      ws_id,      /* workstation identifier */
    Gint      string_num, /* string device number   */
    Gop_mode  op_mode,    /* operating mode         */
    Gecho_switch echo_switch /* echo switch           */
);
```

REQUEST INPUT

```
void greq_in(
    const Gdev_id *dev_id, /* input device number */
    Gin_status    *in_status, /* OUT input status    */
    Gin_value     *log_in_value /* OUT logical input value */
);
```

[REQUEST INPUT]
REQUEST LOCATOR

```
void greq_loc(
    Gint      ws_id,      /* workstation identifier */
    Gint      loc_num,    /* locator device number  */
    Gin_status *in_status, /* OUT input status       */
    Gint      *norm_tran_num, /* OUT normalization
                             transformation number */
    Gpoint    *loc_pos    /* OUT locator position   */
);
```

[REQUEST INPUT]
REQUEST STROKE

```
void greq_stroke(
    Gint      ws_id,          /* workstation identifier */
    Gint      stroke_num,     /* stroke device number   */
    Gin_status *in_status,    /* OUT input status       */
    Gint      *norm_tran_num, /* OUT normalization
                             transformation number */
    Gpoint_list *stroke       /* OUT stroke             */
);
```

REMARK. The application shall allocate the memory for the point list returned by this function. The maximum size of the returned **stroke** is specified by **ginit_stroke**. The maximum size of **stroke** supported by the implementation is returned by **ginq_def_stroke_data**.

[REQUEST INPUT]
REQUEST VALUATOR

```
void greq_val(
    Gint      ws_id,          /* workstation identifier */
    Gint      val_num,        /* valuator device number */
    Gin_status *in_status,    /* OUT input status       */
    Gfloat     *value         /* OUT value              */
);
```

[REQUEST INPUT]
REQUEST CHOICE

```
void greq_choice(
    Gint      ws_id,          /* workstation identifier */
    Gint      choice_num,     /* choice device number   */
    Gin_status *in_status,    /* OUT input status       */
    Gint      *choice         /* OUT requested choice    */
);
```

[REQUEST INPUT]
REQUEST PICK

```
void greq_pick(
    Gint      ws_id,          /* workstation identifier */
    Gint      pick_num,       /* pick device number     */
    Gin_status *in_status,    /* OUT input status       */
    Gpick     *pick           /* OUT requested pick value */
);
```

REMARK. The application shall allocate memory for the output parameter fields **pick->set_names.ws_ids.ints**, **pick->set_names.seg_names.ints**, **pick->set_names.names.ints**. If insufficient space has been allocated, an error message is issued.

[REQUEST INPUT]
REQUEST STRING

```

void greq_string(
    Gint      ws_id,          /* workstation identifier */
    Gint      string_num,     /* string device number   */
    Gint_status *in_status,   /* OUT input status       */
    char      *string         /* OUT requested string    */
);

```

REMARK. The application shall allocate the memory for the string returned by this function. The maximum size of the returned **string** is specified by **ginit_string**.

The maximum size of **string** supported by the implementation is returned by **ginq_def_string_data**.

SAMPLE INPUT

```

void gsample_in(
    const Gdev_id *dev_id,      /* input device number */
    Gint_value    *log_in_value /* OUT logical input value */
);

```

[SAMPLE INPUT]
SAMPLE LOCATOR

```

void gsample_loc(
    Gint      ws_id,          /* workstation identifier */
    Gint      loc_num,        /* locator device number   */
    Gint      *norm_tran_num, /* OUT normalization
                               transformation number */
    Gpoint    *loc_pos        /* OUT locator position    */
);

```

[SAMPLE INPUT]
SAMPLE STROKE

```

void gsample_stroke(
    Gint      ws_id,          /* workstation identifier */
    Gint      stroke_num,     /* stroke device number    */
    Gint      *norm_tran_num, /* OUT normalization
                               transformation number */
    Gpoint_list *stroke       /* OUT stroke              */
);

```

REMARK. The application shall allocate the memory for the point list returned by this function. The maximum size of the returned **stroke** is specified by **ginit_stroke**. The maximum size of **stroke** supported by the implementation is returned by **ginq_def_stroke_data**.

[SAMPLE INPUT]
SAMPLE VALUATOR

```
void gsample_val(
    Gint    ws_id,      /* workstation identifier */
    Gint    val_num,    /* valuator device number */
    Gfloat  *value      /* OUT value */
);
```

[SAMPLE INPUT]
SAMPLE CHOICE

```
void gsample_choice(
    Gint    ws_id,      /* workstation identifier */
    Gint    choice_num, /* choice device number */
    Gint_status *in_status, /* OUT input status */
    Gint    *choice     /* OUT choice */
);
```

[SAMPLE INPUT]
SAMPLE PICK

```
void gsample_pick(
    Gint    ws_id,      /* workstation identifier */
    Gint    pick_num,   /* pick device number */
    Gint_status *in_status, /* OUT input status */
    Gpick    *pick     /* OUT pick value */
);
```

REMARK. The application shall allocate memory for the output parameter fields `pick->set_names.ws_ids.ints`, `pick->set_names.seg_names.ints`, `pick->set_names.names.ints`. If insufficient space has been allocated, an error message is issued.

[SAMPLE INPUT]
SAMPLE STRING

```
void gsample_string(
    Gint    ws_id,      /* workstation identifier */
    Gint    string_num, /* string device number */
    char    *string     /* OUT string */
);
```

REMARK. The application shall allocate the memory for the string returned by this function. The maximum size of the returned `string` is specified by `ginit_string`. The maximum size of `string` supported by the implementation is returned by `ginq_def_string_data`.

AWAIT INPUT

```

void gawait_in(
    Gfloat          timeout,          /* timeout (seconds) */
    Gstore          store,            /* handle to Store object */
    Gdev_id_in_value_list **dev_id_in_values /* OUT logical
                                           input devices and
                                           logical input value */
);

```

REMARK. The memory referenced by ***dev_id_in_values** is managed by the parameter **store**.

**[AWAIT INPUT]
AWAIT EVENT**

```

void gawait_event(
    Gfloat          timeout,          /* timeout (seconds) */
    Gint            *ws_id,           /* OUT workstation identifier */
    Gin_class       *class,           /* OUT device class */
    Gint            *in_num           /* OUT logical input device number */
);

```

**[AWAIT INPUT]
GET LOCATOR**

```

void gget_loc(
    Gint            *norm_tran_num,   /* OUT normalization
                                     transformation number */
    Gpoint          *loc_pos          /* OUT locator position */
);

```

**[AWAIT INPUT]
GET STROKE**

```

void gget_stroke(
    Gint            *norm_tran_num,   /* OUT normalization
                                     transformation number */
    Gpoint_list     *stroke           /* OUT stroke */
);

```

REMARK. The application shall allocate the memory for the point list returned by this function. The maximum size of the returned **stroke** is specified by **ginit_stroke**. The maximum size of **stroke** supported by the implementation is returned by **ginq_def_stroke_data**.

**[AWAIT INPUT]
GET VALUATOR**

```
void gget_val(
    Gfloat *value /* OUT value */
);
```

**[AWAIT INPUT]
GET CHOICE**

```
void gget_choice(
    Gin_status *in_status, /* OUT input status */
    Gint *choice /* OUT choice */
);
```

**[AWAIT INPUT]
GET PICK**

```
void gget_pick(
    Gin_status *in_status, /* OUT input status */
    Gpick *pick /* OUT pick value */
);
```

REMARK. The application shall allocate memory for the output parameter fields

pick->set_names.ws_ids.ints, **pick->set_names.seg_names.ints**, **pick->set_names.names.ints**. If insufficient space has been allocated, an error message is issued.

**[AWAIT INPUT]
GET STRING**

```
void gget_string(
    char *string /* OUT string */
);
```

REMARK. The application shall allocate the memory for the string returned by this function. The maximum size of the returned **string** is specified by **ginit_string**.

The maximum size of **string** supported by the implementation is returned by **ging_def_string_data**.

FLUSH DEVICE EVENTS

```
void gflush_dev_events(
    Gdev_id *dev_id /* device identifier */
);
```

7.2.10 Font and glyph functions

SET FONT INDEX MAPPING

```
void gset_font_ind_map(
    const Gfont_ind_map *font_ind_map /* font index mapping */
);
```

GET GLYPH NAME

```
void gget_glyph_name(
    Gint font_ind, /* font index */
    char char_code, /* character code */
    Gint *glyph_name /* OUT glyph name */
);
```

SET CHARACTER CODE

```
void gset_char_code(
    Gint font_ind, /* font index */
    char char_code, /* character code */
    Gint glyph_name /* glyph name */
);
```

7.2.11 Audit and playback functions

AUDIT

```
void gaudit(
    Gint audit_id, /* audit identifier */
    const Gaudit_op *audit_op /* audit operation */
);
```

WRITE USER RECORD TO AUDIT

```
void gwrite_user_rec_audit(
    Gint audit_id, /* audit identifier */
    const Gaudit_user_data *user_data /* user data record */
);
```

PLAYBACK

```
void gplayback(
    Gint audit_id, /* audit identifier */
    const Gplayback_op *playback_op /* playback operation */
);
```

READ ITEM FUNCTION NAME FROM AUDIT

```

void gread_item_func_name_audit(
    Gint  audit_id,      /* audit identifier */
    Gint  *func_name     /* OUT function name */
);

```

READ ITEM FROM AUDIT

```

void gread_item_audit(
    Gint      audit_id,      /* audit identifier */
    Gstore    store,        /* handle to Store object */
    Gfunc_params **func_params /* OUT function parameters */
);

```

REMARK. The memory referenced by ***func_params** is managed by the parameter **store**.

PROCESS AUDIT ITEM

```

void gproc_audit_item(
    Gint      audit_id,      /* audit identifier */
    Gproc_op  proc_op        /* process operation */
);

```

7.2.12 Inquiry functions

INQUIRE OPERATING STATE ENTRY

```

void ginq_op_st_entry(
    Gop_st_name  op_st_name,      /* entry name */
    Gint         *err_ind,        /* OUT error indicator */
    Gop_st_entry *op_st_entry     /* OUT operating state */
);

```

INQUIRE GKS DESCRIPTION TABLE ENTRY

```

void ginq_gks_dt_entry(
    Ggks_dt_name  gks_dt_name,      /* entry name */
    Gstore        store,            /* handle to Store object */
    Gint          *err_ind,        /* OUT error indicator */
    Ggks_dt_entry *gks_dt          /* OUT GKS
                                   description table entry */
);

```

REMARK. The memory referenced by ***gks_dt** is managed by the parameter **store**.

[INQUIRE GKS DESCRIPTION TABLE ENTRY]
INQUIRE LIST OF AVAILABLE WORKSTATION TYPES

```
void ginq_list_avail_ws_types(
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,          /* starting index */
    Gint      *err_ind,           /* OUT error indicator */
    Gint_list *ws_gen_types,      /* OUT list of available generic
                                ws types */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GKS DESCRIPTION TABLE ENTRY]
INQUIRE LIST OF AVAILABLE FONTS

```
void ginq_list_avail_fonts(
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,          /* starting index */
    Gint      *err_ind,           /* OUT error indicator */
    Gint_list *fonts,             /* OUT list of available fonts */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GKS DESCRIPTION TABLE ENTRY]
INQUIRE DEFAULT FONT INDEX MAPPING

```
void ginq_def_font_ind_map(
    Gint      *err_ind, /* OUT error indicator */
    Gfont_ind_map *font_ind_map /* OUT font index mapping */
);
```

INQUIRE GKS STATE LIST ENTRY

```
void ginq_gks_sl_entry(
    Ggks_sl_name gks_sl_name, /* entry name */
    Gstore       store,        /* handle to Store object */
    Gint         *err_ind,     /* OUT error indicator */
    Ggks_sl_entry **gks_sl_entry /* OUT GKS state
                                list */
);
```

REMARK. The memory referenced by ***gks_sl_entry** is managed by the parameter **store**.

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE ROUTE DIRECTION

```
void ginq_route_dir(
    Gint      *err_ind, /* OUT error indicator */
    Groute_dir *route_dir /* OUT current route direction */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SCISSOR MODE

```
void ginq_scissor_mode(
    Gint      *err_ind,          /* OUT error indicator */
    Gscissor_mode *scissor_mode /* OUT current scissor mode */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF OPEN WORKSTATIONS

```
void ginq_set_open_wss(
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,          /* starting index */
    Gint      *err_ind,          /* OUT error indicator */
    Gint_list *open_ws,          /* OUT list of open ws ids */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF ACTIVE WORKSTATIONS

```
void ginq_set_active_wss(
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,          /* starting index */
    Gint      *err_ind,          /* OUT error indicator */
    Gint_list *active_ws,        /* OUT list of active ws ids */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF OPEN AUDITS

```
void ginq_set_open_audits(
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,          /* starting index */
    Gint      *err_ind,          /* OUT error indicator */
    Gopen_audit_list *open_audit_set, /* OUT set of open audits */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF OPEN PLAYBACKS

```
void ginq_set_open_playbacks(
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,          /* starting index */
    Gint      *err_ind,           /* OUT error indicator */
    Gint_list *open_playbacks,    /* OUT set of open playbacks */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE INPUT QUEUE

```
void ginq_in_queue(
    Gstore store, /* handle to Store object */
    Gint    *err_ind, /* OUT error indicator */
    Gin_queue **in_queue /* OUT input queue */
);
```

REMARK. The memory referenced by **in_queue* is managed by the parameter *store*.

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE FONT INDEX MAPPING

```
void ginq_font_ind_map(
    Gint      *err_ind, /* OUT error indicator */
    Gfont_ind_map *font_ind_map /* OUT font index mapping */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE CURRENT PICK IDENTIFIER VALUE

```
void ginq_cur_pick_id(
    Gint *err_ind, /* OUT error indicator */
    Gint *pick_id /* OUT current pick identifier */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE NAMESET

```
void ginq_nameset(
    Gstore store, /* handle to Store object */
    Gint    *err_ind, /* OUT error indicator */
    Gnameset **nameset /* nameset */
);
```

REMARK. The memory referenced by **nameset* is managed by the parameter *store*.

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SCISSOR SET

```
void ginq_scissor_set(
    Gstore      store,          /* handle to Store object */
    Gint         *err_ind,      /* OUT error indicator */
    Gscissor_list **scissor_set /* scissor */
);
```

REMARK. The memory referenced by ***scissor_set** is managed by the parameter **store**.

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE GLOBAL TRANSFORMATION MATRIX

```
void ginq_global_tran_matrix(
    Gtran_matrix global_tran_matrix /* global transformation
                                     matrix */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LOCAL TRANSFORMATION MATRIX

```
void ginq_local_tran_matrix(
    Gtran_matrix local_tran_matrix /* local transformation
                                     matrix */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE PATTERN SIZE

```
void ginq_pat_size(
    Gint         *err_ind, /* OUT error indicator */
    Gfloat_size  *pat_size /* OUT current pattern size */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE PATTERN REFERENCE POINT

```
void ginq_pat_ref_point(
    Gint         *err_ind, /* OUT error indicator */
    Gpoint       *pat_ref_point /* OUT current pattern reference point */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE CHARACTER HEIGHT

```
void ginq_char_ht(
    Gint         *err_ind, /* OUT error indicator */
    Gfloat       *char_ht  /* OUT current character height */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE CHARACTER UP VECTOR

```
void ginq_char_up_vec(
    Gint    *err_ind,      /* OUT error indicator    */
    Gvec    *char_up_vec  /* OUT current character up vector */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE TEXT SKEW ANGLE

```
void ginq_text_skew_angle(
    Gint    *err_ind,      /* OUT error indicator    */
    Gfloat  *text_skew_angle /* OUT current text skew angle */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE TEXT PATH

```
void ginq_text_path(
    Gint    *err_ind,      /* OUT error indicator    */
    Gtext_path *text_path /* OUT current text path */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE TEXT ALIGNMENT

```
void ginq_text_align(
    Gint    *err_ind,      /* OUT error indicator    */
    Gtext_align *text_align /* OUT current text alignment */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LINE INDEX

```
void ginq_line_ind(
    Gint    *err_ind,      /* OUT error indicator    */
    Gint    *line_ind      /* OUT current line index */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LINETYPE

```
void ginq_linetype(
    Gint    *err_ind,      /* OUT error indicator    */
    Gint    *linetype      /* OUT current linetype */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LINEWIDTH SCALE FACTOR

```
void ginq_linewidth(
    Gint    *err_ind,    /* OUT error indicator */
    Gfloat  *linewidth  /* OUT current linewidth scale factor */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LINE COLOUR SPECIFIER

```
void ginq_line_colr_specif(
    Gint    *err_ind,    /* OUT error indicator */
    Gcolr_specif *line_colr_specif /* OUT current line colour specifier */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LINE COLOUR INDEX

```
void ginq_line_colr_ind(
    Gint    *err_ind,    /* OUT error indicator */
    Gint    *line_colr_ind /* OUT line colour index */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE MARKER INDEX

```
void ginq_marker_ind(
    Gint    *err_ind,    /* OUT error indicator */
    Gint    *marker_ind /* OUT current marker index */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE MARKER TYPE

```
void ginq_marker_type(
    Gint    *err_ind,    /* OUT error indicator */
    Gint    *marker_type /* OUT current marker type */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE MARKER SIZE SCALE FACTOR

```
void ginq_marker_size(
    Gint    *err_ind,    /* OUT error indicator */
    Gfloat  *marker_size /* OUT current marker size scale factor */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE MARKER COLOUR SPECIFIER

```
void ginq_marker_colr_specif(
    Gint      *err_ind,          /* OUT error indicator */
    Gcolr_specif *marker_colr_specif /* OUT current marker
                                     colour specifier */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE MARKER COLOUR INDEX

```
void ginq_marker_colr_ind(
    Gint      *err_ind,          /* OUT error indicator */
    Gint      *marker_colr_ind /* OUT marker colour index */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE AREA INDEX

```
void ginq_area_ind(
    Gint      *err_ind,          /* OUT error indicator */
    Gint      *area_ind         /* OUT current area index */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE INTERIOR STYLE

```
void ginq_int_style(
    Gint      *err_ind,          /* OUT error indicator */
    Gint_style *int_style       /* OUT current interior style */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE INTERIOR STYLE INDEX

```
void ginq_int_style_ind(
    Gint      *err_ind,          /* OUT error indicator */
    Gint      *int_style_ind     /* OUT current interior style index */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE INTERIOR COLOUR SPECIFIER

```
void ginq_int_colr_specif(
    Gint      *err_ind,          /* OUT error indicator */
    Gcolr_specif *int_colr_specif /* OUT current interior
                                     colour specifier */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE INTERIOR COLOUR INDEX**

```
void ginq_int_colr_ind(
    Gint    *err_ind,      /* OUT error indicator    */
    Gint    *int_colr_ind /* OUT interior colour index */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE EDGE FLAG**

```
void ginq_edge_flag(
    Gint    *err_ind,      /* OUT error indicator    */
    Gedge_flag *edge_flag /* OUT current edge flag  */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE EDGETYPE**

```
void ginq_edgetype(
    Gint    *err_ind,      /* OUT error indicator    */
    Gint    *edgetype     /* OUT current edgetype   */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE EDGEWIDTH SCALE FACTOR**

```
void ginq_edgewidth(
    Gint    *err_ind,      /* OUT error indicator    */
    Gfloat  *edgewidth    /* OUT current edgewidth scale factor */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE EDGE COLOUR SPECIFIER**

```
void ginq_edge_colr_specif(
    Gint    *err_ind,      /* OUT error indicator    */
    Gcolr_specif *edge_colr_specif /* OUT current edge colour specifier */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE EDGE COLOUR INDEX**

```
void ginq_edge_colr_ind(
    Gint    *err_ind,      /* OUT error indicator    */
    Gint    *edge_colr_ind /* OUT edge colour index  */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE TEXT INDEX**

```
void ginq_text_ind(
    Gint *err_ind, /* OUT error indicator */
    Gint *text_ind /* OUT current text index */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE TEXT FONT AND PRECISION**

```
void ginq_text_font_prec(
    Gint *err_ind, /* OUT error indicator */
    Gtext_font_prec *font_prec /* OUT current text font and precision */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE CHARACTER EXPANSION FACTOR**

```
void ginq_char_expan(
    Gint *err_ind, /* OUT error indicator */
    Gfloat *char_expan /* OUT current character expansion factor */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE CHARACTER SPACING**

```
void ginq_char_space(
    Gint *err_ind, /* OUT error indicator */
    Gfloat *char_space /* OUT current character spacing */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE TEXT COLOUR SPECIFIER**

```
void ginq_text_colr_specif(
    Gint *err_ind, /* OUT error indicator */
    Gcolr_specif *text_colr_specif /* OUT current text colour specifier */
);
```

**[INQUIRE GKS STATE LIST ENTRY]
INQUIRE TEXT COLOUR INDEX**

```
void ginq_text_colr_ind(
    Gint *err_ind, /* OUT error indicator */
    Gint *text_colr_ind /* OUT text colour index */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE ATTRIBUTE SOURCE FLAGS

```
void ginq_asfs(
    Gint    *err_ind,    /* OUT error indicator */
    Gasfs   *asfs       /* OUT current attribute source flags */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE CURRENT NORMALIZATION TRANSFORMATION NUMBER

```
void ginq_cur_norm_tran_num(
    Gint    *err_ind,    /* OUT error indicator */
    Gint    *norm_tran_num /* OUT current normalization
                           transformation number */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LIST OF NORMALIZATION TRANSFORMATIONS

```
void ginq_list_norm_trans(
    Gint    *err_ind,    /* OUT error indicator */
    Gtran   norm_tran[64] /* OUT list of normalization
                           transformations */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE NORMALIZATION TRANSFORMATION

```
void ginq_norm_tran(
    Gint    num,          /* normalization transformation number */
    Gint    *err_ind,    /* OUT error indicator */
    Gtran   *norm_tran   /* OUT normalization transformation */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE LIST OF VIEWPORT INPUT PRIORITIES

```
void ginq_list_vp_in_pris(
    Gint    *err_ind,    /* OUT error indicator */
    Gint    vp_in_pri[64] /* OUT list of viewport input
                           priorities */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE NAME OF OPEN PICTURE PART

```
void ginq_name_open_pic_part(
    Gint    *err_ind,          /* OUT error indicator    */
    Gint    *name_open_pic_part /* OUT name of open picture
                                part                          */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF PICTURE PART NAMES IN USE

```
void ginq_set_pic_part_names(
    Gint    num_elems_appl_list, /* length of application list */
    Gint    start_ind,          /* starting index             */
    Gint    *err_ind,          /* OUT error indicator        */
    Gint_list *pic_part_names, /* OUT list of picture part names */
    Gint    *num_elems_impl_list /* OUT length of impl. list    */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE NAME OF OPEN SEGMENT

```
void ginq_name_open_seg(
    Gint    *err_ind,          /* OUT error indicator    */
    Gint    *name_open_seg    /* OUT name of open segment */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF SEGMENT NAMES IN USE

```
void ginq_set_seg_names(
    Gint    num_elems_appl_list, /* length of application list */
    Gint    start_ind,          /* starting index             */
    Gint    *err_ind,          /* OUT error indicator        */
    Gint_list *seg_names,      /* OUT list of segment names  */
    Gint    *num_elems_impl_list /* OUT length of impl. list    */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SEGMENT ATTRIBUTES

```
void ginq_seg_attrs(
    Gint    seg_name,          /* segment name             */
    Gint    *err_ind,          /* OUT error indicator        */
    Gseg_attrs *seg_attrs    /* OUT segment attributes    */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF ASSOCIATED WORKSTATIONS

```
void ginq_set_assoc_wss(
    Gint      seg_name,          /* segment name          */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,         /* starting index        */
    Gint      *err_ind,          /* OUT error indicator    */
    Gint_list *assoc_wss,        /* OUT list of
                                associated workstations */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE NAME OF OPEN STENCIL

```
void ginq_name_open_stencil(
    Gint *err_ind, /* OUT error indicator */
    Gint *name_open_stencil /* OUT name of open stencil */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE SET OF STENCIL NAMES IN USE

```
void ginq_set_stencil_names(
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,          /* starting index              */
    Gint      *err_ind,           /* OUT error indicator         */
    Gint_list *stencil_names,     /* OUT list of stencil names   */
    Gint      *num_elems_impl_list /* OUT length of impl. list    */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE STENCIL ATTRIBUTES

```
void ginq_stencil_attrs(
    Gint      stencil_name, /* stencil name          */
    Gint      *err_ind,     /* OUT error indicator    */
    Gint_list *stencil_attrs /* OUT stencil attributes */
);
```

[INQUIRE GKS STATE LIST ENTRY]
INQUIRE CURRENT CONTOUR ATTRIBUTES

```
void ginq_cur_cont_attrs(
    Gint *err_ind, /* OUT error indicator */
    Gint_list *cont_attrs /* OUT contour attributes */
);
```

[INQUIRE GKS STATE LIST ENTRY]

INQUIRE NAME OF OPEN TILING

```

void ginq_name_open_tiling(
    Gint    *err_ind,          /* OUT error indicator    */
    Gint    *name_open_tiling /* OUT name of open tiling */
);

```

[INQUIRE GKS STATE LIST ENTRY]

INQUIRE SET OF TILING NAMES IN USE

```

void ginq_set_tiling_names(
    Gint    num_elems_appl_list, /* length of application list */
    Gint    start_ind,          /* starting index              */
    Gint    *err_ind,          /* OUT error indicator         */
    Gint_list *tiling_names,    /* OUT list of tiling names    */
    Gint    *num_elems_impl_list /* OUT length of impl. list    */
);

```

INQUIRE INPUT QUEUE OVERFLOW

```

void ginq_in_overf(
    Gint    *err_ind,          /* OUT error indicator         */
    Gint    *ws_id,           /* OUT workstation identifier  */
    Gint_list *meas_class,    /* OUT measure class          */
    Gint    *in_num           /* OUT logical input device number */
);

```

7.2.13 Utility functions

7.2.13.1 GKS Utilities

EVALUATE TRANSFORMATION MATRIX

```

void geval_tran_matrix(
    const Gpoint *point,      /* fixed point                */
    const Gvec   *shift,      /* shift vector                */
    Gfloat       angle,       /* rotation angle              */
    const Gvec   *scale,      /* scale factors               */
    Gcoord_switch coord_switch, /* coordinate switch           */
    Gtran_matrix tran_matrix  /* OUT transformation matrix   */
);

```

REMARK. The parameter **coord_switch** is unused.

ACCUMULATE TRANSFORMATION MATRIX

```

void gaccum_tran_matrix(
    const Gtran_matrix  matrix,          /* transformation matrix */
    const Gpoint        *point,          /* fixed point           */
    const Gvec          *shift,          /* shift vector          */
    Gfloat              angle,           /* rotation angle        */
    const Gvec          *scale,          /* scale factors         */
    Gcoord_switch       coord_switch,    /* coordinate switch     */
    Gtran_matrix        tran_matrix      /* OUT transformation matrix */
);

```

REMARK. The parameter `coord_switch` is unused.

EVALUATE CIRCLE

```

void geval_circle(
    const Gpoint  *circ_ctr,  /* circle centre */
    Gfloat        radius,     /* radius         */
    Gconic_matrix circle      /* OUT circle    */
);

```

EVALUATE ELLIPSE

```

void geval_ell(
    const Gpoint  *ell_ctr,          /* ellipse centre */
    const Gpoint  conj_radius_end_point[2], /* conjugate radius end points */
    Gconic_matrix ell               /* OUT ellipse    */
);

```

EVALUATE CIRCULAR ARC 3 POINT

```

void geval_circ_arc_3_point(
    const Gpoint  circ_point[3], /* 3 circle points
                                (start, intermediate, end) */
    Gconic_sec    *circ_arc      /* OUT circular arc */
);

```

EVALUATE CIRCULAR ARC CENTRE

```

void geval_circ_arc_ctr(
    const Gpoint  *circ_ctr,  /* circle centre */
    const Gvec    vec[2],     /* start and end vector */
    Gsense_flag   sense_flag, /* sense flag      */
    Gfloat        radius,     /* radius          */
    Gconic_sec    *circ_arc   /* OUT circular arc */
);

```

EVALUATE ELLIPTIC ARC

```

void geval_ell_arc(
    const Gpoint  *ell_ctr,           /* ellipse centre      */
    const Gpoint  conj_radius_end_point[2], /* conjugate
                                         radius end points    */
    const Gvec     vec[2],           /* start and end vector */
    Gconic_sec     *ell_arc          /* OUT elliptic arc    */
);

```

EVALUATE HYPERBOLIC ARC

```

void geval_hyp_arc(
    const Gpoint  *tran_radius_end_point, /* transverse
                                         radius end point     */
    const Gpoint  *hyp_ctr,             /* hyperbola centre    */
    const Gpoint  *conj_radius_end_point, /* conjugate
                                         radius end point     */
    const Gvec     vec[2],             /* start and end vector */
    Gconic_sec     *hyp_arc            /* OUT hyperbolic arc  */
);

```

EVALUATE PARABOLIC ARC

```

void geval_par_arc(
    const Gpoint  *start_point, /* start point      */
    const Gpoint  *intersec_point, /* tangential
                                         intersection point  */
    const Gpoint  *end_point, /* end point      */
    Gconic_sec     *par_arc    /* OUT parabolic arc */
);

```

EVALUATE WC ORDINATE

```

void geval_wc_ord(
    Gfloat  wc_ord, /* WC ordinate */
    Gord_sel ord_sel, /* ordinate selector */
    Gfloat  *ndc_value /* OUT NDC value */
);

```

7.2.13.2 Binding Specific Utilities

SET ERROR HANDLING

```

void gset_err_hand(
    const void    (*new_hand)(Gint , Gint , const char *),
                  /* the application's error handling address */
    void          (**old_hand)(Gint , Gint , const char *)
                  /* OUT address of the error handling replaced */
);

```

Effect: See 3.11.

CREATE STORAGE

```

void gcreate_store(
    Gint    *err_ind,    /* OUT error indicator */
    Gstore  *store       /* OUT handle to Store object */
);

```

Effect: See 3.9.2

DELETE STORAGE

```

void gdel_store(
    Gint    *err_ind,    /* OUT error indicator */
    Gstore  *store       /* IN/OUT storage to be deleted */
);

```

Effect: See 3.9.2

7.3 Workstation functions

7.3.1 Control functions

OPEN WORKSTATION

```

void gopen_ws(
    Gint    ws_id,          /* workstation identifier */
    const void *ws_specif_info, /* workstation specifier
                                and specific information */
    Gint    ws_gen_type     /* generic workstation type */
);

```

CLOSE WORKSTATION

```

void gclose_ws(
    Gint    ws_id /* workstation identifier */
);

```

SAVE WORKSTATION STATE LIST

```

void gsave_ws_sl(
    Gint          ws_id,          /* workstation identifier */
    const Gws_sl_name_list *entry_names, /* list of entry
                                         names */
    Gstore        store,          /* handle to Store object */
    Gws_sl_entry_list **entry_list /* OUT list of
                                         entry values */
);

```

REMARK. The memory referenced by ***entry_list** is managed by the parameter **store**.

RESTORE WORKSTATION STATE LIST

```

void grestore_ws_sl(
    Gint          ws_id,          /* workstation identifier */
    const Gws_sl_entry_list *entries /* list of entries */
);

```

GET WORKSTATION STATUS

```

void gget_ws_status(
    Gint          ws_id,          /* workstation identifier */
    Gws_status    *ws_status     /* OUT workstation status */
);

```

REMOVE BACKDROP

```

void gremove_backdrop(
    Gint ws_id /* workstation identifier */
);

```

SET REPRESENTATION

```

void gset_rep(
    Gint          ws_id,          /* workstation identifier */
    const Grep    *rep_value     /* representation value */
);

```

**[SET REPRESENTATION]
SET LINE REPRESENTATION**

```

void gset_line_rep(
    Gint          ws_id,          /* workstation identifier */
    Gint          line_ind,       /* line index */
    const Gline_bundle *line_bundle /* line representation */
);

```

[SET REPRESENTATION]
SET MARKER REPRESENTATION

```

void gset_marker_rep(
    Gint          ws_id,          /* workstation identifier */
    Gint          marker_ind,     /* marker index          */
    const Gmarker_bundle *marker_bundle /* marker representation */
);

```

[SET REPRESENTATION]
SET TEXT REPRESENTATION

```

void gset_text_rep(
    Gint          ws_id,          /* workstation identifier */
    Gint          text_ind,       /* text index            */
    const Gtext_bundle *text_bundle /* text representation   */
);

```

[SET REPRESENTATION]
SET AREA REPRESENTATION

```

void gset_area_rep(
    Gint          ws_id,          /* workstation identifier */
    Gint          area_ind,       /* area index            */
    const Garea_bundle *area_bundle /* area representation   */
);

```

[SET REPRESENTATION]
SET PATTERN REPRESENTATION

```

void gset_pat_rep(
    Gint          ws_id,          /* workstation identifier */
    Gint          pat_ind,       /* pattern index          */
    const Gpat_rep *pat_rep     /* pattern representation */
);

```

[SET REPRESENTATION]
SET COLOUR REPRESENTATION

```

void gset_colr_rep(
    Gint          ws_id,          /* workstation identifier */
    Gint          colr_ind,       /* colour index           */
    const Gcolr_rep *colr_rep    /* colour representation  */
);

```

SET VIEW PRIORITY

```
void gset_view_pri(
    Gint      ws_id,          /* workstation identifier */
    Gint      view_ind,       /* view index             */
    Gint      ref_view_ind,   /* reference view index    */
    Grel_pri  rel_pri         /* relative priority       */
);
```

SET VIEW SELECTION CRITERION

```
void gset_view_sel_crit(
    Gint      ws_id,          /* workstation identifier */
    Gint      view_ind,       /* view index             */
    const Gsel_crit *sel_crit /* selection criterion     */
);
```

SET VIEW

```
void gset_view(
    Gint      ws_id,          /* workstation identifier */
    Gint      view_ind,       /* view index             */
    const Gtran_matrix ori_matrix, /* view orientation matrix */
    const Gtran_matrix map_matrix, /* view mapping matrix     */
    const Gscissor *scissor, /* view scissor            */
);
```

SET WORKSTATION VISUAL EFFECTS

```
void gset_ws_vis_effects(
    Gint      ws_id,          /* workstation identifier */
    Gvis_effects_st vis_effects_st /* visual effects state */
);
```

SET WORKSTATION WINDOW AND VIEWPORT

```
void gset_ws_win_vp(
    Gint      ws_id,          /* workstation identifier */
    const Gtran *ws_win_vp /* workstation window
                           and viewport limits */
);
```

[SET WORKSTATION WINDOW AND VIEWPORT]
SET WORKSTATION WINDOW

```
void gset_ws_win(
    Gint      ws_id,          /* workstation identifier */
    const Glimit *ws_win     /* workstation window     */
);
```

**[SET WORKSTATION WINDOW AND VIEWPORT]
SET WORKSTATION VIEWPORT**

```
void gset_ws_vp(
    Gint      ws_id,    /* workstation identifier */
    const Glimit *ws_vp /* workstation viewport limits */
);
```

DEFINE LOGICAL INPUT DEVICE

```
void gdef_in_dev(
    const Gdev_id      *dev_id,    /* device identifier */
    const Gint_list     *meas_seq,  /* measure sequence */
    const Gint_list     *trigger_set, /* trigger set */
    const Ginit_value   *init_value /* initial value */
);
```

INITIALIZE LOGICAL INPUT DEVICE

```
void ginit_in_dev(
    const Gdev_id      *dev_id,    /* device identifier */
    const Ginit_value   *init_value /* initial value */
);
```

**[INITIALIZE LOGICAL INPUT DEVICE]
INITIALIZE LOCATOR**

```
void ginit_loc(
    Gint      ws_id,    /* workstation identifier */
    Gint      loc_num,  /* locator device number */
    Gint      init_norm_tran_num, /* initial normalization
                                transformation number */
    const Gpoint *init_loc_pos, /* initial locator position */
    Gint      pet,        /* prompt and echo type */
    const Glimit *echo_area, /* echo area */
    const Gloc_data *loc_data /* locator data record */
);
```

[INITIALIZE LOGICAL INPUT DEVICE]
INITIALIZE STROKE

```

void ginit_stroke(
    Gint          ws_id,          /* workstation identifier */
    Gint          stroke_num,     /* stroke device number  */
    Gint          init_norm_tran_num, /* initial normalization
                                   transformation number */
    const Gpoint_list *init_stroke, /* initial stroke */
    Gint          pet,            /* prompt and echo type  */
    const Glimit   *echo_area,    /* echo area */
    const Gstroke_data *stroke_data /* stroke data record */
);

```

[INITIALIZE LOGICAL INPUT DEVICE]
INITIALIZE VALUATOR

```

void ginit_val(
    Gint          ws_id,          /* workstation identifier */
    Gint          val_num,        /* valuator device number */
    Gfloat        init_value,     /* initial value */
    Gint          pet,            /* prompt and echo type  */
    const Glimit   *echo_area,    /* echo area */
    const Gval_data *val_data     /* valuator data record */
);

```

[INITIALIZE LOGICAL INPUT DEVICE]
INITIALIZE CHOICE

```

void ginit_choice(
    Gint          ws_id,          /* workstation identifier */
    Gint          choice_num,     /* choice device number  */
    Gin_status    init_status,    /* initial status */
    Gint          init_choice,    /* initial choice */
    Gint          pet,            /* prompt and echo type  */
    const Glimit   *echo_area,    /* echo area */
    const Gchoice_data *choice_data /* choice data record */
);

```

[INITIALIZE LOGICAL INPUT DEVICE]
INITIALIZE PICK

```
void ginit_pick(
    Gint      ws_id,      /* workstation identifier */
    Gint      pick_num,   /* pick device number    */
    Gint      init_status, /* initial status         */
    const Gpick *init_pick, /* initial pick value     */
    Gint      pet,        /* prompt and echo type   */
    const Glimit *echo_area, /* echo area              */
    const Gpick_data *pick_data /* pick data record      */
);
```

[INITIALIZE LOGICAL INPUT DEVICE]
INITIALIZE STRING

```
void ginit_string(
    Gint      ws_id,      /* workstation identifier */
    Gint      string_num, /* string device number   */
    const char *init_string, /* initial string         */
    Gint      pet,        /* prompt and echo type   */
    const Glimit *echo_area, /* echo area              */
    const Gstring_data *string_data /* string data record    */
);
```

SET WORKSTATION SELECTION CRITERION

```
void gset_ws_sel_crit(
    Gint      ws_id, /* workstation identifier */
    const Gsel *sel, /* selection type and criterion */
);
```

COPY REALIZED PICTURE TO REALIZED METAFILE

```
void gcopy_real_pic_real_mf(
    Gint      ws_id, /* workstation identifier */
    const void *mf_specif, /* metafile specifier    */
    Gint      pic_id /* picture identifier     */
);
```

COPY BLANK REALIZED PICTURE TO REALIZED METAFILE

```
void gcopy_blank_real_pic_real_mf(
    Gint      ws_id, /* workstation identifier */
    const void *mf_specif, /* metafile specifier    */
    Gint      pic_id /* picture identifier     */
);
```

COPY REALIZED METAFILE PICTURE TO BACKDROP

```
void gcopy_real_mf_pic_backdrop(
    Gint      ws_id,          /* workstation identifier */
    const void *mf_specif,    /* metafile specifier    */
    Gint      pic_id          /* picture identifier     */
);
```

MESSAGE

```
void gmessage(
    Gint      ws_id,          /* workstation identifier */
    const char *message       /* message string         */
);
```

7.3.2 Inquiry functions

INQUIRE WORKSTATION STATE LIST ENTRY

```
void ginq_ws_sl_entry(
    Gint      ws_id,          /* workstation identifier */
    Gws_sl_name name,        /* entry name             */
    Ginq_type type,          /* type of returned values */
    Gstore    store,         /* handle to Store object  */
    Gint      *err_ind,      /* OUT error indicator     */
    Gws_sl_entry **ws_sl_entry /* OUT workstation state list entry */
);
```

REMARK. The memory referenced by ***ws_sl_entry** is managed by the parameter **store**.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE WORKSTATION CONNECTION AND TYPE

```
void ginq_ws_conn_type(
    Gint      ws_id,          /* workstation identifier */
    Gstore    store,         /* handle to Store object  */
    Gint      *err_ind,      /* OUT error indicator     */
    void      **conn_id,     /* OUT connection identifier */
    Gint      *ws_type       /* OUT workstation type    */
);
```

REMARK. The memory referenced by ***conn_id** is managed by the parameter **store**.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE WORKSTATION STATE

```
void ginq_ws_st(
    Gint    ws_id,      /* workstation identifier */
    Gint    *err_ind,   /* OUT error indicator   */
    Gws_st  *ws_st      /* OUT workstation state  */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LIST OF LINE INDICES

```
void ginq_list_line_inds(
    Gint    ws_id,      /* workstation identifier */
    Gint    num_elems_appl_list, /* length of application list */
    Gint    start_ind,   /* starting index         */
    Gint    *err_ind,   /* OUT error indicator     */
    Gint_list *def_line_inds, /* OUT list of defined
                                line indices             */
    Gint    *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LINE REPRESENTATION

```
void ginq_line_rep(
    Gint    ws_id,      /* workstation identifier */
    Gint    line_ind,   /* line index             */
    Ginq_type type,     /* type of returned values */
    Gint    *err_ind,   /* OUT error indicator     */
    Gline_bundle *line_rep /* OUT line representation */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LIST OF MARKER INDICES

```
void ginq_list_marker_inds(
    Gint    ws_id,      /* workstation identifier */
    Gint    num_elems_appl_list, /* length of application list */
    Gint    start_ind,   /* starting index         */
    Gint    *err_ind,   /* OUT error indicator     */
    Gint_list *def_marker_inds, /* OUT list of defined
                                marker indices             */
    Gint    *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE MARKER REPRESENTATION

```
void ginq_marker_rep(
    Gint      ws_id,          /* workstation identifier */
    Gint      marker_ind,     /* marker index */
    Ginq_type type,           /* type of returned values */
    Gint      *err_ind,       /* OUT error indicator */
    Gmarker_bundle *marker_rep /* OUT marker representation */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LIST OF TEXT INDICES

```
void ginq_list_text_inds(
    Gint      ws_id,          /* workstation identifier */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,       /* starting index */
    Gint      *err_ind,       /* OUT error indicator */
    Gint_list *def_text_inds,   /* OUT list of defined
                                text indices */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE TEXT REPRESENTATION

```
void ginq_text_rep(
    Gint      ws_id,          /* workstation identifier */
    Gint      text_ind,       /* text index */
    Ginq_type type,           /* type of returned values */
    Gint      *err_ind,       /* OUT error indicator */
    Gtext_bundle *text_rep    /* OUT text representation */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LIST OF AREA INDICES

```
void ginq_list_area_inds(
    Gint      ws_id,          /* workstation identifier */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,       /* starting index */
    Gint      *err_ind,       /* OUT error indicator */
    Gint_list *def_area_inds,   /* OUT list of defined
                                area indices */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE AREA REPRESENTATION

```
void ginq_area_rep(
    Gint      ws_id,      /* workstation identifier */
    Gint      area_ind,   /* area index */
    Ginq_type type,       /* type of returned values */
    Gint      *err_ind,   /* OUT error indicator */
    Garea_bundle *area_rep /* OUT area representation */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LIST OF PATTERN INDICES

```
void ginq_list_pat_inds(
    Gint      ws_id,      /* workstation identifier */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,   /* starting index */
    Gint      *err_ind,   /* OUT error indicator */
    Gint_list *def_pat_inds, /* OUT list of defined
                             pattern indices */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE PATTERN REPRESENTATION

```
void ginq_pat_rep(
    Gint      ws_id,      /* workstation identifier */
    Gint      pat_ind,    /* pattern index */
    Ginq_type type,       /* type of returned values */
    Gstore    store,      /* handle to Store object */
    Gint      *err_ind,   /* OUT error indicator */
    Gpat_rep  **pat_rep   /* OUT pattern representation */
);
```

REMARK. The memory referenced by *pat_rep is managed by the parameter store.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LIST OF COLOUR INDICES

```
void ginq_list_colr_inds(
    Gint      ws_id,      /* workstation identifier */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,   /* starting index */
    Gint      *err_ind,   /* OUT error indicator */
    Gint_list *def_colr_inds, /* OUT list of defined
                             colour indices */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE COLOUR REPRESENTATION

```
void ginq_colr_rep(
    Gint      ws_id,      /* workstation identifier */
    Gint      colr_ind,   /* colour index           */
    Ginq_type type,       /* type of returned values */
    Gint      *err_ind,   /* OUT error indicator     */
    Gcolr_rep *colr_rep  /* OUT colour representation */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE WORKSTATION WINDOW AND VIEWPORT

```
void ginq_ws_win_vp(
    Gint      ws_id,      /* workstation identifier */
    Gint      *err_ind,   /* OUT error indicator     */
    Gtran     *ws_win_vp /* OUT workstation window
                        and viewport */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE VISUAL EFFECTS STATE

```
void ginq_vis_effects_st(
    Gint      ws_id,      /* workstation identifier */
    Gint      *err_ind,   /* OUT error indicator     */
    Gvis_effects_st *vis_effects_st /* OUT visual effects state */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE TABLE OF SELECTION CRITERIA

```
void ginq_sel_table(
    Gint      ws_id,      /* workstation identifier */
    Gstore     store,     /* handle to Store object */
    Gint      *err_ind,   /* OUT error indicator     */
    Gsel_table **sel_table /* OUT table of selection criteria */
);
```

REMARK. The memory referenced by ***sel_table** is managed by the parameter **store**.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE SET OF SEGMENT NAMES ON WORKSTATION

```
void ginq_set_seg_names_ws(
    Gint      ws_id,           /* workstation identifier */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,       /* starting index */
    Gint      *err_ind,        /* OUT error indicator */
    Gint_list *seg_names,      /* OUT list of segment names */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE INPUT DEVICE OPERATING MODES AND INITIAL VALUES

```
void ginq_in_dev_op_modes_init_values(
    Gint      ws_id,           /* workstation identifier */
    Gstore     store,          /* handle to Store object */
    Gint      *err_ind,        /* OUT error indicator */
    Gop_modes_init_values **op_modes_init_values /* OUT table of
                                                    input device
                                                    operating modes and
                                                    initial values */
);
```

REMARK. The memory referenced by ***in_table** is managed by the parameter **store**.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE VIEW REPRESENTATION

```
void ginq_view_rep(
    Gint      ws_id,           /* workstation identifier */
    Gint      view_ind,       /* view index */
    Ginq_type type,           /* type of returned values */
    Gstore     store,          /* handle to Store object */
    Gint      *err_ind,        /* OUT error indicator */
    Gview_rep **view_rep      /* OUT view representation */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE VIEW PRIORITIES

```
void ginq_view_pris(
    Gint      ws_id,           /* workstation identifier */
    Ginq_type type,           /* type of returned values */
    Gint      *err_ind,        /* OUT error indicator */
    Gint      view_pri[16]     /* OUT view priorities */
);
```

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE LOCATOR DEVICE STATE

```

void ginq_loc_st(
    Gint      ws_id,          /* workstation identifier */
    Gint      loc_num,        /* locator device number */
    Ginq_type type,           /* type of returned values */
    Gstore     store,         /* handle to Store object */
    Gint      *err_ind,       /* OUT error indicator */
    Gop_mode   *mode,         /* OUT operating mode */
    Gecho_switch *esw,        /* OUT echo switch */
    Gint      *init_norm_tran_num, /* OUT initial normalization
                                transformation number */
    Gpoint     *init_loc_pos, /* OUT initial locator position */
    Gint      *pet,           /* OUT prompt/echo type */
    Glimit     *echo_area,    /* OUT echo area */
    Gloc_data  **loc_data     /* OUT locator data record */
);

```

REMARK. The memory referenced by `*loc_data` is managed by the parameter `store`.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE STROKE DEVICE STATE

```

void ginq_stroke_st(
    Gint      ws_id,          /* workstation identifier */
    Gint      stroke_num,     /* stroke device number */
    Ginq_type type,           /* type of returned values */
    Gstore     store,         /* handle to Store object */
    Gint      *err_ind,       /* OUT error indicator */
    Gop_mode   *mode,         /* OUT operating mode */
    Gecho_switch *esw,        /* OUT echo switch */
    Gint      *init_norm_tran_num, /* OUT initial normalization
                                transformation number */
    Gpoint_list **init_stroke, /* OUT initial stroke */
    Gint      *pet,           /* OUT prompt/echo type */
    Glimit     *echo_area,    /* OUT echo area */
    Gstroke_data **stroke_data /* OUT stroke data record */
);

```

REMARK. The memory referenced by `init_stroke` and `*stroke_data` is managed by `store`.

[INQUIRE WORKSTATION STATE LIST ENTRY]

INQUIRE VALUATOR DEVICE STATE

```

void ginq_val_st(
    Gint      ws_id,          /* workstation identifier */
    Gint      val_num,        /* valuator device number */
    Gstore     store,         /* handle to Store object */
    Gint      *err_ind,       /* OUT error indicator */
    Gop_mode   *mode,         /* OUT operating mode */
    Gecho_switch *esw,        /* OUT echo switch */
    Gfloat     *init_value,   /* OUT initial value */
    Gint      *pet,           /* OUT prompt/echo type */
    Glimit     *echo_area,    /* OUT echo area */
    Gval_data  **val_data     /* OUT valuator data record */
);

```

REMARK. The memory referenced by ***val_data** is managed by the parameter **store**.

[INQUIRE WORKSTATION STATE LIST ENTRY]

INQUIRE CHOICE DEVICE STATE

```

void ginq_choice_st(
    Gint      ws_id,          /* workstation identifier */
    Gint      choice_num,     /* choice device number */
    Gstore     store,         /* handle to Store object */
    Gint      *err_ind,       /* OUT error indicator */
    Gop_mode   *mode,         /* OUT operating mode */
    Gecho_switch *esw,        /* OUT echo switch */
    Gin_status *init_status,  /* OUT initial choice status */
    Gint      *init_choice,   /* OUT initial choice */
    Gint      *pet,           /* OUT prompt/echo type */
    Glimit     *echo_area,    /* OUT echo area */
    Gchoice_data *choice_data /* OUT choice data record */
);

```

REMARK. The memory referenced by ***choice_data** is managed by the parameter **store**.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE PICK DEVICE STATE

```

void ginq_pick_st(
    Gint      ws_id,          /* workstation identifier */
    Gint      pick_num,       /* pick device number */
    Ginq_type type,           /* type of returned values */
    Gstore     store,         /* handle to Store object */
    Gint      *err_ind,       /* OUT error indicator */
    Gop_mode   *mode,         /* OUT operating mode */
    Gecho_switch *esw,        /* OUT echo switch */
    Gint_status *init_status, /* OUT initial pick status */
    Gpick       *init_pick,   /* OUT initial pick value */
    Gint        *pet,         /* OUT prompt/echo type */
    Glimit      *echo_area,   /* OUT echo area */
    Gpick_data  **pick_data  /* OUT pick data record */
);

```

REMARK. The memory referenced by ***pick_data** is managed by the parameter **store**.

[INQUIRE WORKSTATION STATE LIST ENTRY]
INQUIRE STRING DEVICE STATE

```

void ginq_string_st(
    Gint      ws_id,          /* workstation identifier */
    Gint      string_num,     /* string device number */
    Gstore     store,         /* handle to Store object */
    Gint      *err_ind,       /* OUT error indicator */
    Gop_mode   *mode,         /* OUT operating mode */
    Gecho_switch *esw,        /* OUT echo switch */
    char       **init_string, /* OUT initial string */
    Gint        *pet,         /* OUT prompt/echo type */
    Glimit      *echo_area,   /* OUT echo area */
    Gstring_data **string_data /* OUT string data record */
);

```

REMARK. The memory referenced by ***init_string** and ***string_data** is managed by **store**.

INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY

```

void ginq_gen_ws_dt_entry(
    Gint      ws_gen_type, /* workstation generic type */
    Gws_dt_name ws_dt_name, /* workstation description table
                             entry name */
    Gstore     store,      /* handle to Store object */
    Gint      *err_ind,    /* OUT error indicator */
    Gws_dt_entry **ws_dt_entry /* OUT workstation description
                             table entry */
);

```

REMARK. The memory referenced by ***ws_dt_entry** is managed by the parameter **store**.

**[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE WORKSTATION CLASSIFICATION**

```

void ginq_ws_class(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      *err_ind,    /* OUT error indicator */
    Gws_class *class       /* OUT workstation class */
);

```

**[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE DISPLAY SPACE SIZE**

```

void ginq_disp_space_size(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      *err_ind,    /* OUT error indicator */
    Gdisp_space_size *disp_size /* OUT display [space] size */
);

```

**[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE LINE FACILITIES**

```

void ginq_line_facs(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind, /* starting index */
    Gint      *err_ind, /* OUT error indicator */
    Gline_facs *line_facs, /* OUT line facilities */
    Gint      *num_elems_impl_list /* OUT length of linetype
                                   list in impl. */
);

```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE PREDEFINED LINE REPRESENTATION

```
void ginq_pred_line_rep(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      ind,         /* predefined index          */
    Gint      *err_ind,    /* OUT error indicator       */
    Gline_bundle *line_rep /* OUT predefined line rep.  */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE MARKER FACILITIES

```
void ginq_marker_facs(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind, /* starting index            */
    Gint      *err_ind, /* OUT error indicator       */
    Gmarker_facs *marker_facs, /* OUT marker facilities     */
    Gint      *num_elems_impl_list /* OUT length of marker type
                                     list in impl.                */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE PREDEFINED MARKER REPRESENTATION

```
void ginq_pred_marker_rep(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      ind,         /* predefined index          */
    Gint      *err_ind,    /* OUT error indicator       */
    Gmarker_bundle *marker_rep /* OUT predefined marker rep. */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE TEXT FACILITIES

```
void ginq_text_facs(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind, /* starting index            */
    Gint      *err_ind, /* OUT error indicator       */
    Gtext_facs *text_facs, /* OUT text facilities       */
    Gint      *num_elems_impl_list /* OUT length of text font
                                     and precision list in impl. */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE PREDEFINED TEXT REPRESENTATION

```
void ginq_pred_text_rep(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      ind,         /* predefined index          */
    Gint      *err_ind,    /* OUT error indicator       */
    Gtext_bundle *text_rep /* OUT predefined text rep.  */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE AREA FACILITIES

```
void ginq_area_facs(
    Gint      ws_gen_type, /* workstation generic type */
    Gstore    store,       /* handle to Store object    */
    Gint      *err_ind,    /* OUT error indicator       */
    Gareafacs **area_facs /* OUT interior facilities   */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE PREDEFINED AREA REPRESENTATION

```
void ginq_pred_area_rep(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      ind,         /* predefined index          */
    Gint      *err_ind,    /* OUT error indicator       */
    Gareafacs *area_rep    /* OUT predefined area rep.  */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE PATTERN FACILITIES

```
void ginq_pat_facs(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      *err_ind,    /* OUT error indicator       */
    Gint      *num_pred_inds /* OUT num. of predef. pattern indices */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE PREDEFINED PATTERN REPRESENTATION

```
void ginq_pred_pat_rep(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      ind,         /* predefined index          */
    Gstore     store,      /* handle to Store object    */
    Gint      *err_ind,    /* OUT error indicator       */
    Gpat_rep   **pat_rep   /* OUT predefined pattern rep. */
);
```

REMARK. The memory referenced by ***pat_rep** is managed by the parameter **store**.

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE COLOUR FACILITIES

```
void ginq_colr_fac(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      *err_ind,    /* OUT error indicator       */
    Gcolr_fac *colr_fac   /* OUT colour facilities     */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE PREDEFINED COLOUR REPRESENTATION

```
void ginq_pred_colr_rep(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      ind,         /* predefined index          */
    Gint      *err_ind,    /* OUT error indicator       */
    Gcolr_rep *colr_rep   /* OUT predefined colour rep. */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE LIST OF AVAILABLE GENERALIZED DRAWING PRIMITIVES

```
void ginq_list_avail_gdps(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      start_ind,   /* starting index            */
    Gint      *err_ind,    /* OUT error indicator       */
    Gint_list *gdp,        /* OUT list of GDPs         */
    Gint      *num_elems_impl_list /* OUT length of impl. list  */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE SET OF AVAILABLE INPUT DEVICES

```
void ginq_set_avail_in_devs(
    Gint      ws_gen_type,          /* workstation generic type */
    Gint      *err_ind,             /* OUT error indicator */
    Gint      num_elems_appl_list,  /* length of application list */
    Gdev_id_list *dev_ids,          /* OUT set of input devices */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE NUMBER OF AVAILABLE INPUT DEVICES

```
void ginq_num_avail_in(
    Gint      ws_gen_type,  /* workstation generic type */
    Gint      *err_ind,     /* OUT error indicator */
    Gnum_in   *num_in       /* OUT number of input devices */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE INPUT DEVICE INITIAL VALUES

```
void ginq_in_dev_init_values(
    Gint      ws_gen_type,          /* workstation generic type */
    Gstore    store,                /* handle to Store object */
    Gint      *err_ind,             /* OUT error indicator */
    Gin_dev_init_value_list *in_dev_init_values /* OUT input device
                                                initial values */
);
```

REMARK. The memory referenced by ***in_dev_init_values** is managed by the parameter **store**.

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE SET OF AVAILABLE MEASURES

```
void ginq_set_avail_meass(
    Gint      ws_gen_type,          /* workstation generic type */
    Gint      num_elems_appl_list,  /* length of application list */
    Gint      *err_ind,             /* OUT error indicator */
    Gint_list *meas_ids,            /* OUT set of measure ids */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE SET OF AVAILABLE TRIGGERS

```
void ginq_set_avail_triggers(
    Gint      ws_gen_type,      /* workstation generic type */
    Gint      num_elems_appl_list, /* length of application list */
    Gint      *err_ind,         /* OUT error indicator */
    Gint_list *trigger_ids,     /* OUT set of trigger ids */
    Gint      *num_elems_impl_list /* OUT length of impl. list */
);
```

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE INPUT DEVICE COMPOSITIONS

```
void ginq_in_dev_comps(
    Gint      ws_gen_type, /* workstation generic type */
    Gstore    store,       /* handle to Store object */
    Gint      *err_ind,    /* OUT error indicator */
    Gdev_comp_list **dev_comps /* OUT input device
                                compositions */
);
```

REMARK. The memory referenced by ***in_dev_comps** is managed by the parameter **store**.

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE DEFAULT LOCATOR DEVICE DATA

```
void ginq_def_loc_data(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      loc_num,     /* logical input device number */
    Gstore    store,       /* handle to Store object */
    Gint      *err_ind,    /* OUT error indicator */
    Gpoint    *loc_pos,    /* OUT default locator position */
    Gint_list **pet_list,  /* OUT list of prompt and echo types */
    Glimit    *echo_area,  /* OUT default echo area */
    Gloc_data **loc_data   /* OUT default data record */
);
```

REMARK. The memory referenced by ***pet_list** and ***loc_data** is managed by **store**.

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE DEFAULT STROKE DEVICE DATA

```
void ginq_def_stroke_data(
    Gint      ws_gen_type,      /* workstation generic type      */
    Gint      stroke_num,       /* logical input device number   */
    Gstore    store,            /* handle to Store object        */
    Gint      *err_ind,         /* OUT error indicator           */
    Gint      *max_buf_size,    /* OUT max. input buffer size    */
                                /* (nr. of points)               */
    Gint_list **pet_list,       /* OUT list of prompt and echo types */
    Glimit    *echo_area,      /* OUT default echo area        */
    Gstroke_data **stroke_data /* OUT default data record      */
);
```

REMARK. The memory referenced by ***pet_list** and ***stroke_data** is managed by **store**.

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE DEFAULT VALUATOR DEVICE DATA

```
void ginq_def_val_data(
    Gint      ws_gen_type,      /* workstation generic type      */
    Gint      val_num,          /* logical input device number   */
    Gstore    store,            /* handle to Store object        */
    Gint      *err_ind,         /* OUT error indicator           */
    Gfloat    *def_val,         /* OUT default initial value     */
    Gint_list **pet_list,       /* OUT list of prompt and echo types */
    Glimit    *echo_area,      /* OUT default echo area        */
    Gval_data **val_data,       /* OUT default data record      */
);
```

REMARK. The memory referenced by ***pet_list** and ***val_data** is managed by **store**.

[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE DEFAULT CHOICE DEVICE DATA

```
void ginq_def_choice_data(
    Gint      ws_gen_type,      /* workstation generic type      */
    Gint      choice_num,       /* logical input device number   */
    Gstore    store,            /* handle to Store object        */
    Gint      *err_ind,         /* OUT error indicator           */
    Gint      *max_num_choices, /* OUT max. num. of choices     */
    Gint_list **pet_list,       /* OUT list of prompt and echo types */
    Glimit    *echo_area,      /* OUT default echo area        */
    Gchoice_data **choice_data /* OUT default data record      */
);
```

REMARK. The memory referenced by ***pet_list** and ***choice_data** is managed by **store**.

**[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE DEFAULT PICK DEVICE DATA**

```

void ginq_def_pick_data(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      pick_num,    /* logical input device number */
    Gstore    store,       /* handle to Store object */
    Gint      *err_ind,    /* OUT error indicator */
    Gint_list **pet_list,  /* OUT list of prompt and echo types */
    Glimit    *echo_area,  /* OUT default echo area */
    Gpick_data **pick_data /* OUT default data record */
);

```

REMARK. The memory referenced by ***pet_list** and ***pick_data** is managed by **store**.

**[INQUIRE GENERIC WORKSTATION DESCRIPTION TABLE ENTRY]
INQUIRE DEFAULT STRING DEVICE DATA**

```

void ginq_def_string_data(
    Gint      ws_gen_type, /* workstation generic type */
    Gint      string_num,  /* logical input device number */
    Gstore    store,       /* handle to Store object */
    Gint      *err_ind,    /* OUT error indicator */
    Gint      *max_buf_size, /* OUT max. input buffer size
                             (nr. of bytes) */
    Gint_list **pet_list,  /* OUT list of prompt and echo types */
    Glimit    *echo_area,  /* OUT default echo area */
    Gstring_data **string_data /* OUT default data record */
);

```

REMARK. The memory referenced by ***pet_list** and ***string_data** is managed by **store**.

INQUIRE SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY

```

void ginq_specif_ws_dt_entry(
    Gint      ws_id, /* workstation identifier */
    Gws_dt_name ws_dt_name, /* workstation description table
                             entry name */
    Gstore    store, /* handle to Store object */
    Gint      *err_ind, /* OUT error indicator */
    Gws_dt_entry **ws_dt_entry /* OUT workstation description
                             table entry */
);

```

REMARK. The memory referenced by ***ws_dt_entry** is managed by the parameter **store**.

INQUIRE SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY STATE

```

void ginq_specif_ws_dt_entry_st(
    Gint      ws_id,      /* workstation identifier */
    Gws_dt_name ws_dt_name, /* entry name */
    Gint      *err_ind,    /* OUT error indicator */
    Gchange_flag *entry_st /* OUT entry state */
);

```

RESET SPECIFIC WORKSTATION DESCRIPTION TABLE ENTRY STATE

```

void greset_specif_ws_dt_entry_st(
    Gint      ws_id,      /* workstation identifier */
    Gws_dt_name ws_dt_name /* entry name */
);

```

7.3.3 Retrieval functions

GET TEXT EXTENT

```

void gget_text_extent(
    Gint      ws_id,      /* workstation identifier */
    const Gpoint *pos,    /* text position */
    const char *str,      /* character string */
    Gint      *err_ind,    /* OUT error indicator */
    Gtext_extent *extent /* OUT concatenation point and
                        text extent parallelogram */
);

```

[GET TEXT EXTENT]

INQUIRE TEXT EXTENT

```

void ginq_text_extent(
    Gint      ws_id,      /* workstation identifier */
    const Gpoint *pos,    /* text position */
    const char *str,      /* character string */
    Gint      *err_ind,    /* OUT error indicator */
    Gtext_extent *extent /* OUT concatenation point and
                        text extent parallelogram */
);

```


7.3.4 Viewing utility functions

EVALUATE VIEW ORIENTATION MATRIX

```
void geval_view_ori_matrix(
    const Gpoint *ref_point,      /* fixed reference point */
    const Gvec   *view_up,        /* view up vector         */
    Gtran_matrix view_ori_matrix  /* OUT view orientation   */
                                matrix
);
```

EVALUATE VIEW MAPPING MATRIX

```
void geval_view_map_matrix(
    const Gtran *win_vp,          /* window/viewport limits */
    Gtran_matrix view_map_matrix  /* OUT view orientation    */
                                matrix
);
```

7.3.5 Colour utility functions

CONVERT COLOUR

```
void gconv_colr(
    Gint      ws_id,              /* workstation identifier */
    const Gcolr_specif *colr_specif, /* colour specifier      */
    Gint      colr_model,         /* colour model           */
    Gcolr_specif *colr_coords,    /* OUT colour coordinates */
    Gconv_flag *conv_flag         /* OUT conversion flag    */
);
```

7.4 Segment functions and workstation activation functions

REMARK. The segment facilities in ISO/IEC 7942- 1:1994 are identified as obsolescent features.

It is anticipated that they will be considered for deletion for the next edition of ISO/IEC 7942-

1. Consequently, the bindings of these functions, documented in this subclause, will be considered for deletion as well at the next edition of this part of ISO/IEC 8651.

7.4.1 Segment functions

CREATE SEGMENT

```
void gcreate_seg(
    Gint seg_name /* segment name */
);
```

CLOSE SEGMENT

```
void gclose_seg(  
    void  
);
```

RENAME SEGMENT

```
void grename_seg(  
    Gint    old_seg_name,    /* old segment name */  
    Gint    new_seg_name    /* new segment name */  
);
```

DELETE SEGMENT

```
void gdel_seg(  
    Gint    seg_name    /* segment name */  
);
```

DELETE SEGMENT FROM WORKSTATION

```
void gdel_seg_ws(  
    Gint    ws_id,    /* workstation identifier */  
    Gint    seg_name    /* segment name */  
);
```

ASSOCIATE SEGMENT WITH WORKSTATION

```
void gassoc_seg_ws(  
    Gint    ws_id,    /* workstation identifier */  
    Gint    seg_name    /* segment name */  
);
```

COPY SEGMENT TO WORKSTATION

```
void gcopy_seg_ws(  
    Gint    ws_id,    /* workstation identifier */  
    Gint    seg_name    /* segment name */  
);
```

INSERT SEGMENT

```
void ginsert_seg(  
    Gint    seg_name,    /* segment name */  
    const Gtran_matrix    tran_matrix    /* transformation matrix */  
);
```

SET SEGMENT ATTRIBUTE

```
void gset_seg_attr(  
    Gint      seg_name,      /* segment name */  
    const Gseg_attr_value *seg_attr_value /* segment attribute value */  
);
```

**[SET SEGMENT ATTRIBUTE]
SET SEGMENT TRANSFORMATION**

```
void gset_seg_tran(  
    Gint      seg_name,      /* segment name */  
    Gtran_matrix tran_matrix /* transformation matrix */  
);
```

**[SET SEGMENT ATTRIBUTE]
SET VISIBILITY**

```
void gset_vis(  
    Gint      seg_name, /* segment name */  
    Gvis      vis       /* visibility */  
);
```

**[SET SEGMENT ATTRIBUTE]
SET HIGHLIGHTING**

```
void gset_highl(  
    Gint      seg_name, /* segment name */  
    Ghighl    highl     /* highlighting */  
);
```

**[SET SEGMENT ATTRIBUTE]
SET DETECTABILITY**

```
void gset_det(  
    Gint      seg_name, /* segment name */  
    Gdet      det       /* detectability */  
);
```

**[SET SEGMENT ATTRIBUTE]
SET SEGMENT PRIORITY**

```
void gset_seg_pri(  
    Gint      seg_name, /* segment name */  
    Gfloat     seg_pri  /* segment priority */  
);
```

7.4.2 Workstation activation functions

ACTIVATE WORKSTATION

```
void gactivate_ws(
    Gint  ws_id  /* workstation identifier */
);
```

DEACTIVATE WORKSTATION

```
void gdeactivate_ws(
    Gint  ws_id  /* workstation identifier */
);
```

CLEAR WORKSTATION

```
void gclear_ws(
    Gint      ws_id,      /* workstation identifier */
    Gctrl_flag ctrl_flag /* control flag */
);
```

REMARK. The second parameter is unused.

7.4.3 Utility functions

GET MAPPED SEGMENT NAME

```
void gget_map_seg_name(
    Gint  seg_name,      /* segment name */
    Gint  *map_seg_name /* OUT mapped segment name */
);
```

GET MAPPED WORKSTATION IDENTIFIER

```
void gget_map_ws_id(
    Gint  ws_id,      /* workstation identifier */
    Gint  *map_ws_id /* OUT mapped workstation identifier */
);
```

Annex A (informative)

Compiled GKS/C specification

This annex contains a print of the header **gks.h**. This header should be included in any GKS/C application program and contains the following information:

- 1) The data types from clause 5 in compilation order.
- 2) The macros from clause 6.
- 3) The specification of the GKS functions as **extern void**.
- 4) The header **gks_compat.h**; see annex E for a description of this header.
- 5) Additional implementation-dependent items; they should preferably have the sentinels "g" or "G".

This annex only contains the parts 1)-4).

A.1 Data types in compilation order

```
/* Data Types in Compilation Order*/
/* Basic Types*/
/* Gfloat floating point number */
typedef float Gfloat;
/* Gint integer */
typedef int Gint;
/* Gstore store */
typedef void *Gstore;
/* Gtran_matrix transformation matrix */
typedef Gfloat Gtran_matrix[2][3];
/* Gconic_matrix conic matrix */
typedef Gfloat Gconic_matrix[3][3];
/* Gdata data */
typedef struct {
    size_t size; /* size of data*/
    void *data; /* pointer to data*/
} Gdata;
/* Enumeration Types*/
/* Gabut_specif ABUT specifier */
typedef enum {
    GABUT_RIGHT,
    GABUT_LEFT,
    GABUT_TOP,
    GABUT_BOTTOM,
    GABUT_CTR_VERT,
    GABUT_CTR_HOR,
    GABUT_CAP_LINE,
    GABUT_BASE_LINE
} Gabut_specif;
/* Gasf attribute source flag */
typedef enum {
    GASF_BUNDLED,
    GASF_INDIV
} Gasf;
/* Gattr_ctrl_flag attribute control flag */
```

```

typedef enum {
    GFLAG_CUR,
    GFLAG_SPECIF
} Gattr_ctrl_flag;
/* Gprim_attr_name primitive attribute name */
typedef enum {
    GNAME_PICK_ID, /* pick identifier*/
    GNAME_NAMESET, /* nameset */
    GNAME_SCISSOR_SET, /* scissor set*/
    GNAME_GLOBAL_TRAN_MATRIX, /* global transformation matrix */
    GNAME_LOCAL_TRAN_MATRIX, /* local transformation matrix */
    GNAME_PAT_SIZE, /* pattern size*/
    GNAME_PAT_REF_POINT, /* pattern reference point*/
    GNAME_CHAR_HT, /* character height*/
    GNAME_CHAR_UP_VEC, /* character up vector*/
    GNAME_TEXT_SKEW_ANGLE, /* text skew angle*/
    GNAME_TEXT_PATH, /* text path*/
    GNAME_TEXT_ALIGN, /* text alignment*/
    GNAME_LINE_IND, /* line index*/
    GNAME_LINETYPE, /* linetype */
    GNAME_LINEWIDTH, /* linewidth scale factor*/
    GNAME_LINE_COLR_SPECIF, /* line colour specifier*/
    GNAME_MARKER_IND, /* marker index*/
    GNAME_MARKER_TYPE, /* marker type*/
    GNAME_MARKER_SIZE, /* marker size scale factor*/
    GNAME_MARKER_COLR_SPECIF, /* marker colour specifier*/
    GNAME_AREA_IND, /* area index*/
    GNAME_INT_STYLE, /* interior style*/
    GNAME_INT_STYLE_IND, /* interior style index*/
    GNAME_INT_COLR_SPECIF, /* interior colour specifier*/
    GNAME_EDGE_FLAG, /* edge flag */
    GNAME_EDGETYPE, /* edgetype */
    GNAME_EDGEWIDTH, /* edgewidth scale factor */
    GNAME_EDGE_COLR_SPECIF, /* edge colour specifier */
    GNAME_TEXT_IND, /* text index*/
    GNAME_TEXT_FONT_PREC, /* text font and precision*/
    GNAME_CHAR_EXPAN, /* character expansion factor*/
    GNAME_CHAR_SPACE, /* character spacing*/
    GNAME_TEXT_COLR_SPECIF, /* text colour specifier*/
    GNAME_ASFS /* asfs */
} Gprim_attr_name;
/* Gaudit_flag audit flag */
typedef enum {
    GAUDIT_OFF,
    GAUDIT_ON
} Gaudit_flag;
/* Gaudit_op audit operation */
typedef struct {
    enum Gaudit_op_type {
        GAUDIT_OPEN, GAUDIT_CLOSE, GAUDIT_BEGIN, GAUDIT_END
    } type;
    void *specif; /* audit specifier*/

```

```
} Gaudit_op;
/* Gcap cap */
typedef enum {
    GCAP_BUT,
    GCAP_ROUND,
    GCAP_SQUARE
} Gcap;
/* Gchange_flag change flag */
typedef enum {
    GFLAG_CHANGED,
    GFLAG_NOT_CHANGED
} Gchange_flag;
/* Gconv_flag conversion flag */
typedef enum {
    GCONV_DONE,
    GCONV_APPROX,
    GCONV_NOT_CONV
} Gconv_flag;
/* Gchoice_status choice status */
typedef enum {
    GCHOICE_OK,
    GCHOICE_NO_CHOICE
} Gchoice_status;
/* Gclip_ind clipping indicator */
typedef enum {
    GIND_NO_CLIP,
    GIND_CLIP
} Gclip_ind;
/* Gclosed_path_op_st closed path operating state */
typedef enum {
    GCP_ST_CPCL,
    GCP_ST_CPOP
} Gclosed_path_op_st;
/* Gcolr_avail colour available */
typedef enum {
    GAVAIL_MONOCHR,
    GAVAIL_COLR
} Gcolr_avail;
/* Gcolr_kind colour kind */
typedef enum {
    GCOLR_INDIR,
    GCOLR_RGB,
    GCOLR_CIELUV,
    GCOLR_HLS,
    GCOLR_HSV
} Gcolr_kind;
/* Gcont_attr_name contour attribute name */
typedef enum {
    GNAME_STYLE,
    GNAME_WIDTH,
    GNAME_CAP,
    GNAME_JOIN
```

```

} Gcont_attr_name;
/* Gcoord_switch coordinate switch */
typedef enum {
    GCOORD_WC,
    GCOORD_NDC
} Gcoord_switch;
/* Gctrl_flag control flag */
typedef enum {
    GFLAG_COND,
    GFLAG_ALWAYS
} Gctrl_flag;
/* Gdc_units device coordinate units */
typedef enum {
    GDC_METRES,
    GDC_OTHER
} Gdc_units;
/* Gdet detectability */
typedef enum {
    GSEG_UNDET,
    GSEG_DET
} Gdet;
/* Groute_dir direction */
typedef enum {
    GDIR_NDC,
    GDIR_BACKDROP
} Groute_dir;
/* Gecho_switch echo switch */
typedef enum {
    GSWITCH_NO_ECHO,
    GSWITCH_ECHO
} Gecho_switch;
/* Gedge_flag edge flag */
typedef enum {
    GEDGE_OFF,
    GEDGE_ON
} Gedge_flag;
/* Ggks_dt_name GKS description table name */
typedef enum {
    GGKS_DT_AVAIL_WS_GEN_TYPES, /* list of available ws. types*/
    GGKS_DT_AVAIL_FONTS, /* list of available fonts*/
    GGKS_DT_DEF_FONT_IND_MAP /* default font index mapping*/
} Ggks_dt_name;
/* Ggks_op_st GKS operating state */
typedef enum {
    GOP_ST_GKCL,
    GOP_ST_GKOP
} Ggks_op_st;
/* Ggks_sl_name GKS state list name */
typedef enum {
    GGKS_SL_ROUTE_DIR, /* route direction*/
    GGKS_SL_SCISSOR_MODE, /* scissor mode*/
    GGKS_SL_OPEN_WSS, /* list of open workstations.*/

```



```

GGKS_SL_ACTIVE_WSS,      /* list of active workstations*/
GGKS_SL_OPEN_AUDITS,     /* set of open audits*/
GGKS_SL_OPEN_PLAYBACKS, /* set of open playbacks*/
GGKS_SL_IN_QUEUE,        /* input queue*/
GGKS_SL_FONT_IND_MAP,    /* font index mapping*/
GGKS_SL_PICK_ID, /* pick identifier*/
GGKS_SL_NAMESET, /* nameset */
GGKS_SL_GLOBAL_TRAN_MATRIX, /* global
                             transformation matrix */
GGKS_SL_LOCAL_TRAN_MATRIX, /* local
                             transformation matrix */
GGKS_SL_PAT_SIZE,        /* pattern size*/
GGKS_SL_PAT_REF_POINT, /* Pattern reference point*/
GGKS_SL_CHAR_HT, /* Character height*/
GGKS_SL_CHAR_UP_VEC,     /* character up vector*/
GGKS_SL_TEXT_SKEW_ANGLE, /* text skew angle*/
GGKS_SL_TEXT_PATH,       /* text path*/
GGKS_SL_TEXT_ALIGN,      /* text alignment*/
GGKS_SL_SCISSOR_SET,     /* scissor set*/
GGKS_SL_LINE_IND,        /* line index*/
GGKS_SL_LINETYPE,        /* linetype*/
GGKS_SL_LINEWIDTH,       /* linewidth scale factor*/
GGKS_SL_LINE_COLR_SPECIF, /* line colour specifier*/
GGKS_SL_MARKER_IND,      /* marker index*/
GGKS_SL_MARKER_TYPE,     /* marker type*/
GGKS_SL_MARKER_SIZE,     /* marker size scale factor*/
GGKS_SL_MARKER_COLR_SPECIF, /* marker colour specifier*/
GGKS_SL_AREA_IND,        /* area ind*/
GGKS_SL_INT_STYLE,       /* interior style*/
GGKS_SL_INT_STYLE_IND, /* interior style index*/
GGKS_SL_INT_COLR_SPECIF, /* interior colour specifier*/
GGKS_SL_EDGE_FLAG,       /* edge flag */
GGKS_SL_EDGETYPE,        /* edgetype */
GGKS_SL_EDGEWIDTH,       /* edgewidth scale factor */
GGKS_SL_EDGE_COLR_SPECIF, /* edge colour specifier */
GGKS_SL_TEXT_IND,        /* text index*/
GGKS_SL_TEXT_FONT_PREC, /* text font
                             and precision */
GGKS_SL_CHAR_EXPAN,      /* character expansion factor*/
GGKS_SL_CHAR_SPACE,      /* character spacing*/
GGKS_SL_TEXT_COLR_SPECIF, /* text colour specifier*/
GGKS_SL_ASFS, /* asfs */
GGKS_SL_NORM_TRAN_NUM, /* current norm. tran. number */
GGKS_SL_NORM_TRANS,      /* list of norm. tran. */
GGKS_SL_VP_IN_PRI,       /* list of vp input pris*/
GGKS_SL_NAME_OPEN_PIC_PART, /* name of open pic. part*/
GGKS_SL_PIC_PART_NAMES, /* list of picture part names in use*/
GGKS_SL_CONT_ATTRS,      /* contour attributes*/
GGKS_SL_NAME_OPEN_SEG, /* nme of open segment*/
GGKS_SL_SEG_NAMES,       /* list of segments in use*/
GGKS_SL_SEG_SLS, /* list of segment
                  state lists */

```

```

GGKS_SL_NAME_OPEN_STENCIL, /* name of open stencil*/
GGKS_SL_STENCIL_NAMES, /* list of stencils in use*/
GGKS_SL_STENCIL_SLS, /* list of stencil
state lists in use*/
GGKS_SL_NAME_OPEN_TILING, /* name of open tiling*/
GGKS_SL_TILING_NAMES /* list of tilings in use*/
} Ggks_sl_name;
/* Gop_st_name operating state entry name */
typedef enum {
    GOP_ST_GKS, /* GKS operating state*/
    GOP_ST_PIC_PART, /* picture part operating state*/
    GOP_ST_STENCIL, /* stencil operating state*/
    GOP_ST_SEG, /* segment operating state*/
    GOP_ST_CLOSED_PATH, /* closed path operating state */
    GOP_ST_TILING /* tiling operating state*/
} Gop_st_name;
/* Ghighl highlighting */
typedef enum {
    GSEG_NORM,
    GSEG_HIGHL
} Ghighl;
/* Gin_status [input] status */
typedef enum {
    GIN_STATUS_NONE,
    GIN_STATUS_OK ,
    GIN_STATUS_NO_IN
} Gin_status;
/* Ginit_sel initial selector */
typedef enum {
    GSEL_INIT_VALUE, /* initial value*/
    GSEL_PET, /* prompt and echo type */
    GSEL_ECHO_SWITCH, /* echo switch */
    GSEL_ECHO_AREA, /* echo area*/
    GSEL_IN_DATA, /* input data*/
    GSEL_ALL /* all initial input*/
} Ginit_sel;
/* Ginq_type inquire type */
typedef enum {
    GINQ_SET,
    GINQ_REALIZED
} Ginq_type;
/* Ginside_rule inside rule */
typedef enum {
    GRULE_EVEN_ODD,
    GRULE_WINDING
} Ginside_rule;
/* Gint_style interior style */
typedef enum {
    GSTYLE_HOLLOW,
    GSTYLE_SOLID,
    GSTYLE_PAT,
    GSTYLE_HATCH,

```

```

    GSTYLE_EMPTY
} Gint_style;
/* Gproc_op process operation */
typedef enum {
    GPROC_SKIP,
    GPROC_DO
} Gproc_op;
/* Gline_fill_ctrl_flag line/fill control flag */
typedef enum {
    GFLAG_LINE,
    GFLAG_FILL
} Gline_fill_ctrl_flag;
/* Gin_class input [measure] class */
typedef enum {
    GIN_NONE,
    GIN_LOC,
    GIN_STROKE,
    GIN_VAL,
    GIN_CHOICE,
    GIN_PICK,
    GIN_STRING,
    GIN_COMP
} Gin_class;
/* Gop_mode operating mode */
typedef enum {
    GOP_REQ,
    GOP_SAMPLE,
    GOP_EVENT
} Gop_mode;
/* Gord_sel ordinate selector */
typedef enum {
    GORD_X,
    GORD_Y
} Gord_sel;
/* Gtiling_op_st tiling operating state */
typedef enum {
    GOP_ST_TLCL,
    GOP_ST_TLOP
} Gtiling_op_st;
/* Gpic_part_op_st picture part operating state */
typedef enum {
    GOP_ST_PPCL,
    GOP_ST_PPOP
} Gpic_part_op_st;
/* Gpick_status pick status */
typedef enum {
    GPICK_OK,
    GPICK_NO_PICK
} Gpick_status;
/* Gplayback_op playback operation */
typedef struct {
    enum Gplayback_op_type {

```

```

        GPLAYBACK_OPEN, GPLAYBACK_CLOSE
    } type;
    void      *specif;    /* audit specifier*/
} Gplayback_op;
/* Gpr_flag prompt flag */
typedef enum {
    GPR_OFF,
    GPR_ON
} Gpr_flag;
/* Gprim_type primitive type */
typedef enum {
    GPRIM_LINE_SET,
    GPRIM_NURB_SET,
    GPRIM_CONIC_SEC_SET,
    GPRIM_MARKER,
    GPRIM_FILL_SET,
    GPRIM_CLOSED_NURB_SET,
    GPRIM_ELL_SEC_SET,
    GPRIM_ELL_SEG_SET,
    GPRIM_ELL_DISC_SET,
    GPRIM_TEXT,
    GPRIM_CELL_ARRAY,
    GPRIM_DESIGN,
    GPRIM_GDP
} Gprim_type;
/* Grel_pos relative position */
typedef enum {
    GPOS_FRONT,
    GPOS_BACK
} Grel_pos;
/* Grel_pri relative priority */
typedef enum {
    GPRI_HIGHER,
    GPRI_LOWER
} Grel_pri;
/* Gscissor_mode scissor mode */
typedef enum {
    GSCISSOR_LOCUS,
    GSCISSOR_SHAPE
} Gscissor_mode;
/* Gscissor_sel scissor select */
typedef enum {
    GSCISSOR_CHANGE,
    GSCISSOR_LEAVE
} Gscissor_sel;
/* Gseg_attr_name segment attribute name */
typedef enum {
    GNAME_TRAN_MATRIX, /* transformation matrix*/
    GNAME_VIS, /* visibility */
    GNAME_HIGHL, /* hightlighting*/
    GNAME_PRI, /* segment priority*/
    GNAME_DET /* detectability */

```

```

} Gseg_attr_name;
/* Gsel_crit_op selection criterion operation */
typedef enum {
    GOP_CONTAINS,
    GOP_IS_IN,
    GOP_EQUALS,
    GOP_SEL_ALL,
    GOP_REJ_ALL,
    GOP_AND,
    GOP_OR,
    GOP_NOT
} Gsel_crit_op;
/* Gsel_crit_type selection criterion type */
typedef enum {
    GSEL_DISP,
    GSEL_HIGHL,
    GSEL_DET
} Gsel_crit_type;
/* Gsense_flag sense flag */
typedef enum {
    GFLAG_CLOCKWISE,
    GFLAG_ANTI_CLOCKWISE
} Gsense_flag;
/* Gshield_ind shielding indicator */
typedef enum {
    GIND_NO_SHIELD,
    GIND_SHIELD
} Gshield_ind;
/* Gstencil_attr_name stencil attribute name */
typedef enum {
    GNAME_TOP_Y,
    GNAME_CAP_Y,
    GNAME_HALF_Y,
    GNAME_BASE_Y,
    GNAME_BOTTOM_Y,
    GNAME_CTR_Y,
    GNAME_LEFT_X,
    GNAME_RIGHT_X,
    GNAME_CTR_X,
    GNAME_CTR,
    GNAME_ORIGIN,
    GNAME_CTR_TOP,
    GNAME_CTR_BOTTOM,
    GNAME_CTR_LEFT,
    GNAME_CTR_RIGHT,
    GNAME_TOP_LEFT,
    GNAME_TOP_RIGHT,
    GNAME_BOTTOM_LEFT,
    GNAME_BOTTOM_RIGHT
} Gstencil_attr_name;
/* Gstencil_op_st stencil operating state */
typedef enum {

```

```

    GOP_ST_STCL,
    GOP_ST_STOP
} Gstencil_op_st;
/* Gseg_op_st segment operating state */
typedef enum {
    GOP_ST_SGCL,
    GOP_ST_SGOP
} Gseg_op_st;
/* Gtext_path text path */
typedef enum {
    GPATH_RIGHT,
    GPATH_LEFT,
    GPATH_UP,
    GPATH_DOWN
} Gtext_path;
/* Gtext_prec text precision */
typedef enum {
    GPREC_STRING,
    GPREC_CHAR,
    GPREC_STROKE
} Gtext_prec;
/* Gtiling_type tiling type */
typedef enum {
    GTILING_LINE_SET,
    GTILING_NURB_SET,
    GTILING_CONIC_SEC_SET,
    GTILING_FILL_SET,
    GTILING_CLOSED_NURB_SET,
    GTILING_ELL_SEC_SET,
    GTILING_ELL_SEG_SET,
    GTILING_ELL_DISC_SET,
    GTILING_DESIGN
} Gtiling_type;
/* Gtran_mode transformation mode */
typedef enum {
    GTRAN_REPLACE,
    GTRAN_PRE,
    GTRAN_POST
} Gtran_mode;
/* Gvis_visibility */
typedef enum {
    GSEG_INVIS,
    GSEG_VIS
} Gvis;
/* Gvis_effects_st visual effects state */
typedef enum {
    GST_SUPPR,
    GST_ALLOW
} Gvis_effects_st;
/* Gws_class workstation classification [display kind] */
typedef enum {
    GCLASS_VEC,

```

```

    GCLASS_RASTER,
    GCLASS_OTHER
} Gws_class;
/* Gws_dt_name workstation description table name */
typedef enum {
    GWS_DT_TYPE,
    GWS_DT_STATUS,
    GWS_DT_DC_UNITS,
    GWS_DT_DISP_SPACE_SIZE,
    GWS_DT_CLASS,
    GWS_DT_LINE_FACS,
    GWS_DT_LINE_BUNDLE_TABLE,
    GWS_DT_MARKER_FACS,
    GWS_DT_MARKER_BUNDLE_TABLE,
    GWS_DT_AREA_FACS,
    GWS_DT_AREA_BUNDLE_TABLE,
    GWS_DT_PAT_TABLE,
    GWS_DT_TEXT_FACS,
    GWS_DT_TEXT_BUNDLE_TABLE,
    GWS_DT_COLR_FACS,
    GWS_DT_COLR_TABLE,
    GWS_DT_GDP_IDS,
    GWS_DT_DEV_IDS,
    GWS_DT_IN_DEV_INIT_VALUES,
    GWS_DT_MEAS_IDS,
    GWS_DT_TRIGGER_IDS,
    GWS_DT_DEV_COMPS
} Gws_dt_name;
/* Gws_sl_name workstation state list name */
typedef enum{
    GWS_SL_ST,
    GWS_SL_CONN_TYPE,
    GWS_SL_LINE_BUNDLE_TABLE,
    GWS_SL_MARKER_BUNDLE_TABLE,
    GWS_SL_TEXT_BUNDLE_TABLE,
    GWS_SL_AREA_BUNDLE_TABLE,
    GWS_SL_PAT_TABLE,
    GWS_SL_COLR_TABLE,
    GWS_SL_WIN_VP,
    GWS_SL_VIS_EFFECTS_ST,
    GWS_SL_OP_MODES_INIT_VALS,
    GWS_SL_SEL_TABLE,
    GWS_SL_STORED_SEGS,
    GWS_SL_VIEW_TABLE,
    GWS_SL_VIEW_PRIS
} Gws_sl_name;
/* Gws_status workstation status */
typedef enum {
    GWS_UP_TO_DATE,
    GWS_NOT_UP_TO_DATE
} Gws_status;
/* Gws_st workstation state */

```

```

typedef enum {
    GWS_INACTIVE,
    GWS_ACTIVE
} Gws_st;
/* Simple Structures*/
/* Gasfs attribute source flags */
typedef struct {
    Gasf      linetype; /* linetype ASF */
    Gasf      linewidth; /* linewidth scale factor ASF */
    Gasf      line_colr_ind; /* line colour ASF */
    Gasf      marker_type; /* marker type ASF */
    Gasf      marker_size; /* marker size scale factor ASF */
    Gasf      marker_colr_ind; /* marker colour ASF */
    Gasf      text_font_prec; /* text font and precision ASF */
    Gasf      char_expan; /* character expansion factor ASF */
    Gasf      char_space; /* character spacing ASF */
    Gasf      text_colr_ind; /* text colour ASF */
    Gasf      int_style; /* interior style ASF */
    Gasf      int_style_ind; /* interior style index ASF */
    Gasf      int_colr_ind; /* interior colour ASF */
    Gasf      edge_flag; /* edge flag ASF */
    Gasf      edgetype; /* edgetype ASF */
    Gasf      edgewidth; /* edgewidth scale factor ASF */
    Gasf      edge_colr_ind; /* edge colour ASF */
} Gasfs;
/* Gchoice choice [value] */
typedef struct {
    Gchoice_status status; /* status*/
    Gint          num; /* choice number*/
} Gchoice;
/* Gcieluv CIE L*u*v* [colour specification] */
typedef struct {
    Gfloat      u_prime; /* u' coefficient*/
    Gfloat      v_prime; /* v' coefficient*/
    Gfloat      y; /* y luminance*/
} Gcieluv;
/* Gdev_id device identifier */
typedef struct {
    Gint      ws_id; /* workstation identifier*/
    Gint      num; /* device number*/
    Gin_class in_class; /* input [measure] class*/
} Gdev_id;
/* Gdev_id_list device identifier list */
typedef struct {
    Gint      num_dev_ids; /* number of device identifiers in list*/
    Gdev_id   *dev_ids; /* list of device identifiers*/
} Gdev_id_list;
/* Gfloat_list float list */
typedef struct {
    Gint      num_floats; /* number of floats in list*/
    Gint      *floats; /* list of floats*/
} Gfloat_list;

```



```

/* Gfloat_size float size */
typedef struct {
    Gfloat    size_x;    /* x size*/
    Gfloat    size_y;    /* y size*/
} Gfloat_size;
/* Ghls Hue Luminance Saturation [colour specification] */
typedef struct {
    Gfloat    hue;    /* hue */
    Gfloat    lightness;    /* lightness*/
    Gfloat    satur;    /* saturation*/
} Ghls;
/* Ghomo_point homogeneous point */
typedef struct {
    Gfloat    xw;    /* x coordinate*/
    Gfloat    yw;    /* y coordinate*/
    Gfloat    w;    /* w coordinate*/
} Ghomo_point;
/* Ghsv Hue Saturation Value [colour specification] */
typedef struct {
    Gfloat    hue;    /* hue */
    Gfloat    satur;    /* saturation*/
    Gfloat    value;    /* value*/
} Ghsv;
/* Gint_list integer list */
typedef struct {
    Gint    num_ints;    /* number of integers in list*/
    Gint    *ints;    /* list of integers*/
} Gint_list;
/* Gint_size integer size */
typedef struct {
    Gint    size_x;    /* x size*/
    Gint    size_y;    /* y size*/
} Gint_size;
/* Gjoin join */
typedef struct {
    enum Gjoin_name {/* name (ROUND|BEVEL|MITRED) */
        GJOIN_ROUND,
        GJOIN_BEVEL,
        GJOIN_MITRED
    } name;
    Gfloat    mitred;    /* mitred value */
} Gjoin;
/* Glimit limit */
typedef struct {
    Gfloat    x_min;    /* x min*/
    Gfloat    x_max;    /* x max*/
    Gfloat    y_min;    /* y min*/
    Gfloat    y_max;    /* y max*/
} Glimit;
/* Gnum_in number [of] input [devices] */
typedef struct {
    Gint    loc;    /* number of locator devices*/

```

```

Gint      stroke;      /* number of stroke devices*/
Gint      val; /* number of valuator devices*/
Gint      choice;      /* number of choice devices*/
Gint      pick; /* number of pick devices*/
Gint      string;      /* number of string devices*/
Gint      comp; /* number of composed devices*/
} Gnum_in;
/* Gpoint point */
typedef struct {
    Gfloat      x;      /* x coordinate*/
    Gfloat      y;      /* y coordinate*/
} Gpoint;
/* Grgb Red Green Blue [colour specification] */
typedef struct {
    Gfloat      red; /* red intensity*/
    Gfloat      green; /* green intensity*/
    Gfloat      blue; /* blue intensity*/
} Grgb;
/* Gseg_attr_value segment attribute value */
typedef struct {
    Gseg_attr_name name; /* segment attribute name */
    union {
        Gtran_matrix      tran_matrix; /* transformation matrix*/
        Gvis vis; /* visibility*/
        Ghighl highl; /* hightlighting*/
        Gfloat pri; /* segment priority*/
        Gdet det; /* detectability*/
    } value;
} Gseg_attr_value;
/* Gseg_attrs segment attributes */
typedef struct {
    Gtran_matrix      tran_matrix; /* transformation matrix*/
    Gvis vis; /* visibility*/
    Ghighl highl; /* hightlighting*/
    Gfloat pri; /* segment priority*/
    Gdet det; /* detectability*/
} Gseg_attrs;
/* Gseg_sl segment state list */
typedef struct {
    Gint      name; /* segment name*/
    Gint_list assoc_wss; /* associated workstations*/
    Gseg_attrs attrs; /* segment attributes*/
} Gseg_sl;
/* Gseg_sl_list list of segment state lists */
typedef struct {
    Gint      num_seg_sls; /* number of segment state lists in list*/
    Gseg_sl *seg_sls; /* list of segment state lists*/
} Gseg_sl_list;
/* Gtext_align text alignment */
typedef struct {
    enum Ghor_text_align { /* horizontal text alignment */
        GHOR_NORM,

```

```

        GHOR_LEFT,
        GHOR_CTR,
        GHOR_RIGHT
    } hor;
    enum Gvert_text_align { /* vertical text alignment */
        GVERT_NORM,
        GVERT_TOP,
        GVERT_CAP,
        GVERT_HALF,
        GVERT_BASE,
        GVERT_BOTTOM
    } vert;
} Gtext_align;
/* Gtext_font_prec text font [and] precision */
typedef struct {
    Gint      font; /* character font*/
    Gtext_prec prec; /* text precision*/
} Gtext_font_prec;
/* Gvec vector */
typedef struct {
    Gfloat     delta_x; /* x coordinate*/
    Gfloat     delta_y; /* y coordinate*/
} Gvec;
/* Nested Structures */
/* Gcolr_specif colour specifier */
typedef struct {
    Gcolr_kind kind; /* colour kind */
    union {
        Gint  ind; /* colour index*/
        Grgb  rgb; /* Red Green Blue colour specification */
        Gcieluv cieluv; /* CIE L*u*v* 1976 colour specification */
        Ghls  hls; /* Hue Luminance Saturation colour specification */
        Ghsv  hsv; /* Hue Saturation Value colour specification */
    } value;
} Gcolr_specif;
/* Gconic_sec conic section */
typedef struct {
    Gconic_matrix matrix; /* conic matrix */
    Gpoint point_1; /* point # 1 */
    Gpoint point_2; /* point # 2 */
    Gsense_flag sense_flag; /* sense flag */
} Gconic_sec;
/* Gconic_sec_list conic primitive list */
typedef struct {
    Gint      num_conic_prims; /* number of conic primitives in list*/
    Gconic_sec *conic_prims; /* list of conic primitives*/
} Gconic_sec_list;
/* Gcont_attr_value contour attribute value */
typedef struct {
    Gcont_attr_name name; /* attribute name */
    union {
        Gint style; /* style*/

```

```

        Gfloat      width; /* width */
        Gcap  cap;  /* cap */
        Gjoin join; /* join */
    } value;
} Gcont_attr_value;
/* Gcont_attrs contour attributes */
typedef struct {
    Gint      style; /* style */
    Gfloat    width; /* width */
    Gcap      cap;  /* cap */
    Gjoin     join; /* join */
} Gcont_attrs;
/* Gdesign design */
typedef struct {
    Gint      stencil_name; /* stencil name */
    Gpoint    stencil_origin; /* stencil origin */
    Gtran_matrix stencil_tran; /* stencil transformation */
    Gint      tiling_name; /* tiling name */
    Gpoint    tiling_origin; /* tiling origin */
    Gtran_matrix tiling_tran; /* tiling transformation */
} Gdesign;
/* Gdev_comp device composition */
typedef struct {
    Gdev_id  id; /* device id */
    Gint_list meas_set; /* measure set */
    Gint_list trigger_set; /* trigger set */
} Gdev_comp;
/* Gdev_comp_list device composition list */
typedef struct {
    Gint      num_devs; /* number of [basic] devices in list */
    Gdev_comp *dev_comps; /* list of device compositions */
} Gdev_comp_list;
/* Gell_disc_list elliptic disc list */
typedef struct {
    Gint      num_ell_discs; /* number of elliptic discs in list */
    Gconic_matrix *ell_discs; /* list of elliptic discs */
} Gell_disc_list;
/* Gfont_ind_map font index mapping */
typedef struct {
    Gint      ind; /* font index */
    Gint      iso9541_name; /* ISO 9541 font name */
} Gfont_ind_map;
/* Gop_st_entry operating state entry */
typedef struct {
    Gop_st_name name; /* GKS operating state name */
    union {
        Ggks_op_st gks; /* GKS operating state */
        Gpic_part_op_st pic_part; /* picture part operating state */
        Gstencil_op_st stencil; /* stencil operating state */
        Gseg_op_st seg; /* segment operating state */
        Gclosed_path_op_st closed_path; /* closed path operating state */
    }

```

```

        Gtiling_op_st      tiling; /* tiling operating state */
    } value;
} Gop_st_entry;
/* Ginst_specif instance specifier */
typedef struct {
    enum Ginst_type { /* instance type */
        GINST_PUT,
        GINST_ALIGN,
        GINST_MAP
    } type;
    union {
        struct Gput_inst {
            Gpoint      ref_point_inst; /* ref. point on instance */
            Gpoint      ref_point_open_stencil; /* ref. point on
                                                open stencil */
        } put;
        struct Galign_inst {
            Gpoint      ref_point_inst; /* ref. point on instance */
            Gpoint      dir_point_inst; /* direction point on instance */
            Gpoint      ref_point_open_stencil; /* ref. point on
                                                open stencil */
            Gpoint      dir_point_open_stencil; /* direction point on
                                                open stencil */
        } align;
        struct Gmap_inst {
            Gpoint      ref_point_inst[3]; /* 3 ref. points on instance */
            Gpoint      corr_point_open_stencil[3]; /* 3 corr. points on
                                                open stencil */
        } map;
    } specif;
} Ginst_specif;
/* Gopen_audit_list open audit list */
typedef struct {
    Gint      num_audits; /* number of audits */
    Gint      *audit_ids; /* list of audit identifiers */
    Gaudit_flag *audit_flags; /* list of audit flags */
} Gopen_audit_list;
/* Gseq_specif sequence specifier */
typedef struct {
    Gint      inst_name; /* instance name */
    Gint      stencil_name; /* existing stencil name */
    Gpoint      ref_point; /* reference point */
} Gseq_specif;
/* Gseq_specif_list sequence specifier list */
typedef struct {
    Gint      num_seq_specifs; /* number of sequence specifiers */
    Gseq_specif *seq_specif; /* list of sequence specifiers */
} Gseq_specif_list;
/* Gstencil_attr_value stencil attribute value */
typedef struct {
    Gstencil_attr_name      name; /* attribute name */
    union {

```

```

        Gfloat      top_y; /* top y*/
        Gfloat      half_y; /* half y*/
        Gfloat      base_y; /* base y*/
        Gfloat      bottom_y; /* bottom y*/
        Gfloat      ctr_y; /* centre y*/
        Gfloat      left_x; /* left x*/
        Gfloat      ctr_x; /* centre x*/
        Gfloat      right_x; /* right x*/
        Gpoint      ctr; /* centre*/
        Gpoint      origin; /* origin*/
        Gpoint      ctr_top; /* centre top*/
        Gpoint      ctr_bottom; /* centre bottom*/
        Gpoint      ctr_left; /* centre left*/
        Gpoint      ctr_right; /* centre right*/
        Gpoint      top_left; /* top left*/
        Gpoint      top_right; /* top right*/
        Gpoint      bottom_left; /* bottom left*/
        Gpoint      bottom_right; /* bottom right*/
    } value;
} Gstencil_attr_value;
/* Gstencil_attr stencil attributes */
typedef struct {
    Gfloat      top_y; /* top y*/
    Gfloat      cap_y; /* cap y*/
    Gfloat      half_y; /* half y*/
    Gfloat      base_y; /* base y*/
    Gfloat      bottom_y; /* bottom y*/
    Gfloat      ctr_y; /* centre y*/
    Gfloat      left_x; /* left x*/
    Gfloat      ctr_x; /* centre x*/
    Gfloat      right_x; /* right x*/
    Gpoint      ctr; /* centre */
    Gpoint      origin; /* origin*/
    Gpoint      ctr_top; /* centre top*/
    Gpoint      ctr_bottom; /* centre bottom*/
    Gpoint      ctr_right; /* centre right*/
    Gpoint      top_left; /* top left*/
    Gpoint      top_right; /* top right*/
    Gpoint      bottom_left; /* bottom left*/
    Gpoint      bottom_right; /* bottom right*/
} Gstencil_attr;
/* Gstencil_sl stencil state list */
typedef struct {
    Gint      name; /* stencil name*/
    Gstencil_attr      attrs; /* stencil attributes*/
} Gstencil_sl;
/* Gstencil_sl_list list of stencil state lists */
typedef struct {
    Gint      num_stencil_sls; /* number of stencil_sls in the list*/
    Gstencil_sl      *stencil_sls; /* list of stencil_sls*/
} Gstencil_sl_list;
/* Gctrl_point_list control point list */

```

```

typedef struct {
    enum Grat { /* rationality (RATIONAL|POLYNOMIAL) */
        GNURB_RAT,
        GNURB_POL
    } rat;
    Gint      num_points; /* number of points in the list */
    union {
        Ghomo_point *homo_points; /* list of homg. points*/
        Gpoint      *points; /* list of points*/
    } ctrl_points;
} Gctrl_point_list;
/* Gdisp_space_size display space size */
typedef struct {
    Gdc_units dc_units; /* device coordinate units*/
    Gfloat_size size_dc; /* display space size [in] dc [units]*/
    Gint_size size_raster; /* display space size [in]
                           raster [units]*/
} Gdisp_space_size;
/* Garea_facs area facilities */
typedef struct {
    Gint      num_int_styles; /* number of interior styles*/
    Gint_style int_styles[5]; /* list of available interior styles*/
    Gint_list hatch_styles; /* list of available hatch styles*/
    Gint      num_pred_inds; /* number of predef. area indices*/
    Gint_list edgetypes; /* list of edgetypes*/
    Gint      num_edgewidths; /* number of available edgewidths*/
    Gfloat     nom_edgewidth; /* nominal edgewidth*/
    Gfloat     min_edgewidth; /* min. edgewidth*/
    Gfloat     max_edgewidth; /* max. edgewidth*/
} Garea_facs;
/* Glimit_list limit list */
typedef struct {
    Gint      num_limits; /* number of limits in list*/
    Glimit     *limits; /* list of limits*/
} Glimit_list;
/* Gline_facs line facilities */
typedef struct {
    Gint_list types; /* list of linetypes*/
    Gint      num_widths; /* number of available linewidths*/
    Gfloat     nom_width; /* nominal linewidth*/
    Gfloat     min_width; /* min. linewidth*/
    Gfloat     max_width; /* max. linewidth*/
    Gint      num_pred_inds; /* number of predef. line indices*/
} Gline_facs;
/* Gloc locator value */
typedef struct {
    Gpoint     point; /* loc point */
    Gint      norm_tran_num; /* norm. tran. number */
} Gloc;
/* Gmarker_facs marker facilities */
typedef struct {
    Gint_list types; /* list of marker types*/

```

```

Gint      num_sizes; /* number of available marker sizes*/
Gfloat    nom_size;  /* nominal marker size*/
Gfloat    min_size;  /* min. marker size*/
Gfloat    max_size;  /* max. marker size*/
Gint      num_pred_inds; /* number of predef. marker indices*/
} Gmarker_facs;
/* Gnameset nameset */
typedef struct {
    Gint_list ws_ids; /* list of ws identifiers*/
    Gint_list seg_names; /* list of segment names*/
    Gint_list names; /* list of names*/
} Gnameset;
/* Gnurb NURB */
typedef struct {
    Gint order; /* order */
    Gctrl_point_list ctrl_point_list; /* list of control points */
    Gfloat_list weights; /* list of weight factors */
    Gfloat_list knots; /* list of knots */
    Gfloat t_min; /* t_min */
    Gfloat t_max; /* t_max */
} Gnurb;
/* Gnurb_list NURB list */
typedef struct {
    Gint num_nurbs; /* number of NURBs in list*/
    Gnurb *nurbs; /* list of NURBs*/
} Gnurb_list;
/* Gpat_rep pattern representation */
typedef struct {
    Gint_size dims; /* colour array's dimensions*/
    Gcolr_kind colr_kind; /* colour kind*/
    Gint *colr_array; /* colour array*/
    union {
        Grgb *rgb; /* RGB colours */
        Gcieluv *cieluv; /* CIELUV colours */
        Ghls *hls; /* HLS colours */
        Ghsv *hsv; /* HSV colours */
    } dir_colr;
} Gpat_rep;
/* Gpat_table pattern table */
typedef struct {
    Gint num_inds; /* number of pattern indices*/
    Gint *inds; /* list of pattern indices*/
    Gpat_rep *pat_reps; /* list of pattern representations*/
} Gpat_table;
/* Gpick pick [value] */
typedef struct {
    Gpick_status status; /* status*/
    Gnameset set_names; /* set of names*/
    Gint seg_name; /* segment name*/
    Gint pick_id; /* pick identifier*/
} Gpick;
/* Gpoint_list point list */

```



```

typedef struct {
    Gint      num_points; /* number of points in the list*/
    Gpoint    *points;    /* list of points*/
} Gpoint_list;
/* Gpoint_list_list list of point lists */
typedef struct {
    Gint      num_point_lists; /* number of point lists in the list*/
    Gpoint_list *point_lists; /* list of point lists*/
} Gpoint_list_list;
/* Gpath path */
typedef struct {
    enum Gpath_type { /* path type */
        GPATH_LINE,
        GPATH_NURB,
        GPATH_CONIC_SEC
    } type;
    union {
        Gpoint_list polyline; /* polyline */
        Gnurb nurb; /* NURB*/
        Gconic_sec conic_sec; /* conic section */
    } value;
} Gpath;
/* Gpath_list path list */
typedef struct {
    Gint      num_paths; /* number of paths in list*/
    Gpath     *paths;    /* list of paths*/
} Gpath_list;
/* Gpath_specif path specifier */
typedef struct {
    Gabut_specif abut_specif; /* Abut specifier*/
    Gpath        path; /* path */
    Gpoint       ref_point /* reference point */
} Gpath_specif;
/* Gbdry boundary */
typedef struct {
    enum Gbdry_type {
        GBNDRY_CLOSED_PATH,
        GBNDRY_ELL_DISC
    } type;
    union {
        Gpath_list closed_path_seq; /* closed path sequence*/
        Gconic_matrix ell_disc; /* elliptic disc */
    } value;
} Gbdry;
/* Gbdry_list boundary list */
typedef struct {
    Gint      num_bndries; /* number of boundaries in list*/
    Gbdry     *bndries;    /* list of boundaries*/
} Gbdry_list;
/* Grect rectangle */
typedef struct {
    Gpoint     p; /* point p */

```

```

    Gpoint    q;    /* point q */
} Grect;
/* Gscissor scissor */
typedef struct {
    Gclip_ind clip_ind;    /* clipping indicator*/
    Glimit_list clip_rect_set; /* clipping rectangle set*/
    Gshield_ind shield_ind; /* shielding indicator*/
    Glimit_list shield_rect_set; /* shielding rectangle set*/
} Gscissor;
/* Gscissor_list scissor list */
typedef struct {
    Gint    num_scissors;    /* number of scissors in list*/
    Gint    *scissor_ids;    /* list of scissor identifications*/
    Gscissor *scissors;    /* list of scissors*/
} Gscissor_list;
/* Gsel_crit selection criterion */
typedef struct GSEL_CRIT *Gsel_crit_ptr;
typedef struct GSEL_CRIT {
    Gsel_crit_op    op;    /* operation */
    union {
        Gnameset    compar; /* comparison
                                (EQUALS|CONTAINS|IS-IN) */;
        struct Gdyad_sel_crit {
            Gsel_crit_ptrleft; /* left selection operand */
            Gsel_crit_ptrright; /* right selection operand */
        } dyad;    /* dyadic criterion (AND|OR) */
        Gsel_crit_ptr    monad; /* monadic criterion (NOT) */
    } value;
} Gsel_crit;
/* Ggks_dt_entry GKS description table entry */
typedef struct {
    Ggks_dt_name    name; /* entry name */
    union {
        Gint_list    avail_ws_gen_types; /* list of available ws. types*/
        Gint_list    avail_fonts; /* list of available fonts*/
        Gfont_ind_map    def_font_ind_map; /* default font index mapping*/
    } value;
} Ggks_dt_entry;
/* Gsel selection */
typedef struct {
    Gsel_crit_type    type; /* selection type */
    Gsel_crit    crit; /* selection criterion */
} Gsel;
/* Gsel_table selection table */
typedef struct {
    Gint    num_sels;    /* number of selections */
    Gsel    *sels;    /* table of selections */
} Gsel_table;
/* Gstroke stroke value */
typedef struct {
    Gpoint_list    point_list; /* stroke point list */
    Gint    norm_tran_num;    /* norm. tran. number */

```

```

} Gstroke;
/* Gtext_extent text extent */
typedef struct {
    Gpoint    concat_point;    /* concatenation point*/
    Gpoint    paral[4];    /* text extent parallelogram*/
} Gtext_extent;
/* Gtext_fac text facilities */
typedef struct {
    Gint      num_font_precs;    /* number of fonts and precisions*/
    Gtext_font_prec *font_precs; /* list of fonts and precisions*/
    Gint      num_char_hts;    /* number of character heights*/
    Gfloat    min_char_ht;    /* min. character height*/
    Gfloat    max_char_ht;    /* max. character height*/
    Gint      num_char_expans; /* number of char. expansion
                                factors */
    Gfloat    min_char_expan;    /* min. expansion factor*/
    Gfloat    max_char_expan;    /* max. expansion factor*/
    Gint      num_pred_inds;    /* number of predef. text indices*/
} Gtext_fac;
/* Gtran transformation */
typedef struct {
    Glimit    win;    /* window */
    Glimit    vp;    /* viewport */
} Gtran;
/* Gview_rep view representation */
typedef struct {
    Gsel_crit sel_crit;    /* view selection criterion*/
    Gtran_matrix ori_matrix; /* view orientation matrix*/
    Gtran_matrix map_matrix; /* view mapping matrix*/
    Gscissor    scissor;    /* view scissor*/
} Gview_rep;
/* Gprim_attr_value primitive attribute value */
typedef struct {
    Gprim_attr_name name; /* primitive attribute name */
    union {
        Gint    pick_id;    /* pick identifier*/
        Gnameset nameset; /* nameset */
        Gscissor_list scissor_set; /* scissor set*/
        Gtran_matrix global_tran_matrix; /* global
                                           transformation matrix */
        Gtran_matrix local_tran_matrix; /* local
                                           transformation matrix */
        Gfloat_size pat_size; /* pattern size*/
        Gpoint    pat_ref_point; /* pattern
                                   reference point*/
        Gfloat    char_ht; /* character height*/
        Gvec    char_up_vec; /* character up vector*/
        Gfloat    text_skew_angle; /* text skew angle*/
        Gtext_path text_path; /* text path*/
        Gtext_align text_align; /* text alignment*/
        Gint    line_ind;    /* line index*/
        Gint    linetype;    /* linetype*/
    };
}

```

```

        Gfloat      linewidth; /* linewidth
                               scale factor */
        Gcolr_specif line_colr_specif; /* line colour
                               specifier */
        Gint  marker_ind; /* marker index */
        Gint  marker_type; /* marker type */
        Gfloat marker_size; /* marker size
                               scale factor */
        Gcolr_specif marker_colr_specif; /* marker colour
                               specifier */
        Gint  area_ind; /* area ind */
        Gint_style int_style; /* interior style */
        Gint  int_style_ind; /* interior style index */
        Gcolr_specif int_colr_specif; /* interior colour
                               specifier */
        Gedge_flag edge_flag; /* edge flag */
        Gint  edgetype; /* edgetype */
        Gfloat edgewidth; /* edgewidth
                               scale factor */
        Gcolr_specif edge_colr_specif; /* edge colour
                               specifier */
        Gint  text_ind; /* text index */
        Gtext_font_prec text_font_prec; /* text font
                               and precision */
        Gfloat char_expan; /* character
                               expansion factor */
        Gfloat char_space; /* character spacing */
        Gcolr_specif text_colr_specif; /* text colour
                               specifier */
        Gasfs asfs; /* asfs */
    } value;
} Gprim_attr_value;
/* Gbasic_in_value basic input value */
typedef struct {
    Gin_class class; /* basic input [measure] class */
    union {
        Gloc loc; /* locator value */
        Gstroke stroke; /* stroke value */
        Gfloat val; /* valuator value */
        Gchoice choice; /* choice value */
        Gpick pick; /* pick value */
        char *string; /* string value */
    } in_value; /* input value */
} Gbasic_in_value;
/* Gcomp_value composite value */
typedef struct {
    Gint num_devs; /* number of [basic] devices */
    Gbasic_in_value *basic_in_value; /* list of basic input values */
} Gcomp_value;
/* Gin_value input value */
typedef union {
    Gloc loc; /* locator value */

```

```

Gstroke    stroke;    /* strokevalue*/
Gfloat     val; /* valuator value*/
Gchoice    choice;    /* choice value*/
Gpick      pick; /* pick value*/
char       *string;   /* string value*/
Gcomp_value comp; /* composite value*/
} Gin_value;
/* Gin_queue_item input item [in queue] */
typedef struct {
    Gdev_id dev_id;    /* device identifier*/
    Gin_value in_value; /* input value*/
} Gin_queue_item;
/* Gin_queue input queue */
typedef struct {
    Gint num_items; /* number of input items*/
    Gin_queue_item *in_items; /* input items*/
} Gin_queue;
/* Ggks_sl_entry GKS state list entry */
typedef struct {
    Ggks_sl_name name; /* entry name */
    union {
        Groute_dir route_dir; /* route direction*/
        Gscissor_mode scissor_mode; /* scissor mode*/
        Gint_list open_wss; /* list of open workstations*/
        Gint_list active_wss; /* list of active workstations*/
        Gopen_audit_list open_audits; /* set of open audits*/
        Gint_list open_playbacks; /* set of open playbacks*/
        Gin_queue in_queue; /* input queue*/
        Gfont_ind_map font_ind_map; /* font index mapping*/
        Gint pick_id; /* pick identifier*/
        Gnameset nameset; /* nameset */
        Gtran_matrix global_tran_matrix; /* global
            transformation matrix */
        Gtran_matrix local_tran_matrix; /* local
            transformation matrix */
        Gfloat_size pat_size; /* pattern size*/
        Gpoint pat_ref_point; /* pattern reference point*/
        Gfloat char_ht; /* character height*/
        Gvec char_up_vec; /* character up vector*/
        Gfloat text_skew_angle; /* text skew angle*/
        Gtext_path text_path; /* text path*/
        Gtext_align text_align; /* text alignment*/
        Gscissor_list scissor_set; /* scissor set*/
        Gint line_ind; /* line index*/
        Gint linetype; /* linetype*/
        Gfloat linewidth; /* linewidth scale factor*/
        Gcolr_specif line_colr_specif; /* line colour specifier*/
        Gint marker_ind; /* marker index*/
        Gint marker_type; /* marker type*/
        Gfloat marker_size; /* marker size scale factor*/
        Gcolr_specif marker_colr_specif; /* marker colour specifier*/
        Gint area_ind; /* area ind*/
    };
}

```

```

Gint_style  int_style; /* interior style */
Gint  int_style_ind; /* interior style index */
Gcolr_specif  int_colr_specif; /* interior colour specifier */
Gedge_flag  edge_flag; /* edge flag */
Gint  edgetype; /* edgetype */
Gfloat  edgewidth; /* edgewidth scale factor */
Gcolr_specif  edge_colr_specif; /* edge colour specifier */
Gint  text_ind; /* text index */
Gtext_font_prec  text_font_prec; /* text font
                                and precision */
Gfloat  char_expan; /* character expansion factor */
Gfloat  char_space; /* character spacing */
Gcolr_specif  text_colr_specif; /* text colour specifier */
Gasfs asfs; /* asfs */
Gint  norm_tran_num; /* current norm. tran.
                    number */
Gtran norm_tran[64]; /* list of norm. tran. */
Gint  vp_in_pri[64]; /* list of vp input pris */
Gint  name_open_pic_part; /* name of open pic. part */
Gint_list  pic_part_names; /* list of picture parts
                           in use */
Gint  name_open_seg; /* name of open segment */
Gint_list  seg_names; /* list of segments
                     in use */
Gseg_sl_list  seg_sls; /* list of segment
                      state lists */
Gint  name_open_stencil; /* name of open stencil */
Gint_list  stencil_names; /* list of stencils
                          in use */
Gstencil_sl_list  stencil_sls; /* list of stencil
                              state lists in use */
Gcont_attrs cont_attrs; /* contour attributes */
Gint  name_open_tiling; /* name of open tiling */
Gint_list  tiling_names; /* list of tilings in use */

} value;
} Ggks_sl_entry;
/* Ggks_sl_entry_list GKS state list entry list */
typedef struct {
    Gint  num_gks_sl_entries; /* number of entries in list */
    Ggks_sl_entry  *gks_sl_entries; /* list of entries */
} Ggks_sl_entry_list;
/* Ggks_sl_name_list GKS state list name list */
typedef struct {
    Gint  num_gks_sl_names; /* number of names in list */
    Ggks_sl_name  *gks_sl_names; /* list of names */
} Ggks_sl_name_list;
/* Gcolr_chars colour characteristics */
typedef struct {
    enum Gcolr_chars_type {GTYPE_CIELUV, GTYPE_OTHER } type;
    union {
        Gcieluv  prim_colr[3]; /* CIELUV primary colours */
    };

```

```

        Gdata impl_dep;    /* impl.dep. */
    } chars;
} Gcolr_chars;
/* Gcolr_facs colour facilities */
typedef struct {
    Gint      num_colr_models; /* number of colour models*/
    Gint      colr_models[4]; /* list of available colour models*/
    Gint      num_colrs; /* number of colours*/
    Gcolr_chars chars; /* colour characteristics*/
    Gcolr_avail colr_avail; /* colour availability*/
    Gint      num_pred_inds; /* number of predef. colour indices*/
} Gcolr_facs;
/* Gcolr_rep colour representation */
typedef union {
    Grgb      rgb; /* Red Green Blue colour specification */
    Gcieluv   cieluv; /* CIE L*u*v* 1976 colour specification */
    Ghls      hls; /* Hue Luminance Saturation colour specification */
    Ghsv      hsv; /* Hue Saturation Value colour specification */
    /* etc. */
} Gcolr_rep;
/* Garea_bundle area bundle */
typedef struct {
    Gint_style int_style; /* interior style*/
    Gint      style_ind; /* interior style index*/
    Gcolr_kind colr_kind; /* interior colour kind*/
    Gint      colr_ind; /* interior colour index*/
    Gcolr_rep int_dir_colr; /* direct interior colour*/
    Gedge_flag edge_flag; /* edge flag*/
    Gint      edgetype; /* edgetype*/
    Gfloat     edgewidth; /* edgewidth scale factor*/
    Gcolr_kind edge_colr_kind; /* edge colour kind*/
    Gint      edge_colr_ind; /* edge colour index*/
    Gcolr_rep edge_dir_colr; /* direct edge colour*/
} Garea_bundle;
/* Garea_attrs area attributes */
typedef struct {
    Gasf      int_style_asf; /* interior style ASF */
    Gasf      style_ind_asf; /* style index ASF */
    Gasf      colr_ind_asf; /* colour specifier ASF */
    Gasf      edge_flag_asf; /* edge flag ASF */
    Gasf      edgetype_asf; /* edgetype ASF */
    Gasf      edgewidth_asf; /* edgewidth scale factor ASF */
    Gasf      edge_colr_ind_asf; /* edge colour specifier ASF */
    Gint      ind; /* area index*/
    Garea_bundle bundle; /* area bundle*/
} Garea_attrs;
/* Gline_bundle line bundle */
typedef struct {
    Gint      type; /* linetype */
    Gfloat     width; /* linewidth scale factor*/
    Gcolr_kind colr_kind; /* colour kind*/
    Gint      colr_ind; /* colour index*/

```

```

    Gcolr_rep dir_colr; /* direct colour*/
} Gline_bundle;
/* Gline_attrs line attributes */
typedef struct {
    Gasf      type_asf; /* linetype ASF */
    Gasf      width_asf; /* linewidth scale factor ASF */
    Gasf      colr_ind_asf; /* line colour specifier ASF */
    Gint      ind; /* line index*/
    Gline_bundle bundle; /* line bundle*/
} Gline_attrs;
/* Gmarker_bundle marker bundle */
typedef struct {
    Gint      type; /* marker type*/
    Gfloat     size; /* marker size scale factor*/
    Gcolr_kind colr_kind; /* colour kind*/
    Gint      colr_ind; /* colour index*/
    Gcolr_rep dir_colr; /* direct colour*/
} Gmarker_bundle;
/* Gmarker_attrs marker attributes */
typedef struct {
    Gasf      type_asf; /* marker type ASF */
    Gasf      size_asf; /* marker size scale factor ASF */
    Gasf      colr_ind_asf; /* marker colour specifier ASF */
    Gint      ind; /* marker index*/
    Gmarker_bundle bundle; /* marker bundle*/
} Gmarker_attrs;
/* Gareal_bundle_table area bundle table */
typedef struct {
    Gint      num_inds; /* number of area indices*/
    Gint      *inds; /* list of area indices*/
    Gareal_bundle *bundles; /* list of area bundles*/
} Gareal_bundle_table;
/* Gline_bundle_table line bundle table */
typedef struct {
    Gint      num_inds; /* number of line indices*/
    Gint      *inds; /* list of line indices*/
    Gline_bundle *bundles; /* list of line bundles*/
} Gline_bundle_table;
/* Gmarker_bundle_table marker bundle table */
typedef struct {
    Gint      num_inds; /* number of marker indices*/
    Gint      *inds; /* list of marker indices*/
    Gmarker_bundle *bundles; /* list of marker bundles*/
} Gmarker_bundle_table;
/* Gtext_bundle text bundle */
typedef struct {
    Gtext_font_prec text_font_prec; /* text font and precision*/
    Gfloat      char_expan; /* character expansion factor*/
    Gfloat      char_space; /* character spacing*/
    Gcolr_kind colr_kind; /* colour kind*/
    Gint      colr_ind; /* colour index*/
    Gcolr_rep dir_colr; /* direct colour*/

```



```

} Gtext_bundle;
/* Gtext_bundle_table text bundle table */
typedef struct {
    Gint      num_inds;    /* number of character indices*/
    Gint      *inds;      /* list of character indices*/
    Gtext_bundle *bundles; /* list of text bundles*/
} Gtext_bundle_table;
/* Grep representation */
typedef struct {
    Gint ind; /* index */
    enum Grep_design { /* representation designation */
        GREP_LINE, /* line bundle*/
        GREP_MARKER, /* marker bundle*/
        GREP_AREA, /* area bundle*/
        GREP_PAT, /* pattern representation*/
        GREP_TEXT, /* text bundle*/
        GREP_COLR, /* colr specification*/
        GREP_UNDEF /* undefined*/
    } design;
    union {
        Gline_bundle line_bundle; /* line bundle*/
        Gmarker_bundle marker_bundle; /* marker bundle*/
        Gtext_bundle text_bundle; /* text bundle*/
        Gareal_bundle area_bundle; /* area bundle*/
        Gpat_rep pat_rep; /* pattern representation*/
        Gcolr_specif colr_specif; /* colour specification*/
    } value;
} Grep;
/* Grepl_tech replication technique */
typedef struct {
    enum Grepl_dir {
        GREPL_DX,
        GREPL_DY,
        GREPL_DXY,
        GREPL_DYX
    } dir;
    union {
        Gfloat dx; /* dx*/
        Gfloat dy; /* dy*/
        Gvec dxy; /* dxy */
        Gvec dyx; /* dyx */
    } value;
} Grepl_tech;
/* Gcolr_table colour table */
typedef struct {
    Gint      num_inds;    /* number of colour indices*/
    Gint      *inds;      /* list of colour indices*/
    Gcolr_specif *colr_specs; /* list of colour specifications*/
} Gcolr_table;
/* Implementation Dependent Types*/
/* Gchoice_data choice data */
typedef struct {

```

```

union Gchoice_pets {
    struct Gchoice_pet_r1 {
        Gdata impl_dep; /* impl. dep. */
    } pet_r1; /* pet 1 data */
    struct Gchoice_pet_r2 {
        Gint num_prs; /* number of prompts */
        Gpr_flag *prs; /* prompt array */
        Gdata impl_dep; /* impl. dep. */
    } pet_r2; /* pet 2 data */
    struct Gchoice_pet_r3 {
        Gint num_strings; /* number of choice strings */
        char **strings; /* array of choice strings */
        Gdata impl_dep; /* impl. dep. */
    } pet_r3; /* pet 3 data */
    struct Gchoice_pet_r4 {
        Gint num_strings; /* number of choice strings */
        char **strings; /* array of choice strings */
        Gdata impl_dep; /* impl. dep. */
    } pet_r4; /* pet 4 data */
    struct Gchoice_pet_r5 {
        Gint seg_name; /* segment name */
        Gint num_pick_ids; /* number of pick identifiers */
        Gint *pick_ids; /* array of pick identifiers */
        Gdata impl_dep; /* impl. dep. */
    } pet_r5; /* pet 5 data */
    struct Gchoice_pet_u1 {
        Gdata impl_dep; /* impl. dep. */
    } pet_u1; /* pet -1 data */
    /* . . . impl. defined PET's */
} pets;
} Gchoice_data;
/* Gescape_in_data escape input data record */
typedef union {
    struct Gescape_in_r1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_r1; /* escape 1 data */
    struct Gescape_in_u1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_u1; /* escape -1 data */
    /* etc. */
} Gescape_in_data;
/* Gescape_out_data escape output data record */
typedef union {
    struct Gescape_out_r1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_r1; /* escape 1 data */
    struct Gescape_out_u1 {
        Gdata impl_dep; /* impl. dep. */
    } escape_u1; /* escape -1 data */
    /* etc. */
} Gescape_out_data;
/* Ggdp_data gdp data record */

```

```

typedef union {
    struct Ggdp_r1 {
        Gdata impl_dep; /* impl. dep. */
    } gdp_r1; /* gdp 1 data */
    struct Ggdp_u1 {
        Gdata impl_dep; /* impl. dep. */
    } gdp_u1; /* gdp -1 data */
    /* etc. */
} Ggdp_data;
/* Gloc_data locator data record */
typedef struct {
    union Gloc_pets {
        struct Gloc_pet_r1 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gloc_pet_r2 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r2; /* pet 2 data */
        struct Gloc_pet_r3 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r3; /* pet 3 data */
        struct Gloc_pet_r4 {
            Gattr_ctrl_flagattr_ctrl_flag;
            /* attributecontrol flag */
            Gline_attrs lineattrs;
            /* line attributes */
            Gdata impl_dep; /* impl. dep. */
        } pet_r4; /* pet 4 data */
        struct Gloc_pet_r5 {
            Gattr_ctrl_flagattr_ctrl_flag;
            /* attributecontrol flag */
            Gline_fill_ctrl_flagline_fill_ctrl_flag;
            /* line/area control flag */
            union Gloc_attrs {
                Gline_attrslines_attrs;
                /* lineattrs. */
                Garea_attrssarea_attrs;
                /* interiorattrs. */
            } attrs;
            Gdata impl_dep; /* impl. dep. */
        } pet_r5; /* pet 5 data */
        struct Gloc_pet_r6 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r6; /* pet 6 data */
        struct Gloc_pet_u1 {
            Gdata impl_dep; /* impl. dep. */
        } pet_u1; /* pet -1 data */
        /* . . . impl. defined PET's */
    } pets;
} Gloc_data;
/* Gpick_data pick data */
typedef struct {

```

```

union Gpick_pets {
    struct Gpick_pet_r1 {
        Gdata impl_dep; /* impl. dep. */
    } pet_r1; /* pet 1 data */
    struct Gpick_pet_r2 {
        Gint pick_id; /* pick identifier */
        Gint seg_name; /* segment name */
        Gnameset set_names; /* set of names */
        Gdata impl_dep; /* impl. dep. */
    } pet_r2; /* pet 2 data */
    struct Gpick_pet_r3 {
        Gnameset set_names; /* set of names */
        Gdata impl_dep; /* impl. dep. */
    } pet_r3; /* pet 3 data */
    struct Gpick_pet_u1 {
        Gdata data; /* data */
    } pet_u1; /* pet -1 data */
    /* etc. */
} pets;
} Gpick_data;
/* Gstring_data string data record */
typedef struct {
    Gint in_buf_size; /* input buffer size (nr. of bytes) */
    Gint init_pos; /* initial [cursor] position */
    union Gstring_pets {
        struct Gstring_pet_r1 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gstring_pet_u1 {
            Gdata impl_dep; /* impl. dep. */
        } pet_u1; /* pet -1 data */
        /* etc. */
    } pets;
} Gstring_data;
/* Gstroke_data stroke data */
typedef struct {
    Gint init_pos; /* initial buffer editing position */
    Gint in_buf_size; /* input buffer size (nr. of points) */
    Gfloat x_interval; /* X interval */
    Gfloat y_interval; /* Y interval */
    Gfloat time_interval; /* time interval */
    union Gstroke_pets {
        struct Gstroke_pet_r1 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gstroke_pet_r2 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r2; /* pet 2 data */
        struct Gstroke_pet_r3 {
            Gattr_ctrl_flag attr_ctrl_flag;
            /* attribute control flag */
            Gmarker_attr marker_attr;
        }
    }
}

```

```

        /* marker   attrs. */
        Gdata impl_dep; /* impl. dep. */
    } pet_r3; /* pet 3 data */
    struct Gstroke_pet_r4 {
        Gattr_ctrl_flagattr_ctrl_flag;
        /* attributecontrol flag */
        Gline_attrs line_attrs;
        /* line      attrs. */
        Gdata impl_dep; /* impl. dep. */
    } pet_r4; /* pet 4 data */
    struct Gstroke_pet_ul {
        Gdata impl_dep; /* impl. dep. */
    } pet_ul; /* pet -1 data */
    /* etc. */

} pets;
} Gstroke_data;
/* Gval_data valuator data record */
typedef struct {
    Gfloat    low_value; /* low value */
    Gfloat    high_value; /* high value */
    union Gval_pets {
        struct Gval_pet_r1 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r1; /* pet 1 data */
        struct Gval_pet_r2 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r2; /* pet 2 data */
        struct Gval_pet_r3 {
            Gdata impl_dep; /* impl. dep. */
        } pet_r3; /* pet 3 data */
        struct Gval_pet_ul {
            Gdata impl_dep; /* impl. dep. */
        } pet_ul; /* pet -1 data */
        /* etc. */
    } pets;
} Gval_data;
/* Gaudit_user_data audit user data record */
typedef struct {
    Gint      id; /* identifier */
    union {
        Gdata impl_dep; /* impl. dependent */
    } data;
} Gaudit_user_data;
/* Gbasic_in_data basic input data */
typedef struct {
    Gin_class class; /* basic input [measure] class */
    union {
        Gloc_data    loc_data; /* locator data */
        Gstroke_data  stroke_data; /* stroke data */
        Gval_data     val_data; /* valuator data */
        Gchoice_data  choice_data; /* choice data */
        Gpick_data    pick_data; /* pick data */
    }

```

```

        Gstring_data    string_data; /* string data */
    } in_data; /* input data */
} Gbasic_in_data;
/* Gcomp_data composite data */
typedef struct {
    Gint    num_devs; /* number of [basic] devices */
    Gbasic_in_data *basic_in_data; /* list of basic input data */
} Gcomp_data;
/* Gdev_id_in_value_list device identifier and input value list */
typedef struct {
    Gint    num_devs; /* number of [basic] devices in list */
    Gdev_id *dev_ids; /* list of device id values */
    Gin_value *in_values; /* list of device input values */
} Gdev_id_in_value_list;
/* Gin_data input data */
typedef union {
    Gloc_data loc_data; /* locator data */
    Gstroke_data stroke_data; /* strokedata */
    Gval_data val_data; /* valuator data */
    Gchoice_data choice_data; /* choice data */
    Gpick_data pick_data; /* pick data */
    Gstring_data string_data; /* string data */
    Gcomp_data comp_data; /* composite data */
} Gin_data;
/* Ginit_in initial input */
typedef struct {
    Gin_value in_value; /* input value */
    Gint    pet; /* prompt and echo type */
    Gecho_switch echo_switch; /* echo switch */
    Glimit    echo_area; /* echo area */
    Gin_data in_data; /* input data */
} Ginit_in;
/* Ginit_value initial value */
typedef struct {
    Ginit_sel sel; /* initial selector */
    union {
        Gin_value init_value; /* input value */
        Gint    pet; /* prompt and echo type */
        Gecho_switch echo_switch; /* echo switch */
        Glimit    echo_area; /* echo area */
        Gin_data in_data; /* input data */
        Ginit_in all; /* all initial input */
    } value;
} Ginit_value;
/* Gin_dev_init_value input device initial value */
typedef struct {
    Gdev_id dev_id; /* device identifier */
    Ginit_value init_value; /* initial value */
} Gin_dev_init_value;
/* Gin_dev_init_value_list input initial value list */
typedef struct {
    Gint    num_devs; /* number of input devices */

```

```

    Gin_dev_init_value      *init_values; /* list of input initial values */
} Gin_dev_init_value_list;
/* Gop_modes_init_values operating modes and initial values */
typedef struct {
    Gint      num_in_devs;      /* number of input devices */
    Gdev_id   dev_ids;         /* device identifiers */
    Gop_mode  op_modes;        /* operating modes */
    Ginit_in  init_ins;        /* initial input values */
} Gop_modes_init_values;
/* Gprim_params primitive parameters */
typedef struct {
    Gprim_type type; /* primitive type */
    union {
        Gpoint_list_list polyline_set; /* polyline set */
        Gnurb_list nurb_set; /* NURB set */
        Gconic_sec_list conic_sec_set; /* conic section set */

        Gpoint_list polymarker; /* polymarker */
        Gpoint_list_list fill_area_set; /* fill area set */
        Gnurb_list closed_nurb_set; /* closed NURB set */
        Gconic_sec_list ell_sec_set; /* elliptic sector set */
        Gconic_sec_list ell_seg_set; /* elliptic segment set */
        Gell_disc_list ell_disc_set; /* elliptic disc set */
        struct Gtext {
            char *string; /* character string */
            Gpoint pos; /* text position */
        } text;
        struct Gcell_array {
            Grect rect; /* cell rectangle */
            Gpat_rep array; /* cell array */
        } cell_array;
        Gdesign design; /* design */
        struct Ggdp {
            Gpoint_list point_list; /* point_list */
            Gint id; /* gdp identifier */
            Ggdp_data gdp_data; /* gdp_data */
        } gdp;
    } value;
} Gprim_params;
/* Gtiling_params tiling parameters */
typedef struct {
    Gtiling_type type; /* tiling type */
    union {
        struct Gtiling_line_area { /* line or area primitives in tiling */
            Gcolr_specif colr_specif; /* colour specifier */
            union { /* geometric data of line or area primitive */
                Gpoint_list_list polyline_set; /* polyline set */
                Gnurb_list nurb_set; /* NURB set */
                Gconic_sec_list conic_sec_set; /* conic section set */
                Gpoint_list_list fill_area_set; /* fill area set */
                Gnurb_list closed_nurb_set; /* closed NURB set */
                Gconic_sec_list ell_sec_set; /* elliptic sector set */
            }
        }
    }
}

```

```

        Gconic_sec_listell_seg_set; /* elliptic segment set */
        Gell_disc_listell_disc_set; /* elliptic disc set */
    } geom_data;
} tiling_line_area;
Gdesign      design; /* design */
} value;
} Gtiling_params;
/* Gws_type workstation type */
typedef struct {
    Gint      gen_type; /* generic type */
    void      *specif_info; /* specific information */
} Gws_type;
/* Gws_dt_entry workstation description table entry */
typedef struct {
    Gws_dt_name      name; /* entry name */
    union {
        Gws_type      type; /* workstation type */
        Gws_status     ws_status; /* ws. status */
        Gdc_units       dc_units; /* DC units */
        Gdisp_space_size disp_space_size; /* displace
            space size */
        Gws_class       ws_class; /* ws. classification */

        Gline_fac     line_fac; /* line facilities */
        Gline_bundle_tablepred_line_bundles; /* predefined line
            bundle table */

        Gmarker_fac     marker_fac; /* marker
            facilities */
        Gmarker_bundle_tablepred_marker_bundles; /* predefined marker
            bundle table */

        Gareafac     area_fac; /* area facilities */
        Gareafac_bundle_tablepred_area_bundles; /* predefined area
            bundle table */

        Gpat_table     pred_pat_reps; /* predefined pattern
            bundle table */

        Gtext_fac     text_fac; /* text facilities */
        Gtext_bundle_tablepred_text_bundles; /* predefined text
            bundle table */

        Gcolr_fac     colr_fac; /* colour facilities */
        Gcolr_table     pred_colr_reps; /* predefined colour
            bundle table */
        Gint_list       gdp_ids; /* list of available
            GDPs */
        Gdev_id_list     dev_ids; /* list of available
            input devices */
        Gin_dev_init_value_listin_init_values; /* input device
            initial values */
    };
} Gws_dt_entry;

```



```

        Gint_list    meas_ids; /* list of available
                               measures */
        Gint_list    trigger_ids; /* list of available
                               triggers */
        Gdev_comp_list dev_comps; /* device compositions */
    } value;
} Gws_dt_entry;
/* Gws_sl_entry workstation state list entry */
typedef struct {
    Gws_sl_name      name; /* entry name */
    union {
        Gws_st      ws_st; /* ws. state
                           (ACTIVE|INACTIVE) */
        struct {
            void *specif;
            Gint type;
        } specif_type; /* specifier and type */
        Gline_bundle_table line_bundle_table; /* line bundle
        table */
        Gmarker_bundle_table marker_bundle_table; /* marker
        bundle table */
        Gtext_bundle_table text_bundle_table; /* text
        bundle table */
        Garea_bundle_table area_bundle_table; /* area
        bundle table */
        Gpat_table pat_table; /* pattern
        bundle table */
        Gcolr_table colr_table; /* colour
        bundle table */
        Gtran ws_win_vp; /* window
        and viewport */
        Gvis_effects_st vis_effects_st; /* visual effects
        state */
        Gop_modes_init_values op_modes_init_values; /* input device
        operating modes
        and initial values */
        Gsel_table sel_table; /* selection table */
        Gint_list stored_segs; /* set of
        stored segments */
        Gview_rep view_rep[16]; /* view bundle table */
        Gint view_pri[16]; /* view priorities */
    } entry;
} Gws_sl_entry;
/* Gws_sl_entry_list workstation state list entry value list */
typedef struct {
    Gint      num_entries; /* number of WSL entry values
                           in list */
    Gws_sl_entry *entries; /* list of WSL entry values */
} Gws_sl_entry_list;
/* Gws_sl_name_list workstation state list entry name list */
typedef struct {
    Gint      num_names; /* number of WSL entry names in list */

```

```

    Gws_sl_name      *names;      /* list of WSL entry names*/
} Gws_sl_name_list;
/* Gfunc_params function parameters */
typedef struct {
    Gint      func_id;
    union {
    struct Gopen_gks {
        char      *err_file;
    } open_gks;
    struct Gsave_gks_sl {
        Ggks_sl_name_list      entry_names;
        Ggks_sl_entry_list      entries;
    } save_gks_sl;
    struct Grestore_gks_sl {
        Ggks_sl_entry_list      entries;
    } restore_gks_sl;
    struct Gescape {
        Gint      func_id;
        Gescape_in_data      in_data;
        Gescape_out_data      out_data;
    } escape;
    struct Groute {
        Groute_dir      dir;
    } route;
    struct Gcreate_out_prim {
        Gprim_params      prim_params;
    } create_out_prim;
    struct Gopen_stencil {
        Gint      stencil_name;
        Ginside_rule      inside_rule;
    } open_stencil;
    struct Grename_stencil {
        Gint      old_name;
        Gint      new_name;
    } rename_stencil;
    struct Gdel_stencil {
        Gint      name;
    } del_stencil;
    struct Gcreate_stencil_bndry {
        Gint      stencil_name;
        Ginside_rule      inside_rule;
        Gbndry_list      bndry;
    } create_stencil_bndry;
    struct Gcreate_stencil_conts {
        Gint      stencil_name;
        Ginside_rule      inside_rule;
        Gpath_list      path_seq;
    } create_stencil_conts;
    struct Gset_cont_attr {
        Gcont_attr_value      cont_attr;
    } set_cont_attr;
    struct Gset_stencil_attr {

```

```

    Gint      stencil_name;
    Gstencil_attr_value  stencil_attr;
} set_stencil_attr;
struct Gget_stencil_attr {
    Gint      stencil_name;
    Gstencil_attr_name  attr_name;
    Gstencil_attr_value  attr;
} get_stencil_attr;
struct Ginst_stencil {
    Gint      stencil_name;
    Gint      inst_name;
    Gtran_matrix  stencil_tran;
    Ginst_specif  inst_specif;
} inst_stencil;
struct Ginst_stencil_path {
    Gint      stencil_name;
    Gint      inst_name;
    Gpoint     start_map;
    Gpoint     end_map;
    Gint      inst_num;
    Gpath      path;
} inst_stencil_path;
struct Ginst_stencil_seq_path {
    Gseq_specif_list inst_seq_specif;
    Gpath_specif  path_specif;
    Gtran_matrix  stencil_tran;
} inst_stencil_seq_path;
struct Gopen_tiling {
    Gint      tiling_name;
} open_tiling;
struct Grename_tiling {
    Gint      old_name;
    Gint      new_name;
} rename_tiling;
struct Gdel_tiling {
    Gint      name;
} del_tiling;
struct Gcreate_tiling_comp {
    Gtiling_params  tiling_params;
    Gpoint     origin;
    Grepl_tech repl_tech;
} create_tiling_comp;
struct Gset_prim_attr {
    Gprim_attr_value attr_value;
} set_prim_attr;
struct Gadd_set_names_nameset {
    Gnameset  set_names;
} add_set_names_nameset;
struct Gremove_set_names_nameset {
    Gnameset  set_names;
} remove_set_names_nameset;
struct Gadd_set_scissors_scissor_set {

```

```

    Gscissor_list    scissor_set;
} add_set_scissors_scissor_set;
struct Gremove_set_scissors_scissor_set {
    Gint_list    scissor_ids;
} remove_set_scissors_scissor_set;
struct Gset_win_vp {
    Gint        tran_num;
    Gtran        norm_tran;
} set_win_vp;
struct Gset_vp_in_pri {
    Gint        tran_num;
    Gint        ref_tran_num;
    Grel_pri    rel_pri;
} set_vp_in_pri;
struct Gset_scissor_mode {
    Gscissor_mode    scissor_mode;
} set_scissor_mode;
struct Gset_norm_tran_num {
    Gint        tran_num;
} set_norm_tran_num;
struct Gdel_prims_ndc_pic {
    Gsel_crit    sel_crit;
} del_prims_ndc_pic;
struct Gadd_set_names_ndc_pic {
    Gnameset    set_names;
    Gsel_crit    sel_crit;
} add_set_names_ndc_pic;
struct Gremove_set_names_ndc_pic {
    Gnameset    set_names;
    Gsel_crit    sel_crit;
} remove_set_names_ndc_pic;
struct Gset_ndc_pic_prim_attr {
    Gsel_crit    sel_crit;
    Gprim_attr_value    attr_value;
} set_ndc_pic_prim_attr;
struct Gadd_set_scissors_ndc_pic {
    Gscissor_list    scissor_set;
    Gsel_crit    sel_crit;
} add_set_scissors_ndc_pic;
struct Gremove_set_scissors_ndc_pic {
    Gint_list    scissor_ids;
    Gsel_crit    sel_crit;
} remove_set_scissors_ndc_pic;
struct Greorder_ndc_pic {
    Gsel_crit    source_sel_crit;
    Gsel_crit    ref_sel_crit;
    Grel_pos    rel_pos;
} reorder_ndc_pic;
struct Gcopy_ndc_pic_ndc_mf {
    void        *mf_specif;
    Gint        pic_id;
    Gsel_crit    sel_crit;

```

```

    Gnameset    set_names;
} copy_ndc_pic_ndc_mf;
struct Gcopy_ndc_mf_pic_ndc_pic {
    void        *mf_specif;
    Gint        pic_id;
    Gnameset    set_names;
} copy_ndc_mf_pic_ndc_pic;
struct Gopen_pic_part {
    Gint        pic_part_name;
} beg_pic_part;
struct Gar_pic_part {
    Gint        pic_part_name;
    void        *ar_specif;
    Gint        ar_name_pic_part;
} ar_pic_part;
struct Gret_pic_part_ar {
    void        *ar_specif;
    Gint        ar_name_pic_part;
    Gint        pic_part_name;
} ret_pic_part_ar;
struct Greopen_pic_part {
    Gint        pic_part_name;
} reopen_pic_part;
struct Gappend_pic_part {
    Gint        source_pic_part_name;
    Gint        sink_pic_part_name;
    Gtran_matrix global_tran_matrix;
    Gtran_mode global_tran_mode;
    Gtran_matrix local_tran_matrix;
    Gtran_mode local_tran_mode;
    Gnameset    set_names;
} append_pic_part;
struct Grename_pic_part {
    Gint        old_pic_part_name;
    Gint        new_pic_part_name;
} rename_pic_part;
struct Gdel_pic_part {
    Gint        pic_part_name;
} del_pic_part;
struct Gcopy_pic_part_pic_part_store {
    Gint        pic_part_name;
    Gsel_crit   sel_crit;
    Gtran_matrix global_tran_matrix;
    Gtran_mode global_tran_mode;
    Gtran_matrix local_tran_matrix;
    Gtran_mode local_tran_mode;
    Gnameset    set_names;
    Gscissor_sel scissor_sel;
} copy_pic_part_pic_part_store;
struct Gcopy_ndc_pic_pic_part_store {
    Gsel_crit   sel_crit;
    Gint        pic_part_name;

```

```

    Gnameset    set_names;
} copy_ndc_pic_pic_part_store;
struct Gset_in_dev_mode {
    Gdev_id     dev_id;
    Gop_mode    op_mode;
} set_in_dev_mode;
struct Greq_in {
    Gdev_id     dev_id;
    Gin_status  in_status;
    Gin_value   log_in_value;
} req_in;
struct Gsample_in {
    Gdev_id     dev_id;
    Gin_value   log_in_value;
} sample_in;
struct Gawait_in {
    Gfloat      timeout;
    Gdev_id_in_value_list dev_id_values;
} await_in;
struct Gflush_dev_events {
    Gdev_id     dev_id;
} flush_dev_events;
struct Gset_font_ind_map {
    Gfont_ind_map font_ind_map;
} set_font_ind_map;
struct Gget_glyph_name {
    Gint        font_ind;
    char        character;
    Gint        glyph_name;
} get_glyph_name;
struct Gset_char_code {
    Gint        font_ind;
    char        character;
    Gint        glyph_name;
} set_char_code;
struct Geval_tran_matrix {
    Gpoint      point;
    Gvec        shift;
    Gfloat      angle;
    Gvec        scale;
    Gcoord_switch coord_switch;
    Gtran_matrix tran_matrix;
} eval_tran_matrix;
struct Gaccum_tran_matrix {
    Gtran_matrix matrix;
    Gpoint      point;
    Gvec        shift;
    Gfloat      angle;
    Gvec        scale;
    Gcoord_switch coord_switch;
    Gtran_matrix tran_matrix;
} accum_tran_matrix;

```

```

struct Geval_circle {
    Gpoint    ctr;
    Gfloat    radius;
    Gconic_matrix    circle;
} eval_circle;
struct Geval_ell {
    Gpoint    ctr;
    Gpoint    conj_radius_end_point[2];
    Gconic_matrix    ell;
} eval_ell;
struct Geval_circ_arc_3_point {
    Gpoint    circ_point[3];
    Gconic_sec    circ_arc;
} eval_circ_arc_3_point;
struct Geval_circ_arc_ctr {
    Gpoint    ctr;
    Gvec    vec[2];
    Gsense_flag    sense_flag;
    Gfloat    radius;
    Gconic_sec    circ_arc;
} eval_circ_arc_ctr;
struct Geval_ell_arc {
    Gpoint    ctr;
    Gpoint    conj_radius_end_point[2];
    Gvec    vec[2];
    Gconic_sec    conic_arc;
} eval_ell_arc;
struct Geval_hyp_arc {
    Gpoint    ctr;
    Gpoint    tran_radius_end_point;
    Gpoint    conj_radius_end_point;
    Gvec    vec[2];
    Gconic_sec    conic_arc;
} eval_hyp_arc;
struct Geval_par_arc {
    Gpoint    intersec_point;
    Gpoint    start_point;
    Gpoint    end_point;
    Gconic_sec    conic_arc;
} eval_par_arc;
struct Geval_wc_ord {
    Gfloat    wc_ord;
    Gord_sel    ord_sel;
    Gfloat    ndc_value;
} eval_wc_ord;
struct Gopen_ws {
    Gint    ws_id;
    void    *ws_specif_info;
    Gint    ws_gen_type;
} open_ws;
struct Gclose_ws {
    Gint    ws_id;

```

```

} close_ws;
struct Gsave_ws_sl {
    Gint      ws_id;
    Gws_sl_name_list entry_names;
    Gws_sl_entry_list entry_list;
} save_ws_sl;
struct Grestore_ws_sl {
    Gint      ws_id;
    Gws_sl_entry_list entries;
} restore_ws_sl;
struct Gget_ws_status {
    Gint      ws_id;
    Gws_status ws_status;
} get_ws_status;
struct Gremove_backdrop {
    Gint      ws_id;
} remove_backdrop;
struct Gset_rep {
    Gint      ws_id;
    Grep      rep_value;
} set_rep;
struct Gset_view_pri {
    Gint      ws_id;
    Gint      view_ind;
    Gint      ref_view_ind;
    Grel_pri  rel_pri;
} set_view_pri;
struct Gset_view_sel_crit {
    Gint      ws_id;
    Gint      view_ind;
    Gsel_crit sel_crit;
} set_view_sel_crit;
struct Gset_view {
    Gint      ws_id;
    Gint      ind;
    Gtran_matrix ori_matrix;
    Gtran_matrix map_matrix;
    Gscissor    scissor;
} set_view;
struct Gset_ws_vis_effects {
    Gint      ws_id;
    Gvis_effects_st vis_effects_st;
} set_ws_vis_effects;
struct Gset_ws_win_vp {
    Gint      ws_id;
    Gtran      ws_tran;
} set_ws_win_vp;
struct Gdef_in_dev {
    Gdev_id    dev_id;
    Gint_list  meas_set;
    Gint_list  trigger_set;
    Ginit_value init_value;

```



```

} def_in_dev;
struct Ginit_in_dev {
    Gdev_id    dev_id;
    Ginit_value init_value;
} init_in_dev;
struct Gset_ws_sel_crit {
    Gint      ws_id;
    Gsel      sel;
} set_ws_sel_crit;
struct Gcopy_real_pic_real_mf {
    Gint      ws_id;
    void      *mf_specif;
    Gint      pic_id;
} copy_real_pic_real_mf;
struct Gcopy_blank_real_pic_real_mf {
    Gint      ws_id;
    void      *mf_specif;
    Gint      pic_id;
} copy_blank_real_pic_real_mf;
struct Gcopy_real_mf_pic_backdrop {
    Gint      ws_id;
    void      *mf_specif;
    Gint      pic_id;
} copy_real_mf_pic_backdrop;
struct Gmessage {
    Gint      ws_id;
    char      *message;
} message;
struct Greset_specif_ws_dt_entry_st {
    Gint      ws_id;
    Gws_dt_name ws_dt_name;
} reset_specif_ws_dt_entry_st;
struct Gget_text_extent {
    Gint      ws_id;
    Gpoint    pos;
    char      *str;
    Gtext_extent extent;
} get_text_extent;
struct Geval_view_ori_matrix {
    Gpoint    ref_point;
    Gvec      view_up;
    Gtran_matrix view_ori_matrix;
} eval_view_ori_matrix;
struct Geval_view_map_matrix {
    Gtran      win_vp;
    Gtran_matrix view_map_matrix;
} eval_view_map_matrix;
struct Gconv_colr {
    Gint      ws_id;
    Gcolr_specif colr_specif;
    Gint      colr_model;
    Gcolr_specif colr_coords;

```

```

    Gconv_flag conv_flag;
} conv_colr;
struct Gcreate_seg {
    Gint      seg_name;
} create_seg;
struct Grename_seg {
    Gint      old_seg_name;
    Gint      new_seg_name;
} rename_seg;
struct Gdel_seg {
    Gint      seg_name;
} del_seg;
struct Gdel_seg_ws {
    Gint      ws_id;
    Gint      seg_name;
} del_seg_ws;
struct Gassoc_seg_ws {
    Gint      ws_id;
    Gint      seg_name;
} assoc_seg_ws;
struct Gcopy_seg_ws {
    Gint      ws_id;
    Gint      seg_name;
} copy_seg_ws;
struct Ginsert_seg {
    Gint      seg_name;
    Gtran_matrix tran_matrix;
} insert_seg;
struct Gset_seg_attr {
    Gint      seg_name;
    Gseg_attr_value seg_attr_value;
} set_seg_attr;
struct Gactivate_ws {
    Gint      ws_id;
} activate_ws;
struct Gdeactivate_ws {
    Gint      ws_id;
} deactivate_ws;
struct Gclear_ws {
    Gint      ws_id;
    Gctrl_flag ctrl_flag;
} clear_ws;
struct Gget_map_seg_name {
    Gint      seg_name;
    Gint      map_seg_name;
} get_map_seg_name;
struct Gget_map_ws_id {
    Gint      ws_id;
    Gint      map_ws_id;
} get_map_ws_id;
} func_data;
} Gfunc_params;

```

A.2 Macros

/* Macros*/

/* Error macros*/

```

#define GE_NO_ERR (0)
#define GE_GKS_NOT_OPEN (1001)
#define GE_GKS_OPEN (1002)
#define GE_PP_NOT_OPEN (1003)
#define GE_PP_OPEN (1004)
#define GE_SEG_NOT_OPEN (1005)
#define GE_SEG_OPEN (1006)
#define GE_ST_NOT_OPEN (1007)
#define GE_ST_OPEN (1008)
#define GE_TL_NOT_OPEN (1009)
#define GE_TL_OPEN (1010)
#define GE_WS_TYPE_NOT_SUPP (1011)
#define GE_WS_NOT_OPEN (1012)
#define GE_WS_OPEN (1013)
#define GE_WS_NOT_ACTIVE (1014)
#define GE_WS_ACTIVE (1015)
#define GE_AUDIT_NOT_OPEN (1016)
#define GE_AUDIT_OPEN (1017)
#define GE_PLAYBACK_NOT_OPEN (1018)
#define GE_PLAYBACK_OPEN (1019)
#define GE_PP_NOT_EXIST (1020)
#define GE_PP_NAME_USE (1021)
#define GE_OLD_PP_NOT_EXIST (1022)
#define GE_NEW_PP_NAME_USE (1023)
#define GE_SRC_PP_NOT_EXIST (1024)
#define GE_SINK_PP_NOT_EXIST (1025)
#define GE_SEG_NOT_EXIST (1026)
#define GE_SEG_NAME_IN_USE (1027)
#define GE_ST_NOT_EXIST (1028)
#define GE_ST_NAME_USE (1029)
#define GE_OLD_ST_NOT_EXIST (1030)
#define GE_NEW_ST_NAME_USE (1031)
#define GE_INST_NAME_EQ_ST_NAME_USE (1032)
#define GE_TL_NOT_EXIST (1033)
#define GE_TL_NAME_USE (1034)
#define GE_OLD_TL_NOT_EXIST (1035)
#define GE_NEW_TL_NAME_USE (1036)
#define GE_IN_Q_OVERF (1037)
#define GE_IN_Q_NOT_OVERF (1038)
#define GE_IN_Q_OVERF_WS_CLOSED (1039)
#define GE_ESCAPE_FUNC_NOT_SUPP (1040)
#define GE_GLYPH_NOT_AVAIL (1041)
#define GE_FONT_NAME_NOT_AVAIL (1042)
#define GE_LINETYPE_NOT_SUPP (1043)
#define GE_MARKER_TYPE_NOT_SUPP (1044)
#define GE_FONT_NOT_SUPP_PREC (1045)
#define GE_INT_STYLE_NOT_SUPP (1046)
#define GE_HATCH_STYLE_NOT_SUPP (1047)
#define GE_EDGETYPE_NOT_SUPP (1048)

```

```

#define GE_COLR_MODEL_NOT_SUPP (1049)
#define GE_GDP_NOT_SUPP (1050)
#define GE_IN_DEV_NOT_EXIST (1051)
#define GE_COMB_MEAS_TRIG_NOT_AVAIL (1052)
#define GE_SEG_NOT_EXIST_WS (1053)
#define GE_PIC_NOT_EXIST_IN_MF (1054)
#define GE_NO_ITEM_PLAYBACK (1055)
#define GE_PLAYBACK_ITEM_INVAL (1056)
#define GE_PP_NOT_EXIST_AR (1057)
#define GE_EDGE_NOT_INTERSECT_PATH (1058)
#define GE_START_VEC_NOT_INTERSECT_HYP (1059)
#define GE_END_VEC_NOT_INTERSECT_HYP (1060)
#define GE_OLD_PP_NAME_EQ_NEW_PP_NAME (1061)
#define GE_OLD_ST_NAME_EQ_NEW_ST_NAME (1062)
#define GE_OLD_TL_NAME_EQ_NEW_TL_NAME (1063)
/*
 * Binding specific errors
 */
#define GE_START_IND_INVAL (2201)
#define GE_APPL_LIST_LENGTH_LT_ZERO (2202)
#define GE_ENUM_TYPE_INVAL (2203)
#define GE_ALLOC_STORE (2204)
#define GE_ALLOC_MEM_STORE (2205)
#define GE_ERR_FILE_INVAL (2250)
#define GE_INSUFF_STORE (2251)
#define GE_ENTRIES_INVAL (2252)
#define GE_ESC_FUNC_ID_INVAL (2253)
#define GE_ESC_IN_DATA_INVAL (2254)
#define GE_ERR_NUM_INVAL (2255)
#define GE_FUNC_NAME_INVAL (2256)
#define GE_DIR_INVAL (2257)
#define GE_PRIM_TYPE_INVAL (2258)
#define GE_NUM_POINTS_INVAL (2259)
#define GE_CODE_INVAL (2260)
#define GE_DIMS_COLR_ARRAY_INVAL (2261)
#define GE_GDP_ID_INVAL (2262)
#define GE_GDP_DATA_INVAL (2263)
#define GE_NURB_DEF_INVAL (2264)
#define GE_CONIC_SEC_INVAL (2265)
#define GE_INSIDE_RULE_INVAL (2266)
#define GE_SEQ_PATHS_INVAL (2267)
#define GE_CONT_ATTR_NAME_INVAL (2268)
#define GE_CONT_ATTR_VALUE_INVAL (2269)
#define GE_ST_NAME_INVAL (2270)
#define GE_OLD_NEW_ST_NAME_INVAL (2271)
#define GE_ST_ATTR_NAME_INVAL (2272)
#define GE_BNDRY_SPECIF_INVAL (2273)
#define GE_ST_ATTR_VALUE_INVAL (2274)
#define GE_INST_NAME_INVAL (2275)
#define GE_INST_TYPE_INVAL (2276)
#define GE_INST_SPECIF_INVAL (2277)
#define GE_PATH_INVAL (2278)

```

```
#define GE_TL_NAME_INVAL (2279)
#define GE_REPL_TECH_INVAL (2280)
#define GE_ATTR_NAME_INVAL (2281)
#define GE_ATTR_VALUE_INVAL (2282)
#define GE_SET_NAMES_INVAL (2283)
#define GE_SCISSOR_SPECIF_INVAL (2284)
#define GE_SCISSOR_IDS_INVAL (2285)
#define GE_SCISSOR_MODE_INVAL (2286)
#define GE_TRAN_NUM_INVAL (2287)
#define GE_WIN_DEF_INVAL (2288)
#define GE_VP_DEF_INVAL (2289)
#define GE_SEL_CRIT_INVAL (2290)
#define GE_MF_SPECIF_INVAL (2291)
#define GE_PIC_ID_INVAL (2292)
#define GE_PP_NAME_INVAL (2293)
#define GE_AR_SPECIF_INVAL (2294)
#define GE_AR_NAME_PP_INVAL (2295)
#define GE_SRC_PP_NAME_INVAL (2296)
#define GE_SINK_PP_NAME_INVAL (2297)
#define GE_GLOBAL_TRAN_MODE_INVAL (2298)
#define GE_LOCAL_TRAN_MODE_INVAL (2299)
#define GE_OLD_PP_NAME_INVAL (2300)
#define GE_NEW_PP_NAME_INVAL (2301)
#define GE_SCISSOR_SEL_INVAL (2302)
#define GE_IN_DEV_INVAL (2303)
#define GE_OP_MODE_INVAL (2304)
#define GE_TIMEOUT_INVAL (2305)
#define GE_FONT_IND_ZERO (2306)
#define GE_FONT_NAME_INVAL (2307)
#define GE_CHAR_CODE_INVAL (2308)
#define GE_AUDIT_ID_INVAL (2309)
#define GE_AUDIT_OP_INVAL (2310)
#define GE_AUDIT_USER_DATA_INVAL (2311)
#define GE_PLAYBACK_OP_INVAL (2312)
#define GE_PROC_OP_INVAL (2313)
#define GE_ENTRY_NAME_INVAL (2314)
#define GE_FIXED_POINT_INVAL (2315)
#define GE_SHIFT_VEC_INVAL (2316)
#define GE_RADIUS_INVAL (2317)
#define GE_RADII_ID (2318)
#define GE_POINTS_COLLIN (2319)
#define GE_SENSE_FLAG_INVAL (2320)
#define GE_ORD_SEL_INVAL (2321)
#define GE_WS_ID_INVAL (2322)
#define GE_WS_TYPE_INVAL (2323)
#define GE_WS_SPECIF_INVAL (2324)
#define GE_REP_INVAL (2325)
#define GE_IND_INVAL (2326)
#define GE_TYPE_ZERO (2327)
#define GE_SCALE_FAC_NEG (2328)
#define GE_CHAR_EXPAN_NOT_POS (2329)
#define GE_EDGE_FLAG_INVAL (2330)
```

```

#define GE_INT_STYLE_INVAL (2331)
#define GE_COLR_IND_INVAL (2332)
#define GE_PAT_IND_INVAL (2333)
#define GE_COLR_SPECIF_INVAL (2334)
#define GE_VIEW_IND_INVAL (2335)
#define GE_REF_IND_INVAL (2336)
#define GE_REL_PRI_INVAL (2337)
#define GE_VIEW_SCISSOR_INVAL (2338)
#define GE_VIS_EFFECTS_ST_INVAL (2339)
#define GE_WS_WIN_LIMITS_INVAL (2340)
#define GE_WS_VP_LIMITS_INVAL (2341)
#define GE_WS_VP_NOT_IN_DISP_SPACE (2342)
#define GE_MEAS_SEQ_INVAL (2343)
#define GE_TRIGGER_SET_INVAL (2344)
#define GE_ECHO_SWITCH_INVAL (2345)
#define GE_ECHO_AREA_RECT_INVAL (2346)
#define GE_SEL_TYPE_INVAL (2347)
#define GE_TYPE_RETURNED_VALUES_INVAL (2348)
#define GE_WS_GEN_TYPE_INVAL (2349)
#define GE_COLR_MODEL_INVAL (2350)
#define GE_SEG_NAME_INVAL (2351)
#define GE_OLD_NEW_SEG_NAME_INVAL (2352)
#define GE_SEG_ATTR_VALUE_INVAL (2353)

```

```

/* Function identifier macros*/

```

```

#define Gfn_open_gks (0)
#define Gfn_close_gks (1)
#define Gfn_save_gks_sl (200)
#define Gfn_restore_gks_sl (201)
#define Gfn_escape (11)
#define Gfn_emergency_close_gks (153)
#define Gfn_err_hand (154)
#define Gfn_err_log (155)
#define Gfn_route (202)
#define Gfn_create_out_prim (203)
#define Gfn_polyline (12)
#define Gfn_polyline_set (204)
#define Gfn_nurb_set (205)
#define Gfn_conic_sec_set (206)
#define Gfn_polymarker (13)
#define Gfn_fill_area (15)
#define Gfn_fill_area_set (207)
#define Gfn_ell_sec_set (208)
#define Gfn_ell_seg_set (209)
#define Gfn_ell_disc_set (210)
#define Gfn_closed_nurb_set (211)
#define Gfn_text (14)
#define Gfn_cell_array (16)
#define Gfn_design (212)
#define Gfn_gdp (17)
#define Gfn_open_stencil (213)
#define Gfn_close_stencil (214)

```

#define Gfn_rename_stencil	(215)
#define Gfn_del_stencil	(216)
#define Gfn_create_stencil_bndry	(217)
#define Gfn_create_stencil_conts	(218)
#define Gfn_set_cont_attr	(219)
#define Gfn_set_stencil_attr	(220)
#define Gfn_get_stencil_attr	(221)
#define Gfn_inst_stencil	(222)
#define Gfn_inst_stencil_path	(223)
#define Gfn_inst_stencil_seq_path	(224)
#define Gfn_open_tiling	(225)
#define Gfn_close_tiling	(226)
#define Gfn_rename_tiling	(227)
#define Gfn_del_tiling	(228)
#define Gfn_create_tiling_comp	(229)
#define Gfn_set_prim_attr	(230)
#define Gfn_set_line_ind	(18)
#define Gfn_set_linetype	(19)
#define Gfn_set_linewidth	(20)
#define Gfn_set_line_colr_specif	(231)
#define Gfn_set_line_colr_ind	(21)
#define Gfn_set_marker_ind	(22)
#define Gfn_set_marker_type	(23)
#define Gfn_set_marker_size	(24)
#define Gfn_set_marker_colr_specif	(232)
#define Gfn_set_marker_colr_ind	(25)
#define Gfn_set_text_ind	(26)
#define Gfn_set_text_font_prec	(27)
#define Gfn_set_char_expan	(28)
#define Gfn_set_char_space	(29)
#define Gfn_set_text_colr_specif	(233)
#define Gfn_set_text_colr_ind	(30)
#define Gfn_set_char_ht	(31)
#define Gfn_set_char_up_vec	(32)
#define Gfn_set_text_path	(33)
#define Gfn_set_text_align	(34)
#define Gfn_set_text_skew_angle	(234)
#define Gfn_set_area_ind	(235)
#define Gfn_set_int_style	(236)
#define Gfn_set_int_style_ind	(237)
#define Gfn_set_int_colr_specif	(238)
#define Gfn_set_int_colr_ind	(239)
#define Gfn_set_pat_size	(39)
#define Gfn_set_pat_ref_point	(40)
#define Gfn_set_global_tran_matrix	(240)
#define Gfn_set_local_tran_matrix	(241)
#define Gfn_set_edge_flag	(242)
#define Gfn_set_edgetype	(243)
#define Gfn_set_edgewidth	(244)
#define Gfn_set_edge_colr_specif	(245)
#define Gfn_set_edge_colr_ind	(246)
#define Gfn_set_asfs	(41)


```

#define Gfn_set_pick_id (42)
#define Gfn_set_nameset (247)
#define Gfn_set_scissor_set (248)
#define Gfn_add_set_names_nameset (249)
#define Gfn_remove_set_names_nameset (250)
#define Gfn_add_set_scissors_scissor_set (251)
#define Gfn_remove_set_scissors_scissor_set (252)
#define Gfn_set_win_vp (49)
#define Gfn_set_win (49)
#define Gfn_set_vp (50)
#define Gfn_set_vp_in_pri (50)
#define Gfn_set_scissor_mode (253)
#define Gfn_set_norm_tran_num (254)
#define Gfn_sel_norm_tran (52)
#define Gfn_del_prims_ndc_pic (255)
#define Gfn_remove_set_names_ndc_pic (256)
#define Gfn_add_set_names_ndc_pic (257)
#define Gfn_set_ndc_pic_prim_attr (258)
#define Gfn_add_set_scissors_ndc_pic (259)
#define Gfn_remove_set_scissors_ndc_pic (260)
#define Gfn_reorder_ndc_pic (261)
#define Gfn_copy_ndc_pic_ndc_mf (262)
#define Gfn_copy_ndc_mf_pic_ndc_pic (263)
#define Gfn_open_pic_part (264)
#define Gfn_close_pic_part (265)
#define Gfn_ar_pic_part (266)
#define Gfn_ret_pic_part_ar (267)
#define Gfn_reopen_pic_part (268)
#define Gfn_append_pic_part (269)
#define Gfn_rename_pic_part (270)
#define Gfn_del_pic_part (271)
#define Gfn_copy_pic_part_pic_part_store (272)
#define Gfn_copy_ndc_pic_pic_part_store (273)
#define Gfn_set_in_dev_mode (274)
#define Gfn_set_loc_mode (75)
#define Gfn_set_stroke_mode (76)
#define Gfn_set_val_mode (77)
#define Gfn_set_choice_mode (78)
#define Gfn_set_pick_mode (79)
#define Gfn_set_string_mode (80)
#define Gfn_req_in (275)
#define Gfn_req_loc (81)
#define Gfn_req_stroke (82)
#define Gfn_req_val (83)
#define Gfn_req_choice (84)
#define Gfn_req_pick (85)
#define Gfn_req_string (86)
#define Gfn_sample_in (276)
#define Gfn_sample_loc (87)
#define Gfn_sample_stroke (88)
#define Gfn_sample_val (89)
#define Gfn_sample_choice (90)

```



```
#define Gfn_sample_pick (91)
#define Gfn_sample_string (92)
#define Gfn_await_in (277)
#define Gfn_await_event (93)
#define Gfn_flush_dev_events (278)
#define Gfn_get_loc (95)
#define Gfn_get_stroke (96)
#define Gfn_get_val (97)
#define Gfn_get_choice (98)
#define Gfn_get_pick (99)
#define Gfn_get_string (100)
#define Gfn_set_font_ind_map (279)
#define Gfn_get_glyph_name (280)
#define Gfn_set_char_code (281)
#define Gfn_audit (282)
#define Gfn_write_user_rec_audit (283)
#define Gfn_playback (284)
#define Gfn_read_item_func_name_audit (285)
#define Gfn_read_item_audit (286)
#define Gfn_proc_audit_item (287)
#define Gfn_eval_tran_matrix (105)
#define Gfn_accum_tran_matrix (106)
#define Gfn_eval_circle (288)
#define Gfn_eval_ell (289)
#define Gfn_eval_circ_arc_3_point (290)
#define Gfn_eval_circ_arc_ctr (291)
#define Gfn_eval_ell_arc (292)
#define Gfn_eval_hyp_arc (293)
#define Gfn_eval_par_arc (294)
#define Gfn_eval_wc_ord (295)
#define Gfn_set_err_hand (156)
#define Gfn_create_store (296)
#define Gfn_del_store (297)
#define Gfn_open_ws (2)
#define Gfn_close_ws (3)
#define Gfn_save_ws_sl (298)
#define Gfn_restore_ws_sl (299)
#define Gfn_get_ws_status (300)
#define Gfn_remove_backdrop (301)
#define Gfn_set_rep (302)
#define Gfn_set_line_rep (43)
#define Gfn_set_marker_rep (44)
#define Gfn_set_text_rep (45)
#define Gfn_set_area_rep (303)
#define Gfn_set_pat_rep (47)
#define Gfn_set_colr_rep (48)
#define Gfn_set_view_pri (304)
#define Gfn_set_view_sel_crit (305)
#define Gfn_set_view (306)
#define Gfn_set_ws_vis_effects (307)
#define Gfn_set_ws_win_vp (308)
#define Gfn_set_ws_win (54)
```

```

#define Gfn_set_ws_vp (55)
#define Gfn_def_in_dev (309)
#define Gfn_init_in_dev (310)
#define Gfn_init_loc (69)
#define Gfn_init_stroke (70)
#define Gfn_init_val (71)
#define Gfn_init_choice (72)
#define Gfn_init_pick (73)
#define Gfn_init_string (74)
#define Gfn_set_ws_sel_crit (311)
#define Gfn_copy_real_pic_real_mf (312)
#define Gfn_copy_blank_real_pic_real_mf (313)
#define Gfn_copy_real_mf_pic_backdrop (314)
#define Gfn_message (10)
#define Gfn_reset_specif_ws_dt_entry_st (315)
#define Gfn_get_text_extent (316)
#define Gfn_eval_view_ori_matrix (317)
#define Gfn_eval_view_map_matrix (318)
#define Gfn_conv_colr (319)
#define Gfn_create_seg (56)
#define Gfn_close_seg (57)
#define Gfn_rename_seg (58)
#define Gfn_del_seg (59)
#define Gfn_del_seg_ws (60)
#define Gfn_assoc_seg_ws (61)
#define Gfn_copy_seg_ws (62)
#define Gfn_insert_seg (63)
#define Gfn_set_seg_attr (320)
#define Gfn_set_seg_tran (64)
#define Gfn_set_vis (65)
#define Gfn_set_highl (66)
#define Gfn_set_det (68)
#define Gfn_set_seg_pri (67)
#define Gfn_activate_ws (4)
#define Gfn_deactivate_ws (5)
#define Gfn_clear_ws (6)
#define Gfn_get_map_seg_name (321)
#define Gfn_get_map_ws_id (322)
/* Miscellaneous macros*/
#define GLINE_SOLID (1)
#define GLINE_DASH (2)
#define GLINE_DOT (3)
#define GLINE_DASH_DOT (4)
#define GLINE_DASH_DOT_DOT (5)
#define GMARKER_DOT (1)
#define GMARKER_PLUS (2)
#define GMARKER_ASTERISK (3)
#define GMARKER_CIRCLE (4)
#define GMARKER_CROSS (5)
#define GHATCH_HOR (1)
#define GHATCH_VERT (2)
#define GHATCH_DIAG_45 (3)

```

```

#define GHATCH_DIAG_135 (4)
#define GHATCH_HOR_VERT (5)
#define GHATCH_DIAG_45_135 (6)
#define GMODEL_RGB (1)
#define GMODEL_CIELUV (2)
#define GMODEL_HSV (3)
#define GMODEL_HLS (4)
#define GLOC_DEF (1)
#define GLOC_CROSS_HAIR (2)
#define GLOC_TRACK_CROSS (3)
#define GLOC_RUB_BAND (4)
#define GLOC_RECT (5)
#define GLOC_DIGIT (6)
#define GSTROKE_DEF (1)
#define GSTROKE_DIGIT (2)
#define GSTROKE_MARKER (3)
#define GSTROKE_LINE (4)
#define GVAL_DEF (1)
#define GVAL_GRAPH (2)
#define GVAL_DIGIT (3)
#define GCHOICE_DEF (1)
#define GCHOICE_PR_ECHO (2)
#define GCHOICE_STRING_PR (3)
#define GCHOICE_STRING_IN (4)
#define GCHOICE_SEG (5)
#define GPICK_DEF (1)
#define GPICK_GROUP_HIGHL (2)
#define GPICK_SEG_HIGHL (3)
#define GPICK_SET_NAMES_HIGHL (3)
#define GSTRING_DEF (1)
#define GDEF_ERR_FILE ((char*)0)

```

A.3 Function calls

```

/* GKS Functions
/* Control functions*/
extern void gopen_gks(
    const char *err_file, /* name of error file*/
    size_t mem_units /* number of units of memory available
                        for buffer space*/);
extern void gclose_gks(
    void );
extern void gsave_gks_sl(
    const Ggks_sl_name_list *entry_names, /* GKS state list entry
                                           names */
    Gstore store, /* handle to Store object*/
    Ggks_sl_entry_list **entries /* OUT GKS state
                                list entries */);
extern void grestore_gks_sl(
    const Ggks_sl_entry_list *entries /* GKS state list entries */);
extern void gescape(
    Gint func_id, /* escape function identifier*/
    const Gescape_in_data *in_data, /* escape input data record*/

```

```

Gstore      store,      /* handle to Store object*/
Gescape_out_data **out_data /* OUT  escape output data
                        record */);
extern void gemergency_close_gks(
    void
    );
extern void gerr_hand(
    Gint      err_num,      /* error number*/
    Gint      func_num,     /* number of function that detected the error*/
    const char *err_file    /* name of error file*/);
extern void gerr_log(
    Gint      err_num,      /* error number*/
    Gint      func_num,     /* number of function that detected the error*/
    const char *err_file    /* name of error file*/);
extern void groute(
    Groute_dir dir /* direction*/);
/* Output functions*/
extern void gcreate_out_prim(
    const Gprim_params *prim_params/* primitive parameters*/);
extern void gpolyline(
    const Gpoint_list *point_list/* list of points*/);
extern void gpolyline_set(
    const Gpoint_list_list *point_list_list/* list of point lists*/);
extern void gnurb_set(
    const Gnurb_list *nurb_set /* NURB parameter lists*/);
extern void gconic_sec_set(
    const Gconic_sec_list *conic_sec_set/* Conic section set*/);
extern void gpolymarker(
    const Gpoint_list *point_list/* list of points*/);
extern void gfill_area(
    const Gpoint_list *point_list/* list of points*/);
extern void gfill_area_set(
    const Gpoint_list_list *point_list_list/* list of point lists*/);
extern void gclosed_nurb_set(
    const Gnurb_list *closed_nurb_set/* NURB parameter lists*/);
extern void gell_sec_set(
    const Gconic_sec_list *ell_sec_set/* elliptic sector set*/);
extern void gell_seg_set(
    const Gconic_sec_list *ell_seg_set/* elliptic segment set*/);
extern void gell_disc_set(
    const Gell_disc_list *ell_disc_set/* elliptic disc set*/);
extern void gtext(
    const Gpoint *text_pos, /* text position*/
    const char *char_string /* character string*/);
extern void gcell_array(
    const Grect *rect,      /* cell rectangle*/
    const Gpat_rep *colr_array /* colour array*/);
extern void gdesign(
    const Gdesign *design /* design*/);
extern void ggdp(
    const Gpoint_list *point_list/* list of points*/
    Gint      gdp_id,      /* gdp identifier*/
    const Ggdp_data *gdp_data /* gdp data record*/);

```

```

/* Design output functions*/
extern void gopen_stencil(
    Gint      stencil_name,      /* stencil name*/
    Ginside_rule  inside_rule /* inside rule*/);
extern void gclose_stencil(
    void);
extern void grename_stencil(
    Gint      old_name,      /* old stencil name*/
    Gint      new_name      /* new stencil name*/);
extern void gdel_stencil(
    Gint      name /* stencil name*/);
extern void gcreate_stencil_bndry(
    Gint      stencil_name,      /* stencil name*/
    Ginside_rule  inside_rule, /* inside rule*/
    const Gbndry_list  *bndry/* boundary*/);
extern void gcreate_stencil_conts(
    Gint      stencil_name,      /* stencil name*/
    Ginside_rule  inside_rule, /* inside rule*/
    const Gpath_list *path_seq  /* path sequence*/);
extern void gset_cont_attr(
    const Gcont_attr_value *cont_attr/* contour attribute*/);
extern void gset_stencil_attr(
    Gint      stencil_name,      /* stencil name*/
    const Gstencil_attr_value  *stencil_attr/* stencil attribute*/);
extern void gget_stencil_attr(
    Gint      stencil_name,      /* stencil name*/
    Gstencil_attr_name      attr_name, /* stencil attribute name*/
    Gint      *err_ind,      /* OUT error indicator*/
    Gstencil_attr_value  *attr /* OUT stencil attribute*/);
extern void ginst_stencil(
    Gint      stencil_name,      /* stencil name*/
    Gint      inst_name, /* instance name*/
    Gtran_matrix  stencil_tran, /* stencil transformation*/
    const Ginst_specif  *inst_specif/* instance specifier*/);
extern void ginst_stencil_path(
    Gint      stencil_name,      /* stencil name*/
    Gint      inst_name, /* instance name*/
    const Gpoint  *start_map, /* start map*/
    const Gpoint  *end_map,  /* end map*/
    Gint      inst_num, /* instance number*/
    const Gpath  *path_def  /* path definition*/);
extern void ginst_stencil_seq_path(
    const Gseq_specif_list *inst_seq_specif, /* instance sequence
                                              specifier*/
    const Gpath_specif  *path_specif, /* path specifier*/
    Gtran_matrix  stencil_tran/* stencil transformation*/);
extern void gopen_tiling(
    Gint      tiling_name /* tiling name*/);
extern void gclose_tiling(
    void);
extern void grename_tiling(
    Gint      old_name,      /* old tiling name*/

```

```

    Gint      new_name      /* new tiling name*/);
extern void gdel_tiling(
    Gint      name /* tiling name*/);
extern void gcreate_tiling_comp(
    const Gtiling_params *tiling_params, /* tiling parameters*/
    const Gpoint *origin, /* origin */
    const Grepl_tech *repl_tech /* replication technique*/);
extern void gset_prim_attr(
    const Gprim_attr_value *attr_value /* attr_value */);
extern void gset_pick_id(
    Gint      pick_id /* pick identifier*/);
extern void gset_nameset(
    const Gnameset *nameset /* nameset */);
extern void gset_scissor_set(
    const Gscissor_list *scissor_set /* scissor_set */);
extern void gset_global_tran_matrix(
    Gtran_matrix global_tran_matrix /* global transformation
                                   matrix */);
extern void gset_local_tran_matrix(
    Gtran_matrix local_tran_matrix /* local transformation
                                   matrix */);
extern void gset_pat_size(
    const Gfloat_size *pat_size /* pattern size*/);
extern void gset_pat_ref_point(
    const Gpoint *pat_ref_point /* pattern reference point*/);
extern void gset_char_ht(
    Gfloat      char_ht /* character height*/);
extern void gset_char_up_vec(
    const Gvec *char_up_vec /* character up vector*/);
extern void gset_text_skew_angle(
    Gfloat      text_skew_angle /* text skew angle*/);
extern void gset_text_path(
    Gtext_path text_path /* text path*/);
extern void gset_text_align(
    const Gtext_align *text_align /* text alignment*/);
extern void gset_line_ind(
    Gint      line_ind /* line index*/);
extern void gset_linetype(
    Gint      linetype /* linetype*/);
extern void gset_linewidth(
    Gfloat      linewidth /* linewidth scale factor*/);
extern void gset_line_colr_specif(
    const Gcolr_specif *line_colr_specif /* line colour specifier*/);
extern void gset_line_colr_ind(
    Gint      line_colr_ind /* line colour index*/);
extern void gset_marker_ind(
    Gint      marker_ind /* marker index*/);
extern void gset_marker_type(
    Gint      marker_type /* marker type*/);
extern void gset_marker_size(
    Gfloat      marker_size /* marker size scale factor*/);
extern void gset_marker_colr_specif(

```

```

    const Gcolr_specif    *marker_colr_specif/* marker colour
                           specifier*/);
extern void gset_marker_colr_ind(
    Gint    marker_colr_ind    /* marker colour index*/);
extern void gset_area_ind(
    Gint    area_ind    /* area index*/);
extern void gset_int_style(
    Gint_style int_style    /* interior style*/);
extern void gset_int_style_ind(
    Gint    int_style_ind    /* interior style index*/);
extern void gset_int_colr_specif(
    const Gcolr_specif    *int_colr_specif/* interior colour specifier*/);
extern void gset_int_colr_ind(
    Gint    int_colr_ind    /* interior colour index*/);
extern void gset_edge_flag(
    Gedge_flag edge_flag    /* edge flag*/);
extern void gset_edgetype(
    Gint    edgetype    /* edgetype*/);
extern void gset_edgewidth(
    Gfloat    edgewidth    /* edgewidth scale factor*/);
extern void gset_edge_colr_specif(
    const Gcolr_specif    *edge_colr_specif/* edge colour specifier*/);
extern void gset_edge_colr_ind(
    Gint    edge_colr_ind    /* edge colour index*/);
extern void gset_text_ind(
    Gint    text_ind    /* text index*/);
extern void gset_text_font_prec(
    const Gtext_font_prec *text_font_prec/* text font and precision */);
extern void gset_char_expan(
    Gfloat    char_expan    /* character expansion factor*/);
extern void gset_char_space(
    Gfloat    char_space    /* character spacing*/);
extern void gset_text_colr_specif(
    const Gcolr_specif    *text_colr_specif/* text colour specifier*/);
extern void gset_text_colr_ind(
    Gint    text_colr_ind    /* text colour index*/);
extern void gset_asfs(
    const Gasfs    *asfs /* list of attribute source flags */);
extern void gadd_set_names_nameset(
    const Gnameset *set_names /* set of names */);
extern void gremove_set_names_nameset(
    const Gnameset *set_names /* set of names */);
extern void gadd_set_scissors_scissor_set(
    const Gscissor_list *set_scissors/*set of scissors */);
extern void gremove_set_scissors_scissor_set(
    const Gint_list *scissor_ids/* scissor identifiers */);
/* Normalization transformation functions*/
extern void gset_win_vp(
    Gint    tran_num,    /* transformation number*/
    const Gtran    *win_wp    /* window and viewport limits*/);
extern void gset_win(
    Gint    tran_num,    /* transformation number*/

```



```

    const Glimit      *win /* window limits*/);
extern void gset_vp(
    Gint      tran_num, /* transformation number*/
    const Glimit *vp /* viewport limits*/);
extern void gset_vp_in_pri(
    Gint      tran_num, /* transformation number*/
    Gint      ref_tran_num, /* reference transformation number*/
    Grel_pri  rel_pri /* relative priority*/);
extern void gset_scissor_mode(
    Gscissor_mode scissor_mode/* scissor mode */);
extern void gset_norm_tran_num(
    Gint      tran_num /* transformation number*/);
extern void gsel_norm_tran(
    Gint      tran_num /* transformation number*/);
/* NDC picture functions*/
extern void gdel_prims_ndc_pic(
    const Gsel_crit *sel_crit /* selection criterion*/);
extern void gadd_set_names_ndc_pic(
    const Gnameset *set_names, /* set of names*/
    const Gsel_crit *sel_crit /* selection criterion*/);
extern void gremove_set_names_ndc_pic(
    const Gnameset *set_names, /* set of names*/
    const Gsel_crit *sel_crit /* selection criterion*/);
extern void gset_ndc_pic_prim_attr(
    const Gsel_crit *sel_crit, /* selection criterion*/
    const Gprim_attr_value *attr_value/* attr_value */);
extern void gadd_set_scissors_ndc_pic(
    const Gscissor_list *set_scissors,/* scissor set*/
    const Gsel_crit *sel_crit /* selection criterion*/);
extern void gremove_set_scissors_ndc_pic(
    const Gint_list *scissor_ids,/* scissor identifiers*/
    const Gsel_crit *sel_crit /* selection criterion*/);
extern void greorder_ndc_pic(
    const Gsel_crit *source_sel_crit,/* source selection criterion*/
    const Gsel_crit *ref_sel_crit,/* reference selection criterion*/
    Grel_pos  rel_pos /* relative position*/);
/* Metafile functions*/
extern void gcopy_ndc_pic_ndc_mf(
    const void *mf_specif, /* metafile specifier*/
    Gint      pic_id, /* picture identifier*/
    const Gsel_crit *sel_crit, /* selection criterion*/
    const Gnameset *set_names /* set of names*/);
extern void gcopy_ndc_mf_pic_ndc_pic(
    const void *mf_specif, /* metafile specifier*/
    Gint      pic_id, /* picture identifier*/
    const Gnameset *set_names /* set of names*/);
/* Picture part store functions*/
extern void gopen_pic_part(
    Gint      pic_part_name /* picture part name*/);
extern void gclose_pic_part(
    void );
extern void gar_pic_part(

```



```

Gint      pic_part_name,      /* picture part name*/
const void *ar_specif, /* archive specifier*/
Gint      ar_name_pic_part /* archive name of picture part*/);
extern void gret_pic_part_ar(
const void *ar_specif, /* archive specifier*/
Gint      ar_name_pic_part, /* archive name of picture part*/
Gint      pic_part_name /* picture part name*/);
extern void greopen_pic_part(
Gint      pic_part_name /* picture part name*/);
extern void gappend_pic_part(
Gint      source_pic_part_name, /* source
picture part name*/
Gint      sink_pic_part_name, /* sink
picture part name*/
const Gtran_matrix global_tran_matrix, /* global
transformation matrix*/
Gtran_mode global_tran_mode, /* global
transformation mode*/
const Gtran_matrix local_tran_matrix, /* local
transformation matrix*/
Gtran_mode local_tran_mode, /* local
transformation mode*/
const Gnameset *set_names /* set of names*/);
extern void grename_pic_part(
Gint      old_pic_part_name, /* old picture part name*/
Gint      new_pic_part_name /* new picture part name*/);
extern void gdel_pic_part(
Gint      pic_part_name /* picture part name*/);
extern void gcopy_pic_part_pic_part_store(
Gint      pic_part_name, /* picture part name*/
const Gsel_crit *sel_crit, /* selection criterion*/
const Gtran_matrix global_tran_matrix, /* global
transformation matrix*/
Gtran_mode global_tran_mode, /* global
transformation mode*/
const Gtran_matrix local_tran_matrix, /* local
transformation matrix*/
Gtran_mode local_tran_mode, /* local
transformation mode*/
const Gnameset *set_names, /* set of names*/
Gscissor_sel scissor_sel /* scissor select*/);
extern void gcopy_ndc_pic_part_store(
const Gsel_crit *sel_crit, /* sel. criterion*/
Gint      pic_part_name, /* picture part name*/
const Gnameset *set_names /* set of names*/);
/* Input functions*/
extern void gset_in_dev_mode(
const Gdev_id *dev_id, /* input device number*/
Gop_mode op_mode /* operating mode*/);
extern void gset_loc_mode(
Gint      ws_id, /* workstation identifier*/
Gint      loc_num, /* locator device number*/

```

```

    Gop_mode   op_mode,      /* operating mode*/
    Gecho_switch echo_switch /* echo switch*/);
extern void gset_stroke_mode(
    Gint      ws_id,        /* workstation identifier*/
    Gint      stroke_num,   /* stroke device number*/
    Gop_mode   op_mode,      /* operating mode*/
    Gecho_switch echo_switch /* echo switch*/);
extern void gset_val_mode(
    Gint      ws_id,        /* workstation identifier*/
    Gint      val_num,      /* valuator device number*/
    Gop_mode   op_mode,      /* operating mode*/
    Gecho_switch echo_switch /* echo switch*/);
extern void gset_choice_mode(
    Gint      ws_id,        /* workstation identifier*/
    Gint      choice_num,   /* choice device number*/
    Gop_mode   op_mode,      /* operating mode*/
    Gecho_switch echo_switch /* echo switch*/);
extern void gset_pick_mode(
    Gint      ws_id,        /* workstation identifier*/
    Gint      pick_num,     /* pick device number*/
    Gop_mode   op_mode,      /* operating mode*/
    Gecho_switch echo_switch /* echo switch*/);
extern void gset_string_mode(
    Gint      ws_id,        /* workstation identifier*/
    Gint      string_num,   /* string device number*/
    Gop_mode   op_mode,      /* operating mode*/
    Gecho_switch echo_switch /* echo switch*/);
extern void greg_in(
    const Gdev_id *dev_id,  /* input device number*/
    Gin_status *in_status,  /* OUT input status*/
    Gin_value *log_in_value /* OUT logical input value*/);
extern void greg_loc(
    Gint      ws_id,        /* workstation identifier*/
    Gint      loc_num,      /* locator device number*/
    Gin_status *in_status,  /* OUT input status*/
    Gint      *norm_tran_num, /* OUT normalization
                               transformation number*/
    Gpoint    *loc_pos     /* OUT locator position*/);
extern void greg_stroke(
    Gint      ws_id,        /* workstation identifier*/
    Gint      stroke_num,   /* stroke device number*/
    Gin_status *in_status,  /* OUT input status*/
    Gint      *norm_tran_num, /* OUT normalization
                               transformation number*/
    Gpoint_list *stroke     /* OUT stroke*/);
extern void greg_val(
    Gint      ws_id,        /* workstation identifier*/
    Gint      val_num,      /* valuator device number*/
    Gin_status *in_status,  /* OUT input status*/
    Gfloat    *value       /* OUT value*/);
extern void greg_choice(
    Gint      ws_id,        /* workstation identifier*/

```

```

    Gint      choice_num, /* choice device number*/
    Gin_status *in_status, /* OUT input status*/
    Gint      *choice      /* OUT requested choice*/);
extern void greg_pick(
    Gint      ws_id,      /* workstation identifier*/
    Gint      pick_num,   /* pick device number*/
    Gin_status *in_status, /* OUT input status*/
    Gpick     *pick /* OUT requested pick value*/);
extern void greg_string(
    Gint      ws_id,      /* workstation identifier*/
    Gint      string_num, /* string device number*/
    Gin_status *in_status, /* OUT input status*/
    char      *string     /* OUT requested string*/);
extern void gsampl_in(
    const Gdev_id *dev_id, /* input device number*/
    Gin_value     *log_in_value /* OUT logical input value*/);
extern void gsampl_loc(
    Gint      ws_id,      /* workstation identifier*/
    Gint      loc_num,    /* locator device number*/
    Gint      *norm_tran_num, /* OUT normalization
                               transformation number*/
    Gpoint     *loc_pos   /* OUT locator position*/);
extern void gsampl_stroke(
    Gint      ws_id,      /* workstation identifier*/
    Gint      stroke_num, /* stroke device number*/
    Gint      *norm_tran_num, /* OUT normalization
                               transformation number*/
    Gpoint_list *stroke   /* OUT stroke*/);
extern void gsampl_val(
    Gint      ws_id,      /* workstation identifier*/
    Gint      val_num,    /* valuator device number*/
    Gfloat     *value     /* OUT value*/);
extern void gsampl_choice(
    Gint      ws_id,      /* workstation identifier*/
    Gint      choice_num, /* choice device number*/
    Gin_status *in_status, /* OUT input status*/
    Gint      *choice     /* OUT choice*/);
extern void gsampl_pick(
    Gint      ws_id,      /* workstation identifier*/
    Gint      pick_num,   /* pick device number*/
    Gin_status *in_status, /* OUT input status*/
    Gpick     *pick /* OUT pick value*/);
extern void gsampl_string(
    Gint      ws_id,      /* workstation identifier*/
    Gint      string_num, /* string device number*/
    char      *string     /* OUT string*/);
extern void gawait_in(
    Gfloat     timeout,    /* timeout (seconds)*/
    Gstore     store,      /* handle to Store object*/
    Gdev_id_in_value_list **dev_id_in_values /* OUT logical
                                               input devices and
                                               logical input value*/);

```

```

extern void gawait_event(
    Gfloat      timeout,      /* timeout (seconds)*/
    Gint        *ws_id,      /* OUT workstation identifier*/
    Gin_class   *class,      /* OUT device class*/
    Gint        *in_num      /* OUT logical input device number*/);

extern void gget_loc(
    Gint        *norm_tran_num, /* OUT normalization
                                transformation number*/
    Gpoint      *loc_pos      /* OUT locator position*/);

extern void gget_stroke(
    Gint        *norm_tran_num, /* OUT normalization
                                transformation number*/
    Gpoint_list *stroke      /* OUT stroke*/);

extern void gget_val(
    Gfloat      *value      /* OUT value*/);

extern void gget_choice(
    Gin_status  *in_status, /* OUT input status*/
    Gint        *choice     /* OUT choice*/);

extern void gget_pick(
    Gin_status  *in_status, /* OUT input status*/
    Gpick       *pick      /* OUT pick value*/);

extern void gget_string(
    char        *string     /* OUT string*/);

extern void gflush_dev_events(
    Gdev_id     *dev_id     /* device identifier*/);

extern void gset_font_ind_map(
    const Gfont_ind_map *font_ind_map/* font index mapping*/);

extern void gget_glyph_name(
    Gint        font_ind,    /* font index */
    char        char_code,   /* character code*/
    Gint        *glyph_name /* OUT glyph name*/);

extern void gset_char_code(
    Gint        font_ind,    /* font index */
    char        char_code,   /* character code*/
    Gint        glyph_name  /* glyph name*/);

/* Audit and playback functions */

extern void gaudit(
    Gint        audit_id,    /* audit identifier*/
    const Gaudit_op *audit_op /* audit operation*/);

extern void gwrite_user_rec_audit(
    Gint        audit_id,    /* audit identifier*/
    const Gaudit_user_data *user_data/* user data record*/);

extern void gplayback(
    Gint        audit_id,    /* audit identifier*/
    const Gplayback_op *playback_op/* playback operation*/);

extern void gread_item_func_name_audit(
    Gint        audit_id,    /* audit identifier*/
    Gint        *func_name  /* OUT function name*/);

extern void gread_item_audit(
    Gint        audit_id,    /* audit identifier*/
    Gstore      store,      /* handle to Store object*/
    Gfunc_params **func_params/* OUT function parameters*/);

```

```

extern void gproc_audit_item(
    Gint      audit_id, /* audit identifier*/
    Gproc_op  proc_op  /* process operation*/);
extern void ginq_op_st_entry(
    Gop_st_name  op_st_name, /* entry name*/
    Gint         *err_ind,   /* OUT error indicator*/
    Gop_st_entry *op_st_entry/* OUT operating state */);
extern void ginq_gks_dt_entry(
    Ggks_dt_name  gks_dt_name, /* entry name*/
    Gstore        store,       /* handle to Store object*/
    Gint         *err_ind,   /* OUT error indicator*/
    Ggks_dt_entry **gks_dt   /* OUT GKS
                               description table entry*/);
extern void ginq_list_avail_ws_types(
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind,  /* OUT error indicator*/
    Gint_list *ws_gen_types, /* OUT list of available generic
                               ws types */
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_list_avail_fonts(
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind,  /* OUT error indicator*/
    Gint_list *fonts,    /* OUT list of available fonts */
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_def_font_ind_map(
    Gint      *err_ind, /* OUT error indicator*/
    Gfont_ind_map *font_ind_map/* OUT font index mapping*/);
extern void ginq_gks_sl_entry(
    Ggks_sl_name  gks_sl_name, /* entry name*/
    Gstore        store,       /* handle to Store object*/
    Gint         *err_ind,   /* OUT error indicator*/
    Ggks_sl_entry **gks_sl_entry/* OUT GKS state
                               list */);
extern void ginq_route_dir(
    Gint      *err_ind, /* OUT error indicator*/
    Groute_dir *route_dir /* OUT current route direction*/);
extern void ginq_scissor_mode(
    Gint      *err_ind, /* OUT error indicator*/
    Gscissor_mode *scissor_mode/* OUT current scissor mode*/);
extern void ginq_set_open_wss(
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind,  /* OUT error indicator*/
    Gint_list *open_ws,  /* OUT list of open ws ids*/
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_set_active_wss(
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind,  /* OUT error indicator*/
    Gint_list *active_ws, /* OUT list of active ws ids*/

```

```

    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_set_open_audits(
    Gint      num_elems_appl_list/* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gopen_audit_list *open_audit_set/* OUT set of open audits*/
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_set_open_playbacks(
    Gint      num_elems_appl_list/* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gint_list *open_playbacks, /* OUT set of open playbacks*/
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_in_queue(
    Gstore     store, /* handle to Store object*/
    Gint      *err_ind, /* OUT error indicator*/
    Gin_queue  **in_queue /* OUT input queue */);
extern void ginq_font_ind_map(
    Gint      *err_ind, /* OUT error indicator*/
    Gfont_ind_map *font_ind_map/* OUT font index mapping*/);
extern void ginq_cur_pick_id(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *pick_id /* OUT current pick identifier*/);
extern void ginq_nameset(
    Gstore     store, /* handle to Store object*/
    Gint      *err_ind, /* OUT error indicator*/
    Gnameset   **nameset /* nameset */);
extern void ginq_scissor_set(
    Gstore     store, /* handle to Store object*/
    Gint      *err_ind, /* OUT error indicator*/
    Gscissor_list **scissor_set/* scissor */);
extern void ginq_global_tran_matrix(
    Gtran_matrix global_tran_matrix/* global transformation
    matrix */);
extern void ginq_local_tran_matrix(
    Gtran_matrix local_tran_matrix/* local transformation
    matrix */);
extern void ginq_pat_size(
    Gint      *err_ind, /* OUT error indicator*/
    Gfloat_size *pat_size /* OUT current pattern size*/);
extern void ginq_pat_ref_point(
    Gint      *err_ind, /* OUT error indicator*/
    Gpoint     *pat_ref_point /* OUT current pattern reference point*/);
extern void ginq_char_ht(
    Gint      *err_ind, /* OUT error indicator*/
    Gfloat     *char_ht /* OUT current character height*/);
extern void ginq_char_up_vec(
    Gint      *err_ind, /* OUT error indicator*/
    Gvec       *char_up_vec /* OUT current character up vector*/);
extern void ginq_text_skew_angle(
    Gint      *err_ind, /* OUT error indicator*/
    Gfloat     *text_skew_angle /* OUT current text skew angle*/);

```

```

extern void ginq_text_path(
    Gint      *err_ind, /* OUT error indicator*/
    Gtext_path *text_path /* OUT current text path*/);
extern void ginq_text_align(
    Gint      *err_ind, /* OUT error indicator*/
    Gtext_align *text_align /* OUT current text alignment*/);
extern void ginq_line_ind(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *line_ind /* OUT current line index*/);
extern void ginq_linetype(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *linetype /* OUT current linetype*/);
extern void ginq_linewidth(
    Gint      *err_ind, /* OUT error indicator*/
    Gfloat     *linewidth /* OUT current linewidth scale factor*/);
extern void ginq_line_colr_specif(
    Gint      *err_ind, /* OUT error indicator*/
    Gcolr_specif *line_colr_specif /* OUT current line colour specifier*/);
extern void ginq_line_colr_ind(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *line_colr_ind /* OUT line colour index*/);
extern void ginq_marker_ind(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *marker_ind /* OUT current marker index*/);
extern void ginq_marker_type(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *marker_type /* OUT current marker type*/);
extern void ginq_marker_size(
    Gint      *err_ind, /* OUT error indicator*/
    Gfloat     *marker_size /* OUT current marker size scale factor*/);
extern void ginq_marker_colr_specif(
    Gint      *err_ind, /* OUT error indicator*/
    Gcolr_specif *marker_colr_specif /* OUT current marker
                                     colour specifier*/);
extern void ginq_marker_colr_ind(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *marker_colr_ind /* OUT marker colour index*/);
extern void ginq_area_ind(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *area_ind /* OUT current area index*/);
extern void ginq_int_style(
    Gint      *err_ind, /* OUT error indicator*/
    Gint_style *int_style /* OUT current interior style*/);
extern void ginq_int_style_ind(
    Gint      *err_ind, /* OUT error indicator*/
    Gint      *int_style_ind /* OUT current interior style index*/);
extern void ginq_int_colr_specif(
    Gint      *err_ind, /* OUT error indicator*/
    Gcolr_specif *int_colr_specif /* OUT current interior
                                     colour specifier*/);
extern void ginq_int_colr_ind(
    Gint      *err_ind, /* OUT error indicator*/

```



```

    Gint      *int_colr_ind      /* OUT interior colour index*/);
extern void ginq_edge_flag(
    Gint      *err_ind,         /* OUT error indicator*/
    Gedge_flag *edge_flag /* OUT current edge flag*/);
extern void ginq_edgetype(
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      *edgetype /* OUT current edgetype*/);
extern void ginq_edgewidth(
    Gint      *err_ind,         /* OUT error indicator*/
    Gfloat    *edgewidth /* OUT current edgewidth scale factor*/);
extern void ginq_edge_colr_specif(
    Gint      *err_ind,         /* OUT error indicator*/
    Gcolr_specif *edge_colr_specif/* OUT current edge colour specifier*/);
extern void ginq_edge_colr_ind(
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      *edge_colr_ind /* OUT edge colour index*/);
extern void ginq_text_ind(
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      *text_ind /* OUT current text index*/);
extern void ginq_text_font_prec(
    Gint      *err_ind,         /* OUT error indicator*/
    Gtext_font_prec *font_prec /* OUT current text font and precision */);
extern void ginq_char_expan(
    Gint      *err_ind,         /* OUT error indicator*/
    Gfloat    *char_expan /* OUT current character expansion factor*/);
extern void ginq_char_space(
    Gint      *err_ind,         /* OUT error indicator*/
    Gfloat    *char_space /* OUT current character spacing*/);
extern void ginq_text_colr_specif(
    Gint      *err_ind,         /* OUT error indicator*/
    Gcolr_specif *text_colr_specif/* OUT current text colour specifier*/);
extern void ginq_text_colr_ind(
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      *text_colr_ind /* OUT text colour index*/);
extern void ginq_asfs(
    Gint      *err_ind,         /* OUT error indicator*/
    Gasfs     *asfs /* OUT current attribute source flags */);
extern void ginq_cur_norm_tran_num(
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      *norm_tran_num /* OUT current normalization
                                transformation number*/);
extern void ginq_list_norm_trans(
    Gint      *err_ind,         /* OUT error indicator*/
    Gtran     norm_tran[64] /* OUT list of normalization
                                transformations */);
extern void ginq_norm_tran(
    Gint      num, /* normalization transformation number*/
    Gint      *err_ind, /* OUT error indicator*/
    Gtran     *norm_tran /* OUT normalization transformation*/);
extern void ginq_list_vp_in_pris(
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      vp_in_pri[64] /* OUT list of viewport input

```



```

        priorities*/);
extern void ginq_name_open_pic_part(
    Gint    *err_ind, /* OUT error indicator*/
    Gint    *name_open_pic_part/* OUT name of open picture
        part */);
extern void ginq_set_pic_part_names(
    Gint    num_elems_appl_list,/* length of application list*/
    Gint    start_ind, /* starting index*/
    Gint    *err_ind, /* OUT error indicator*/
    Gint_list *pic_part_names, /* OUT list of picture part names*/
    Gint    *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_name_open_seg(
    Gint    *err_ind, /* OUT error indicator*/
    Gint    *name_open_seg /* OUT name of open segment*/);
extern void ginq_set_seg_names(
    Gint    num_elems_appl_list,/* length of application list*/
    Gint    start_ind, /* starting index*/
    Gint    *err_ind, /* OUT error indicator*/
    Gint_list *seg_names, /* OUT list of segment names*/
    Gint    *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_seg_attrs(
    Gint    seg_name, /* segment name*/
    Gint    *err_ind, /* OUT error indicator*/
    Gseg_attrs *seg_attrs /* OUT segment attributes */);
extern void ginq_set_assoc_wss(
    Gint    seg_name, /* segment name*/
    Gint    num_elems_appl_list,/* length of application list*/
    Gint    start_ind, /* starting index*/
    Gint    *err_ind, /* OUT error indicator*/
    Gint_list *assoc_wss, /* OUT list of
        associated workstations*/
    Gint    *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_name_open_stencil(
    Gint    *err_ind, /* OUT error indicator*/
    Gint    *name_open_stencil/* OUT name of open stencil*/);
extern void ginq_set_stencil_names(
    Gint    num_elems_appl_list,/* length of application list*/
    Gint    start_ind, /* starting index*/
    Gint    *err_ind, /* OUT error indicator*/
    Gint_list *stencil_names, /* OUT list of stencil names*/
    Gint    *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_stencil_attrs(
    Gint    stencil_name, /* stencil name*/
    Gint    *err_ind, /* OUT error indicator*/
    Gstencil_attrs *stencil_attrs/* OUT stencil attributes */);
extern void ginq_cur_cont_attrs(
    Gint    *err_ind, /* OUT error indicator*/
    Gcont_attrs *cont_attrs /* OUT contour attributes */);
extern void ginq_name_open_tiling(
    Gint    *err_ind, /* OUT error indicator*/
    Gint    *name_open_tiling /* OUT name of open tiling*/);
extern void ginq_set_tiling_names(

```

```

Gint      num_elems_appl_list, /* length of application list*/
Gint      start_ind, /* starting index*/
Gint      *err_ind, /* OUT error indicator*/
Gint_list *tiling_names, /* OUT list of tiling names*/
Gint      *num_elems_impl_list /* OUT length of impl. list */);
extern void ginq_in_overf(
Gint      *err_ind, /* OUT error indicator*/
Gint      *ws_id, /* OUT workstation identifier*/
Gin_class *meas_class, /* OUT measure class*/
Gint      *in_num /* OUT logical input device number*/);
/* Utility functions*/
/* GKS Utilities*/
extern void geval_tran_matrix(
const Gpoint *point, /* fixed point*/
const Gvec *shift, /* shift vector*/
Gfloat angle, /* rotation angle*/
const Gvec *scale, /* scale factors*/
Gcoord_switch coord_switch, /* coordinate switch*/
Gtran_matrix tran_matrix /* OUT transformation matrix*/);
extern void gaccum_tran_matrix(
const Gtran_matrix matrix, /* transformation matrix*/
const Gpoint *point, /* fixed point*/
const Gvec *shift, /* shift vector*/
Gfloat angle, /* rotation angle*/
const Gvec *scale, /* scale factors*/
Gcoord_switch coord_switch, /* coordinate switch*/
Gtran_matrix tran_matrix /* OUT transformation matrix*/);
extern void geval_circle(
const Gpoint *circ_ctr, /* circle centre*/
Gfloat radius, /* radius*/
Gconic_matrix circle /* OUT circle*/);
extern void geval_ell(
const Gpoint *ell_ctr, /* ellipse centre*/
const Gpoint conj_radius_end_point[2], /* conjugate
radius end points*/
Gconic_matrix ell /* OUT ellipse*/);
extern void geval_circ_arc_3_point(
const Gpoint circ_point[3], /* 3 circle points
(start, intermediate, end)*/
Gconic_sec *circ_arc /* OUT circular arc*/);
extern void geval_circ_arc_ctr(
const Gpoint *circ_ctr, /* circle centre*/
const Gvec vec[2], /* start and end vector*/
Gsense_flag sense_flag, /* sense flag*/
Gfloat radius, /* radius*/
Gconic_sec *circ_arc /* OUT circular arc*/);
extern void geval_ell_arc(
const Gpoint *ell_ctr, /* ellipse centre*/
const Gpoint conj_radius_end_point[2], /* conjugate
radius end points*/
const Gvec vec[2], /* start and end vector*/
Gconic_sec *ell_arc /* OUT elliptic arc*/);

```

```

extern void geval_hyp_arc(
    const Gpoint      *tran_radius_end_point, /* transverse
                                                radius end point*/
    const Gpoint      *hyp_ctr, /* hyperbola centre*/
    const Gpoint      *conj_radius_end_point, /* conjugate
                                                radius end point*/
    const Gvec vec[2], /* start and end vector*/
    Gconic_sec *hyp_arc /* OUT hyperbolic arc*/);
extern void geval_par_arc(
    const Gpoint      *start_point, /* start point*/
    const Gpoint      *intersec_point, /* tangential
                                        intersection point*/
    const Gpoint      *end_point, /* end point*/
    Gconic_sec *par_arc /* OUT parabolic arc*/);
extern void geval_wc_ord(
    Gfloat      wc_ord, /* WC ordinate*/
    Gord_sel    ord_sel, /* ordinate selector */
    Gfloat      *ndc_value /* OUT NDC value */);
extern void gset_err_hand(
    const void (*new_hand)(Gint , Gint , const char *),
    /* the application's error handling address */
    void (*old_hand)(Gint , Gint , const char *)
    /* OUT address of the error handling replaced */);
extern void gcreate_store(
    Gint      *err_ind, /* OUT error indicator*/
    Gstore     *store /* OUT handle to Store object*/);
extern void gdel_store(
    Gint      *err_ind, /* OUT error indicator*/
    Gstore     *store /* IN/OUT storage to be deleted*/);
/* Workstation functions*/
/* Control functions*/
extern void gopen_ws(
    Gint      ws_id, /* workstation identifier*/
    const void *ws_specif_info, /* workstation specifier
                                and specific information*/
    Gint      ws_gen_type /* generic workstation type*/);
extern void gclose_ws(
    Gint      ws_id /* workstation identifier*/);
extern void gsave_ws_sl(
    Gint      ws_id, /* workstation identifier*/
    const Gws_sl_name_list *entry_names, /* list of entry
                                        names */
    Gstore     store, /* handle to Store object*/
    Gws_sl_entry_list **entry_list /* OUT list of
                                entry values*/);
extern void grestore_ws_sl(
    Gint      ws_id, /* workstation identifier*/
    const Gws_sl_entry_list *entries /* list of entries*/);
extern void gget_ws_status(
    Gint      ws_id, /* workstation identifier*/
    Gws_status *ws_status /* OUT workstation status*/);
extern void gremove_backdrop(

```

```

    Gint      ws_id /* workstation identifier*/);
extern void gset_rep(
    Gint      ws_id, /* workstation identifier*/
    const Grep *rep_value /* representation value */);
extern void gset_line_rep(
    Gint      ws_id, /* workstation identifier*/
    Gint      line_ind, /* line index*/
    const Gline_bundle *line_bundle/* line representation */);
extern void gset_marker_rep(
    Gint      ws_id, /* workstation identifier*/
    Gint      marker_ind, /* marker index*/
    const Gmarker_bundle *marker_bundle/* marker representation */);
extern void gset_text_rep(
    Gint      ws_id, /* workstation identifier*/
    Gint      text_ind, /* text index*/
    const Gtext_bundle *text_bundle/* text representation */);
extern void gset_area_rep(
    Gint      ws_id, /* workstation identifier*/
    Gint      area_ind, /* area index*/
    const Gareal_bundle *area_bundle/* area representation */);
extern void gset_pat_rep(
    Gint      ws_id, /* workstation identifier*/
    Gint      pat_ind, /* pattern index*/
    const Gpat_rep *pat_rep /* pattern representation */);
extern void gset_colr_rep(
    Gint      ws_id, /* workstation identifier*/
    Gint      colr_ind, /* colour index*/
    const Gcolr_rep *colr_rep /* colour representation */);
extern void gset_view_pri(
    Gint      ws_id, /* workstation identifier*/
    Gint      view_ind, /* view index*/
    Gint      ref_view_ind, /* reference view index*/
    Grel_pri rel_pri /* relative priority*/);
extern void gset_view_sel_crit(
    Gint      ws_id, /* workstation identifier*/
    Gint      view_ind, /* view index*/
    const Gsel_crit *sel_crit /* selection criterion*/);
extern void gset_view(
    Gint      ws_id, /* workstation identifier*/
    Gint      view_ind, /* view index*/
    const Gtran_matrix ori_matrix, /* view orientation matrix*/
    const Gtran_matrix map_matrix, /* view mapping matrix*/
    const Gscissor *scissor /* view scissor*/);
extern void gset_ws_vis_effects(
    Gint      ws_id, /* workstation identifier*/
    Gvis_effects_st vis_effects_st/* visual effects state*/);
extern void gset_ws_win_vp(
    Gint      ws_id, /* workstation identifier*/
    const Gtran *ws_win_vp /* workstation window
                           and viewport limits*/);
extern void gset_ws_win(
    Gint      ws_id, /* workstation identifier*/

```

```

    const Glimit      *ws_win      /* workstation window */);
extern void gset_ws_vp(
    Gint      ws_id,      /* workstation identifier*/
    const Glimit      *ws_vp      /* workstation viewport limits*/);
extern void gdef_in_dev(
    const Gdev_id      *dev_id,      /* device identifier*/
    const Gint_list      *meas_seq, /* measure sequence*/
    const Gint_list      *trigger_set,/* trigger set*/
    const Ginit_value      *init_value/* initial value*/);
extern void ginit_in_dev(
    const Gdev_id      *dev_id,      /* device identifier*/
    const Ginit_value      *init_value/* initial value*/);
extern void ginit_loc(
    Gint      ws_id,      /* workstation identifier*/
    Gint      loc_num,      /* locator device number*/
    Gint      init_norm_tran_num,/* initial normalization
                                transformation number*/
    const Gpoint      *init_loc_pos,/* initial locator position*/
    Gint      pet, /* prompt and echo type*/
    const Glimit      *echo_area, /* echo area*/
    const Gloc_data      *loc_data /* locator data record*/);
extern void ginit_stroke(
    Gint      ws_id,      /* workstation identifier*/
    Gint      stroke_num, /* stroke device number*/
    Gint      init_norm_tran_num,/* initial normalization
                                transformation number*/
    const Gpoint_list      *init_stroke,/* initial stroke*/
    Gint      pet, /* prompt and echo type*/
    const Glimit      *echo_area, /* echo area*/
    const Gstroke_data      *stroke_data/* stroke data record*/);
extern void ginit_val(
    Gint      ws_id,      /* workstation identifier*/
    Gint      val_num,      /* valuator device number*/
    Gfloat      init_value, /* initial value*/
    Gint      pet, /* prompt and echo type*/
    const Glimit      *echo_area, /* echo area*/
    const Gval_data      *val_data /* valuator data record*/);
extern void ginit_choice(
    Gint      ws_id,      /* workstation identifier*/
    Gint      choice_num, /* choice device number*/
    Gint_status      init_status, /* initial status*/
    Gint      init_choice, /* initial choice*/
    Gint      pet, /* prompt and echo type*/
    const Glimit      *echo_area, /* echo area*/
    const Gchoice_data      *choice_data/* choice data record*/);
extern void ginit_pick(
    Gint      ws_id,      /* workstation identifier*/
    Gint      pick_num, /* pick device number*/
    Gint_status      init_status, /* initial status*/
    const Gpick      *init_pick, /* initial pick value */
    Gint      pet, /* prompt and echo type*/
    const Glimit      *echo_area, /* echo area*/

```

```

    const Gpick_data *pick_data /* pick data record*/);
extern void ginit_string(
    Gint      ws_id, /* workstation identifier*/
    Gint      string_num, /* string device number*/
    const char *init_string, /* initial string*/
    Gint      pet, /* prompt and echo type*/
    const Glimit *echo_area, /* echo area*/
    const Gstring_data *string_data/* string data record*/);
extern void gset_ws_sel_crit(
    Gint      ws_id, /* workstation identifier*/
    const Gsel *sel /* selection type and criterion*/);
extern void gcopy_real_pic_real_mf(
    Gint      ws_id, /* workstation identifier*/
    const void *mf_specif, /* metafile specifier*/
    Gint      pic_id /* picture identifier*/);
extern void gcopy_blank_real_pic_real_mf(
    Gint      ws_id, /* workstation identifier*/
    const void *mf_specif, /* metafile specifier*/
    Gint      pic_id /* picture identifier*/);
extern void gcopy_real_mf_pic_backdrop(
    Gint      ws_id, /* workstation identifier*/
    const void *mf_specif, /* metafile specifier*/
    Gint      pic_id /* picture identifier*/);
extern void gmessage(
    Gint      ws_id, /* workstation identifier*/
    const char *message /* message string*/);
/* Inquiry functions*/
extern void ginq_ws_sl_entry(
    Gint      ws_id, /* workstation identifier*/
    Gws_sl_name name, /* entry name*/
    Ginq_type type, /* type of returned values*/
    Gstore     store, /* handle to Store object*/
    Gint      *err_ind, /* OUT error indicator*/
    Gws_sl_entry **ws_sl_entry/* OUT workstation
                                state list entry*/);
extern void ginq_ws_conn_type(
    Gint      ws_id, /* workstation identifier*/
    Gstore     store, /* handle to Store object*/
    Gint      *err_ind, /* OUT error indicator*/
    void      **conn_id, /* OUT connection identifier*/
    Gint      *ws_type /* OUT workstation type*/);
extern void ginq_ws_st(
    Gint      ws_id, /* workstation identifier*/
    Gint      *err_ind, /* OUT error indicator*/
    Gws_st     *ws_st /* OUT workstation state*/);
extern void ginq_list_line_inds(
    Gint      ws_id, /* workstation identifier*/
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gint_list *def_line_inds, /* OUT list of defined
                                line indices*/

```

```

    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_line_rep(
    Gint      ws_id,      /* workstation identifier*/
    Gint      line_ind,   /* line index*/
    Ginq_type type, /* type of returned values*/
    Gint      *err_ind,   /* OUT error indicator*/
    Gline_bundle *line_rep /* OUT line representation*/);
extern void ginq_list_marker_inds(
    Gint      ws_id,      /* workstation identifier*/
    Gint      num_elems_appl_list,/* length of application list*/
    Gint      start_ind,  /* starting index*/
    Gint      *err_ind,   /* OUT error indicator*/
    Gint_list *def_marker_inds, /* OUT list of defined
                                marker indices*/
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_marker_rep(
    Gint      ws_id,      /* workstation identifier*/
    Gint      marker_ind, /* marker index*/
    Ginq_type type, /* type of returned values*/
    Gint      *err_ind,   /* OUT error indicator*/
    Gmarker_bundle *marker_rep /* OUT marker representation*/);
extern void ginq_list_text_inds(
    Gint      ws_id,      /* workstation identifier*/
    Gint      num_elems_appl_list,/* length of application list*/
    Gint      start_ind,  /* starting index*/
    Gint      *err_ind,   /* OUT error indicator*/
    Gint_list *def_text_inds, /* OUT list of defined
                                text indices*/
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_text_rep(
    Gint      ws_id,      /* workstation identifier*/
    Gint      text_ind,   /* text index*/
    Ginq_type type, /* type of returned values*/
    Gint      *err_ind,   /* OUT error indicator*/
    Gtext_bundle *text_rep /* OUT text representation*/);
extern void ginq_list_area_inds(
    Gint      ws_id,      /* workstation identifier*/
    Gint      num_elems_appl_list,/* length of application list*/
    Gint      start_ind,  /* starting index*/
    Gint      *err_ind,   /* OUT error indicator*/
    Gint_list *def_area_inds, /* OUT list of defined
                                area indices*/
    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_area_rep(
    Gint      ws_id,      /* workstation identifier*/
    Gint      area_ind,   /* area index*/
    Ginq_type type, /* type of returned values*/
    Gint      *err_ind,   /* OUT error indicator*/
    Gareap_bundle *area_rep /* OUT area representation*/);
extern void ginq_list_pat_inds(
    Gint      ws_id,      /* workstation identifier*/
    Gint      num_elems_appl_list,/* length of application list*/

```



```

Gint      start_ind, /* starting index*/
Gint      *err_ind,  /* OUT error indicator*/
Gint_list *def_pat_inds, /* OUT list of defined
                        pattern indices*/
Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_pat_rep(
Gint      ws_id,      /* workstation identifier*/
Gint      pat_ind,    /* pattern index*/
Ginq_type type, /* type of returned values*/
Gstore    store,      /* handle to Store object*/
Gint      *err_ind,    /* OUT error indicator*/
Gpat_rep  **pat_rep /* OUT pattern representation*/);
extern void ginq_list_colr_inds(
Gint      ws_id,      /* workstation identifier*/
Gint      num_elems_appl_list, /* length of application list*/
Gint      start_ind, /* starting index*/
Gint      *err_ind,    /* OUT error indicator*/
Gint_list *def_colr_inds, /* OUT list of defined
                        colour indices*/
Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_colr_rep(
Gint      ws_id,      /* workstation identifier*/
Gint      colr_ind,   /* colour index*/
Ginq_type type, /* type of returned values*/
Gint      *err_ind,    /* OUT error indicator*/
Gcolr_rep *colr_rep /* OUT colour representation*/);
extern void ginq_ws_win_vp(
Gint      ws_id,      /* workstation identifier*/
Gint      *err_ind,    /* OUT error indicator*/
Gtran     *ws_win_vp /* OUT workstation window
                        and viewport*/);
extern void ginq_vis_effects_st(
Gint      ws_id,      /* workstation identifier*/
Gint      *err_ind,    /* OUT error indicator*/
Gvis_effects_st *vis_effects_st/* OUT visual effects state*/);
extern void ginq_sel_table(
Gint      ws_id,      /* workstation identifier*/
Gstore    store,      /* handle to Store object*/
Gint      *err_ind,    /* OUT error indicator*/
Gsel_table **sel_table /* OUT table of selection criteria*/);
extern void ginq_set_seg_names_ws(
Gint      ws_id,      /* workstation identifier*/
Gint      num_elems_appl_list, /* length of application list*/
Gint      start_ind, /* starting index*/
Gint      *err_ind,    /* OUT error indicator*/
Gint_list *seg_names, /* OUT list of segment names*/
Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_in_dev_op_modes_init_values(
Gint      ws_id,      /* workstation identifier*/
Gstore    store,      /* handle to Store object*/
Gint      *err_ind,    /* OUT error indicator*/
Gop_modes_init_values **op_modes_init_values/* OUT table of

```



```

        input device
        operating modes and
        initial values*/);

extern void ginq_view_rep(
    Gint    ws_id,      /* workstation identifier*/
    Gint    view_ind,   /* view index*/
    Ginq_type type, /* type of returned values*/
    Gstore  store,      /* handle to Store object*/
    Gint    *err_ind,   /* OUT error indicator*/
    Gview_rep **view_rep /* OUT view representation*/);

extern void ginq_view_pri(
    Gint    ws_id,      /* workstation identifier*/
    Ginq_type type, /* type of returned values*/
    Gint    *err_ind,   /* OUT error indicator*/
    Gint    view_pri[16] /* OUT view priorities*/);

extern void ginq_loc_st(
    Gint    ws_id,      /* workstation identifier*/
    Gint    loc_num,    /* locator device number*/
    Ginq_type type, /* type of returned values*/
    Gstore  store,      /* handle to Store object*/
    Gint    *err_ind,   /* OUT error indicator*/
    Gop_mode *mode,     /* OUT operating mode*/
    Gecho_switch *esw, /* OUT echo switch*/
    Gint    *init_norm_tran_num, /* OUT initial normalization
        transformation number*/
    Gpoint   *init_loc_pos, /* OUT initial locator position*/
    Gint    *pet, /* OUT prompt/echo type*/
    Glimit   *echo_area, /* OUT echo area*/
    Gloc_data **loc_data /* OUT locator data record*/);

extern void ginq_stroke_st(
    Gint    ws_id,      /* workstation identifier*/
    Gint    stroke_num, /* stroke device number*/
    Ginq_type type, /* type of returned values*/
    Gstore  store,      /* handle to Store object*/
    Gint    *err_ind,   /* OUT error indicator*/
    Gop_mode *mode,     /* OUT operating mode*/
    Gecho_switch *esw, /* OUT echo switch*/
    Gint    *init_norm_tran_num, /* OUT initial normalization
        transformation number*/
    Gpoint_list **init_stroke, /* OUT initial stroke*/
    Gint    *pet, /* OUT prompt/echo type*/
    Glimit   *echo_area, /* OUT echo area*/
    Gstroke_data **stroke_data /* OUT stroke data record*/);

extern void ginq_val_st(
    Gint    ws_id,      /* workstation identifier*/
    Gint    val_num,    /* valuator device number*/
    Gstore  store,      /* handle to Store object*/
    Gint    *err_ind,   /* OUT error indicator*/
    Gop_mode *mode,     /* OUT operating mode*/
    Gecho_switch *esw, /* OUT echo switch*/
    Gfloat   *init_value, /* OUT initial value*/
    Gint    *pet, /* OUT prompt/echo type*/

```

```

Glimit      *echo_area, /* OUT echo area*/
Gval_data   **val_data /* OUT valuator data record*/);
extern void ginq_choice_st(
Gint        ws_id,      /* workstation identifier*/
Gint        choice_num, /* choice device number*/
Gstore      store,      /* handle to Store object*/
Gint        *err_ind,   /* OUT error indicator*/
Gop_mode    *mode,      /* OUT operating mode*/
Gecho_switch *esw,      /* OUT echo switch*/
Gin_status  *init_status, /* OUT initial choice status*/
Gint        *init_choice, /* OUT initial choice*/
Gint        *pet, /* OUT prompt/echo type*/
Glimit      *echo_area, /* OUT echo area*/
Gchoice_data **choice_data/* OUT choice data record*/);
extern void ginq_pick_st(
Gint        ws_id,      /* workstation identifier*/
Gint        pick_num,   /* pick device number*/
Ginq_type   type, /* type of returned values*/
Gstore      store,      /* handle to Store object*/
Gint        *err_ind,   /* OUT error indicator*/
Gop_mode    *mode,      /* OUT operating mode*/
Gecho_switch *esw,      /* OUT echo switch*/
Gin_status  *init_status, /* OUT initial pick status*/
Gpick       *init_pick, /* OUT initial pick value*/
Gint        *pet, /* OUT prompt/echo type*/
Glimit      *echo_area, /* OUT echo area*/
Gpick_data  **pick_data /* OUT pick data record*/);
extern void ginq_string_st(
Gint        ws_id,      /* workstation identifier*/
Gint        string_num, /* string device number*/
Gstore      store,      /* handle to Store object*/
Gint        *err_ind,   /* OUT error indicator*/
Gop_mode    *mode,      /* OUT operating mode*/
Gecho_switch *esw,      /* OUT echo switch*/
char        **init_string, /* OUT initial string*/
Gint        *pet, /* OUT prompt/echo type*/
Glimit      *echo_area, /* OUT echo area*/
Gstring_data **string_data/* OUT string data record*/);
extern void ginq_gen_ws_dt_entry(
Gint        ws_gen_type, /* workstation generic type*/
Gws_dt_name ws_dt_name, /* workstation description table
                        entry name*/
Gstore      store,      /* handle to Store object*/
Gint        *err_ind,   /* OUT error indicator*/
Gws_dt_entry **ws_dt_entry/* OUT workstation description
                        table entry*/);
extern void ginq_ws_class(
Gint        ws_gen_type, /* workstation generic type*/
Gint        *err_ind,   /* OUT error indicator*/
Gws_class   *class      /* OUT workstation class*/);
extern void ginq_disp_space_size(
Gint        ws_gen_type, /* workstation generic type*/

```

```

    Gint      *err_ind, /* OUT error indicator*/
    Gdisp_space_size *disp_size /* OUT display [space] size*/);
extern void ginq_line_facs(
    Gint      ws_gen_type, /* workstation generic type*/
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gline_facs *line_facs, /* OUT line facilities*/
    Gint      *num_elems_impl_list, /* OUT length of linetype
                                     list in impl.*/);
extern void ginq_pred_line_rep(
    Gint      ws_gen_type, /* workstation generic type*/
    Gint      ind, /* predefined index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gline_bundle *line_rep /* OUT predefined line rep.*/);
extern void ginq_marker_facs(
    Gint      ws_gen_type, /* workstation generic type*/
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gmarker_facs *marker_facs, /* OUT marker facilities*/
    Gint      *num_elems_impl_list, /* OUT length of marker type
                                     list in impl.*/);
extern void ginq_pred_marker_rep(
    Gint      ws_gen_type, /* workstation generic type*/
    Gint      ind, /* predefined index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gmarker_bundle *marker_rep /* OUT predefined marker rep.*/);
extern void ginq_text_facs(
    Gint      ws_gen_type, /* workstation generic type*/
    Gint      num_elems_appl_list, /* length of application list*/
    Gint      start_ind, /* starting index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gtext_facs *text_facs, /* OUT text facilities*/
    Gint      *num_elems_impl_list, /* OUT length of text font
                                     and precision list in impl.*/);
extern void ginq_pred_text_rep(
    Gint      ws_gen_type, /* workstation generic type*/
    Gint      ind, /* predefined index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gtext_bundle *text_rep /* OUT predefined text rep.*/);
extern void ginq_area_facs(
    Gint      ws_gen_type, /* workstation generic type*/
    Gstore store, /* handle to Store object*/
    Gint      *err_ind, /* OUT error indicator*/
    Gareafacs **area_facs /* OUT interior facilities*/);
extern void ginq_pred_area_rep(
    Gint      ws_gen_type, /* workstation generic type*/
    Gint      ind, /* predefined index*/
    Gint      *err_ind, /* OUT error indicator*/
    Gareafacs *area_rep /* OUT predefined area rep.*/);
extern void ginq_pat_facs(

```

```

Gint      ws_gen_type,      /* workstation generic type*/
Gint      *err_ind,      /* OUT error indicator*/
Gint      *num_pred_inds    /* OUT num. of predef. pattern indices*/);
extern void ginq_pred_pat_rep(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      ind, /* predefined index*/
Gstore    store,      /* handle to Store object*/
Gint      *err_ind,      /* OUT error indicator*/
Gpat_rep  **pat_rep    /* OUT predefined pattern rep.*/);
extern void ginq_colr_fac(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      *err_ind,      /* OUT error indicator*/
Gcolr_fac *colr_fac /* OUT colour facilities*/);
extern void ginq_pred_colr_rep(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      ind, /* predefined index*/
Gint      *err_ind,      /* OUT error indicator*/
Gcolr_rep *colr_rep    /* OUT predefined colour rep.*/);
extern void ginq_list_avail_gdps(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      num_elems_appl_list, /* length of application list*/
Gint      start_ind, /* starting index*/
Gint      *err_ind,      /* OUT error indicator*/
Gint_list *gdp, /* OUT list of GDPs*/
Gint      *num_elems_impl_list /* OUT length of impl. list */);
extern void ginq_set_avail_in_devs(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      *err_ind,      /* OUT error indicator*/
Gint      num_elems_appl_list, /* length of application list*/
Gdev_id_list *dev_ids, /* OUT set of input devices*/
Gint      *num_elems_impl_list /* OUT length of impl. list */);
extern void ginq_num_avail_in(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      *err_ind,      /* OUT error indicator*/
Gnum_in   *num_in    /* OUT number of input devices*/);
extern void ginq_in_dev_init_values(
Gint      ws_gen_type,      /* workstation generic type*/
Gstore    store,      /* handle to Store object*/
Gint      *err_ind,      /* OUT error indicator*/
Gin_dev_init_value_list **in_dev_init_values /* OUT input device
initial values */);
extern void ginq_set_avail_meas(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      num_elems_appl_list, /* length of application list*/
Gint      *err_ind,      /* OUT error indicator*/
Gint_list *meas_ids, /* OUT set of measure ids*/
Gint      *num_elems_impl_list /* OUT length of impl. list */);
extern void ginq_set_avail_triggers(
Gint      ws_gen_type,      /* workstation generic type*/
Gint      num_elems_appl_list, /* length of application list*/
Gint      *err_ind,      /* OUT error indicator*/
Gint_list *trigger_ids, /* OUT set of trigger ids*/

```

```

    Gint      *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_in_dev_comps(
    Gint      ws_gen_type,      /* workstation generic type*/
    Gstore    store,            /* handle to Store object*/
    Gint      *err_ind,         /* OUT error indicator*/
    Gdev_comp_list **dev_comps /* OUT input device
                                compositions */);
extern void ginq_def_loc_data(
    Gint      ws_gen_type,      /* workstation generic type*/
    Gint      loc_num,          /* logical input device number*/
    Gstore    store,            /* handle to Store object*/
    Gint      *err_ind,         /* OUT error indicator*/
    Gpoint    *loc_pos,         /* OUT default locator position*/
    Gint_list **pet_list,       /* OUT list of prompt and echo types*/
    Glimit    *echo_area,       /* OUT default echo area*/
    Gloc_data **loc_data /* OUT default data record*/);
extern void ginq_def_stroke_data(
    Gint      ws_gen_type,      /* workstation generic type*/
    Gint      stroke_num,       /* logical input device number*/
    Gstore    store,            /* handle to Store object*/
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      *max_buf_size,     /* OUT max. input buffer size
                                (nr. of points)*/
    Gint_list **pet_list,       /* OUT list of prompt and echo types*/
    Glimit    *echo_area,       /* OUT default echo area*/
    Gstroke_data **stroke_data /* OUT default data record*/);
extern void ginq_def_val_data(
    Gint      ws_gen_type,      /* workstation generic type*/
    Gint      val_num,          /* logical input device number*/
    Gstore    store,            /* handle to Store object*/
    Gint      *err_ind,         /* OUT error indicator*/
    Gfloat    *def_val,         /* OUT default initial value*/
    Gint_list **pet_list,       /* OUT list of prompt and echo types*/
    Glimit    *echo_area,       /* OUT default echo area*/
    Gval_data **val_data /* OUT default data record*/);
extern void ginq_def_choice_data(
    Gint      ws_gen_type,      /* workstation generic type*/
    Gint      choice_num,       /* logical input device number*/
    Gstore    store,            /* handle to Store object*/
    Gint      *err_ind,         /* OUT error indicator*/
    Gint      *max_num_choices, /* OUT max. num. of choices*/
    Gint_list **pet_list,       /* OUT list of prompt and echo types*/
    Glimit    *echo_area,       /* OUT default echo area*/
    Gchoice_data **choice_data /* OUT default data record*/);
extern void ginq_def_pick_data(
    Gint      ws_gen_type,      /* workstation generic type*/
    Gint      pick_num,         /* logical input device number*/
    Gstore    store,            /* handle to Store object*/
    Gint      *err_ind,         /* OUT error indicator*/
    Gint_list **pet_list,       /* OUT list of prompt and echo types*/
    Glimit    *echo_area,       /* OUT default echo area*/
    Gpick_data **pick_data /* OUT default data record*/);

```

```

extern void ginq_def_string_data(
    Gint      ws_gen_type,      /* workstation generic type*/
    Gint      string_num, /* logical input device number*/
    Gstore    store,           /* handle to Store object*/
    Gint      *err_ind,        /* OUT error indicator*/
    Gint      *max_buf_size,   /* OUT max. input buffer size
                                (nr. of bytes)*/
    Gint_list **pet_list, /* OUT list of prompt and echo types*/
    Glimit     *echo_area, /* OUT default echo area*/
    Gstring_data **string_data /* OUT default data record*/);
extern void ginq_specif_ws_dt_entry(
    Gint      ws_id,           /* workstation identifier*/
    Gws_dt_name ws_dt_name, /* workstation description table
                                entry name*/
    Gstore    store,           /* handle to Store object*/
    Gint      *err_ind,        /* OUT error indicator*/
    Gws_dt_entry **ws_dt_entry /* OUT workstation description
                                table entry*/);
extern void ginq_specif_ws_dt_entry_st(
    Gint      ws_id,           /* workstation identifier*/
    Gws_dt_name ws_dt_name, /* entry name*/
    Gint      *err_ind,        /* OUT error indicator*/
    Gchange_flag *entry_st /* OUT entry state*/);
extern void greset_specif_ws_dt_entry_st(
    Gint      ws_id,           /* workstation identifier*/
    Gws_dt_name ws_dt_name /* entry name*/);
/* Retrieval functions*/
extern void gget_text_extent(
    Gint      ws_id,           /* workstation identifier*/
    const Gpoint *pos, /* text position*/
    const char *str, /* character string*/
    Gint      *err_ind,        /* OUT error indicator*/
    Gtext_extent *extent /* OUT concatenation point and
                                text extent parallelogram*/);
extern void ginq_text_extent(
    Gint      ws_id,           /* workstation identifier*/
    const Gpoint *pos, /* text position*/
    const char *str, /* character string*/
    Gint      *err_ind,        /* OUT error indicator*/
    Gtext_extent *extent /* OUT concatenation point and
                                text extent parallelogram*/);
extern void geval_view_ori_matrix(
    const Gpoint *ref_point, /* fixed reference point*/
    const Gvec *view_up, /* view up vector*/
    Gtran_matrix view_ori_matrix /* OUT view orientation
                                matrix */);
extern void geval_view_map_matrix(
    const Gtran *win_vp, /* window/viewport limits*/
    Gtran_matrix view_map_matrix /* OUT view orientation
                                matrix */);
/* Segment functions*/
extern void gcreate_seg(

```

```

    Gint      seg_name    /* segment name*/);
extern void gclose_seg(
    void
    );
extern void grename_seg(
    Gint      old_seg_name,    /* old segment name*/
    Gint      new_seg_name    /* new segment name*/);
extern void gdel_seg(
    Gint      seg_name    /* segment name*/);
extern void gdel_seg_ws(
    Gint      ws_id,        /* workstation identifier*/
    Gint      seg_name    /* segment name*/);
extern void gassoc_seg_ws(
    Gint      ws_id,        /* workstation identifier*/
    Gint      seg_name    /* segment name*/);
extern void gcopy_seg_ws(
    Gint      ws_id,        /* workstation identifier*/
    Gint      seg_name    /* segment name*/);
extern void ginsert_seg(
    Gint      seg_name,    /* segment name*/
    const Gtran_matrix    tran_matrix/* transformation matrix*/);
extern void gset_seg_attr(
    Gint      seg_name,    /* segment name*/
    const Gseg_attr_value *seg_attr_value/* segment attribute value*/);
extern void gset_seg_tran(
    Gint      seg_name,    /* segment name*/
    Gtran_matrix    tran_matrix /* transformation matrix*/);
extern void gset_vis(
    Gint      seg_name,    /* segment name*/
    Gvis      vis    /* visibility */);
extern void gset_highl(
    Gint      seg_name,    /* segment name*/
    Ghighl    highl /* highlighting*/);
extern void gset_det(
    Gint      seg_name,    /* segment name*/
    Gdet      det    /* detectability*/);
extern void gset_seg_pri(
    Gint      seg_name,    /* segment name*/
    Gfloat    seg_pri    /* segment priority */);
/* Workstation activation functions*/
extern void gactivate_ws(
    Gint      ws_id /* workstation identifier*/);
extern void gdeactivate_ws(
    Gint      ws_id /* workstation identifier*/);
extern void gclear_ws(
    Gint      ws_id,        /* workstation identifier*/
    Gctrl_flag ctrl_flag    /* control flag*/);
/* Utility functions*/
extern void gget_map_seg_name(
    Gint      seg_name,    /* segment name*/
    Gint      *map_seg_name    /* OUT mapped segment name*/);
extern void gget_map_ws_id(
    Gint      ws_id,        /* workstation identifier*/

```



```
Gint      *map_ws_id /* OUT mapped workstation identifier*/);
```

A.4 Compatibility layer

```
/* Data types */
typedef Garea_attrs      Gfill_attrs;
typedef Garea_bundle     Gfill_bundle;
typedef Garea_facs       Gfill_facs;
typedef Gint_style       Gfill_int_style;
/* Overtaken data types */
/* Implementation independent */
/* Gattrs attributes [used] */
typedef enum {
    GATTR_LINE,
    GATTR_MARKER,
    GATTR_TEXT,
    GATTR_FILL
} Gattrs;
/* Gclip clipping */
typedef struct {
    Gclip_ind      clip_ind; /* clipping indicator */
    Glimit         clip_rect; /* clipping rectangle */
} Gclip;
/* Gdefer_mode deferral mode */
typedef enum {
    GDEFER_ASAP,
    GDEFER_BNIG,
    GDEFER_BNIL,
    GDEFER_ASTI
} Gdefer_mode;
/* Gdisp_surf_empty display surface empty */
typedef enum {
    GSURF_NOT_EMPTY,
    GSURF_EMPTY
} Gdisp_surf_empty;
/* Gdyn_mod dynamic modification [accepted] */
typedef enum {
    GDYN_IRG,
    GDYN_IMM
} Gdyn_mod;
/* Gdyn_mod_seg_attrs dynamic modification [of] segment attributes */
typedef struct {
    /* changeability of: */
    Gdyn_mod      tran; /* segment transformation */
    Gdyn_mod      invis_vis; /* appearing (invisible → visible) */
    Gdyn_mod      vis_invis; /* disappearing (visible → invisible) */
    Gdyn_mod      highl; /* highlighting */
    Gdyn_mod      pri; /* priority */
    Gdyn_mod      add_prims; /* addition of primitives to segment */
    Gdyn_mod      del; /* deletion of segment */
} Gdyn_mod_seg_attrs;
/* Gdyn_mod_ws_attrs dynamic modification [of] workstation attributes */
typedef struct {
```



```

        /* changeability of:*/
        Gdyn_mod    line_bundle;/* polyline representation */
        Gdyn_mod    marker_bundle;/* polymarker representation */
        Gdyn_mod    text_bundle;/* text representation */
        Gdyn_mod    fill_bundle;/* fill area representation */
        Gdyn_mod    pat_rep;/* pattern representation */
        Gdyn_mod    colr_rep;/* colour representation */
        Gdyn_mod    ws_tran;/* workstation transformation */
    } Gdyn_mod_ws_attr;
    /* Gindiv_attr individual attributes */
    typedef struct {
        Gint          linetype;/* linetype*/
        Gfloat         linewidth;/* linewidth scale factor*/
        Gint           line_colr_ind;/* polyline colour index*/
        Gint           marker_type;/* marker type*/
        Gfloat         marker_size;/* marker size scale factor*/
        Gint           marker_colr_ind;/* polymarker colour index*/
        Gtext_font_prec text_font_prec;/* text font and precision*/
        Gfloat         char_expan;/* character expansion factor*/
        Gfloat         char_space;/* character spacing*/
        Gint           text_colr_ind;/* text colour index*/
        Gfill_int_style fill_int_style;/* fill area interior style*/
        Gint           fill_style_ind;/* fill area style index*/
        Gint           fill_colr_ind;/* fill area colour index*/
        Gasfs          asfs;/* aspect source flags */
    } Gindiv_attr;
    /* Girg_mode implicit regeneration mode */
    typedef enum {
        GIRG_SUPPR,
        GIRG_ALLOWED
    } Girg_mode;
    /* Glevel GKS level */
    typedef enum {
        GLEVEL_0A,
        GLEVEL_0B,
        GLEVEL_0C,
        GLEVEL_1A,
        GLEVEL_1B,
        GLEVEL_1C,
        GLEVEL_2A,
        GLEVEL_2B,
        GLEVEL_2C
    } Glevel;
    /* Gmax_ws_st_tables max. [length of] workstation state tables */
    typedef struct {
        /* max. num. of */
        Gint    line_bundles;/* polyline bundle table entries*/
        Gint    marker_bundles;/* polymarker bundle table entries*/
        Gint    text_bundles;/* text bundle table entries*/
        Gint    fill_bundles;/* fill area bundle table entries*/
        Gint    pat_reps;/* pattern table entries*/
        Gint    colr_reps;/* colour table entries*/
    }

```

```

} Gmax_ws_st_tables;
/* Gmore_simult_events more simultaneous events */
typedef enum {
    GSIMULT_NO_MORE,
    GSIMULT_MORE
} Gmore_simult_events;
/* Gnew_frame_nec_upd new frame [action] necessary [at] update */
typedef enum {
    GNEW_NO,
    GNEW_YES
} Gnew_frame_nec_upd;
/* Gop_st operating state */
typedef enum {
    GST_GKCL,
    GST_GKOP,
    GST_WSOP,
    GST_WSAC,
    GST_SGOP
} Gop_st;
/* Gpres_inval presence [of] invalid [values] */
typedef enum {
    GINVAL_ABSENT,
    GINVAL_PRESENT
} Gpres_inval;
/* Gprim_attrs primitive attributes */
typedef struct {
    Gint          line_ind; /* polyline index*/
    Gint          marker_ind; /* polymarker index*/
    Gint          text_ind; /* text index*/
    Gfloat        char_ht; /* character height*/
    Gvec          char_up_vec; /* character up vector*/
    Gfloat        char_width; /* character width*/
    Gvec          char_base_vec; /* character base vector*/
    Gtext_path    text_path; /* text path*/
    Gtext_align   text_align; /* text alignment*/
    Gint          fill_ind; /* fill area index*/
    Gvec          pat_width_vec; /* pattern width vector*/
    Gvec          pat_ht_vec; /* pattern height vector*/
    Gpoint        pat_ref_point; /* pattern reference point*/
} Gprim_attrs;
/* Gupd_regen_flag update regeneration flag */
typedef enum {
    GFLAG_POSTPONE,
    GFLAG_PERFORM
} Gupd_regen_flag;
/* Gupd_st update state */
typedef enum {
    GUPD_NOT_PEND,
    GUPD_PEND
} Gupd_st;
/* Gws_cat workstation category */
typedef enum {

```

```

        GCAT_OUT,
        GCAT_IN,
        GCAT_OUTIN,
        GCAT_WISS,
        GCAT_MO,
        GCAT_MI
    } Gws_cat;
/* Gws_max_nums workstation max. numbers */
typedef struct {
    Gint          simult_open; /* max. num. of simult. open wss */
    Gint          simult_active; /* max. num. of simult. active wss */
    Gint          assoc_seg; /* max. num. of wss associated with segment */
} Gws_max_nums;
/* Implementation dependent */
/* Gitem_data item data record */
typedef struct {
    Gint          type; /* item type */
    Gint          length; /* item data record length */
    union {
        Gaudit_user_data user_rec; /* user record */
        Gfunc_params func_params; /* function parameters flag */
        Gdataimpl_dep; /* impl. dependent */
    } data;
} Gitem_data;
/* Conversion macros for fields */
#define fill_int_style      int_style
#define fill_style_ind      int_style_ind
#define fill_colr_ind      int_colr_ind
#define pet_r5.attrs.fill_attrs pet_r5.attrs.area_attrs
/* Obsolete macros */
/* Function macros */
#define Gfn_redraw_all_segs_ws (7)
#define Gfn_upd_ws            (8)
#define Gfn_set_defer_st      (9)
#define Gfn_set_fill_ind      (35)
#define Gfn_set_fill_int_style (36)
#define Gfn_set_fill_style_ind (37)
#define Gfn_set_fill_colr_ind (38)
#define Gfn_set_fill_rep      (46)
#define Gfn_set_clip_ind      (53)
#define Gfn_flush_events      (94)
#define Gfn_write_item         (101)
#define Gfn_get_item_type      (102)
#define Gfn_interpret_item     (104)
/* Error macros */
#define GE_NOT_GKCL            (1)
#define GE_NOT_GKOP            (2)
#define GE_NOT_WSAC            (3)
#define GE_NOT_SGOP            (4)
#define GE_NOT_WSAC_SGOP      (5)
#define GE_NOT_WSOP_WSAC      (6)
#define GE_GKCL_GKOP          (7)

```

```
#define GE_GKCL (8)
#define GE_CONN_ID_INVALID (21)
#define GE_NO_WS_TYPE (23)
#define GE_WS_CANT_OPEN (26)
#define GE_WISS_NOT_OPEN (27)
#define GE_WISS_OPEN (28)
#define GE_WS_INACTIVE (30)
#define GE_WS_MO (31)
#define GE_WS_NOT_MO (32)
#define GE_WS_MI (33)
#define GE_WS_NOT_MI (34)
#define GE_WS_IN (35)
#define GE_WS_WISS (36)
#define GE_WS_NOT_OUTIN (37)
#define GE_WS_NOT_IN_OUTIN (38)
#define GE_WS_NOT_OUT_OUTIN (39)
#define GE_WS_NO_PIXEL (40)
#define GE_WS_TYPE_NO_GDP (41)
#define GE_WS_MAX_OPEN (42)
#define GE_WS_MAX_ACTIVE (43)
#define GE_RECT_INVALID (51)
#define GE_VP_INVALID (52)
#define GE_WIN_INVALID (53)
#define GE_WS_VP_INVALID (54)
#define GE_LINE_IND_INVALID (60)
#define GE_LINE_REP_UNDEF (61)
#define GE_LINE_REP_NOT_PRED (62)
#define GE_LINETYPE_ZERO (63)
#define GE_LINETYPE_NOT_WS (64)
#define GE_LINEWIDTH_LT_ZERO (65)
#define GE_MARKER_IND_INVALID (66)
#define GE_MARKER_REP_UNDEF (67)
#define GE_MARKER_REP_NOT_PRED (68)
#define GE_MARKER_TYPE_ZERO (69)
#define GE_MARKER_TYPE_NOT_WS (70)
#define GE_MARKER_SIZE_LT_ZERO (71)
#define GE_TEXT_IND_INVALID (72)
#define GE_TEXT_REP_UNDEF (73)
#define GE_TEXT_REP_NOT_PRED (74)
#define GE_FONT_ZERO (75)
#define GE_FONT_NOT_WS (76)
#define GE_EXPAN_LE_ZERO (77)
#define GE_HT_LE_ZERO (78)
#define GE_UP_VEC_ZERO (79)
#define GE_FILL_IND_INVALID (80)
#define GE_FILL_REP_UNDEF (81)
#define GE_FILL_REP_NOT_PRED (82)
#define GE_INT_STYLE_NOT_WS (83)
#define GE_STYLE_IND_ZERO (84)
#define GE_HATCH_STYLE_NOT_WS (86)
#define GE_PAT_SIZE_LE_ZERO (87)
#define GE_PAT_REP_UNDEF (88)
```

```
#define GE_PAT_REP_NOT_PRED (89)
#define GE_PAT_NOT_WS      (90)
#define GE_DIM_INVALID     (91)
#define GE_COLR_IND_LT_ZERO (92)
#define GE_COLR_REP_UNDEF  (94)
#define GE_COLR_REP_NOT_PRED (95)
#define GE_COLR_INVALID    (96)
#define GE_PICK_ID_INVALID (97)
#define GE_COLR_MODEL_UNAVAIL (98)
#define GE_NUM_POINT_INVALID (100)
#define GE_INVALID_CODE     (101)
#define GE_CANT_GEN_GDP     (104)
#define GE_CANT_GEN_GDP_CLIP (105)
#define GE_SEG_NAME_USED    (121)
#define GE_SEG_ABSENT       (122)
#define GE_SEG_NOT_WS       (123)
#define GE_SEG_NOT_WISS     (124)
#define GE_SEG_PRI_INVALID  (126)
#define GE_IN_DEV_NOT_WS    (140)
#define GE_IN_DEV_NOT_REQ   (141)
#define GE_IN_DEV_NOT_SAMPLE (142)
#define GE_EV_SAMPLE_UNAVAIL (143)
#define GE_PET_NOT_WS       (144)
#define GE_ECHO_INVALID     (145)
#define GE_IN_DATA_INVALID  (146)
#define GE_QUE_OVERF        (147)
#define GE_NO_QUE_OVERF     (148)
#define GE_ASSOC_WS_CLOSED  (149)
#define GE_NO_CUR_EV        (150)
#define GE_INIT_INVALID     (152)
#define GE_INIT_STROKE_INVALID (153)
#define GE_INIT_STRING_INVALID (154)
#define GE_ITEM_RESERVED    (160)
#define GE_ITEM_LENGTH_INVALID (161)
#define GE_NO_ITEM_MI       (162)
#define GE_ITEM_INVALID     (163)
#define GE_ITEM_GKS_INVALID (164)
#define GE_ITEM_DATA_INVALID (165)
#define GE_MAX_ITEM_DATA_INVALID (166)
#define GE_USER_ITEM        (167)
#define GE_FUNC_UNAVAIL     (168)
#define GE_ESCAPE_FUNC_UNAVAIL (180)
#define GE_ESCAPE_ID_INVALID (181)
#define GE_ESCAPE_DATA_INVALID (182)
#define GE_MEM_OVERF        (300)
#define GE_SEG_MEM_OVERF    (301)
#define GE_IO_ERR_READ      (302)
#define GE_IO_ERR_WRITE     (303)
#define GE_IO_ERR_WRITE_WS  (304)
#define GE_IO_ERR_READ_WS   (305)
#define GE_IO_ERR_LIB       (306)
#define GE_IO_ERR_WS_TABLE  (307)
```

```

#define GE_ARITH_ERR          (308)
/* GKSM macros */
#define Gksm_end_item         ( 0)
#define Gksm_clear_ws         ( 1)
#define Gksm_redraw_all_segs_ws ( 2)
#define Gksm_upd_ws           ( 3)
#define Gksm_defer_st         ( 4)
#define Gksm_message          ( 5)
#define Gksm_escape           ( 6)
#define Gksm_polyline         (11)
#define Gksm_polymarker       (12)
#define Gksm_text             (13)
#define Gksm_fill_area        (14)
#define Gksm_cell_array       (15)
#define Gksm_gdp              (16)
#define Gksm_line_ind         (21)
#define Gksm_linetype         (22)
#define Gksm_linewidth        (23)
#define Gksm_line_colr_ind    (24)
#define Gksm_marker_ind       (25)
#define Gksm_marker_type      (26)
#define Gksm_marker_size      (27)
#define Gksm_marker_colr_ind  (28)
#define Gksm_text_ind         (29)
#define Gksm_text_font_prec   (30)
#define Gksm_char_expan       (31)
#define Gksm_char_space       (32)
#define Gksm_text_colr_ind    (33)
#define Gksm_char_vec         (34)
#define Gksm_text_path        (35)
#define Gksm_text_align       (36)
#define Gksm_fill_ind         (37)
#define Gksm_fill_int_style   (38)
#define Gksm_fill_style_ind   (39)
#define Gksm_fill_colr_ind    (40)
#define Gksm_pat_ref_point    (41)
#define Gksm_pat_vecs         (42)
#define Gksm_asf              (43)
#define Gksm_pick_id          (44)
#define Gksm_line_rep         (51)
#define Gksm_marker_rep       (52)
#define Gksm_text_rep         (53)
#define Gksm_fill_rep         (54)
#define Gksm_pat_rep          (55)
#define Gksm_colr_rep         (56)
#define Gksm_clip_rect        (61)
#define Gksm_ws_win           (71)
#define Gksm_ws_vp            (72)
#define Gksm_create_seg       (81)
#define Gksm_close_seg        (82)
#define Gksm_rename_seg       (83)
#define Gksm_del_seg          (84)

```

```

#define Gksm_set_seg_tran    (91)
#define Gksm_set_vis        (92)
#define Gksm_set_highl      (93)
#define Gksm_set_seg_pri    (94)
#define Gksm_set_det        (95)
#define Gksm_user_item_start (100)
/* Miscellaneous */
#define GDEF_MEM_SIZE        (0)
/* GKS functions */
/* Renamed GKS functions */
/* Output attribute functions */
extern void gset_fill_ind(
    Gint          fill_ind/* fill area index*/);
extern void gset_fill_int_style(
    Gfill_int_style fill_int_style/* fill area interior style*/);
extern void gset_fill_style_ind(
    Gint          fill_style_ind/* fill area style index*/);
extern void gset_fill_colr_ind(
    Gint          fill_colr_ind/* fill area colour index*/);
extern void gset_fill_rep(
    Gint          ws_id/* workstation identifier*/
    Gint          fill_ind/* fill area index*/
    const Gfill_bundle *fill_bundle/* fill area representation */);
/* Inquire functions */
extern void ginq_fill_ind(
    Gint          *err_ind/* OUT error indicator*/
    Gint          *fill_ind/* OUT current fill area index*/);
extern void ginq_fill_int_style(
    Gint          *err_ind/* OUT error indicator*/
    Gfill_int_style *fill_int_style/* OUT current fill area
                                interior style*/);
extern void ginq_fill_style_ind(
    Gint          *err_ind/* OUT error indicator*/
    Gint          *fill_style_ind/* OUT current fill area style index*/);
extern void ginq_fill_colr_ind(
    Gint          *err_ind/* OUT error indicator*/
    Gint          *fill_colr_ind/* OUT current fill area colour index*/);
extern void ginq_list_fill_inds(
    Gint          ws_id/* workstation identifier*/
    Gint          num_elems_appl_list/* length of application list*/
    Gint          start_ind/* starting index*/
    Gint          *err_ind/* OUT error indicator*/
    Gint_list     *def_fill_inds/* OUT list of defined fill area indices*/
    Gint          *num_elems_impl_list/* OUT length of impl. list */);
extern void ginq_fill_rep(
    Gint          ws_id/* workstation identifier*/
    Gint          fill_ind/* fill area index*/
    Ginq_type     type/* type of returned values*/
    Gint          *err_ind/* OUT error indicator*/
    Gfill_bundle  *fill_rep/* OUT fill area representation*/);
extern void ginq_fill_fac(
    Gint          ws_gen_type/* workstation generic type*/

```

```

    Gint          num_elems_appl_list, /* length of application list */
    Gint          start_ind, /* starting index */
    Gint          *err_ind, /* OUT error indicator */
    Gfill_fac     *fill_fac, /* OUT fill area facilities */
    Gint          *num_elems_impl_list /* OUT length of hatch list */);

extern void ginq_pred_fill_rep(
    Gint          ws_gen_type, /* workstation generic type */
    Gint          ind, /* predefined index */
    Gint          *err_ind, /* OUT error indicator */
    Gfill_bundle  *fill_rep /* OUT predefined fill area rep. */);

/* Overtaken functions */
/* Control functions */
extern void gredraw_all_segs_ws(
    Gint          ws_id /* workstation identifier */);

extern void gupd_ws(
    Gint          ws_id, /* workstation identifier */
    Gupd_regen_flag upd_regen_flag /* update regeneration flag */);

extern void gset_defer_st(
    Gint          ws_id, /* workstation identifier */
    Gdefer_mode   defer_mode, /* deferral mode */
    Girg_mode     irg_mode /* implicit regeneration mode */);

/* Transformation functions */
extern void gset_clip_ind(
    Gclip_ind     clip_ind /* clipping indicator */);

/* Input functions */
extern void gflush_events(
    Gint          ws_id, /* workstation identifier */
    Gin_class     class, /* device class */
    Gint          in_num /* logical input device number */);

/* GKSM functions */
extern void gwrite_item(
    Gint          ws_id, /* workstation identifier */
    Gint          item_type, /* item type */
    Gint          item_data_length, /* item data record length */
    const Gitem_data *item_data /* item data record */);

extern void gget_item_type(
    Gint          ws_id, /* workstation identifier */
    Gint          *item_type, /* OUT item type */
    Gint          *item_data_length /* OUT item data record length */);

extern void gread_item(
    Gint          ws_id, /* workstation identifier */
    Gint          max_item_data_length, /* max. item data record length */
    Gitem_data    *item_data /* OUT item data record */);

extern void ginterpret_item(
    Gint          type, /* item type */
    Gint          item_data_length, /* item data record length */
    const Gitem_data *item_data /* item data record */);

/* Inquire functions */
extern void ginq_op_st(
    Gop_st        *op_st /* OUT operating state value */);

extern void ginq_level_gks(
    Gint          *err_ind, /* OUT error indicator */

```



```

    Glevel          *level/* OUT level of GKS */);
extern void ginq_ws_max_nums(
    Gint            *err_ind,/* OUT error indicator*/
    Gws_max_nums    *ws_max_num/* OUT workstation maximum numbers */);
extern void ginq_max_norm_tran_num(
    Gint            *err_ind,/* OUT error indicator*/
    Gint            *max_norm_tran_num/* OUT maximum normalization
                                transformation number */);
extern void ginq_cur_prim_attrs(
    Gint            *err_ind,/* OUT error indicator*/
    Gprim_attrs     *prim_attrs/* OUT current primitive
                                attribute structure*/);
extern void ginq_char_width(
    Gint            *err_ind,/* OUT error indicator*/
    Gfloat          *char_width/* OUT current character width*/);
extern void ginq_char_base_vec(
    Gint            *err_ind,/* OUT error indicator*/
    Gvec            *char_base_vec/* OUT current character base vector*/);
extern void ginq_pat_width_vec(
    Gint            *err_ind,/* OUT error indicator*/
    Gvec            *pat_width_vec/* OUT current pattern width vector*/);
extern void ginq_pat_ht_vec(
    Gint            *err_ind,/* OUT error indicator*/
    Gvec            *pat_ht_vec/* OUT current pattern height vector*/);
extern void ginq_cur_indiv_attrs(
    Gint            *err_ind,/* OUT error indicator*/
    Gindiv_attrs    *indiv_attr/* OUT current individual
                                attribute structure*/);
extern void ginq_clip(
    Gint            *err_ind,/* OUT error indicator*/
    Gclip           *clip_ind_rect/* OUT current clipping indicator
                                and rectangle*/);
extern void ginq_more_simult_events(
    Gint            *err_ind,/* OUT error indicator*/
    Gmore_simult_events*simult_events/* OUT [more]
                                simultaneous events*/);
extern void ginq_ws_defer_upd_sts(
    Gint            ws_id,/* workstation identifier*/
    Gint            *err_ind,/* OUT error indicator*/
    Gdefer_mode     *defer_mode,/* OUT deferral mode*/
    Girg_mode       *irg_mode,/* OUT IRG mode*/
    Gdisp_surf_empty *disp_surf_empty,/* OUT display surface empty*/
    Gnew_frame_nec_upd *new_frame/* OUT new frame action
                                necessary at update*/);
extern void ginq_ws_tran(
    Gint            ws_id,/* workstation identifier*/
    Gint            *err_ind,/* OUT error indicator*/
    Gupd_st         *ws_tran_upd_st,/* OUT workstation transformation
                                update state*/
    Glimit          *req_ws_win,/* OUT requested workstation window*/
    Glimit          *cur_ws_win,/* OUT current workstation window*/
    Glimit          *req_ws_vp,/* OUT requested workstation viewport*/

```

```

        Glimit                *cur_ws_vp/* OUT current workstation viewport*/);
extern void ginq_ws_cat(
    Gint                ws_gen_type/* workstation generic type*/
    Gint                *err_ind/* OUT error indicator*/
    Gws_cat             *cat/* OUT workstation category*/);
extern void ginq_dyn_mod_ws_attrs(
    Gint                ws_gen_type/* workstation generic type*/
    Gint                *err_ind/* OUT error indicator*/
    Gdyn_mod_ws_attrs  *dyn_mod/* OUT dynamic modification of
                                workstation attributes */);
extern void ginq_def_defer_sts(
    Gint                ws_gen_type/* workstation generic type*/
    Gint                *err_ind/* OUT error indicator*/
    Gdefer_mode         *defer_mode/* OUT default deferral mode */
    Girg_mode           *irg_mode/* OUT default impl. reg. mode */);
extern void ginq_gdp(
    Gint                ws_gen_type/* workstation generic type*/
    Gint                gdp/* GDP function number*/
    Gint                *err_ind/* OUT error indicator*/
    Gint                *num_attr/* OUT num. of attributes used*/
    Gattrs              attr[4]/* OUT list of attributes used*/);
extern void ginq_max_ws_st_tables(
    Gint                ws_gen_type/* workstation generic type*/
    Gint                *err_ind/* OUT error indicator*/
    Gmax_ws_st_tables   *lengths/* OUT lengths of workstation tables*/);
extern void ginq_num_seg_pris(
    Gint                ws_gen_type/* workstation generic type*/
    Gint                *err_ind/* OUT error indicator*/
    Gint                *num_seg_pris/* OUT num. of segment priorities*/);
extern void ginq_dyn_mod_seg_attrs(
    Gint                ws_gen_type/* workstation generic type*/
    Gint                *err_ind/* OUT error indicator*/
    Gdyn_mod_seg_attrs  *dyn_mod/* OUT dynamic modification of
                                segment attributess*/);
extern void ginq_pixel_array_dims(
    Gint                ws_id/* workstation identifier*/
    const Grect         *rect/* rectangle */
    Gint                *err_ind/* OUT error indicator*/
    Gint_size           *dims/* OUT pixel array dimensions */);
extern void ginq_pixel_array(
    Gint                ws_id/* workstation identifier*/
    const Gpoint         *pixel_loc/* pixel location */
    const Gint_size      *dims/* pixel array dimensions */
    Gint                *err_ind/* OUT error indicator*/
    Gpres_inval         *pres_inval/* OUT presence of invalid values*/
    Gint                *pixel_array/* OUT colour specifier array*/);
extern void ginq_pixel(
    Gint                ws_id/* workstation identifier*/
    const Gpoint         *pixel_loc/* pixel location */
    Gint                *err_ind/* OUT error indicator*/
    Gint                *colr_ind/* OUT colour index*/);

```

Annex B (informative)

Sample programs

B.1 STAR

```

/*      Program:      STAR
 *      File:          star.c          5.1
 *
 *      Description
 *
 *      This program draws a yellow star on a blue background and writes
 *      The title "STAR" in white under the star.
 */

/*
 *      Include files
 */
#include <stdio.h>
#include <math.h>
#include "gks.h"          /* GKS definitions */
/*
 *      Local definitions (implementation and site dependent)
 */
#define GKS_ERR           "gks.err"      /* Name of the GKS error file */
#define WS_SPECIF         "file.star"    /* Workstation specifier */
#define WS_TYPE           (19)          /* Workstation type */
/*
 *      Convenient definitions
 */
#define MY_WS              (1)           /* The workstation we'll be using */
#define TRAN_NUM           (1)           /* Normalization transformation number */
#define BLUE               (0)           /* Some colours we define below */
#define YELLOW             (1)
#define WHITE              (2)
#define PI                 (3.14159265) /* The well-known number */
#define LARGE_TEXT         (0.15)       /* Size of large texts */

/*
 *      State Variables:
 *
 *      These variables are used to set the
 *      corresponding GKS state
 */

static Glimit             win = {        /* Window Limits */
    -1.25, 1.25, -1.25, 1.25};

Gcolr_rep                 colr[3] ;      /* Colour Table */

```

```

static Gtext_align    ct_half = {    /* Text Alignment */
    GHOR_CTR, GVERT_HALF};

static Gpoint         title_pos =    /* Position for title */
    {0.0, -1.1};

static char           title[] = "STAR";          /* Title text */

/* Main entry point */
int main()
{
    Gpoint_list    star;          /* Points of the star */
    double angle; /* Current angle */
    Gpoint *starptr;          /* Star point pointer */
    Gint colr_ind; /* Colour index */
    Gcolr_rep *colrptr;        /* Colour representation pointer */
    Gint i;

/*
 *   colours are set
 *
 *   colr[0] = blue;
 *   colr[1] = yellow;
 *   colr[2] = white;
 */

    for (i=0; i<3; i++){
        colr[i].rgb.red = 1.0;
        colr[i].rgb.green = 1.0;
        colr[i].rgb.blue = 1.0;
    }
    colr[0].rgb.red = colr[0].rgb.green = colr[1].rgb.blue = 0.0;

/*
 *   Define the coordinates of star
 */
    star.num_points = 5;
    star.points = calloc(5, sizeof(Gpoint));
    for (starptr = star.points, angle = 0.0;
        angle < (4.*PI); angle += 0.8*PI, starptr++) {
        starptr->x = (Gfloat)sin(angle);
        starptr->y = (Gfloat)cos(angle);
    }

/*
 *   Open GKS and open/ and activate the workstation
 */
    gopen_gks(GKS_ERR, 0);
    gopen_ws(MY_WS, WS_SPECIF, WS_TYPE);
    gactivate_ws(MY_WS);

/*

```