


4730



ISSUED	1992-07-30	REVISED
--------	------------	---------

SHEET 1 OF 3

"This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS4377

TABLE 1A - DIMENSIONS A-F

BASIC NO. AS4377 /8/ SIZE CODE	(NOMINAL TUBE SIZE)	T THREAD PER MIL-S-8879	A ±.003	B	C	D +.004 -.000	E	F +.002 -.003
02	.125	.3125-24UNJF-3A	.093	.1630	.189	.135	.552-.565	.250
03	.187	.3750-24UNJF-3A	.125	.2340	.267	.196	.615-.628	.312
04	.250	.4375-20UNJF-3A	.187	.2930	.319	.261	.678-.691	.364
05	.312	.5000-20UNJF-3A	.234	.3560	.382	.324	.740-.753	.426
06	.375	.5625-18UNJF-3A	.297	.4160	.441	.386	.802-.816	.481
08	.500	.7500-16UNJF-3A	.422	.5600	.601	.514	.990-1.003	.660
10	.625	.8750-14UNJF-3A	.500	.6860	.727	.641	1.115-1.128	.773
12	.750	1.0625-12UNJ -3A	.656	.8100	.852	.766	1.365-1.380	.945
14	.875	1.1875-12UNJ -3A	.765	.9360	.977	.891	1.490-1.505	1.070
16	1.000	1.3125-12UNJ -3A	.875	1.0620	1.102	1.016	1.615-1.630	1.195
20	1.250	1.6250-12UNJ -3A	1.093	1.3160	1.355	1.270	1.865-1.880	1.507
24	1.500	1.8750-12UNJ -3A	1.344	1.5650	1.604	1.520	2.115-2.135	1.756
32	2.500	2.5000-12UNJ -3A	1.813	2.0680	2.108	2.022	2.740-2.760	2.381

TABLE 1B - DIMENSIONS G-P

BASIC NO. AS4377 /8/ SIZE CODE	G +.000 -.005	H ±.003	J ±.016	K ±.016	L ±.016	M ±.010 -.000	N +.010 -.000	P ±.005
02	.245	.188	.3053-.3125	.828	.094	.005	.125	.290
03	.307	.234	.3678-.3750	.875	.094	.005	.131	.340
04	.359	.234	.4294-.4375	.938	.094	.005	.140	.355
05	.421	.250	.4919-.5000	.938	.094	.010	.140	.355
06	.476	.250	.5538-.5625	.984	.094	.010	.156	.365
08	.654	.305	.7406-.7500	1.125	.125	.010	.187	.445
10	.767	.350	.8647-.8750	1.266	.125	.010	.219	.495
12	.938	.350	1.0511-1.0625	1.375	.125	.010	.234	.545
14	1.064	.356	1.1761-1.1875	1.375	.125	.010	.234	.545
16	1.188	.415	1.3011-1.3125	1.375	.125	.010	.234	.545
20	1.501	.415	1.6136-1.6250	1.375	.125	.015	.234	.545
24	1.750	.485	1.8636-1.8750	1.375	.125	.015	.234	.545
32	2.375	.485	2.4886-2.5000	1.578	.125	.015	.234	.545