

Connector Accessories, Electrical, Strain relief, Straight, Self-locking and Non-self-locking, Category 4C
(For MIL-DTL-38999 Series I and II Connectors)

This amendment forms a part of AS85049/121 Dated 2004-11

1). Present Requirement: (Sheet 1)

The requirements for acquiring the accessories described herein shall consist of this specification and the latest issue of SAE AS85049.

Change Requirement: (sheet 1)

NOTICE

The requirements for procuring the product described herein shall consist of this specification sheet and the latest issue of SAE AS85049.

Rationale for Change: Up-dated the procurement statement to comply with SAE guidelines.

2). Present Requirement: (Requirements, Paragraph 6, Material and Finish, Table 2 , sheet 3)

TABLE 2 - MATERIAL AND FINISH

FIGURE	MATERIAL	FINISH
1	ALUMINUM ALLOY IN ACCORDANCE WITH SAE AS85049	A N ^{1/} W ^{2/}
	CORROSION RESISTANT STEEL 300 SERIES IN ACCORDANCE WITH SAE AMS 763	S

^{1/} NOT FOR NAVY USE. AIR FORCE USE IS FOR SPACE APPLICATIONS ONLY. W IS THE PREFERRED FINISH.
^{2/} W IS NOT FOR USE IN SPACE APPLICATION.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2010 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: <http://www.sae.org>

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/AS85049/121A_A2**

Change Requirement: (Requirements, Paragraph 6, Material and Finish, Table 2, sheet 3)

Material and Finish: In accordance with SAE AS85049.

Table 2. Material and Finish

Figure	Material	Finish
1	Aluminum alloy in accordance with AS85049	A, <u>1</u> / N, <u>2</u> / W, X, Y, <u>2</u> / Z
	Corrosion resistant steel 300 series in accordance with AS85049	S, XS, YS, ZS

1/ N finish not for Navy use, restricted to Air Force space applications only.

2/ W and Z finish are not for use in space applications. Also see specification notes.

Rationale for Change: Added the X Y, Z, XS, YS and ZS plating options and appropriate footnotes to this detail sheet in support of the AS85049B-A3 amendment.

3). Present Requirement: (None)

Change Requirement: (End of document, Specification Notes)

1. Specification notes:

Notice

This document references a part which contains cadmium as a plating material. Consult local officials if you have questions concerning cadmium's use.

Rationale for Change: Added this statement to comply with SAE guidelines.