



UL 768

STANDARD FOR SAFETY

Combination Locks

ULNORM.COM : Click to view the full PDF of UL 768 2023

ULNORM.COM : Click to view the full PDF of UL 768 2023

UL Standard for Safety for Combination Locks, UL 768

Eighth Edition, Dated January 6, 2006

Summary of Topics

This revision of ANSI/UL 768 dated August 22, 2023 includes a clarification to Scope and References: [1.3](#), [2.3.2](#), [12.1](#) and [13.2.2](#).

Text that has been changed in any manner or impacted by ULSE's electronic publishing system is marked with a vertical line in the margin.

The new and revised requirements are substantially in accordance with Proposal(s) on this subject dated May 5, 2023.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

ULNORM.COM *Click to view the full PDF of UL768 2023*

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 768 2023

JANUARY 6, 2006
(Title Page Reprinted: August 22, 2023)



ANSI/UL 768-2023

1

UL 768

Standard for Combination Locks

First Edition – January, 1953
Second Edition – May, 1961
Third Edition – July, 1972
Fourth Edition – August, 1978
Fifth Edition – June, 1984
Sixth Edition – February, 1994
Seventh Edition – December, 1999

Eighth Edition

January 6, 2006

This ANSI/UL Standard for Safety consists of the Eighth Edition including revisions through August 22, 2023.

The most recent designation of ANSI/UL 768 as an American National Standard (ANSI) occurred on August 22, 2023. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

The Department of Defense (DoD) has adopted UL 768 on April 5, 1976. The publication of revised pages or a new edition of this Standard will not invalidate the DoD adoption.

Comments or proposals for revisions on any part of the Standard may be submitted to ULSE at any time. Proposals should be submitted via a Proposal Request in the Collaborative Standards Development System (CSDS) at <https://csds.ul.com>.

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

COPYRIGHT © 2023 ULSE INC.

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 768 2023

CONTENTS

INTRODUCTION

1	Scope	5
2	General	5
2.1	Components	5
2.2	Units of measurement.....	5
2.3	Referenced publications	5
3	Classification	6
4	Glossary.....	6

CONSTRUCTION

5	General	7
6	Nonmetallic Parts	7
7	Corrosion Protection.....	8

PERFORMANCE

8	General	8
9	Operation Test	8
10	Resistance to Unauthorized Opening.....	8
10.1	Group 1	8
10.2	Group 1R	9
10.3	Group 2M.....	9
10.4	Group 2	9
10.5	All classes.....	9
11	Endurance Test	10
12	Salt Spray Corrosion Test.....	11
13	Tests of Polymeric Material.....	11
13.1	Strength.....	11
13.2	Aging-stress distortion.....	11
13.3	Moisture absorption	11
14	Vibration Test.....	12

MARKING

15	General.....	12
----	--------------	----

UNNORM. COPY. Click to view the full PDF of UL 768 2023

No Text on This Page

ULNORM.COM : Click to view the full PDF of UL 768 2023

INTRODUCTION

1 Scope

1.1 These requirements cover combination locks intended for attachment on doors of safes, chests, vaults, and the like, to provide a means of locking the boltwork against unauthorized opening.

1.2 These requirements are intended to test the ability of combination locks to resist unauthorized opening of the combination locks by sense of sight, touch, or hearing. Combination locks covered by these requirements may or may not have integral protection against entry by force.

1.3 These requirements do not cover electronic locks.

2 General

2.1 Components

2.1.1 Except as indicated in [2.1.2](#), a component of a product covered by this standard shall comply with the requirements for that component.

2.1.2 A component is not required to comply with a specific requirement that:

- a) Involves a feature or characteristic not required in the application of the component in the product covered by this standard, or
- b) Is superseded by a requirement in this standard.

2.1.3 A component shall be used in accordance with its rating established for the intended conditions of use.

2.1.4 Specific components are incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions.

2.2 Units of measurement

2.2.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

2.3 Referenced publications

2.3.1 Any undated reference to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard.

2.3.2 The following publications are referenced in this Standard:

ASTM B117, *Standard Practice for Operating Salt Spray (Fog) Apparatus*

ASTM D5423, *Standard Specification for Forced-Convection Laboratory Ovens for Evaluation of Electric Insulation*

3 Classification

3.1 Combination locks are classified as Group 1, Group 1R, Group 2M, or Group 2.

3.2 GROUP 1 – Those locks that have a high-degree of resistance to expert or professional manipulation. The protection against expert manipulation includes advanced construction features not found in conventional designs. Group 1 locks shall have 20 working hours of resistance to expert or professional manipulation. See [10.1.1 – 10.1.5](#) and [10.5.1 – 10.5.8](#).

3.3 GROUP 1R – Group 1R locks shall have 20 working hours of resistance to expert or professional manipulation, the same as for Group 1 and, in addition, have 20 working hours of resistance to radiological attack. See [10.2.1](#) and [10.5.1 – 10.5.8](#).

3.4 GROUP 2M – Those locks that have 2 working hours of resistance to expert or professional manipulation. See [10.3.1 – 10.3.5](#) and [10.5.1 – 10.5.8](#).

3.5 GROUP 2 – Those locks that have a moderate degree of resistance to unauthorized opening. See [10.4.1 – 10.4.4](#) and [10.5.1 – 10.5.8](#).

4 Glossary

4.1 For the purpose of this standard the following definitions apply.

4.2 DRIVE CAM –

a) A circular component connected directly to the spindle; its drive pin transfers rotation to the wheels, and its gate is shaped to accept the lever nose.

b) The drive cam screws onto the spindle within the lock case. It is locked into position by a spline key that is pushed snugly into a groove milled into the drive cam and spindle. Once locked into position on the spindle, the drive cam's purpose is to transmit the drive to the wheels and also to withdraw the lock bolt. The drive from the drive cam to the third wheel is transmitted via a small drive pin on the cam.

4.3 DRIVE PIN – A pin extending from the underside of the drive cam and from all but the first wheel in a wheel pack; it transfers motion to the next component in the wheel pack.

4.4 FENCE – A part of the lever (see [4.6](#)) projecting across the periphery of the wheels that fit into the wheel gates, permitting the lever nose to engage in the drive cam.

4.5 GATE – The cutout in the periphery of the tumbler that is engaged by the fence on the lever assembly.

4.6 LEVER (DROP LEVER) –

a) Connects bolt and drive cam during lock operation.

b) Serves to retract the bolt when the proper combination has been aligned.

c) The drop lever attaches to the bolt via a pivot screw or post. Attached to the lever is a fence (see [4.4](#)) that drops into the wheel gate when they are correctly aligned. The nose of the drop lever rides on the drive cam, dropping into a gate in the drive cam when the wheels are correctly positioned. When the combination wheels of the lock are properly aligned, the fence of the lever enters the wheel pack only after the drive cam gate is positioned at the lever nose. Once the lever nose has

entered the drive cam gate and the lever fence has entered into the wheel gates, the locking, or blocking bolt of the lock is capable of being withdrawn by further rotation of the lock dial.

4.7 TUMBLER PACK – Set of wheels, flies, and isolation (spacing) washers supported by a torque adjuster or wave washer and secured with a retainer.

4.8 WHEEL POST – A component, usually cast as part of the lock case or cover, on which the wheel pack is assembled and about which the wheels rotate.

4.9 WHEEL – Assembly, usually in the form of a circular disc, having a gate and drive pin whose locations are set to selected positions to permit combination change.

CONSTRUCTION

5 General

5.1 A lock shall present a user with a minimum of 1,000,000 (one million) separate dialable or enterable codes or combinations. Although a combination lock may provide for a choice of 1,000,000 codes or combinations, there may be some codes or combinations that the user is advised not to use. The instructions with the lock shall advise the user of these cautions and conditions; for example:

- a) The same digit or character for each input;
- b) Digits or characters in rising or descending order with spacing of 5 or less digits or characters between each entry;
- c) Telephone numbers and birth dates;
- d) Digits or characters that associate with a company or individual name;
- e) Simple combinations such as 20-40-60; and
- f) An original factory combination or code.

On mechanical dial-type combination locks, there is a segment of numbers that cannot be used as the last number in a sequence since the use of numbers in that segment will cause a malfunction of the lock.

6 Nonmetallic Parts

6.1 Factors taken into consideration when determining compliance with the requirements of nonmetallic parts are:

- a) Mechanical strength,
- b) Resistance to impact,
- c) Moisture absorptive properties, and
- d) Resistance to distortion of the material under conditions of normal or abnormal usage.

See Tests of Polymeric Material, Section [13](#).

7 Corrosion Protection

7.1 All working parts of the lock mechanisms shall be constructed of brass, bronze, stainless steel, or equivalent corrosion-resistant materials, or shall have a protective finish that permits the lock mechanism to comply with the Salt Spray Corrosion Test, Section [12](#).

PERFORMANCE

8 General

8.1 Fourteen samples of a Group 1, a Group 1R, and a Group 2M lock, and five samples of a Group 2 lock are to be tested. All samples are to be mounted on 1/4-inch (6.4-mm) thick steel plates 6 by 8 inches (152 by 203 mm).

9 Operation Test

9.1 The lock shall operate as intended on the code or combination to which it is set.

10 Resistance to Unauthorized Opening

10.1 Group 1

10.1.1 A Group 1 lock shall resist unauthorized opening for a period of 20 working hours when subjected to the manipulation techniques specified in [10.5.3](#) – [10.5.5](#).

10.1.2 The time period specified in [3.2](#) and [10.1.1](#) may include one person working 20 hours, two people working together 10 hours, or equivalent combinations. This time limit is not to include the time spent on the unsealed sample.

10.1.3 A three-wheel lock shall not open when the dial is turned more than one full dial graduation on either side of the proper graduation for each wheel. A four-wheel lock shall not open when the dial is turned more than 1-1/4 dial graduations on either side of the proper graduation for each wheel.

10.1.4 The test for a three-wheel lock is to be conducted by changing the combination one number at a time in the following manner:

- a) Dial the combination with the first number one graduation lower than set, and the second and third numbers as they are set;
- b) Then dial the combination with the first number one graduation higher than set, and the second and third numbers as they are set;
- c) Then dial the combination with the second number one graduation lower than set, and the first and third numbers as they are set;
- d) Then dial the combination with the second number one graduation higher than set, and the first and third numbers as they are set;
- e) Then dial the combination with the third number one graduation lower than set, and the first and second numbers as they are set; and
- f) Then dial the combination with the third number one graduation higher than set, and the first and second numbers as they are set.

10.1.5 A four-wheel lock is to be tested in the same sequence as described in [10.1.4](#) except that the change is to be 1-1/4 dial graduations lower or higher.

10.1.6 If the lock opens as a result of any of these attempts, the trial is to be repeated with the number changed 1/4 of a graduation more. The lock shall not open on that trial.

10.2 Group 1R

10.2.1 A Group 1R combination lock shall comply with all of the requirements for Group 1 locks and in addition shall be secure against radiological attack for 20 hours with a radioactive source not exceeding the equivalent of 10 curies of cobalt 60 at a 30-inch (762-mm) distance.

10.3 Group 2M

10.3.1 A Group 2M lock shall resist unauthorized opening for a period of two working hours when subjected to the manipulation techniques specified in [10.5.3 – 10.5.5](#).

10.3.2 The time period specified in [3.4](#) and [10.3.1](#) may include one person working 2 hours, two persons working 1 hour, or equivalent combinations. This time limit is not to include the time spent on the unsealed sample.

10.3.3 A three-wheel lock shall not open when the dial is turned more than 1-1/4 dial graduations on either side of the proper graduation for each wheel. A four-wheel lock shall not open when the dial is turned more than 1-1/2 dial graduations on either side of the proper graduation for each wheel.

10.3.4 The test is to be conducted as described in [10.1.4](#) except that the change in the graduation is to be 1-1/4 for a three-wheel lock and 1-1/2 for a four-wheel lock.

10.3.5 If the lock opens as a result of any of these attempts, the trial is to be repeated with the number changed 1/4 of a graduation more. The lock shall not open on that trial.

10.4 Group 2

10.4.1 Testing of a Group 2 lock is to consist of setting the wheels to various combinations to determine that the lock operates as intended but does not open with the dial turned beyond the tolerances specified in [10.4.2](#).

10.4.2 A three-wheel lock shall not open when the dial is turned more than 1-1/4 dial graduations on either side of the proper graduation for each wheel. A four-wheel lock shall not open when the dial is turned more than 1-1/2 dial graduations on either side of the proper graduation for each wheel.

10.4.3 The test is to be conducted as described in [10.1.4](#) except that the change in graduation is to be 1-1/4 for a three-wheel lock and 1-1/2 for a four-wheel lock.

10.4.4 If the lock opens as a result of any of these attempts, the trial is to be repeated with the number changed 1/4 of a graduation more. The lock shall not open on that trial.

10.5 All classes

10.5.1 Punching of a combination lock shall result in the lock bolt becoming immobilized by mechanical means.